

Application for FCC Certification
On behalf of

ZHEJIANG REXENSE TECHNOLOGY CO., LTD.

Product Name: 802.15.4 / ZigBee Module

Model No.: REX3

Serial No.: 1016BCE3, 1016BCE7

FCC ID: O46RY12M01

(MPE Calculation)

Prepared For : ZHEJIANG REXENSE TECHNOLOGY CO., LTD.
Room 105, Hangzhou E-Commerce Industry Park, No.7
Cuibai Road, Hangzhou 310012 P.R.C

Prepared By : Audix Technology (Shanghai) Co., Ltd.
3F 34Bldg 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500
Fax: +86-21-64955491

Report No. : ACI-F12097
Date of Test : May. 10, 2012
Date of Report : May. 22, 2012

TABLE OF CONTENTS

	Page
1 GENERAL INFORMATION.....	4
1.1 Description of Equipment Under Test.....	4
1.2 Description of Test Facility.....	5
1.3 Measurement Uncertainty	5
2 SUMMARY OF STANDARDS AND RESULTS.....	6
2.1 Applicable Standard	6
2.2 Specification Limits	6
2.3 MPE Calculation Method.....	6
2.4 Calculated Result.....	7

TEST REPORT FOR FCC CERTIFICATE

Applicant : ZHEJIANG REXENSE TECHNOLOGY CO., LTD.
Manufacturer : ZHEJIANG REXENSE TECHNOLOGY CO., LTD.
EUT Description : 802.15.4 / ZigBee Module
(A) Model No. : REX3
(B) Serial No. : 1016BCE3, 1016BCE7
(C) Test Voltage : DC 3.3V

Test Procedure Used:

FCC OET Bulletin 65 August 1997

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC OET Bulletin 65.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: REX3, S/N: 1016BCE3, 1016BCE7), which was tested on May. 10, 2012 is technically compliance with the FCC limits.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : May. 10, 2012 Date of Report : May. 22, 2012

Producer : Alan He
ALAN HE / Assistant

Review : DIO YANG
DIO YANG / Assistant Manager

AUDIX® For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : SAMMY CHEN
Authorized Signature EMC SAMMY CHEN / Deputy Manager

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test

Description : 802.15.4 / ZigBee Module

Type of EUT : Production Pre-product Pro-type

Model Number : REX3

Note 1 : The REX3 has 2 types of antenna:
one is the PCB antenna on board, the other
is the external SMA antenna.

Serial Number : 1016BCE3 (PCB antenna type),
1016BCE7 (SMA antenna type)

Note 2 : The only difference of above 2 samples is using PCB
antenna or SMA antenna, so we select 1 sample to
perform the RF conducted test.

Radio Tech : IEEE 802.15.4 (ZigBee®)

Freq. Band : 2405 MHz - 2480 MHz
Total 16 Channels in 5 MHz Separation

Tested Freq. : 2405 MHz (Channel 11)
2440 MHz (Channel 18)
2480 MHz (Channel 26)

Antenna Gain : 2.0 dBi (for both PCB antenna and SMA antenna)

Applicant : ZHEJIANG REXENSE TECHNOLOGY CO., LTD.
Room 105, Hangzhou E-Commerce Industry Park,
No.7 Cuibai Road, Hangzhou 310012 P.R.C

Manufacturer : ZHEJIANG REXENSE TECHNOLOGY CO., LTD.
Room 105, Hangzhou E-Commerce Industry Park,
No.7 Cuibai Road, Hangzhou 310012 P.R.C

1.2 Description of Test Facility

Site Description : Sept. 17, 1998 file on
(Semi-Anechoic Chamber) Apr 29, 2009 Renewed
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3 F 34 Bldg 680 Guiping Rd.,
Caohejing Hi-Tech Park,
Shanghai 200233, China

FCC registration Number : 91789

Accredited by NVLAP, Lab Code : 200371-0

1.3 Measurement Uncertainty

Output Power Expanded Uncertainty : $U = 0.30 \text{ dB}$

2 SUMMARY OF STANDARDS AND RESULTS

2.1 Applicable Standard

FCC OET Bulletin 65:1997

2.2 Specification Limits

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

NOTE: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The limit value 1.0mW/cm² is available for this EUT.

2.3 MPE Calculation Method

$$S = PG/(4 \pi R^2)$$

$$R = [PG/(4 \pi S)]^{0.5}$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)
(the measured power value see Report: F12088 Section 5.6)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

2.4 Calculated Result

2.4.1 Radio Frequency Radiation Exposure Evaluation

Frequency (MHz)	Output Power to Antenna (mW)	Antenna Gain (dBi)	Antenna Gain (Numeric)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2405	4.56	2.0	1.585	0.001438	1.0
2440	3.97	2.0	1.585	0.001252	1.0
2480	3.43	2.0	1.585	0.001082	1.0

Separation distance R= 20cm.

Frequency (MHz)	Output Power to Antenna (mW)	Antenna Gain (dBi)	Antenna Gain (Numeric)	Limit (mW/cm ²)	Distance (cm)
2405	4.56	2.0	1.585	1.0	0.76
2440	3.97	2.0	1.585	1.0	0.71
2480	3.43	2.0	1.585	1.0	0.66

The antenna used for this transmitter must be installed to provide a separation distance of at least 0.76cm from all persons.