

TEST REPORT

Reference No...... : WTS16S0344759-2E V3
FCC ID..... : O46RY12M03
Applicant..... : Zhejiang Rexense Technology Co., Ltd.
Address..... : Room 105, Hangzhou E-Commerce Industry Park, No.7 Cuibai Road,
Hangzhou 310012 P. R. China
Manufacturer : Zhejiang Rexense Technology Co., Ltd.
Address..... : Room 105, Hangzhou E-Commerce Industry Park, No.7 Cuibai Road,
Hangzhou 310012 P. R. China
Product Name..... : 802.15.4/ ZigBee Module
Model No...... : REX3L
Brand..... : REXENSE
Standards..... : FCC Part 2.1091
Date of Receipt sample..... : Mar. 14, 2016
Date of Test..... : Mar. 15 - 24, 2016
Date of Issue..... : May. 10, 2016
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.
The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

Remark:

N/A: Not Applicable

PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY.....	2
3 CONTENTS.....	3
4 REPORT REVISION HISTORY.....	4
5 GENERAL INFORMATION.....	4
5.1 GENERAL DESCRIPTION OF E.U.T.....	4
5.2 DETAILS OF E.U.T.....	4
5.3 CHANNEL LIST.....	4
5.4 TEST FACILITY.....	5
5.5 TEST EQUIPMENT CALIBRATION.....	5
6 RF EXPOSURE.....	6
6.1 REQUIREMENTS.....	6
6.2 THE PROCEDURES / LIMIT.....	6
6.3 MPE CALCULATION METHOD.....	7
7 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	8
7.1 EXTERNAL PHOTOS.....	8

4 Report Revision History

Report No.	Report Version	Description	Issue Date
WTS16S0344759-2E	NONE	Original	Mar. 25, 2016
WTS16S0344759-2E	V1	Version 1	May. 09, 2016
WTS16S0344759-2E	V2	Version 2	May. 10, 2016
WTS16S0344759-2E	V3	Version 3	May. 10, 2016

5 General Information

5.1 General Description of E.U.T.

Product Name:	802.15.4/ ZigBee Module
Model No.:	REX3L
Model Difference:	N/A
Operation Frequency:	2405MHz ~ 2480MHz
The Lowest Oscillator:	24MHz
Antenna Gain	0 dBi for ZigBee
Type of modulation:	O-QPSK

5.2 Details of E.U.T.

Technical Data:	DC 3.3V
-----------------	---------

5.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2405	2	2410	3	2415	4	2420
5	2425	6	2430	7	2435	8	2440
9	2445	10	2450	11	2455	12	2460
13	2465	14	2470	15	2475	16	2480

5.4 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A-1, Oct. 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

5.5 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 RF Exposure

Test Requirement:

FCC Part 1.1307

Evaluation Method:

FCC Part 2.1091

KDB 447498 D01 General RF Exposure Guidance v06

6.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

6.3 MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor, is normally numeric gain.



R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
0 (for ZigBee)	1.000	6.90	4.90	0.00097	1

7 Photographs - Constructional Details

7.1 External Photos



=====End of Report=====