



Report No.: SZ12050002E02



# FCC TEST REPORT

*Issued to*

**Tecmobile (International) Ltd**

*For*

**Mobile phone**

Model Name: TEC/R30  
Trade Name: N/A  
Brand Name: Tecmobile  
FCC ID: O4FR3035268605  
Standard: 47 CFR Part 15 Subpart B  
Test date: May 7, 2012 – May 22, 2012  
Issue date: June 12, 2012

Shenzhen Morlab Communications Technology Co., Ltd.

Tested by Xiao Xiong  
Xiao Xiong

Date 2012.6.12



Review by Huang Pulong  
Huang Pulong

Date 2012.6.12

CTIA Authorized Test Lab  
LAB CODE 20081223-00

IEEE 1725 OTA

OFTA

電訊管理局



GCF  
Official Observer of  
Global Certification Forum

Bluetooth

FCC

Reg. No.  
741109

BQTF

*The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen MORLAB Communication Technology Co., Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the Shenzhen MORLAB Telecommunication Co., Ltd to his customer. Supplier or others persons directly concerned. Shenzhen MORLAB Telecommunication Co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report, Shenzhen MORLAB Telecommunication Co., Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.*

## TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>1. GENERAL INFORMATION .....</b>            | <b>3</b>  |
| <b>1.1 EUT Description .....</b>               | <b>3</b>  |
| <b>1.2 Test Standards and Results .....</b>    | <b>4</b>  |
| <b>1.3 Facilities and Accreditations .....</b> | <b>5</b>  |
| 1.3.1 Facilities .....                         | 5         |
| 1.3.2 Test Environment Conditions .....        | 5         |
| 1.3.3 Measurement Uncertainty .....            | 5         |
| <b>2. TEST CONDITIONS SETTING.....</b>         | <b>6</b>  |
| <b>2.1 Test Mode .....</b>                     | <b>6</b>  |
| <b>2.2 Test Setup and Equipments List.....</b> | <b>7</b>  |
| 2.2.1 Conducted Emission.....                  | 7         |
| 2.2.2 Radiated Emission.....                   | 8         |
| <b>3. 47 CFR PART 15B REQUIREMENTS .....</b>   | <b>11</b> |
| <b>3.1 Conducted Emission .....</b>            | <b>11</b> |
| 3.1.1 Requirement .....                        | 11        |
| 3.1.2 Test Description .....                   | 11        |
| 3.1.3 Test Result .....                        | 11        |
| <b>3.2 Radiated Emission .....</b>             | <b>13</b> |
| 3.2.1 Requirement .....                        | 13        |
| 3.2.2 Test Description .....                   | 13        |
| 3.2.3 Test Result .....                        | 13        |

| Change History |               |                   |
|----------------|---------------|-------------------|
| Issue          | Date          | Reason for change |
| 1.0            | June 12, 2012 | First edition     |
|                |               |                   |
|                |               |                   |

## 1. GENERAL INFORMATION

### 1.1 EUT Description

EUT Type..... Mobile Phone  
Serial No. .... (n.a., marked #1 by test site)  
Hardware Version ..... A107-MB-V0.7  
Software Version..... A107V07\_tekmobile\_BT\_V06  
Applicant..... Tecmobile (International) Ltd  
Manufacturer..... Tecmobile (International) Ltd  
Modulation Type..... GMSK, FHSS  
Power supply ..... Battery  
Brand Name: Tecmobile  
Model No.: TEC/R30  
Serial No.: (n.a. marked #1 by test site)  
Capacitance: 850mAh  
Rated Voltage: 3.8V  
Charge Limit: 4.2V

*Note 1:* The product have a variety of models, model No. is TEC/R30AABBC and “AABBC” combination indicate following:

|                        |  |
|------------------------|--|
| “AA” refer to color:   | BK, WH, BL, PK, SL                                     |
| “BB” refer to country: | EN, DE, NL, FR, TR, KL, SP, PL, UR, AR, RO, CS, RU, SK |
| “C” refer to Number:   | 2, 3, 4, 5,  |

They are all kinds of model name only the model name different and all same to hardware.

*Note 2:* The EUT is GSM Phone, it supports GSM 850MHz, 1900MHz, GPRS and ISM 2.4G Bluetooth bands.

*Note 3:* The EUT is equipped with a T-Flash card slot; equipped with a USB port which can be connected to the ancillary equipments supplied by the manufacturer e.g. the AC Adapter and the USB Cable.

*Note 4:* For a more detailed description, please refer to Specification or User’s Manual supplied by the applicant and/or manufacturer.



## 1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

| No. | Identity                            | Document Title          |
|-----|-------------------------------------|-------------------------|
| 1   | 47 CFR Part 15<br>(10-1-09 Edition) | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section | Description        | Result |
|-----|---------|--------------------|--------|
| 1   | 15.107  | Conducted Emission | PASS   |
| 2   | 15.109  | Radiated Emission  | PASS   |

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4 2009.

## 1.3 Facilities and Accreditations

### 1.3.1 Facilities

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at 3/F, Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### 1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

|                             |         |
|-----------------------------|---------|
| Temperature (°C):           | 15 - 35 |
| Relative Humidity (%):      | 30 -60  |
| Atmospheric Pressure (kPa): | 86-106  |

### 1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

|                                    |        |
|------------------------------------|--------|
| Uncertainty of Conducted Emission: | ±1.8dB |
| Uncertainty of Radiated Emission:  | ±3.1dB |

## 2. TEST CONDITIONS SETTING

### 2.1 Test Mode

#### (1) The first test mode (USB)

The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a USB cable supplied by applicant. During the measurement, the data is transmitting between the PC and the TransFlash Card of the EUT.

#### (2) The second test mode (PC Web Camera)

The EUT configuration of the emission tests is EUT + Battery + PC.


The EUT supports PC Web Camera function. During the measurement, the EUT was connected with a PC via a special USB cable supplied by applicant, and the EUT working by way of the PC Web Camera.

NOTE: These test modes are performed, only the worst cases are recorded in this report.

## 2.2 Test Setup and Equipments List

### 2.2.1 Conducted Emission

#### A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides  $50\Omega/50\mu\text{H}$  of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


#### B. Equipments List:

| Description          | Manufacturer | Model       | Serial No. | Cal. Date |
|----------------------|--------------|-------------|------------|-----------|
| EMC Analyzer         | Agilent      | E7405A      | US44210471 | 2012.05   |
| Receiver             | Narda        | PMM 9060    | 001WX11001 | 2011.12   |
| Receiver             | Narda        | PMM 9010    | 595WX11007 | 2011.11   |
| LISN                 | Schwarzbeck  | NSLK 8127   | 812744     | 2012.05   |
| Pulse Limiter (20dB) | Schwarzbeck  | VTSD 9561-D | 9391       | (n.a.)    |
| System Simulator     | Agilent      | E5515C      | GB43130131 | 2012.05   |
| T-Flash Card         | SanDisk      | 256MB       | (n.a.)     | (n.a.)    |


## 2.2.2 Radiated Emission

### A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



## B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range of 9KHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

## C. Equipments List:

| Description  | Manufacturer | Model    | Serial No. | Cal. Date |
|--------------|--------------|----------|------------|-----------|
| EMC Analyzer | Agilent      | E7405A   | US44210471 | 2012.05   |
| Receiver     | Narda        | PMM 9060 | 001WX11001 | 2011.12   |



| Description           | Manufacturer | Model      | Serial No. | Cal. Date |
|-----------------------|--------------|------------|------------|-----------|
| Receiver              | Narda        | PMM 9010   | 595WX11007 | 2011.11   |
| Semi-Anechoic Chamber | Albatross    | 9m*6m*6m   | (n.a.)     | 2012.05   |
| Test Antenna - Bi-Log | Schwarzbeck  | VULB 9163  | 9163-274   | 2012.05   |
| Test Antenna - Horn   | Schwarzbeck  | BBHA 9120D | 9120D-963  | 2012.05   |
| Test Antenna -Loop    | Schwarzbeck  | FMZB 1519  | 1519-022   | 2012.05   |
| T-Flash Card          | SanDisk      | 256MB      | (n.a.)     | (n.a.)    |

### 3. 47 CFR PART 15B REQUIREMENTS

#### 3.1 Conducted Emission

##### 3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

| Frequency range (MHz) | Conducted Limit (dB $\mu$ V) |          |
|-----------------------|------------------------------|----------|
|                       | Quasi-peak                   | Average  |
| 0.15 - 0.50           | 66 to 56                     | 56 to 46 |
| 0.50 - 5              | 56                           | 46       |
| 5 - 30                | 60                           | 50       |

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

##### 3.1.2 Test Description


See section 2.2.1 of this report.

##### 3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

###### 3.1.3.1 Test Mode

###### A. Test Plot and Suspicious Points:



(Plot A: L Phase)



(Plot B: N Phase)

**Test Result: PASS**

## 3.2 Radiated Emission

### 3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency range (MHz) | Field Strength  |      | Field Strength Limitation at 3m Measurement Dist |                        |
|-----------------------|-----------------|------|--|------------------------|
|                       | $\mu\text{V/m}$ | Dist | (uV/m)   | (dBuV/m)               |
| 0.009 - 0.490         | 2400/F(KHz)     | 300m | 10000* 2400/F(KHz)                               | 20log 2400/F(KHz) + 80 |
| 0.490 - 1.705         | 2400/F(KHz)     | 30m  | 100* 2400/F(KHz)                                 | 20log 2400/F(KHz) + 40 |
| 1.705 - 30.00         | 30              | 30m  | 100*30   | 20log 30 + 40          |
| 30.0 - 88.0           | 100             | 3m   | 100  | 20log 100              |
| 88.0 - 216.0          | 150             | 3m   | 150  | 20log 150              |
| 216.0 - 960.0         | 200             | 3m   | 200  | 20log 200              |
| Above 960.0           | 500             | 3m   | 500  | 20log 500              |

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by  $20\log$  Emission Level(uV/m).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $Ld1 = Ld2 * (d2/d1)^2$ .

Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as  
 $Ld1 = Ld2 * (10)^2 = 100 * 30\text{uV/m}$

### 3.2.2 Test Description

See section 2.2.2 of this report.

### 3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to


perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

#### A. Test Plots and Suspicious Points:

NOTE: The emissions are too small to be measured and are at least 6 dB below the limit, So all the data of marked are pass.




(Plot A: 9K – 30M)



(Plot A: Test Antenna Vertical)

| NO | Fre.<br>(MHz) | Pk    | QP    | AV  | Limit-<br>PK | Limit-<br>QP | Limit-<br>AV | Antenna  | Verdict |
|----|---------------|-------|-------|-----|--------------|--------------|--------------|----------|---------|
| 1  | 136.434       | 37.32 | 32.67 | N.A | N.A          | 43.5         | N.A          | Vertical | Pass    |
| 2  | 167.880       | 33.69 | N.A   | N.A | N.A          | 43.5         | N.A          | Vertical | Pass    |
| 3  | 216.259       | 40.04 | 36.79 | N.A | N.A          | 43.5         | N.A          | Vertical | Pass    |
| 4  | 663.766       | 40.04 | N.A   | N.A | N.A          | 46.0         | N.A          | Vertical | Pass    |
| 5  | 1000.000      | 42.96 | N.A   | N.A | N.A          | 54.0         | N.A          | Vertical | Pass    |
| 6  | 2496.509      | 46.44 | N.A   | N.A | 54.0         | N.A          | 74.0         | Vertical | Pass    |



(Plot B: Test Antenna Horizontal)

| Fre.<br>(MHz) | Pk    | QP  | AV  | Limit-<br>PK | Limit-<br>QP | Limit-<br>AV | Antenna    | Verdict |
|---------------|-------|-----|-----|--------------|--------------|--------------|------------|---------|
| 136.434       | 28.49 | N.A | N.A | N.A          | 43.5         | N.A          | Horizontal | Pass    |
| 240.449       | 33.38 | N.A | N.A | N.A          | 46.0         | N.A          | Horizontal | Pass    |
| 431.546       | 36.17 | N.A | N.A | N.A          | 46.0         | N.A          | Horizontal | Pass    |
| 2483.791      | 45.94 | N.A | N.A | 74.0         | N.A          | 54.0         | Horizontal | Pass    |

**Test Result: PASS**

\*\* END OF REPORT \*\*