

TEST REPORT

Ref. Report No.

01-341-014

Name and address of the applicant

DYNAFINE INC.
Room 905, DongAh-Height Bldg., 449-1, Sang-Dong,
Wonmi-Ku, Bucheon-Shi, Kyungki-Do, Korea 420-030

Standard / Test regulation

FCC Part 15, Subpart B

Test result

Pass

Incoming date : March 8, 2001

Test date : March 14, 2001

Test item(s) ;

Communication Receiver
(Pager Receiver)

Model/type ref. ;

LEGEND

Manufacturer ;

DYNAFINE INC.


Additional information ;

-Required Authorization : Certification
-FCC ID. : O4WLEGEND

Issue date : March 15, 2001

This test report only responds to the tested sample and shall not be reproduced except in full without written approval of the Korea Testing Laboratory.

Tested and reported by



Jeong-Min Kim, Senior Engineer

Reviewed by



Won-Seo Cho, EMC Team Leader

**KOREA TESTING
LABORATORY**

TABLE OF CONTENTS

| | |
|---|---|
| I. GENERAL INFORMATION | 3 |
| 1. Grantee's Name and Mailing Address | |
| 2. Manufacturer's Name and Mailing Address | |
| 3. Equipment Descriptions | |
| 4. Rules and Regulations | |
| 5. Measuring Procedure | |
| 6. Date of Measurement | |
| α. GENERAL REQUIREMENTS OF THE EUT | 4 |
| 1. Labelling Requirement (Section 15.19) | |
| 2. Information to User (Sections 15.21) | |
| 3. Special Accessories (Section 15.27) | |
| β. RADIATED EMISSION MEASUREMENT (Section 15.109) | 5 |
| 1. Test Procedure | |
| 2. Photograph for the worst case configuration | |
| 3. Sample Calculation | |
| 4. Measurement Data | |
| χ. TEST EQUIPMENTS USED FOR MEASUREMENT..... | 8 |

. GENERAL INFORMATION

1. Grantee's Name and
Mailing Address : DYNAFINE INC.
Room 905, DongAh-Height Bldg., 449-1, Sang-Dong, Wonmi-Ku,
Bucheon-Shi, Kyungki-Do, Korea 420-030

2. Manufacturer's Name and
Mailing Address : DYNAFINE INC.
Room 905, DongAh-Height Bldg., 449-1, Sang-Dong, Wonmi-Ku,
Bucheon-Shi, Kyungki-Do, Korea 420-030

3. Equipment Descriptions

3.1 Operating Frequency : 929.0125 MHz
3.2 Detect Method : Superheterodyne Detector
3.3 Local Oscillator : 1st Local Osc. Frequency = Operating Frequency - 21.4 MHz (1st IF)
2nd Local Osc. Frequency = 20.945 MHz (2nd IF : 455 kHz)
3.4 Oscillator : Crystal = 12.8 MHz, 20.945 MHz, 4.19 MHz
3.5 Power Supply : DC 1.5V (Battery)

4. Rules and Regulations : FCC Part 15, Subpart B

5. Measuring Procedure : ANSI C63.4-1992

6. Date of Measurement

6.1 Line Conducted : Not Applicable
6.2 Radiated Emission : March 14, 2001

. GENERAL REQUIREMENTS OF THE EUT**1. Labelling Requirement (Section 15.19)**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

1.1 Location of Label : User's Guide Manual

1.2 How Applied : Printing

2. Information to User (Section 15.21)

The following or similar statements were provided in the manual for user instruction.
Please refer page 3 of the attached manual for details.

CAUTION : Any changes or modifications in construction of this device which are not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. Special Accessories (Section 15.27)

3.1 Were the special Accessories provided? [] yes, [x] no

3.2 If yes, details for the special accessories are as follows :

3.3 If yes, were the appropriate instructions provided on the first page of the text concerned with the device?

[] yes, [] no

3.4 Are these accessories provided of the type which can be readily obtained from multiple retail outlets ?

[] yes, [] no

And therefore does the manual specify what additional components or accessories are required to be used in order to comply with the Rules?

[] yes, [] no

. RADIATED EMISSION MEASUREMENT (Section 15.109)**1. Test Procedure****1.1 Preliminary Testing for Reference**

This pager receiver (EUT) is designed to operate in the band 929.0125 MHz.

Preliminary testing was performed in a KTL absorber-lined room to determine the emission characteristics of the EUT. The EUT was placed on the wooden table which has dimensions of 0.8 meters in height, 1 meter in length and 1.5 meters in width. Receiving antenna (Biconical antenna : 30 to 300 MHz, Log-periodic antenna : 200 to 1000 MHz or Horn Antenna : 1 to 18 GHz) was placed at the distance of 1 meter from the EUT.

An attempt was made to maximize the emission level with the various configurations of the EUT while rotating the table and varying antenna height.

Emission levels from the EUT with various configurations were examined on a Spectrum Analyzer connected with a RF amplifier and graphed by a plotter.

1.2 Final Radiated Emission Test at an Absorber-Lined Room

The final measurement of radiated field strength was carried out in a KTL Absorber-Lined Room that was listed up at FCC according to the "Radiated Emissions Testing" procedure specified by ANSI C63.4.


Based on the test results in preliminary test, measurement was made in same test set up and configuration which produced maximum emission level. Receiving antenna was installed at 3-meter distance from the EUT, and was connected to an EMI receiver or spectrum analyzer (for above 1GHz) with a RF amplifier.

Turntable was rotated through 360 degrees and receiving antenna height was varied from 1 to 4 meters above the ground plane to read maximum emission level.

If necessary, the radiated emission measurements could be performed at a closer distance than specified distance to ensure higher accuracy and their results were extrapolated to the specified distance using an inverse linear distance extrapolation factor(20 dB/decade) as per Section 15.31(f).

The maximum emission level from the EUT occurred in such configuration as shown in the following photograph.

2. Photograph for the worst case configuration



3. Sample Calculation

The emission level measured in decibels above one microvolt ($\text{dB}\delta$) was converted into microvolt per meter (δ/m) as shown in following sample calculation.

For example :

| | | | |
|-------|------------------------------|-------------------|---------------------------------|
| | Measured Value at | <u>907.62 MHz</u> | 6.6 $\text{dB}\delta$ |
| + | Antenna Factor | | 23.0 dB/m |
| + | Cable Loss | | 5.6 dB |
| • | Preamplifier | | 0.0 dB |
| • | Distance Correction Factor * | | 0.0 dB |
| ----- | | | |
| = | Radiated Emission | | 35.2 $\text{dB}\delta/\text{m}$ |
| | | | (= 57.5 δ/m) |

* Extrapolated from the measured distance (1 m) to the specified distance (3 m) by an inverse linear distance extrapolation.

4. Measurement Data

- Resolution Bandwidth : x CISPR Quasi-Peak (6 dB Bandwidth : 120 kHz)
 Peak (3 dB Bandwidth : 300 kHz)
- Measurement Distance : 3 Meter

| Frequency (MHz) | * D.M. | * A.P. | Measured Value (dB δ) | * A.F. + C.L (dB) | * A.G. (dB) | * D.C.F. (dB) | Emission Level (dB δ /m) | Limit (dB δ /m) | ** Margin (dB) |
|--------------------|-----------|-----------|-------------------------------------|-------------------------------|-------------------|---------------------|---------------------------------------|---------------------------|----------------------|
| 226.90 | Q | H | 4.7 | 20.1 | - | - | 24.8 | 46.0 | - 21.2 |
| 907.62 | Q | H | 6.6 | 28.6 | - | - | 35.2 | 46.0 | - 10.8 |
| - | - | - | - | - | - | - | - | - | - |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

Note

The observed EMI receiver(ESVS30) noise floor level was 2.0dB δ . And all other emissions not reported on data were more than 25dB below the permitted level.

* D.M. : Detect Mode (P : Peak, Q : Quasi-Peak, A : Average)
 A.P. : Antenna Polarization (H : Horizontal, V : Vertical)
 A.F. : Antenna Factor
 C.L. : Cable Loss
 A.G. : Amplifier Gain
 D.C.F. : Distance Correction Factor
 < : Less than

** Margin (dB) = Emission Level (dB) - Limit (dB)

7. TEST EQUIPMENT USED FOR MEASUREMENTS

| <u>Equipment</u> | <u>Model No.</u> | <u>Manufacturer</u> | <u>Serial No.</u> | <u>Effective Cal. Duration</u> |
|--|------------------|---------------------|-------------------|--------------------------------|
| [x] EMI Receiver (20 MHz-1 GHz) | ESVS30 | R & S | 830516/002 | 06/13/00-06/12/01 |
| [x] Spectrum Analyzer (9 kHz-26.5 GHz) | 8563A | H. P. | 3222A02069 | 02/18/01-02/17/02 |
| [] Spectrum Analyzer (100 Hz-22 GHz) | 8566B | H. P. | 3014A07057 | 05/24/00-05/23/01 |
| [] Quasi-Peak Adapter (10 kHz-1 GHz) | 85650A | H. P. | 3107A01511 | 05/24/00-05/23/01 |
| [] RF-Preselector (20 Hz-2 GHz) | 85685A | H. P. | 3010A01181 | 05/24/00-05/23/01 |
| [] Test Receiver (9 kHz-30 MHz) | ESH3 | R & S | 860905/001 | 06/13/00-06/12/01 |
| [x] Pre-Amplifier (0.1-3000 MHz, 30 dB) | 8347A | H. P. | 2834A00543 | 05/24/00-05/23/01 |
| [x] Pre-Amplifier (1-26.5 GHz, 35 dB) | 8449B | H. P. | 3008A00302 | 06/13/00-06/12/01 |
| [] LISN(50 , 50 H) (10 kHz-100 MHz) | 3825/2 | EMCO | 9010-1710 | - |
| [] LISN(50 , 50 H) (10 kHz-100 MHz) | 3825/2 | EMCO | 9011-1720 | - |
| [x] Plotter | 7470A | H. P. | 3104A21292 | - |
| [x] Tuned Dipole Ant. (30 MHz-300 MHz) | VHA 9103 | Schwarzbeck | - | * |
| [x] Tuned Dipole Ant. (300 MHz-1 GHz) | UHA 9105 | Schwarzbeck | - | * |
| [x] Biconical Ant. (30 MHz-300 MHz) | BBA 9106 | Schwarzbeck | - | * |
| [x] Log Periodic Ant. (200 MHz-1 GHz) | 3146 | EMCO | - | * |
| [x] Horn Ant. (1 GHz-18 GHz) | 3115 | EMCO | - | * |
| [] DC Power Supply | 6260B | H.P. | 1145A04822 | - |
| [] Shielded Room (5.0 m x 4.5 m) | - | SIN-MYUNG | - | - |

* Each set of antennas has been calibrated to ensure correlation with ANSI C63.5 standard. The calibration of antennas is traceable to Korea Standard Research Institute(KSRI).