

FCC RF Test Report

(LTE)

Report No.: JYTSZ-R12-2500771

Applicant: SWAGTEK

Address of Applicant: 10205 NW 19th Street, STE 101, Miami, FL33172.USA

Equipment Under Test (EUT)

Product Name: 4G Tablet

Model No.: T10L PLUS, Grad, Slate

Trade Mark: LOGIC, ISWAG, UNONU

FCC ID: O551001923

Applicable Standards: FCC CFR Title 47 Part 2, 22H, 24E, 27L H

Date of Sample Receipt: 21 May, 2025

Date of Test: 22 May, to 25 Jun., 2025

Date of Report Issued: 25 Jun., 2025

Test Result: PASS

Tested by:

Victor Zhang
Project Engineer

Date:

25 Jun., 2025

Reviewed by:

W. Ding
Senior Engineer

Date:

25 Jun., 2025

Approved by:

James Wei
Manager

Date:

25 Jun., 2025

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	25 Jun., 2025	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions from the Method	5
3.7 Laboratory Facility	6
3.8 Laboratory Location.....	6
3.9 Test Instruments List	7
4 Measurement Setup and Procedure	9
4.1 Test Channel	9
4.2 Test Setup	11
4.3 Test Procedure	12
5 Test Results.....	13
5.1 Summary	13
5.1.1 Clause and Data Summary.....	13
5.1.2 Test Limit.....	15
5.2 Field Strength of Spurious Radiation Measurement	16

3 General Information

3.1 Client Information

Applicant:	SWAGTEK
Address:	10205 NW 19th Street,STE 101,Miami, FL33172.USA
Manufacturer/Factory:	SWAGTEK
Address:	10205 NW 19th Street,STE 101,Miami, FL33172.USA

3.2 General Description of E.U.T.

Product Name:	4G Tablet		
Model No.:	T10L PLUS, Grad, Slate		
Operation Frequency Range:	LTE band 2:	Tx: 1850 MHz - 1910 MHz	Rx: 1930 MHz - 1990 MHz
	LTE band 4:	Tx: 1710 MHz - 1755 MHz	Rx: 2110 MHz - 2155 MHz
	LTE band 5:	Tx: 824 MHz - 849 MHz	Rx: 869 MHz - 894 MHz
	LTE band 7:	Tx: 2500 MHz - 2570 MHz	Rx: 2620 MHz - 2690 MHz
	LTE band 12:	Tx: 699 MHz - 716 MHz	Rx: 729 MHz - 746 MHz
	LTE band 17:	Tx: 704 MHz - 716 MHz	Rx: 734 MHz - 746 MHz
Modulation Type:	☑QPSK ☑16QAM ☑64QAM(only supports downlink)		
Antenna Type:	Internal Antenna		
Antenna Gain:	LTE band 2:	0.85 dBi (declare by Applicant)	
	LTE band 4:	-2.02 dBi (declare by Applicant)	
	LTE band 5:	-4.63 dBi (declare by Applicant)	
	LTE band 7:	1.2 dBi (declare by Applicant)	
	LTE band 12:	-3.88 dBi (declare by Applicant)	
	LTE band 17:	-3.88 dBi (declare by Applicant)	
Power Supply:	Rechargeable Li-ion Battery DC3.8V, 5000mAh		
AC Adapter:	Model: YD2.0AN-003 Input: AC100-240V, 50/60Hz, 0.2A Output: DC 5.0V, 2.0A		
Test Sample Condition:	The test samples were provided in good working order with no visible defects.		
Remark:	All the model are the same circuit and RF module, except the model names.		

3.3 Test Mode and Environment

Test Mode:	
QPSK mode:	Keep the EUT communication with simulated station in QPSK mode
16QAM mode:	Keep the EUT communication with simulated station in 16QAM mode
Remark: The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report.	
Operating Environment:	
Temperature:	Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.80Vdc, Extreme: Low 3.50Vdc, High 4.35Vdc
Test Engineer:	Robin Gu(Radiated measurement)

3.4 Description of Test Auxiliary Equipment

Test Equipment	Manufacturer	Model No.	Serial No.
Simulated Station	Anritsu	MT8820C	6201026545
Simulated Station	Rohde & Schwarz	CMW500	108209

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	±4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	±5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m SAC)	±4.5 dB
Radiated Emission (6GHz ~ 18GHz) (3m SAC)	4.7 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	5.34 dB
Radiated Emission (30MHz ~ 1GHz) (3m FAR)	3.39 dB
Radiated Emission (1GHz ~ 18GHz) (3m FAR)	5.15 dB
Radiated Emission (18GHz ~ 40GHz) (3m FAR)	5.30 dB
Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.	

3.6 Additions to, Deviations, or Exclusions from the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2026
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	01-03-2025	01-02-2026
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	01-03-2025	01-02-2026
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-01-2024	06-30-2027
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	01-03-2025	01-02-2026
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	12-25-2024	12-24-2025
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	12-25-2024	12-24-2025
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	12-25-2024	12-24-2025
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	12-16-2024	12-15-2025
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	12-16-2024	12-15-2025
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	12-16-2024	12-15-2025
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	12-16-2024	12-15-2025
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-16-2024	12-15-2025
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	09-09-2024	09-08-2025
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-15-2025	01-14-2026
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-15-2025	01-14-2026
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	01-15-2025	01-14-2026
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Radiated Emission(3m FAR):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m FAR	YUNYI	9m*6m*6m	WXJ097	06-15-2023	06-14-2028
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ097-2	07-01-2024	06-30-2025
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-01-2024	06-30-2027
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ097-3	06-16-2024	06-15-2025
				06-14-2025	06-13-2026
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	12-25-2024	12-24-2025
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	12-25-2024	12-24-2025
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	12-25-2024	12-24-2025
Pre-amplifier (30MHz ~ 1GHz)	YUNYI	PAM-310N	WXJ097-5	04-21-2025	04-20-2026
Pre-amplifier (1GHz ~ 18GHz)	YUNYI	PAM-118N	WXJ097-6	04-21-2025	04-20-2026
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	12-16-2024	12-15-2025
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	12-16-2024	12-15-2025
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	12-16-2024	12-15-2025
Spectrum Analyzer	KEYSIGHT	N9020B	WXJ081-1	06-11-2024	06-10-2025
				06-09-2025	06-08-2026
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-13M	WXG097-1	07-30-2024	07-29-2025
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG097-2	07-30-2024	07-29-2025
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG097-3	07-30-2024	07-29-2025
High Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Low Band Reject Filter Group	Tonscend	JS0806-F	WXJ097-4	N/A	
Test Software	Tonscend	TS+	Version: 5.0.0		

4 Measurement Setup and Procedure

4.1 Test Channel

According to ANSI C63.26-2015 chapter 5.1.2.1 Table 2 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:


LTE band 2					
Channels		Frequency (MHz)	Channels		Frequency (MHz)
1.4 MHz			3 MHz		
Lowest channel	18607	1850.7	Lowest channel	18915	1851.5
Middle channel	18900	1880.0	Middle channel	18900	1880.0
Highest channel	19193	1909.3	Highest channel	19185	1908.5
5 MHz			10 MHz		
Lowest channel	18625	1852.5	Lowest channel	18650	1855.0
Middle channel	18900	1880.0	Middle channel	18900	1880.0
Highest channel	19175	1907.5	Highest channel	19150	1905.0
15 MHz			20 MHz		
Lowest channel	18675	1857.5	Lowest channel	18700	1860.0
Middle channel	18900	1880.0	Middle channel	18900	1880.0
Highest channel	19125	1902.5	Highest channel	19100	1900.0
LTE band 4					
Channels		Frequency (MHz)	Channels		Frequency (MHz)
1.4 MHz			3 MHz		
Lowest channel	19957	1710.7	Lowest channel	19965	1711.5
Middle channel	20175	1732.5	Middle channel	20175	1732.5
Highest channel	20393	1754.3	Highest channel	20385	1753.5
5 MHz			10 MHz		
Lowest channel	19975	1712.5	Lowest channel	20000	1715.0
Middle channel	20175	1732.5	Middle channel	20175	1732.5
Highest channel	20375	1752.5	Highest channel	20350	1750.0
15 MHz			20 MHz		
Lowest channel	20025	1717.5	Lowest channel	20050	1720.0
Middle channel	20175	1732.5	Middle channel	20175	1732.5
Highest channel	20325	1747.5	Highest channel	20300	1745.0
LTE band 5					
Channels		Frequency (MHz)	Channels		Frequency (MHz)
1.4 MHz			3 MHz		
Lowest channel	20407	824.7	Lowest channel	20415	825.5
Middle channel	20525	836.5	Middle channel	20525	836.5
Highest channel	20643	848.3	Highest channel	20635	847.5
5 MHz			10 MHz		
Lowest channel	20425	826.5	Lowest channel	20450	829.0
Middle channel	20525	836.5	Middle channel	20525	836.5
Highest channel	20625	846.5	Highest channel	20600	844.0

LTE band 7					
Channels		Frequency (MHz)	Channels		Frequency (MHz)
5 MHz			10 MHz		
Lowest channel	20775	2502.5	Lowest channel	20800	2505.0
Middle channel	21100	2535.0	Middle channel	21100	2535.0
Highest channel	21425	2567.5	Highest channel	21400	2565.0
15 MHz			20 MHz		
Lowest channel	20825	2507.5	Lowest channel	20850	2510.0
Middle channel	21100	2535.0	Middle channel	21100	2535.0
Highest channel	21375	2562.5	Highest channel	21350	2560.0
LTE band 12					
Channels		Frequency (MHz)	Channels		Frequency (MHz)
1.4 MHz			3 MHz		
Lowest channel	23017	699.70	Lowest channel	23025	700.50
Middle channel	23095	707.50	Middle channel	23095	707.50
Highest channel	23173	715.30	Highest channel	23165	714.50
5 MHz			10 MHz		
Lowest channel	23035	701.50	Lowest channel	23060	704.00
Middle channel	23095	707.50	Middle channel	23095	707.50
Highest channel	23155	713.50	Highest channel	23130	711.00
LTE band 17					
5 MHz			10 MHz		
Lowest channel	23755	706.50	Lowest channel	23780	709.00
Middle channel	23790	710.00	Middle channel	23790	710.00
Highest channel	23825	713.50	Highest channel	23800	711.00


4.2 Test Setup

1) Radiated emission measurement:

Below 1GHz (3m SAC)



Above 1GHz (3m FAR)



4.3 Test Procedure

Test method	Test step
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

This report was amended on FCC ID: O551001923 follow FCC Class II Permissive Change. The original report: JYTSZ-R12-2500287, issued by JianYan Testing Group Shenzhen Co., Ltd. The differences between them as below: Update the 234G and BT&WIFI antenna, update the screen and screen backlight, update the battery, speaker, USB Cable and the adapter.

So need to retest spurious radiation.

Test items	Standard clause	Test data	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
RF Output Power	Part 2.1046 Part 22.913 (a)(5) Part 24.232 (c) Part 27.50 (c)(10) Part 27.50 (d)(4) Part 27.50 (h)(2)	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
Peak-to-Average Power Ratio	Part 24.232 (d) Part 27.50 (d)(5)	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
Modulation Characteristics	Part 2.1047	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
26dB Emission Bandwidth 99% Occupied Bandwidth	Part 2.1049	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
Out of Band Emission at Antenna Terminals	Part 2.1051 Part 22.917 (a) Part 24.238 (a) Part 27.53 (g) Part 27.53 (h) Part 27.53 (m)(4)	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a) Part 27.53 (g) Part 27.53 (h) Part 27.53 (m)(4)	See Section 5.2	Pass
Frequency Stability vs. Temperature	Part 2.1055 (a)(1)(b) Part 22.355 Part 24.235 Part 27.54	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.
Frequency Stability vs. Voltage	Part 2.1055 (d)(2) Part 22.355 Part 24.235 Part 27.54	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.	Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287.

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (Fundamental Frequency below 1GHz)/1.0dB (Fundamental Frequency above 1GHz) (provided by the customer).
3. Please refer to FCC ID: O551001923, report No.: JYTSZ-R12-2500287 issued by JianYan Testing Group Shenzhen Co., Ltd.

Test Method:

ANSI/TIA-603-E-2016
ANSI C63.26-2015

5.1.2 Test Limit

Test items	Limit
Out of Band Emission at Antenna Terminals Field Strength of Spurious Radiation	LTE band 2, 4, 5, 12, 17: The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. LTE band 7: For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.

5.2 Field Strength of Spurious Radiation Measurement

Note: All bandwidths, modulation types and RB configurations were pretested, and it was found that minimum bandwidths, QPSK modulation and 1RB0 were the worst modes, and only the worst modes were reflected in the report.

LTE band 2 – 1.4 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3701.40	-51.27	-0.36	-51.63	-13.00	38.63	Vertical
5552.10	-55.07	4.16	-50.91	-13.00	37.91	Vertical
7402.00	-61.68	6.10	-55.58	-13.00	42.58	Vertical
3701.40	-54.08	-0.17	-54.25	-13.00	41.25	Horizontal
5552.10	-53.38	4.07	-49.31	-13.00	36.31	Horizontal
7402.00	-63.09	5.78	-57.31	-13.00	44.31	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-50.18	-1.01	-51.19	-13.00	38.19	Vertical
5640.00	-54.47	3.96	-50.51	-13.00	37.51	Vertical
7520.00	-61.79	5.55	-56.24	-13.00	43.24	Vertical
3760.00	-54.20	-0.56	-54.76	-13.00	41.76	Horizontal
5640.00	-53.32	4.14	-49.18	-13.00	36.18	Horizontal
7520.00	-63.57	5.56	-58.01	-13.00	45.01	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3816.60	-51.29	-0.59	-51.88	-13.00	38.88	Vertical
5724.90	-55.49	3.42	-52.07	-13.00	39.07	Vertical
7633.20	-61.32	6.40	-54.92	-13.00	41.92	Vertical
3816.60	-54.26	-0.10	-54.36	-13.00	41.36	Horizontal
5724.90	-53.71	3.80	-49.91	-13.00	36.91	Horizontal
7633.20	-63.92	6.24	-57.68	-13.00	44.68	Horizontal
Remark:						
1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

LTE band 4 – 1.4 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.40	-56.31	-2.15	-58.46	-13.00	45.46	Vertical
5132.10	-63.77	3.80	-59.97	-13.00	46.97	Vertical
6842.80	-45.03	5.86	-39.17	-13.00	26.17	Vertical
3421.40	-63.28	-2.22	-65.50	-13.00	52.50	Horizontal
5132.10	-61.68	3.86	-57.82	-13.00	44.82	Horizontal
6842.80	-49.48	6.07	-43.41	-13.00	30.41	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.00	-55.25	-2.54	-57.79	-13.00	44.79	Vertical
5197.50	-63.05	3.25	-59.80	-13.00	46.80	Vertical
6930.00	-44.43	5.20	-39.23	-13.00	26.23	Vertical
3465.00	-62.26	-2.54	-64.80	-13.00	51.80	Horizontal
5197.50	-60.80	3.17	-57.63	-13.00	44.63	Horizontal
6930.00	-48.60	5.17	-43.43	-13.00	30.43	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.60	-55.96	-3.13	-59.09	-13.00	46.09	Vertical
5262.90	-63.79	3.11	-60.68	-13.00	47.68	Vertical
7017.20	-45.51	5.74	-39.77	-13.00	26.77	Vertical
3508.60	-63.15	-2.96	-66.11	-13.00	53.11	Horizontal
5262.90	-61.66	3.46	-58.20	-13.00	45.20	Horizontal
7017.20	-49.52	5.80	-43.72	-13.00	30.72	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

LTE band 5 – 1.4 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1649.40	-48.12	-11.51	-59.63	-13.00	46.63	Vertical
2474.10	-40.21	-8.67	-48.88	-13.00	35.88	Vertical
3298.80	-25.61	-3.89	-29.50	-13.00	16.50	Vertical
1649.40	-50.85	-10.85	-61.70	-13.00	48.70	Horizontal
2474.10	-41.81	-9.13	-50.94	-13.00	37.94	Horizontal
3298.80	-34.02	-3.96	-37.98	-13.00	24.98	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.30	-47.23	-10.70	-57.93	-13.00	44.93	Vertical
2509.50	-39.18	-8.66	-47.84	-13.00	34.84	Vertical
3346.00	-24.76	-3.33	-28.09	-13.00	15.09	Vertical
1673.30	-50.05	-10.28	-60.33	-13.00	47.33	Horizontal
2509.50	-40.88	-8.73	-49.61	-13.00	36.61	Horizontal
3346.00	-33.00	-3.42	-36.42	-13.00	23.42	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1696.60	-48.21	-9.90	-58.11	-13.00	45.11	Vertical
2544.90	-39.84	-8.45	-48.29	-13.00	35.29	Vertical
3393.20	-25.37	-2.59	-27.96	-13.00	14.96	Vertical
1696.60	-50.83	-9.70	-60.53	-13.00	47.53	Horizontal
2544.90	-41.46	-8.21	-49.67	-13.00	36.67	Horizontal
3393.20	-33.65	-2.65	-36.30	-13.00	23.30	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

LTE band 7 – 5 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
5005.00	-58.56	3.69	-54.87	-25.00	29.87	Vertical
7507.50	-56.97	5.56	-51.41	-25.00	26.41	Vertical
10010.00	-60.55	10.09	-50.46	-25.00	25.46	Vertical
5005.00	-58.32	4.02	-54.30	-25.00	29.30	Horizontal
7507.50	-54.45	5.56	-48.89	-25.00	23.89	Horizontal
10010.00	-66.11	9.47	-56.64	-25.00	31.64	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070.00	-57.48	4.23	-53.25	-25.00	28.25	Vertical
7605.00	-56.07	6.06	-50.01	-25.00	25.01	Vertical
10140.00	-59.78	10.48	-49.30	-25.00	24.30	Vertical
5070.00	-57.73	3.51	-54.22	-25.00	29.22	Horizontal
7605.00	-53.87	5.95	-47.92	-25.00	22.92	Horizontal
10140.00	-65.20	10.21	-54.99	-25.00	29.99	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
5135.00	-58.13	3.78	-54.35	-25.00	29.35	Vertical
7702.50	-57.11	6.22	-50.89	-25.00	25.89	Vertical
10270.00	-60.37	11.48	-48.89	-25.00	23.89	Vertical
5135.00	-58.57	3.83	-54.74	-25.00	29.74	Horizontal
7702.50	-54.66	5.97	-48.69	-25.00	23.69	Horizontal
10270.00	-66.04	11.00	-55.04	-25.00	30.04	Horizontal
Remark:						
1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

LTE band 12 – 1.4 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1399.40	-51.50	-11.68	-63.18	-13.00	50.18	Vertical
2099.10	-42.43	-9.89	-52.32	-13.00	39.32	Vertical
2798.80	-62.44	-7.09	-69.53	-13.00	56.53	Vertical
1399.40	-49.06	-11.43	-60.49	-13.00	47.49	Horizontal
2099.10	-41.59	-9.44	-51.03	-13.00	38.03	Horizontal
2798.80	-62.68	-6.71	-69.39	-13.00	56.39	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.00	-50.69	-11.77	-62.46	-13.00	49.46	Vertical
2122.50	-41.45	-9.58	-51.03	-13.00	38.03	Vertical
2830.00	-61.47	-6.50	-67.97	-13.00	54.97	Vertical
1415.00	-48.26	-11.45	-59.71	-13.00	46.71	Horizontal
2122.50	-40.74	-8.86	-49.60	-13.00	36.60	Horizontal
2830.00	-61.71	-5.97	-67.68	-13.00	54.68	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1430.60	-51.37	-11.92	-63.29	-13.00	50.29	Vertical
2145.90	-42.04	-9.51	-51.55	-13.00	38.55	Vertical
2861.20	-62.46	-5.55	-68.01	-13.00	55.01	Vertical
1430.60	-49.21	-11.66	-60.87	-13.00	47.87	Horizontal
2145.90	-41.79	-9.15	-50.94	-13.00	37.94	Horizontal
2861.20	-62.70	-5.44	-68.14	-13.00	55.14	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

LTE band 17 – 5 MHz bandwidth						
Lowest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1413.00	-46.39	-12.29	-58.68	-13.00	45.68	Vertical
2119.50	-38.88	-9.97	-48.85	-13.00	35.85	Vertical
2826.00	-61.88	-7.59	-69.47	-13.00	56.47	Vertical
1413.00	-40.15	-11.98	-52.13	-13.00	39.13	Horizontal
2119.50	-40.83	-9.21	-50.04	-13.00	37.04	Horizontal
2826.00	-62.05	-7.02	-69.07	-13.00	56.07	Horizontal
Middle channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1420.00	-46.39	-12.41	-58.80	-13.00	45.80	Vertical
2130.00	-38.88	-9.81	-48.69	-13.00	35.69	Vertical
2840.00	-61.88	-6.98	-68.86	-13.00	55.86	Vertical
1420.00	-40.15	-12.07	-52.22	-13.00	39.22	Horizontal
2130.00	-40.83	-9.20	-50.03	-13.00	37.03	Horizontal
2840.00	-62.05	-6.59	-68.64	-13.00	55.64	Horizontal
Highest channel						
Frequency (MHz)	Reading Level (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Polarization
1427.00	-46.39	-12.46	-58.85	-13.00	45.85	Vertical
2140.50	-38.88	-9.69	-48.57	-13.00	35.57	Vertical
2854.00	-61.88	-7.47	-69.35	-13.00	56.35	Vertical
1427.00	-40.15	-12.16	-52.31	-13.00	39.31	Horizontal
2140.50	-40.83	-9.24	-50.07	-13.00	37.07	Horizontal
2854.00	-62.05	-7.27	-69.32	-13.00	56.32	Horizontal
Remark: 1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report.						

-----End of report-----