

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	32.75	30.4	38.45	PASS
GSM850	190	5	33.03	30.68	38.45	PASS
GSM850	251	5	32.88	30.53	38.45	PASS
GSM1900	512	0	29.88	30.38	33.00	PASS
GSM1900	661	0	30.05	30.55	33.00	PASS
GSM1900	810	0	30.22	30.72	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	32.74	30.39	38.45	PASS
GPRS850	128	5	2	30.37	28.02	38.45	PASS
GPRS850	128	5	3	28.57	26.22	38.45	PASS
GPRS850	128	5	4	26.59	24.24	38.45	PASS
GPRS850	190	5	1	33.00	30.65	38.45	PASS
GPRS850	190	5	2	30.70	28.35	38.45	PASS
GPRS850	190	5	3	28.87	26.52	38.45	PASS
GPRS850	190	5	4	26.85	24.5	38.45	PASS
GPRS850	251	5	1	32.85	30.5	38.45	PASS
GPRS850	251	5	2	30.65	28.3	38.45	PASS
GPRS850	251	5	3	28.84	26.49	38.45	PASS
GPRS850	251	5	4	26.72	24.37	38.45	PASS
GPRS1900	512	0	1	29.85	30.35	33.00	PASS
GPRS1900	512	0	2	27.48	27.98	33.00	PASS
GPRS1900	512	0	3	25.78	26.28	33.00	PASS
GPRS1900	512	0	4	23.76	24.26	33.00	PASS
GPRS1900	661	0	1	30.01	30.51	33.00	PASS
GPRS1900	661	0	2	27.66	28.16	33.00	PASS
GPRS1900	661	0	3	25.98	26.48	33.00	PASS
GPRS1900	661	0	4	23.97	24.47	33.00	PASS
GPRS1900	810	0	1	30.21	30.71	33.00	PASS
GPRS1900	810	0	2	27.70	28.2	33.00	PASS
GPRS1900	810	0	3	26.00	26.5	33.00	PASS
GPRS1900	810	0	4	24.03	24.53	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)

JianYan Testing Group Shenzhen Co., Ltd.

No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2503028


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.74	13	PASS
GSM1900	661	0	2.69	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs




Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24357	0.3124	---	PASS
GSM850	190	5	0.24160	0.3046	---	PASS
GSM850	251	5	0.24082	0.3020	---	PASS
GSM1900	512	0	0.24203	0.3072	---	PASS
GSM1900	661	0	0.24173	0.3096	---	PASS
GSM1900	810	0	0.24157	0.3042	---	PASS

Test Graphs




Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	824.00	-23.95	-13	PASS
GSM850	251	5	849.02	-24.21	-13	PASS
GSM1900	512	0	1850.00	-13.79	-13	PASS
GSM1900	810	0	1910.02	-13.18	-13	PASS

Test Graphs




Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-53.83	-33	PASS
GSM850	128	5	0.15~30MHz	0.16	-41.87	-13	PASS
GSM850	128	5	30~1000MHz	934.91	-45.02	-13	PASS
GSM850	128	5	1000~10000MHz	1648.6	-29.48	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-54.28	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-42.65	-13	PASS
GSM850	190	5	30~1000MHz	697.26	-45.4	-13	PASS
GSM850	190	5	1000~10000MHz	2509.6	-29.83	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-54.89	-33	PASS
GSM850	251	5	0.15~30MHz	0.17	-41.59	-13	PASS
GSM850	251	5	30~1000MHz	985.35	-44.96	-13	PASS
GSM850	251	5	1000~10000MHz	1697.8	-29.65	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-56.36	-43	PASS
GSM1900	512	0	0.15~30MHz	0.16	-42.21	-23	PASS
GSM1900	512	0	30~1000MHz	926.57	-45.3	-13	PASS
GSM1900	512	0	1000~18000MHz	16993.03	-21.92	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-56.11	-43	PASS
GSM1900	661	0	0.15~30MHz	0.15	-41.98	-23	PASS
GSM1900	661	0	30~1000MHz	787.6	-45.69	-13	PASS
GSM1900	661	0	1000~18000MHz	16149.27	-22.02	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-56.88	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-42.72	-23	PASS
GSM1900	810	0	30~1000MHz	668.97	-45.75	-13	PASS
GSM1900	810	0	1000~18000MHz	16764.1	-22.07	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2503028







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	-2.91	-0.003478	±2.5	Pass
	-20	-1.42	-0.001697		
	-10	-2.45	-0.002929		
	0	8.33	0.009957		
	10	6.55	0.007829		
	20	8.81	0.010531		
	30	-1.68	-0.002008		
	40	-1.58	-0.001889		
	50	-3.87	-0.004626		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	9.04	0.010806	±2.5	Pass
	3.70	8.17	0.009766		
	4.20	-3.84	-0.004590		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.70	-30	10.85	0.005771	Within authorized band for PCS 1900	Pass
	-20	1.49	0.000793		
	-10	4.49	0.002388		
	0	4.00	0.002128		
	10	-1.58	-0.000840		
	20	-0.52	-0.000277		
	30	-5.13	-0.002729		
	40	-9.04	-0.004809		
	50	-7.26	-0.003862		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.50	-0.19	-0.000101	Within authorized band for PCS 1900	Pass
	3.70	2.26	0.001202		
	4.20	7.10	0.003777		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
GSM1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

