



FCC PART 22H, PART 24E

TEST REPORT

For

SWAGTEK

10205 NW 19th Street, STE 101, Miami, FL33172, United States

FCC ID: O55401417

Report Type: Original Report	Product Type: 4 inch Smart Phone
Report Number: RSZ170410002-00D	
Report Date: 2017-06-23	
Oscar Ye	
Reviewed By:	Engineer
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH	15
APPLICABLE STANDARD	15
TEST PROCEDURE	15
TEST DATA	15
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	39

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The SWAGTEK's product, model number: X4V (FCC ID: O55401417, Brand: LOGIC, iSWAG,) or the "EUT" in this report was a 4 inch Smart Phone, which was measured approximately: 12.4 cm (L) × 6.5 cm (W) × 1.07 cm (H), rated with input voltage: DC 3.7V rechargeable Li-ion battery or DC 5.0V from adapter.

Adapter Information:

Input: AC100-240V, 50/60Hz, 0.2 A

Output: DC5.0V, 700mA

Notes: This series products model: LOGIC X4V, iSWAG Univrs, iSWAG Univrs-T, UNONU UM 400 and X4V are identical; they have the identical schematics, only named differently. Model X4V was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: 1700635 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-04-10.*

Objective

This type approval report is prepared on behalf of SWAGTEK in accordance with Part 2, Part 22-Subpart H, Part 24-Subpart E of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS & DTS submissions with FCC ID: O55401417.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
RF conducted test with spectrum		$\pm 0.9\text{dB}$
Radiated emission	30MHz~1GHz	$\pm 5.91\text{dB}$
	Above 1G	$\pm 4.92\text{dB}$
Occupied Bandwidth		$\pm 0.5\text{kHz}$
Temperature		$\pm 1.0^{\circ}\text{C}$
Humidity		$\pm 6\%$

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ170410002-20.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrument	Amplifier	330	171377	2016-10-21	2017-10-21
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2019-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
WEINSCHEL	3dB Attenuator	5326	N/A	2016-06-18	2017-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2016-06-12	2017-06-12

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ170410002-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.


FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER**Applicable Standard**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

Test Procedure*Conducted method:*

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.

*Radiated method:*

TIA 603-D section 2.2.17

Test Data**Environmental Conditions**

Temperature:	25.5 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Alisa Gao on 2017-05-04.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.53	38.45
	190	836.6	32.53	38.45
	251	848.8	32.52	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.55	30.72	28.86	27.36	38.45
	190	836.6	32.54	30.71	28.84	27.33	38.45
	251	848.8	32.54	30.67	28.79	27.25	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.08	22.13	22.07
		HSDPA	1	20.95	21.69	20.97
			2	20.90	21.57	20.86
			3	21.01	21.80	21.01
			4	20.90	21.59	20.84
		HSUPA	1	21.24	21.51	20.90
			2	21.14	21.43	20.81
			3	21.34	21.63	20.97
			4	21.18	21.48	20.87
			5	21.36	21.62	20.96

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.83	33
	661	1880.0	29.62	33
	810	1909.8	29.29	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	29.85	27.34	25.80	24.17	33
	661	1880.0	29.64	27.14	25.58	23.98	33
	810	1909.8	29.28	26.74	25.13	23.46	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.57	22.31	21.95
		HSDPA	1	20.85	20.85	20.61
			2	20.79	20.77	20.53
			3	20.96	20.94	20.68
			4	20.78	20.77	20.49
		HSUPA	1	21.00	21.62	20.96
			2	20.87	21.54	20.86
			3	21.12	21.65	21.08
			4	20.90	21.53	20.83
			5	21.05	21.66	21.06

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.44	13
	Middle	0.38	13
	High	0.42	13

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	3.78	13
	Middle	3.63	13
	High	3.74	13
HSDPA (16QAM)	Low	3.72	13
	Middle	3.68	13
	High	3.74	13
HSUPA (BPSK)	Low	3.75	13
	Middle	3.69	13
	High	3.71	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.49	13
	Middle	0.34	13
	High	0.49	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.47	13
	Middle	3.37	13
	High	3.41	13
HSDPA (16QAM)	Low	3.48	13
	Middle	3.35	13
	High	3.43	13
HSUPA (BPSK)	Low	3.45	13
	Middle	3.34	13
	High	3.46	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	95.12	22	2.4	H	24.9	0.26	4.75	29.39	38.45	9.06
836.6	87.14	223	2.0	V	12.9	0.26	4.75	17.39	38.45	21.06
EIRP for PCS Band (Part 24E), Low Channel										
1850.20	80.08	34	1.5	H	18.6	0.45	8.84	26.99	33	6.01
1850.20	75.97	195	2.0	V	12.3	0.45	8.84	20.69	33	12.31

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	85.92	78	1.7	H	15.7	0.26	4.75	20.19	38.45	18.26
836.6	84.04	159	1.1	V	9.8	0.26	4.75	14.29	38.45	24.16
EIRP for WCDMA Band II (Part 24E), Low Channel										
1852.40	74.99	166	2.2	H	13.5	0.45	8.84	21.89	33	11.11
1852.40	73.52	9	2.1	V	9.8	0.45	8.84	18.19	33	14.81

Note:

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH**Applicable Standard**

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (GSM) & 100 kHz (WCDMA) and the 26 dB & 99% bandwidth was recorded.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	103.0 kPa

The testing was performed by Alisa Gao on 2017-04-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	316.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.108	4.669
HSUPA (BPSK)	836.6	4.108	4.810
HSDPA (16QAM)	836.6	4.088	4.669


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	252.5	324.6


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.108	4.689
HSUPA (BPSK)	1880.0	4.108	4.729
HSDPA (16QAM)	1880.0	4.088	4.729

Cellular Band (Part 22H)


99% Occupied Bandwidth & 26 dB Emissions Bandwidth for GSM (GMSK) Mode




99% Occupied Bandwidth & 26 dB Emissions Bandwidth for RMC (BPSK) Mode



99% Occupied Bandwidth & 26 dB Emissions Bandwidth for HSUPA (BPSK) Mode




99% Occupied Bandwidth & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode




PCS Band (Part 24E)

99% Occupied Bandwidth & 26 dB Emissions Bandwidth for GSM (GMSK) Mode



99% Occupied Bandwidth & 26 dB Emissions Bandwidth for RMC (BPSK) Mode



Ref Lvl 35.5 dBm

Marker 1 [T1] -4.69 dBm

RBW 100 kHz

VBW 300 kHz

RF Att 40 dB

SWT 200 ms

Unit dBm

7.5 dB Offset

D1 19.36 dBm

D2 -6.64 dBm

1MAX

Marker 1 [T1] -4.69 dBm

1.87764529 GHz

4.10821643 MHz

1.87792585 GHz

16.86 dBm

1.88203407 GHz

-2.76 dB

4.72945892 MHz

Center 1.88 GHz

1 MHz/

Span 10 MHz

Date: 20.MAY.2017 11:11:31

Ref Lvl 37.5 dBm Marker 1 [T1] -5.03 dBm RBW 100 kHz RF Att 40 dB
 37.5 dBm 1.87762525 GHz VBW 300 kHz Unit dBm

7.5 dB Offset

1MAX

D1 18.93 dBm

D2 -7.07 dBm

1

1 [T1] -5.03 dBm

OPB 4.08817635 MHz

1 [T1] 9.14 dBm

1.87794589 GHz

1 [T1] 16.57 dBm

1.88203407 GHz

1 [T1] -4.17 dB

4.72945892 MHz

1MA

Center 1.88 GHz 1 MHz/ Span 10 MHz

Date: 20.APR.2017 14:42:07

FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	23-25 °C
Relative Humidity:	48-55 %
ATM Pressure:	100.0-103.0 kPa


The testing was performed by Alisa Gao on 2017-04-20 and 2017-05-26.

EUT operation mode: Transmitting

Test result: Compliance, please refer to the following plots.


Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Fundamental test


1 GHz – 10 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)




PCS Band (Part 24E)


30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)




2 GHz – 20 GHz (GSM Mode)




30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 2 GHz (WCDMA Mode)



2 GHz – 20 GHz (WCDMA Mode)



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS**Applicable Standard**

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2017-04-20.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:**Cellular Band (Part 22H)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
236.54	45.55	186	2.0	H	-62.5	0.14	2.05	-60.59	-13	47.59
236.54	44.49	2	1.2	V	-64.0	0.14	2.05	-62.09	-13	49.09
1673.20	52.30	76	1.4	H	-49.5	0.40	8.52	-41.38	-13	28.38
1673.20	56.97	198	1.1	V	-46.8	0.40	8.52	-38.68	-13	25.68
WCDMA Mode, Middle channel										
242.35	45.45	25	1.3	H	-62.6	0.14	2.05	-60.69	-13	47.69
242.35	44.69	202	2.0	V	-63.8	0.14	2.05	-61.89	-13	48.89
1673.20	45.40	325	1.8	H	-56.4	0.40	8.52	-48.28	-13	35.28
1673.20	50.57	262	1.5	V	-53.2	0.40	8.52	-45.08	-13	32.08

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Low channel										
236.54	45.35	152	2.5	H	-62.7	0.14	2.05	-60.79	-13	47.79
236.54	44.69	324	1.8	V	-63.8	0.14	2.05	-61.89	-13	48.89
3700.40	41.56	58	1.8	H	-54.8	0.58	9.78	-45.6	-13	32.6
3700.40	42.03	283	1.0	V	-55.5	0.58	9.78	-46.3	-13	33.3
WCDMA Mode, Low channel										
242.35	45.65	106	2.4	H	-62.4	0.14	2.05	-60.49	-13	47.49
242.35	44.49	127	2.0	V	-64.0	0.14	2.05	-62.09	-13	49.09
3704.80	50.36	283	1.2	H	-46.0	0.58	9.78	-36.8	-13	23.8
3704.80	48.73	14	1.3	V	-48.8	0.58	9.78	-39.6	-13	26.6

Note:

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Data



Environmental Conditions



Temperature:	23~26 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.0~103.0 kPa

The testing was performed by Alisa Gao on 2017-04-20 and 2017-05-20.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following plots.


Cellular Band, Left Band Edge for GSM (GMSK) Mode**Cellular Band, Right Band Edge for GSM (GMSK) Mode**

Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**


Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode




PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode



PCS Band, Right Band Edge for HSDPA (16QAM) Mode



PCS Band, Left Band Edge for HSUPA (BPSK) Mode



PCS Band, Right Band Edge for HSUPA (BPSK) Mode



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055, §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	23 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Alisa Gao on 2017-04-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-6	-0.00717	2.5
-20		-6	-0.00717	2.5
-10		-6	-0.00717	2.5
0		-3	-0.00359	2.5
10		-3	-0.00359	2.5
20		-1	-0.00120	2.5
30		-2	-0.00239	2.5
40		-4	-0.00478	2.5
50		-5	-0.00598	2.5
25	V _{min} = 3.5	-9	-0.01076	2.5
25	V _{max} = 4.2	-12	-0.01434	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-7	-0.00837	2.5
-20		-7	-0.00837	2.5
-10		-4	-0.00478	2.5
0		-4	-0.00478	2.5
10		-3	-0.00359	2.5
20		-1	-0.00120	2.5
30		-2	-0.00239	2.5
40		-3	-0.00359	2.5
50		-5	-0.00598	2.5
25	V _{min} = 3.5	-6	-0.00717	2.5
25	V _{max} = 4.2	-9	-0.01076	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-7	-0.00372	pass
-20		-7	-0.00372	pass
-10		-7	-0.00372	pass
0		-3	-0.00160	pass
10		-3	-0.00160	pass
20		-1	-0.00053	pass
30		-2	-0.00106	pass
40		-5	-0.00266	pass
50		-9	-0.00479	pass
25	V _{min.} = 3.5	-12	-0.00638	pass
25	V _{max.} = 4.2	-14	-0.00745	pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-9	-0.00479	Pass
-20		-9	-0.00479	Pass
-10		-5	-0.00266	Pass
0		-5	-0.00266	Pass
10		-5	-0.00266	Pass
20		3	0.00160	Pass
30		-2	-0.00106	Pass
40		-6	-0.00319	Pass
50		-7	-0.00372	Pass
25	V _{min.} = 3.5	-15	-0.00798	Pass
25	V _{max.} = 4.2	-21	-0.01117	pass

******* END OF REPORT *******