



# FCC RF Test Report

**APPLICANT** : Lenovo (Shanghai) Electronics Technology Co., Ltd.  
**EQUIPMENT** : Tablet PC  
**BRAND NAME** : Vodafone  
**MODEL NAME** : Smart Tab III<sup>7</sup>  
**MARKETING NAME** : Vodafone Smart Tab III7  
**FCC ID** : O57A3000VDF3G  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)

The product was received on Feb. 27, 2013 and completely tested on Jun. 18, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test ..... 6

    1.5 Modification of EUT ..... 6

    1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator ..... 7

    1.7 Testing Site ..... 7

    1.8 Applied Standards ..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Test Mode..... 8

    2.2 Connection Diagram of Test System ..... 9

    2.3 Support Unit used in test configuration and system..... 10

    2.4 Measurement Results Explanation Example ..... 10

**3 TEST RESULT..... 11**

    3.1 Conducted Output Power Measurement..... 11

    3.2 Peak-to-Average Ratio ..... 13

    3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement ..... 21

    3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 27

    3.5 Band Edge Measurement..... 47

    3.6 Conducted Spurious Emission Measurement..... 60

    3.7 Field Strength of Spurious Radiation Measurement ..... 76

    3.8 Frequency Stability Measurement..... 94

**4 LIST OF MEASURING EQUIPMENT ..... 99**

**5 UNCERTAINTY OF EVALUATION ..... 100**

**APPENDIX A. PHOTOGRAPHS OF EUT**

**APPENDIX B. SETUP PHOTOGRAPHS**





## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a)	99% Occupied Bandwidth and 26dB Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 13.47 dB at 5640.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

# 1 General Description

## 1.1 Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.

No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ, Shanghai, China

## 1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	Vodafone
Model Name	Smart Tab III <sup>7</sup>
Marketing Name	Vodafone Smart Tab III7
FCC ID	O57A3000VDF3G
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/ WLAN 11bgn/Bluetooth/Bluetooth 4.0 - LE
HW Version	H402
SW Version	A3000-S3
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GPRS850: 824.2 MHz ~ 848.8 MHz GPRS1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
<b>Rx Frequency</b>	GPRS850: 869.2 MHz ~ 893.8 MHz GPRS1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
<b>Maximum Output Power to Antenna</b>	GPRS850 : 31.55 dBm GPRS1900 : 29.47 dBm WCDMA Band V : 22.24 dBm WCDMA Band II : 22.37 dBm
<b>Antenna Type</b>	Fixed Internal Antenna
<b>Type of Modulation</b>	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Uplink) DC-HSDPA: 64QAM (Downlink Only)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GPRS850 GPRS 8	GMSK	0.7834	0.07 ppm	246KGXW
Part 22	GPRS850 EDGE 8	8PSK	0.2239	0.07 ppm	242KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1358	0.08 ppm	4M18F9W
Part 24	GPRS1900 GPRS 8	GMSK	0.6761	0.08 ppm	248KGXW
Part 24	GPRS1900 EDGE 8	8PSK	0.3027	0.08 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2094	0.08 ppm	4M18F9W

## 1.7 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	TH01-KS	03CH01-KS	149928/4086E-1

## 1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (Z plane).

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GPRS850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GPRS1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GPRS 850	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>
GPRS 1900	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS 8 Link</li> <li>■ EDGE 8 Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>


**Note:** The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GPRS850			GPRS1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1 Tx slot) – CS1	31.35	31.53	31.55	29.16	29.47	29.26
GPRS (GMSK, 2 Tx slots) – CS1	28.98	29.13	29.16	26.50	26.79	26.63
GPRS (GMSK, 3 Tx slots) – CS1	27.38	27.55	27.59	24.95	25.17	25.06
GPRS (GMSK, 4 Tx slots) – CS1	26.12	26.32	26.36	23.78	24.09	23.91
EDGE (8PSK, 1 Tx slot) – MCS5	26.48	26.10	25.97	25.48	25.44	24.95
EDGE (8PSK, 2 Tx slots) – MCS5	22.93	22.63	22.50	21.95	21.91	21.60
EDGE (8PSK, 3 Tx slots) – MCS5	20.93	20.53	20.44	19.85	19.66	19.04
EDGE (8PSK, 4 Tx slots) – MCS5	19.50	19.15	19.04	18.72	18.35	17.74

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.24	22.18	22.12	22.23	22.35	22.37
HSDPA Subtest-1	22.15	22.10	21.94	22.13	22.18	22.23
HSDPA Subtest-2	22.14	22.08	21.94	22.11	22.15	22.23
HSDPA Subtest-3	21.59	21.59	21.45	21.70	21.72	21.76
HSDPA Subtest-4	21.58	21.57	21.50	21.68	21.70	21.73
DC-HSDPA Subtest-1	22.19	22.20	22.15	22.50	21.44	21.74
DC-HSDPA Subtest-2	21.94	21.96	22.03	22.50	21.09	21.56
DC-HSDPA Subtest-3	21.46	21.52	21.49	22.00	20.92	21.06
DC-HSDPA Subtest-4	21.48	21.50	21.44	22.00	20.90	21.02
HSUPA Subtest-1	19.76	19.89	19.68	20.01	19.81	19.84
HSUPA Subtest-2	18.74	18.87	18.67	19.00	18.79	18.84
HSUPA Subtest-3	19.74	19.86	19.74	19.92	19.77	19.88
HSUPA Subtest-4	18.18	18.24	18.13	18.46	18.33	18.34
HSUPA Subtest-5	20.27	20.33	20.25	20.55	20.36	20.34
HSPA+ (16QAM) Subtest-1	20.45	20.48	20.44	19.70	20.02	20.40

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.2 + 10 = 15.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GPRS and maximum average power for other modulation signal.

##### 3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GPRS850 (GPRS 8)			GPRS850 (EDGE 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.35	31.53	31.55	26.48	26.10	25.97	22.24	22.18	22.12
Conducted Power (Watts)	1.36	1.42	1.43	0.44	0.41	0.40	0.17	0.17	0.16

PCS Band									
Modes	GPRS1900 (GPRS 8)			GPRS1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.16	29.47	29.26	25.48	25.44	24.95	22.23	22.35	22.37
Conducted Power (Watts)	0.82	0.89	0.84	0.35	0.35	0.31	0.17	0.17	0.17

Note: maximum burst average power for GPRS, and maximum average power for WCDMA.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
  - a. Set EUT in maximum power output.
  - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
  - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
  - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

### 3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GPRS1900 (GPRS 8)			GPRS1900 (EDGE 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.26	0.27	0.26	2.64	2.90	2.74	2.80	2.92	2.84




### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GPRS1900	Test Mode :	GPRS 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 8.APR.2013 10:41:14




Band :	GPRS1900	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 8.APR.2013 10:53:28


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 8.APR.2013 10:45:13



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 8.APR.2013 10:44:19



<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link
---------------	---------------	--------------------	-------------------

**Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)**




Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean	20.95 dBm
Peak	24.07 dBm
Crest	3.11 dB
10 %	1.68 dB
1 %	2.44 dB
.1 %	2.80 dB
.01 %	3.00 dB

Date: 12.MAR.2013 07:01:39

**Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)**



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean	21.51 dBm
Peak	24.70 dBm
Crest	3.19 dB
10 %	1.72 dB
1 %	2.48 dB
.1 %	2.92 dB
.01 %	3.12 dB

Date: 12.MAR.2013 07:00:52



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean 21.32 dBm  
 Peak 24.42 dBm  
 Crest 3.10 dB

10 % 1.72 dB  
 1 % 2.40 dB  
 .1 % 2.84 dB  
 .01 % 3.00 dB

Date: 12.MAR.2013 07:00:17

### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GPRS operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

$P_s$  (dBm) : Input power to substitution antenna.

$G_s$  (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

$R_t$  : The highest received signal in spectrum analyzer for EUT.

$R_s$  : The highest received signal in spectrum analyzer for substitution antenna.

### 3.3.4 Test Setup



3.3.5 Test Result of ERP

GPRS850 (GPRS 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-20.30	-48.12	0.00	-1.08	26.74	0.4721
836.40	-19.46	-48.28	0.00	-0.93	27.89	0.6152
848.80	-18.65	-48.35	0.00	-0.76	28.94	0.7834
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-20.95	-47.97	0.00	-1.08	25.94	0.3926
836.40	-19.94	-48.01	0.00	-0.93	27.14	0.5176
848.80	-19.16	-48.05	0.00	-0.76	28.13	0.6501

GPRS850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.14	-48.12	0.00	-1.08	22.90	0.1950
836.40	-24.22	-48.28	0.00	-0.93	23.13	0.2056
848.80	-24.09	-48.35	0.00	-0.76	23.50	0.2239
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.81	-47.97	0.00	-1.08	22.08	0.1614
836.40	-24.77	-48.01	0.00	-0.93	22.31	0.1702
848.80	-24.47	-48.05	0.00	-0.76	22.82	0.1914



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.33	-48.12	0.00	-1.08	19.71	0.0935
836.40	-26.02	-48.28	0.00	-0.93	21.33	0.1358
846.60	-26.97	-48.35	0.00	-0.76	20.62	0.1153
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.93	-47.97	0.00	-1.08	18.96	0.0787
836.40	-26.63	-48.01	0.00	-0.93	20.45	0.1109
846.60	-27.63	-48.05	0.00	-0.76	19.66	0.0925

3.3.6 Test Result of EIRP

GPRS1900 (GPRS 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.50	-51.88	0.00	1.96	27.34	0.5420
1880.00	-26.69	-52.99	0.00	2.00	28.30	0.6761
1909.80	-28.23	-54.28	0.00	1.98	28.03	0.6353
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.13	-52.13	0.00	1.96	26.96	0.4966
1880.00	-27.53	-53.17	0.00	2.00	27.64	0.5808
1909.80	-28.04	-54.13	0.00	1.98	28.07	0.6412

GPRS1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.33	-51.88	0.00	1.96	24.51	0.2825
1880.00	-30.18	-52.99	0.00	2.00	24.81	0.3027
1909.80	-32.06	-54.28	0.00	1.98	24.20	0.2630
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.08	-52.13	0.00	1.96	24.01	0.2518
1880.00	-31.25	-53.17	0.00	2.00	23.92	0.2466
1909.80	-32.20	-54.13	0.00	1.98	23.91	0.2460



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-30.63	-51.88	0.00	1.96	23.21	0.2094
1880.00	-32.41	-52.99	0.00	2.00	22.58	0.1811
1907.60	-34.54	-54.28	0.00	1.98	21.72	0.1486
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-31.36	-52.13	0.00	1.96	22.73	0.1875
1880.00	-33.28	-53.17	0.00	2.00	21.89	0.1545
1907.60	-34.23	-54.13	0.00	1.98	21.88	0.1542

### 3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

#### 3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, sample detector, trace maximum hold.

The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

#### 3.4.4 Test Setup



**3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth**

Cellular Band						
Modes	GPRS850 (GPRS 8)			GPRS850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	244.00	246.00	246.00	242.00	242.00	236.00
26dB BW (kHz)	318.00	316.00	314.00	290.00	280.00	290.00

PCS Band						
Modes	GPRS1900 (GPRS 8)			GPRS1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	246.00	248.00	246.00	246.00	242.00	246.00
26dB BW (kHz)	318.00	316.00	310.00	318.00	312.00	310.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.16	4.16
26dB BW (MHz)	4.68	4.70	4.68

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.18
26dB BW (MHz)	4.70	4.70	4.72

### 3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GPRS 850	Test Mode :	GPRS 8 Link
--------	----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 11.MAR.2013 12:09:59


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 11.MAR.2013 12:18:16




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 11.MAR.2013 12:26:02


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 11.MAR.2013 12:09:07




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 11.MAR.2013 11:52:54

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 11.MAR.2013 12:19:08




Band :	GPRS 850	Test Mode :	EDGE 8 Link
--------	----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 12.MAR.2013 03:59:53


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 12.MAR.2013 04:07:15




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 12.MAR.2013 04:00:19


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 12.MAR.2013 04:08:35




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 12.MAR.2013 04:00:45

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 12.MAR.2013 04:17:46




Band :	GPRS 1900	Test Mode :	GPRS 8 Link
--------	-----------	-------------	-------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 11.MAR.2013 13:02:00


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 11.MAR.2013 13:00:43




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 11.MAR.2013 12:35:14


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 11.MAR.2013 13:01:08




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 11.MAR.2013 13:02:52

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 11.MAR.2013 12:53:32






99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 12.MAR.2013 06:03:22


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 12.MAR.2013 06:02:03




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 12.MAR.2013 06:22:44

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 12.MAR.2013 06:21:08




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
--------	--------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 12.MAR.2013 04:39:15


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 12.MAR.2013 04:37:57




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 12.MAR.2013 05:01:34


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 12.MAR.2013 04:38:23




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 12.MAR.2013 04:40:07

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 12.MAR.2013 04:38:49




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
--------	---------------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 12.MAR.2013 06:54:42


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 12.MAR.2013 06:53:23




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 12.MAR.2013 06:55:08


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 12.MAR.2013 06:53:50




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 12.MAR.2013 06:55:34

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 12.MAR.2013 06:54:16

### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.


#### 3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RBW was replaced by 10 kHz, slightly smaller than the value in (2), due to the spectrum analyzer limitation to set the exact value. A worst case correction factor of  $10 \cdot \log (1\% \text{ emission-BW}/\text{measurement RBW})$  was compensated.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)
 
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


#### 3.5.4 Test Setup



### 3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GPRS850	Test Mode :	GPRS 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-17.72dBm	Measurement Value :	-17.97dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 11.MAR.2013 11:54:18

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
  2. Band Edge= Measurement Value + Correction Factor(dB)
- For example,  $-17.97\text{dBm} + 0.25\text{dB} = -17.72\text{dBm}$



Band :	GPRS850	Test Mode :	GPRS 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-17.93dBm	Measurement Value :	-18.18dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 11.MAR.2013 11:54:44

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS850	Test Mode :	EDGE 8 Link
Correction Factor :	-0.15dB	Maximum 26dB Bandwidth :	0.290MHz
Band Edge :	-24.72dBm	Measurement Value :	-24.57dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Date: 12.MAR.2013 04:02:11

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS850	Test Mode :	EDGE 8 Link
Correction Factor :	-0.15dB	Maximum 26dB Bandwidth :	0.290MHz
Band Edge :	-19.04dBm	Measurement Value :	-18.89dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 12.MAR.2013 04:02:38

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	GPRS 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-20.70dBm	Measurement Value :	-20.95dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 11.MAR.2013 12:37:04

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	GPRS 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-20.24dBm	Measurement Value :	-20.49dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 11.MAR.2013 12:37:30

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-24.28dBm	Measurement Value :	-24.53dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 12.MAR.2013 06:05:14

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	GPRS1900	Test Mode :	EDGE 8 Link
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-24.45dBm	Measurement Value :	-24.70dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 12.MAR.2013 06:05:40

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-29.57dBm	Measurement Value :	-26.29dBm

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Date: 12.MAR.2013 04:41:35

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.70MHz
Band Edge :	-26.79dBm	Measurement Value :	-23.51dBm

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 12.MAR.2013 04:42:02

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.72MHz
Band Edge :	-27.78dBm	Measurement Value :	-24.52dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)




Date: 12.MAR.2013 06:57:03

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)



Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link
Correction Factor :	-3.26dB	Maximum 26dB Bandwidth :	4.72MHz
Band Edge :	-26.47dBm	Measurement Value :	-23.21dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



Date: 12.MAR.2013 06:57:29

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

### 3.6 Conducted Spurious Emission Measurement

#### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

#### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.


#### 3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)
 
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$

#### 3.6.4 Test Setup






### 3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GPRS850	Channel :	CH189
Test Mode :	GPRS 8 Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 11.MAR.2013 12:01:19


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 11.MAR.2013 12:02:36




Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 17.MAR.2013 02:16:59

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 11.MAR.2013 12:04:40




Band :	GPRS850	Channel :	CH189
Test Mode :	EDGE 8 Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 12.MAR.2013 03:39:24


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.MAR.2013 03:40:58




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 12.MAR.2013 03:43:27

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 12.MAR.2013 03:43:57




Band :	GPRS1900	Channel :	CH661
Test Mode :	GPRS 8 Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 11.MAR.2013 12:47:34


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 11.MAR.2013 12:48:11




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 11.MAR.2013 12:48:43


### Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 11.MAR.2013 12:49:55



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 11.MAR.2013 12:50:25




Band :	GPRS1900	Channel :	CH661
Test Mode :	EDGE 8 Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 12.MAR.2013 06:32:08


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.MAR.2013 06:32:50




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 12.MAR.2013 06:33:35


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 12.MAR.2013 06:34:14



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 12.MAR.2013 06:34:51




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 12.MAR.2013 04:53:17


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.MAR.2013 04:55:23




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 12.MAR.2013 04:55:57

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 12.MAR.2013 04:56:37




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 12.MAR.2013 07:02:21


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 12.MAR.2013 07:03:00




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 12.MAR.2013 07:04:14


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 12.MAR.2013 07:04:54



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 12.MAR.2013 07:05:29

## 3.7 Field Strength of Spurious Radiation Measurement

### 3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

### 3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	GPRS 8 Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-64.54	-13	-51.54	-63.70	-65.19	0.57	3.37	H	Pass
2509	-59.28	-13	-46.28	-64.99	-61.51	0.78	5.16	H	Pass
3340	-55.31	-13	-42.31	-61.95	-58.95	0.87	6.66	H	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	GPRS 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1674	-59.97	-13	-46.97	-60.59	-60.62	0.57	3.37	V	Pass
2509	-56.03	-13	-43.03	-64.22	-58.26	0.78	5.16	V	Pass
3344	-55.80	-13	-42.80	-64.25	-59.44	0.87	6.66	V	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-61.85	-13	-48.85	-61.01	-62.50	0.57	3.37	H	Pass
2510	-57.67	-13	-44.67	-63.38	-59.90	0.78	5.16	H	Pass
3345	-56.62	-13	-43.62	-63.26	-60.26	0.87	6.66	H	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-61.71	-13	-48.71	-62.33	-62.36	0.57	3.37	V	Pass
2510	-54.90	-13	-41.90	-63.09	-57.13	0.78	5.16	V	Pass
3345	-52.99	-13	-39.99	-61.44	-56.63	0.87	6.66	V	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE8 Link + USB Cable 2 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-62.73	-13	-49.73	-61.89	-63.38	0.57	3.37	H	Pass
2510	-58.18	-13	-45.18	-63.89	-60.41	0.78	5.16	H	Pass
3345	-56.90	-13	-43.90	-63.54	-60.54	0.87	6.66	H	Pass



<b>Band :</b>	GPRS850	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE8 Link + USB Cable 2 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-61.54	-13	-48.54	-62.16	-62.19	0.57	3.37	V	Pass
2510	-53.87	-13	-40.87	-62.06	-56.10	0.78	5.16	V	Pass
3345	-53.88	-13	-40.88	-62.33	-57.52	0.87	6.66	V	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	GPRS 8 Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-54.41	-13	-41.41	-61.31	-60.79	0.78	7.16	H	Pass
5640	-32.06	-13	-19.06	-52.10	-40.60	1.04	9.58	H	Pass
7520	-34.80	-13	-21.80	-56.68	-44.91	1.35	11.46	H	Pass
9399	-39.58	-13	-26.58	-60.37	-50.64	1.75	12.81	H	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	GPRS 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-54.91	-13	-41.91	-62.73	-61.29	0.78	7.16	V	Pass
5640	-31.36	-13	-18.36	-51.84	-39.90	1.04	9.58	V	Pass
7520	-37.69	-13	-24.69	-59.38	-47.80	1.35	11.46	V	Pass
9399	-41.41	-13	-28.41	-61.21	-52.47	1.75	12.81	V	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-54.91	-13	-41.91	-61.81	-61.29	0.78	7.16	H	Pass
5640	-26.47	-13	-13.47	-47.34	-35.01	1.04	9.58	H	Pass
7520	-44.47	-13	-31.47	-61.10	-54.58	1.35	11.46	H	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-54.39	-13	-41.39	-62.21	-60.77	0.78	7.16	V	Pass
5640	-30.48	-13	-17.48	-50.85	-39.02	1.04	9.58	V	Pass
7520	-45.67	-13	-32.67	-62.88	-55.78	1.35	11.46	V	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 2 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-50.13	-13	-37.13	-59.67	-56.51	0.78	7.16	H	Pass
5640	-28.45	-13	-15.45	-49.05	-36.99	1.04	9.58	H	Pass
7520	-49.85	-13	-36.85	-64.95	-59.96	1.35	11.46	H	Pass



<b>Band :</b>	GPRS1900	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	EDGE 8 Link+ USB Cable 2 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-50.40	-13	-37.40	-61.2	-56.78	0.78	7.16	V	Pass
5640	-32.12	-13	-19.12	-52.46	-40.66	1.04	9.58	V	Pass
7520	-47.07	-13	-34.07	-64.28	-57.18	1.35	11.46	V	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-63.92	-13	-50.92	-63.08	-64.57	0.57	3.37	H	Pass
2509	-58.51	-13	-45.51	-64.22	-60.74	0.78	5.16	H	Pass
3344	-56.53	-13	-43.53	-63.17	-60.17	0.87	6.66	H	Pass



<b>Band :</b>	WCDMA Band V	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-62.43	-13	-49.43	-63.05	-63.08	0.57	3.37	V	Pass
2509	-57.17	-13	-44.17	-65.36	-59.40	0.78	5.16	V	Pass
3344	-55.06	-13	-42.06	-63.51	-58.70	0.87	6.66	V	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR HORIZONTAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-52.53	-13	-39.53	-60.55	-58.91	0.78	7.16	H	Pass
5640	-36.41	-13	-23.41	-55.36	-44.95	1.04	9.58	H	Pass
7520	-49.09	-13	-36.09	-64.19	-59.20	1.35	11.46	H	Pass



<b>Band :</b>	WCDMA Band II	<b>Temperature :</b>	22~23°C
<b>Test Mode :</b>	RMC 12.2Kbps Link + USB Cable 1 (Charging from Adapter) + Battery + Earphone	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS  
 Condition : FCC PART22 24 HF EIRP FACTOR VERTICAL

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3760	-45.42	-13	-32.42	-58.73	-51.80	0.78	7.16	V	Pass
5640	-39.83	-13	-26.83	-58.1	-48.37	1.04	9.58	V	Pass
7520	-46.94	-13	-33.94	-64.15	-57.05	1.35	11.46	V	Pass

## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^{\circ}\text{C}$ , the testing lowest temperature will be raised in  $10^{\circ}\text{C}$  step until the EUT can be turned on.

### 3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup





3.8.6 Test Result of Temperature Variation

Band :	GPRS850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-39	-0.05	-44	-0.05	PASS
-20	-43	-0.05	-50	-0.06	
-10	-40	-0.05	51	+0.06	
0	-44	-0.05	53	+0.06	
10	38	+0.04	56	+0.07	
20	36	+0.04	50	+0.06	
30	39	+0.05	-49	-0.06	
40	41	+0.05	-52	-0.06	
50	40	+0.05	-56	-0.07	

Band :	GPRS 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-132	-0.07	98	+0.05	PASS
-20	-110	-0.06	103	+0.05	
-10	-121	-0.06	112	+0.06	
0	-102	-0.05	103	+0.05	
10	-80	-0.04	-120	-0.06	
20	118	+0.06	-126	-0.07	
30	136	+0.07	132	+0.07	
40	139	+0.07	-144	-0.08	
50	146	+0.08	-140	-0.07	



<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	4182
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-58	-0.07	PASS
-20	-43	-0.05	
-10	-52	-0.06	
0	-56	-0.07	
10	-43	-0.05	
20	-59	-0.07	
30	-62	-0.07	
40	-66	-0.08	
50	-69	-0.08	

<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	9400
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-139	-0.07	PASS
-20	-102	-0.05	
-10	-131	-0.07	
0	-96	-0.05	
10	-98	-0.05	
20	102	+0.05	
30	131	+0.07	
40	136	+0.07	
50	143	+0.08	



3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GPRS 850 CH189	GPRS 8	3.8	-56	-0.07	2.5	PASS
		BEP	43	+0.05		
		4.1	36	+0.04		
	EDGE 8	3.8	56	+0.07		
		BEP	51	+0.06		
		4.1	62	+0.07		
GPRS 1900 CH661	GPRS 8	3.8	86	+0.05		
		BEP	-98	-0.05		
		4.1	120	+0.06		
	EDGE 8	3.8	-108	-0.06		
		BEP	-120	-0.06		
		4.1	-140	-0.07		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	38	+0.04		
		BEP	49	+0.06		
		4.1	-62	-0.07		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	-120	-0.06		
		BEP	-100	-0.05		
		4.1	-98	-0.05		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.6 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Mar. 11, 2013~ Apr. 08, 2013	Dec. 28, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2012	Mar. 11, 2013~ Apr. 08, 2013	Dec. 28, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Mar. 14, 2013~ Jun. 18, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	Jun. 01, 2012 May 30, 2013	Mar. 14, 2013~ Jun. 18, 2013	May 31, 2013 May 29, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Mar. 14, 2013~ Jun. 18, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Mar. 14, 2013~ Jun. 18, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	N/A	Mar. 14, 2013~ Jun. 18, 2013	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	N/A	Mar. 14, 2013~ Jun. 18, 2013	N/A	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	Jun. 01, 2012	Mar. 14, 2013~ Jun. 18, 2013	May 31, 2013	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Mar. 14, 2013~ Jun. 18, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Mar. 14, 2013~ Jun. 18, 2013	Nov. 22, 2013	Radiation (03CH01-KS)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
---	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
---	------



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP350204 as below.