

FCC RF Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : lenovo
MODEL NAME : Lenovo B8000-F; 60046; Z0AL
MARKETING NAME : YOGA TABLET 10
FCC ID : O57B8000F
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jul. 26, 2013 and completely tested on Aug. 26, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

 1.1 Applicant 5

 1.2 Manufacturer..... 5

 1.3 Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test..... 5

 1.5 Modification of EUT 6

 1.6 Testing Site..... 6

 1.7 Applied Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7

 2.1 Descriptions of Test Mode 7

 2.2 Test Mode..... 8

 2.3 Connection Diagram of Test System..... 9

 2.4 Support Unit used in test configuration and system 10

 2.5 Description of RF Function Operation Test Setup..... 10

 2.6 Measurement Results Explanation Example..... 11

3 TEST RESULT 12

 3.1 6dB and 99% Bandwidth Measurement 12

 3.2 Peak Output Power Measurement 17

 3.3 Power Spectral Density Measurement 19

 3.4 Conducted Band Edges and Spurious Emission Measurement 25

 3.5 Radiated Band Edges and Spurious Emission Measurement 34

 3.6 AC Conducted Emission Measurement..... 46

 3.7 Antenna Requirements..... 53

4 LIST OF MEASURING EQUIPMENT..... 54

5 UNCERTAINTY OF EVALUATION..... 55

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-210 A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)(1)	RSS-210 A8.1(b)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	RSS-210 A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.4	15.247(d)	RSS-210 A8.5	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.93 dB at 32.910 MHz
3.6	15.207	RSS-210 Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 4.55 dB at 0.640 MHz
3.7	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.

No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ, Shanghai, China

1.2 Manufacturer

Lenovo PC HK Limited

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	lenovo
Model Name	Lenovo B8000-F; 60046; Z0AL
Marketing Name	YOGA TABLET 10
FCC ID	O57B8000F
EUT supports Radios application	WLAN 2.4GHz 11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0
HW Version	Lenovo B8000-F
SW Version	B8000-130906
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples is only different supplier for RAM/ Panel/ Touch panel/ camera.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	1.39 dBm (0.0014 W)
99% Occupied Bandwidth	1.026MHz
Antenna Type	PIFA Antenna with gain 1.6 dBi
Type of Modulation	Bluetooth v4.0 - LE : GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	CO01-KS	03CH01-KS
			149928

The test site complies with ANSI C63.4 2003 requirement.

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3
- ♦ NOTICE 2012-DRS0126

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. Per the section 2.2.3 of Notice of 2012-DRS0126, " Receivers Excluded from Industry Canada Requirements", only radio communication receivers operating in stand-alone mode within the band 30-960 MHz and scanner receivers are subject to Industry Canada requirements.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth v4.0 – LE RF Output Power	
		Data Rate / Modulation	
		GFSK	
		1Mbps	
Ch00	2402MHz	1.28 dBm	
Ch19	2440MHz	1.35 dBm	
Ch39	2480MHz	1.39 dBm	

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, EUT is rotated on three test planes in Tablet PC configurations and one test plane in Laptop PC configuration to find out the worst emission and recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth v4.0 – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps with USB Cable 1 for Sample 1 Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps with USB Cable 1 for Sample 1 Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps with USB Cable 1 for Sample 1 Mode 4: Bluetooth Tx CH39_2480 MHz_1Mbps with USB Cable 2 for Sample 2
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1 Mode 2 : Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter) + Earphone for Sample 2
Remark:	
<ol style="list-style-type: none"> The worst case of conducted emission is mode 1; only the test data of it was reported. All the radiated test cases were performance with Adapter and Earphone. 	

2.3 Connection Diagram of Test System

<Bluetooth v4.0 – LE Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GWINSTEK	GPS-3030D	FCC DoC	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 0.9 m DC O/P: Shielded, 1.8 m
4.	Earphone	Lenovo	SH100	FCC DoC	N/A	N/A
5.	Bluetooth Earphone	Lenovo	LBH301	FCC DoC	N/A	N/A

2.5 Description of RF Function Operation Test Setup

For WLAN RF test items, turn on “EnterEngMode” test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5 + 10 = 15 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
00	2402	0.680	0.5	Pass
19	2440	0.680	0.5	Pass
39	2480	0.680	0.5	Pass


6 dB Bandwidth Plot on Channel 00



Date: 10.AUG.2013 13:37:12




6 dB Bandwidth Plot on Channel 19



Date: 10.AUG.2013 13:38:07

6 dB Bandwidth Plot on Channel 39



Date: 10.AUG.2013 13:38:47




3.1.6 Test Result of 99% Occupied Bandwidth

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.026
19	2440	1.026
39	2480	1.026


99% Bandwidth Plot on Channel 00



Date: 10.AUG.2013 13:40:37




99% Occupied Bandwidth Plot on Channel 19



Date: 10.AUG.2013 13:40:12

99% Occupied Bandwidth Plot on Channel 39



Date: 10.AUG.2013 13:39:43

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r01.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.28	30.00	Pass
19	2440	1.35	30.00	Pass
39	2480	1.39	30.00	Pass

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Engineer :	Adonis Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	Power Density		Max. Limits (dBm/3kHz)	Pass/Fail
		PSD/100kHz (dBm)	PSD/3kHz (dBm)		
00	2402	-0.00	-14.22	8	Pass
19	2440	-0.00	-14.27	8	Pass
39	2480	-0.03	-14.20	8	Pass


Note:

1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


PSD 100kHz Plot on Channel 00



Date: 10.AUG.2013 13:43:02




PSD 100kHz Plot on Channel 19



Date: 10.AUG.2013 13:43:28

PSD 100kHz Plot on Channel 39




Date: 10.AUG.2013 13:43:53



3.3.7 Test Result of Power Spectral Density Plots (3kHz)


PSD 3kHz Plot on Channel 00



Date: 10.AUG.2013 14:18:00




PSD 3kHz Plot on Channel 19



Date: 10.AUG.2013 14:16:16

PSD 3kHz Plot on Channel 39



Date: 10.AUG.2013 14:15:33

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Channel :	00 and 39	Relative Humidity :	47~48%
		Test Engineer :	Adonis Li


Low Band Edge Plot on Channel 00



Date: 10.AUG.2013 14:39:04



High Band Edge Plot on Channel 39




Date: 10.AUG.2013 14:37:18

3.4.6 Test Result of Conducted Spurious Emission

Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	47~48%
		Test Engineer :	Adonis Li


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00



Date: 10.AUG.2013 14:50:32



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00




Date: 10.AUG.2013 14:51:07



Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Channel :	19	Relative Humidity :	47~48%
		Test Engineer :	Adonis Li


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 10.AUG.2013 14:51:51



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 10.AUG.2013 14:52:21



Test Mode :	Bluetooth v4.0 - LE	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	47~48%
		Test Engineer :	Adonis Li


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 26.AUG.2013 15:16:19



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 26.AUG.2013 15:16:50



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.


3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r01.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
 For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth v4.0 - LE	60.76	0.384	2.604	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	40~41%
		Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV /m)	Over Limit (dB)	Limit Line (dBμV /m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2386.23	51.1	-22.9	74	45.75	32.86	3.17	30.68	100	62	Peak
2386.14	39.44	-14.56	54	34.09	32.86	3.17	30.68	100	62	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV /m)	Over Limit (dB)	Limit Line (dBμV /m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2377.5	50.78	-23.22	74	45.49	32.83	3.16	30.7	170	145	Peak
2386.23	39.1	-14.9	54	33.75	32.86	3.17	30.68	170	145	Average

Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
		Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV /m)	Over Limit (dB)	Limit Line (dBμV /m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	57.84	-16.16	74	52.21	33.01	3.22	30.6	100	123	Peak
2483.5	39.37	-14.63	54	33.74	33.01	3.22	30.6	100	123	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV /m)	Over Limit (dB)	Limit Line (dBμV /m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	59.41	-14.59	74	53.78	33.01	3.22	30.6	104	256	Peak
2483.5	40.18	-13.82	54	34.55	33.01	3.22	30.6	104	256	Average



Test Mode :	Mode 4	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
		Test Engineer :	Jun Liu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dB μ V / m)	Over Limit (dB)	Limit Line (dB μ V / m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	58.87	-15.13	74	53.24	33.01	3.22	30.6	100	71	Peak
2483.5	40.13	-13.87	54	34.5	33.01	3.22	30.6	100	71	Peak

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dB μ V / m)	Over Limit (dB)	Limit Line (dB μ V / m)	Read Level (dB μ V)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	59.85	-14.15	74	54.22	33.01	3.22	30.6	128	245	Peak
2483.5	40.69	-13.31	54	35.06	33.01	3.22	30.6	128	245	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	<ol style="list-style-type: none"> 2402 MHz is fundamental signal which can be ignored. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. For example, 98.06 dBµV/m - 20dB = 78.06dBµV/m. Average measurement was not performed if peak level went lower than the average limit. 		

Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	98.06	-	-	92.71	32.86	3.17	30.68	100	62	Peak
2402	97.18	-	-	91.83	32.86	3.17	30.68	100	62	Average
4804	50.04	-23.96	74	39.61	35.17	4.58	29.32	100	261	Peak
7206	53.31	-24.75	78.06	41.67	36.16	5.61	30.13	200	301	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	Mode 1	Temperature :	22~23°C
Test Channel :	00	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2402 MHz is fundamental signal which can be ignored. 2. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. 3. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	95.97	-	-	90.62	32.86	3.17	30.68	171	145	Peak
2402	94.59	-	-	89.24	32.86	3.17	30.68	171	145	Average
4804	49.04	-24.96	74	38.61	35.17	4.58	29.32	100	14	Peak
7206	53.06	-22.91	75.97	41.42	36.16	5.61	30.13	100	0	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	Mode 2	Temperature :	22~23°C
Test Channel :	19	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2440 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2440	96.23	-	-	90.71	32.95	3.2	30.63	120	321	Peak
2440	94.98	-	-	89.46	32.95	3.2	30.63	120	321	Average
4880	50.14	-23.86	74	39.68	35.18	4.6	29.32	120	320	Peak
7320	53.26	-20.74	74	41.6	36.21	5.64	30.19	130	200	Peak

Note: Other harmonics are lower than background noise.

Test Mode :	Mode 2	Temperature :	22~23°C
Test Channel :	19	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2440 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2440	94.87	-	-	89.35	32.95	3.2	30.63	200	145	Peak
2440	93.66	-	-	88.14	32.95	3.2	30.63	200	145	Average
4880	50.68	-23.32	74	40.22	35.18	4.6	29.32	100	154	Peak
7320	52.67	-21.33	74	41.01	36.21	5.64	30.19	130	156	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2480	96.56	-	-	90.93	33.01	3.22	30.6	100	63	Peak
2480	95.19	-	-	89.56	33.01	3.22	30.6	100	63	Average
4960	49.46	-24.54	74	38.95	35.2	4.62	29.31	100	162	Peak
7440	53.34	-20.66	74	41.64	36.27	5.67	30.24	100	166	Peak

Note: Other harmonics are lower than background noise.

Test Mode :	Mode 3	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2480	96.33	-	-	90.7	33.01	3.22	30.6	130	295	Peak
2480	95.28	-	-	89.65	33.01	3.22	30.6	130	295	Average
4960	50.22	-23.78	74	39.71	35.2	4.62	29.31	100	160	Peak
7440	53.89	-20.11	74	42.19	36.27	5.67	30.24	100	148	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	Mode 4	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Horizontal
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.91	22.82	-17.18	40	40.54	16.04	-0.17	33.59	-	-	Peak
121.18	29.47	-14.03	43.5	50.26	11.79	1.02	33.6	-	-	Peak
277.35	19.61	-26.39	46	38.88	12.58	1.55	33.4	-	-	Peak
422.85	21.34	-24.66	46	36.59	16.13	1.88	33.26	-	-	Peak
837.04	26.4	-19.6	46	36.11	20.37	2.63	32.71	-	-	Peak
942.77	35.12	-10.88	46	44.05	20.7	2.81	32.44	100	0	Peak
2480	97.29	-	-	91.66	33.01	3.22	30.6	100	127	Peak
2480	96.27	-	-	90.64	33.01	3.22	30.6	100	127	Average
4960	50.95	-23.05	74	40.44	35.2	4.62	29.31	100	12	Peak
7440	51.1	-22.9	74	39.4	36.27	5.67	30.24	100	162	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	Mode 4	Temperature :	22~23°C
Test Channel :	39	Relative Humidity :	40~41%
Test Engineer :	Jun Liu	Polarization :	Vertical
Remark :	1. 2480 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.91	33.07	-6.93	40	50.79	16.04	-0.17	33.59	100	200	Peak
42.61	28.44	-11.56	40	50.97	10.48	0.62	33.63	-	-	Peak
54.25	30	-10	40	56.41	6.49	0.68	33.58	-	-	Peak
109.54	29.79	-13.71	43.5	50.62	11.8	0.98	33.61	-	-	Peak
855.47	22.14	-23.86	46	31.71	20.5	2.64	32.71	-	-	Peak
957.32	31.18	-14.82	46	40.03	20.77	2.82	32.44	-	-	Peak
2480	96.02	-	-	90.39	33.01	3.22	30.6	103	293	Peak
2480	95.13	-	-	89.5	33.01	3.22	30.6	103	293	Average
4960	50.11	-23.89	74	39.6	35.2	4.62	29.31	100	52	Peak
7440	50.16	-23.84	74	38.46	36.27	5.67	30.24	100	13	Peak

Note: Other harmonics are lower than background noise.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup




AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Henry Chen	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1		




Site : C001-KS
 Condition: FCC PART15C LISN-L20130306 LINE

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.17	38.51	-16.30	54.81	26.39	1.48	10.64	Average
2	0.17	48.81	-16.00	64.81	36.69	1.48	10.64	QP
3	0.21	39.94	-13.20	53.14	28.41	0.97	10.56	Average
4	0.21	49.94	-13.20	63.14	38.41	0.97	10.56	QP
5	0.23	41.08	-11.49	52.57	29.60	0.94	10.54	Average
6	0.23	50.58	-11.99	62.57	39.10	0.94	10.54	QP
7	0.30	50.09	-10.19	60.28	39.00	0.70	10.39	QP
8	0.30	40.19	-10.09	50.28	29.10	0.70	10.39	Average
9	0.33	47.44	-11.96	59.40	36.60	0.50	10.34	QP
10	0.33	37.24	-12.16	49.40	26.40	0.50	10.34	Average
11	0.36	38.31	-10.38	48.69	27.60	0.40	10.31	Average
12	0.36	48.21	-10.48	58.69	37.50	0.40	10.31	QP
13	0.39	45.92	-12.11	58.03	35.30	0.33	10.29	QP
14	0.39	36.72	-11.31	48.03	26.10	0.33	10.29	Average
15	0.41	46.78	-10.90	57.68	36.20	0.30	10.28	QP
16	0.41	35.98	-11.70	47.68	25.40	0.30	10.28	Average
17	0.44	47.43	-9.64	57.07	36.90	0.26	10.27	QP
18	0.44	36.33	-10.74	47.07	25.80	0.26	10.27	Average
19	0.47	38.19	-8.30	46.49	27.69	0.23	10.27	Average
20	0.47	48.99	-7.50	56.49	38.49	0.23	10.27	QP
21	0.50	46.67	-9.38	56.05	36.21	0.20	10.26	QP
22	0.50	35.87	-10.18	46.05	25.41	0.20	10.26	Average
23	0.56	36.95	-9.05	46.00	26.50	0.20	10.25	Average
24	0.56	46.65	-9.35	56.00	36.20	0.20	10.25	QP
25	0.59	49.84	-6.16	56.00	39.40	0.20	10.24	QP
26	0.59	40.14	-5.86	46.00	29.70	0.20	10.24	Average
27	0.66	40.22	-5.78	46.00	29.80	0.20	10.22	Average
28	0.66	50.02	-5.98	56.00	39.60	0.20	10.22	QP



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Henry Chen	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1		




Site : C001-KS
 Condition: FCC PART15C LISN-L20130306 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
29	0.71	45.61	-10.39	56.00	35.20	0.20	10.21	QP
30	0.71	36.51	-9.49	46.00	26.10	0.20	10.21	Average
31	0.75	36.49	-9.51	46.00	26.10	0.19	10.20	Average
32	0.75	46.89	-9.11	56.00	36.50	0.19	10.20	QP
33	0.83	48.55	-7.45	56.00	38.21	0.15	10.19	QP
34	0.83	39.45	-6.55	46.00	29.11	0.15	10.19	Average
35	0.88	47.42	-8.58	56.00	37.10	0.13	10.19	QP
36	0.88	34.42	-11.58	46.00	24.10	0.13	10.19	Average
37	0.93	36.70	-9.30	46.00	26.41	0.11	10.18	Average
38	0.93	46.70	-9.30	56.00	36.41	0.11	10.18	QP
39	0.99	48.38	-7.62	56.00	38.10	0.10	10.18	QP
40	0.99	38.68	-7.32	46.00	28.40	0.10	10.18	Average
41	1.06	47.28	-8.72	56.00	37.00	0.10	10.18	QP
42	1.06	37.38	-8.62	46.00	27.10	0.10	10.18	Average
43	1.15	33.68	-12.32	46.00	23.40	0.10	10.18	Average
44	1.15	43.58	-12.42	56.00	33.30	0.10	10.18	QP
45	1.20	35.88	-10.12	46.00	25.60	0.10	10.18	Average
46	1.20	45.78	-10.22	56.00	35.50	0.10	10.18	QP
47	1.29	44.18	-11.82	56.00	33.90	0.10	10.18	QP
48	1.29	33.38	-12.62	46.00	23.10	0.10	10.18	Average
49	1.37	47.68	-8.32	56.00	37.40	0.10	10.18	QP
50	1.37	37.08	-8.92	46.00	26.80	0.10	10.18	Average
51	1.46	34.79	-11.21	46.00	24.50	0.10	10.19	Average
52	1.46	44.99	-11.01	56.00	34.70	0.10	10.19	QP
53	1.58	34.89	-11.11	46.00	24.60	0.10	10.19	Average
54	1.58	44.49	-11.51	56.00	34.20	0.10	10.19	QP
55	1.69	32.59	-13.41	46.00	22.30	0.10	10.19	Average
56	1.69	42.59	-13.41	56.00	32.30	0.10	10.19	QP
57	1.79	28.49	-17.51	46.00	18.20	0.10	10.19	Average
58	1.79	37.89	-18.11	56.00	27.60	0.10	10.19	QP
59	2.69	32.63	-13.37	46.00	22.30	0.12	10.21	Average
60	2.69	41.43	-14.57	56.00	31.10	0.12	10.21	QP
61	3.01	33.76	-12.24	46.00	23.40	0.14	10.22	Average
62	3.01	43.96	-12.04	56.00	33.60	0.14	10.22	QP
63	3.24	43.38	-12.62	56.00	32.99	0.16	10.23	QP
64	3.24	33.48	-12.52	46.00	23.09	0.16	10.23	Average



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Henry Chen	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1		




Site : C001-KS
 Condition: FCC PART15C LISN-N20130306 NEUTRAL

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15	41.42	-14.32	55.74	28.90	1.83	10.69	Average
2	0.15	51.12	-14.62	65.74	38.60	1.83	10.69	QP
3	0.17	52.28	-12.88	65.16	39.99	1.63	10.66	QP
4	0.17	42.38	-12.78	55.16	30.09	1.63	10.66	Average
5	0.18	41.03	-13.52	54.55	29.10	1.31	10.62	Average
6	0.18	50.53	-14.02	64.55	38.60	1.31	10.62	QP
7	0.19	40.78	-13.15	53.93	29.11	1.08	10.59	Average
8	0.19	49.88	-14.05	63.93	38.21	1.08	10.59	QP
9	0.22	51.33	-11.68	63.01	39.80	0.97	10.56	QP
10	0.22	39.93	-13.08	53.01	28.40	0.97	10.56	Average
11	0.24	48.96	-13.30	62.26	37.50	0.93	10.53	QP
12	0.24	38.26	-14.00	52.26	26.80	0.93	10.53	Average
13	0.26	38.75	-12.63	51.38	27.41	0.86	10.48	Average
14	0.26	48.55	-12.83	61.38	37.21	0.86	10.48	QP
15	0.27	48.28	-12.75	61.03	37.00	0.83	10.45	QP
16	0.27	36.88	-14.15	51.03	25.60	0.83	10.45	Average
17	0.29	38.46	-11.95	50.41	27.30	0.76	10.40	Average
18	0.29	48.66	-11.75	60.41	37.50	0.76	10.40	QP
19	0.33	37.53	-12.00	49.53	26.59	0.59	10.35	Average
20	0.33	48.93	-10.60	59.53	37.99	0.59	10.35	QP
21	0.35	39.22	-9.69	48.91	28.40	0.50	10.32	Average
22	0.35	50.22	-8.69	58.91	39.40	0.50	10.32	QP
23	0.39	37.81	-10.31	48.12	27.10	0.42	10.29	Average
24	0.39	47.91	-10.21	58.12	37.20	0.42	10.29	QP
25	0.40	46.88	-10.93	57.81	36.20	0.40	10.28	QP
26	0.40	36.78	-11.03	47.81	26.10	0.40	10.28	Average
27	0.44	39.02	-8.00	47.02	28.40	0.35	10.27	Average
28	0.44	48.92	-8.10	57.02	38.30	0.35	10.27	QP



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Henry Chen	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1		




Site : C001-KS
 Condition: FCC PART15C LISM-N20130306 NEUTRAL

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISM	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
29	0.46	49.90	-6.73	56.63	39.30	0.33	10.27	QP
30	0.46	39.70	-6.93	46.63	29.10	0.33	10.27	Average
31	0.51	37.76	-8.24	46.00	27.20	0.30	10.26	Average
32	0.51	46.66	-9.34	56.00	36.10	0.30	10.26	QP
33	0.56	39.23	-6.77	46.00	28.71	0.27	10.25	Average
34	0.56	48.83	-7.17	56.00	38.31	0.27	10.25	QP
35	0.59	39.80	-6.20	46.00	29.31	0.25	10.24	Average
36	0.59	49.80	-6.20	56.00	39.31	0.25	10.24	QP
37	0.64	50.75	-5.25	56.00	40.30	0.22	10.23	QP
38	0.64	41.45	-4.55	46.00	31.00	0.22	10.23	Average
39	0.73	48.00	-8.00	56.00	37.60	0.19	10.21	QP
40	0.73	38.20	-7.80	46.00	27.80	0.19	10.21	Average
41	0.81	47.26	-8.74	56.00	36.90	0.16	10.20	QP
42	0.81	36.16	-9.84	46.00	25.80	0.16	10.20	Average
43	0.85	48.63	-7.37	56.00	38.30	0.14	10.19	QP
44	0.85	38.53	-7.47	46.00	28.20	0.14	10.19	Average
45	0.94	37.10	-8.90	46.00	26.81	0.11	10.18	Average
46	0.94	46.90	-9.10	56.00	36.61	0.11	10.18	QP
47	0.99	38.68	-7.32	46.00	28.40	0.10	10.18	Average
48	0.99	48.78	-7.22	56.00	38.50	0.10	10.18	QP
49	1.10	36.58	-9.42	46.00	26.30	0.10	10.18	Average



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Henry Chen	Relative Humidity :	51~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Earphone for Sample 1		



Site : C001-KS
 Condition: FCC PART15C LISN-N20130306 NEUTRAL

mode : Mode 1

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
50	1.10	46.78	-9.22	56.00	36.50	0.10	10.18	QP
51	1.16	37.38	-8.62	46.00	27.10	0.10	10.18	Average
52	1.16	46.88	-9.12	56.00	36.60	0.10	10.18	QP
53	1.23	47.58	-8.42	56.00	37.30	0.10	10.18	QP
54	1.23	36.78	-9.22	46.00	26.50	0.10	10.18	Average
55	1.34	46.28	-9.72	56.00	36.00	0.10	10.18	QP
56	1.34	37.08	-8.92	46.00	26.80	0.10	10.18	Average
57	1.43	45.49	-10.51	56.00	35.20	0.10	10.19	QP
58	1.43	36.59	-9.41	46.00	26.30	0.10	10.19	Average
59	1.59	43.79	-12.21	56.00	33.50	0.10	10.19	QP
60	1.59	34.39	-11.61	46.00	24.10	0.10	10.19	Average
61	1.65	42.59	-13.41	56.00	32.30	0.10	10.19	QP
62	1.65	33.59	-12.41	46.00	23.30	0.10	10.19	Average
63	1.80	41.29	-14.71	56.00	31.00	0.10	10.19	QP
64	1.80	31.29	-14.71	46.00	21.00	0.10	10.19	Average
65	2.65	41.53	-14.47	56.00	31.20	0.12	10.21	QP
66	2.65	31.73	-14.27	46.00	21.40	0.12	10.21	Average
67	2.87	39.65	-16.35	56.00	29.30	0.13	10.22	QP
68	2.87	30.25	-15.75	46.00	19.90	0.13	10.22	Average
69	3.12	42.97	-13.03	56.00	32.59	0.15	10.23	QP
70	3.12	32.87	-13.13	46.00	22.49	0.15	10.23	Average
71	3.31	41.89	-14.11	56.00	31.50	0.16	10.23	QP
72	3.31	31.89	-14.11	46.00	21.50	0.16	10.23	Average
73	4.18	32.83	-13.17	46.00	22.40	0.19	10.24	Average
74	4.18	42.73	-13.27	56.00	32.30	0.19	10.24	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Connected Construction

Non-standard connector used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Aug. 10, 2013~ Aug. 26, 2013	Dec. 28, 2013	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY45101555	N/A	Aug. 23, 2012 Aug. 22, 2013	Aug. 10, 2013~ Aug. 26, 2013	Aug. 22, 2013 Aug. 21, 2014	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY44421198	N/A	Aug. 23, 2012 Aug. 22, 2013	Aug. 10, 2013~ Aug. 26, 2013	Aug. 22, 2013 Aug. 21, 2014	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Aug. 17, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	May 23, 2013	Aug. 17, 2013	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Aug. 17, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2012	Aug. 17, 2013	Oct. 21, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Aug. 17, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Aug. 17, 2013	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Aug. 17, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Aug. 17, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	N/A	Aug. 17, 2013	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	N/A	Aug. 17, 2013	N/A	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	May 23, 2013	Aug. 01, 2013	May 22, 2014	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 29, 2012	Aug. 01, 2013	Dec. 28, 2013	Conduction (CO01-KS)
LISN (for auxiliary equipment)	MessTec	AN3016	60105	9kHz~30MHz	Dec. 29, 2012	Aug. 01, 2013	Dec. 28, 2013	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	N/A	Nov. 15, 2012	Aug. 01, 2013	Nov. 14, 2013	Conduction (CO01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------