



FCC RADIO TEST REPORT

FCC ID : O57FLEX5G14X05
Equipment : Notebook Computer
Brand Name : Lenovo
Model Name : Lenovo Flex 5G 14Q8CX05*****, 82AK*****, Yoga 5G 14Q8CX05*****, 81XE***** (* = 0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)
Applicant : Lenovo (Shanghai) Electronics Technology Co., Ltd.
Section 304-305, Building No. 4, # 222, Meiyue Road, China
(Shanghai) Pilot Free Trade Zone, Shanghai
Manufacturer : Lenovo PC HK Limited
23/F, Lincoln House, Taikoo Place, 979 King's Road, Quarry Bay, Hong Kong
Standard : FCC Part 15 Subpart C §15.247

Equipment: Murata LBDD5WV1US-575 and HON LIN T99W175 tested inside of Lenovo Notebook Computer.

The product was received on Nov. 27, 2019 and testing was started from Nov. 27, 2019 and completed on Dec. 19, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
4 List of Measuring Equipment	42
5 Uncertainty of Evaluation.....	44
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR9N2705B	01	Initial issue of report	Feb. 18, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Peak Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
0	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 6.18 dB at 2492.480 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 12.29 dB at 0.209 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Lucy Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	Lenovo Flex 5G 14Q8CX05*****, 82AK*****, Yoga 5G 14Q8CX05*****, 81XE***** (* = 0~9, A~Z, a~z, "-" or blank, for marketing use only, with no impact on RF compliance of the product)
FCC ID	O57FLEX5G14X05
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/RFID/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer.
2. Equipment: Murata LBDD5WV1US-575 and HON LIN T99W175 tested inside of Lenovo Notebook Computer.

Antenna Information			
Notebook Mode	Antenna Type	Main: PIFA Antenna	Aux: PIFA Antenna
	Part number	AML6Y-100089 (AM2RC000600)	AML6Y-100090 (AM2RC000700)
	Peak gain (dbi)	Main Antenna : WLAN (2.4GHz): -1.34 Bluetooth: -1.34	Aux. Antenna : WLAN (2.4GHz): -1.89
Tablet Mode	Antenna Type	Main: PIFA Antenna	Aux: PIFA Antenna
	Part number	AML6Y-100089 (AM2RC000600)	AML6Y-100090 (AM2RC000700)
	Peak gain (dbi)	Main Antenna : WLAN (2.4GHz): -1.73 Bluetooth: -1.73	Aux. Antenna : WLAN (2.4GHz): -0.52

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	6.10 dBm (0.0041 W) for 1Mbps 6.10 dBm (0.0041 W) for 2Mbps
99% Occupied Bandwidth	1.025 MHz for 1Mbps 2.030 MHz for 2Mbps
Type of Modulation	Bluetooth LE : GFSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan	
Test Site No.	Sporton Site No.	
	03CH13-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z, and Notebook Mode. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: Bluetooth Tx + WLAN (2.4GHz) Tx + Adapter + Type-C Cable + Earphone

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
2.	Earphone	Zyia	N/A	N/A	Unshielded, 1.2m	N/A
3.	Hard disk	Lenovo	F310S	FCC DoC	Shielded, 0.5m	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "QRCT_V 4.0-00142" was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup







3.1.5 Test Result of 6dB Bandwidth


Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00_1Mbps




6 dB Bandwidth Plot on Channel 19_1Mbps




6 dB Bandwidth Plot on Channel 39_1Mbps



Date: 29.NOV.2019 21:16:09

6 dB Bandwidth Plot on Channel 00_2Mbps


Date: 29.NOV.2019 21:23:17

6 dB Bandwidth Plot on Channel 19_2Mbps


Date: 29.NOV.2019 21:31:32

6 dB Bandwidth Plot on Channel 39_2Mbps



Date: 29.NOV.2019 21:37:40



3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

99% Bandwidth Plot on Channel 00_1Mbps




Date: 29.NOV.2019 21:09:09


99% Occupied Bandwidth Plot on Channel 19_1Mbps





Date: 29.NOV.2019 21:14:21

**99% Occupied Bandwidth Plot on Channel 39_1Mbps**

Date: 29.NOV.2019 21:19:45

99% Bandwidth Plot on Channel 00_2Mbps

Date: 29.NOV.2019 21:29:02

**99% Occupied Bandwidth Plot on Channel 19_2Mbps****99% Occupied Bandwidth Plot on Channel 39_2Mbps**

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for average output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the average output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00_1Mbps



Date: 29.NOV.2019 21:05:50


PSD 100kHz Plot on Channel 19_1Mbps



Date: 29.NOV.2019 21:12:30




PSD 100kHz Plot on Channel 39_1Mbps



Date: 29.NOV.2019 21:17:31


PSD 100kHz Plot on Channel 00_2Mbps



Date: 29.NOV.2019 21:25:25




PSD 100kHz Plot on Channel 19_2Mbps



Date: 29.NOV.2019 21:33:23


PSD 100kHz Plot on Channel 39_2Mbps




Date: 29.NOV.2019 21:38:31

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00_1Mbps




PSD 3kHz Plot on Channel 19_1Mbps






PSD 3kHz Plot on Channel 39_1Mbps




PSD 3kHz Plot on Channel 00_2Mbps






PSD 3kHz Plot on Channel 19_2Mbps



PSD 3kHz Plot on Channel 39_2Mbps



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure


1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00_1Mbps




Date: 29.NOV.2019 21:07:11


High Band Edge Plot on Channel 39_1Mbps



Date: 29.NOV.2019 21:17:54

Low Band Edge Plot on Channel 00_2Mbps



Date: 29.NOV.2019 21:25:51

High Band Edge Plot on Channel 39_2Mbps


Date: 29.NOV.2019 21:38:49


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 29.NOV.2019 21:08:01

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 29.NOV.2019 21:08:22

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 29.NOV.2019 21:13:37

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 29.NOV.2019 21:13:50

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 29.NOV.2019 21:19:02

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 29.NOV.2019 21:19:16

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00




Date: 29.NOV.2019 21:28:10

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00




Date: 29.NOV.2019 21:28:23

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 29.NOV.2019 21:34:57

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19




Date: 29.NOV.2019 21:35:12

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 29.NOV.2019 21:39:47

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 29.NOV.2019 21:40:07

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H2	41410069	N/A	Jun. 17, 2019	Nov. 27, 2019~ Nov. 29, 2019	Jun. 16, 2020	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SN O32	9kHz~6GHz	Dec. 03, 2018	Nov. 27, 2019~ Nov. 29, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Jul. 15, 2019	Nov. 27, 2019~ Nov. 29, 2019	Jul. 14, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1208382	N/A	Mar. 27, 2019	Nov. 27, 2019~ Nov. 29, 2019	Mar. 26, 2020	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 19, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Dec. 19, 2019	Nov. 14, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Dec. 19, 2019	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Dec. 19, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Dec. 19, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Dec. 19, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Dec. 01, 2019~ Dec. 04, 2019	Jan. 06, 2020	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jul. 02, 2019	Dec. 01, 2019~ Dec. 04, 2019	Jul. 01, 2020	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N 1D01N-06	40103 & 07	30MHz~1GHz	Apr. 30, 2019	Dec. 01, 2019~ Dec. 04, 2019	Apr. 29, 2020	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91705 76	18GHz- 40GHz	May 14, 2019	Dec. 01, 2019~ Dec. 04, 2019	May 13, 2020	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY5327014 7	1GHz~26.5GHz	Mar. 15, 2019	Dec. 01, 2019~ Dec. 04, 2019	Mar. 14, 2020	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 20, 2019	Dec. 01, 2019~ Dec. 04, 2019	May 19, 2020	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 18, 2018	Dec. 01, 2019~ Dec. 04, 2019	Dec. 17, 2019	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 06, 2018	Dec. 01, 2019~ Dec. 04, 2019	Dec. 05, 2019	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 13, 2019	Dec. 01, 2019~ Dec. 04, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 13, 2019	Dec. 01, 2019~ Dec. 04, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30M-18G	Feb. 13, 2019	Dec. 01, 2019~ Dec. 04, 2019	Feb. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Mar. 13, 2019	Dec. 01, 2019~ Dec. 04, 2019	Mar. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30M~40GHz	Mar. 13, 2019	Dec. 01, 2019~ Dec. 04, 2019	Mar. 12, 2020	Radiation (03CH13-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 19, 2019	Dec. 01, 2019~ Dec. 04, 2019	Mar. 18, 2020	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 01, 2019~ Dec. 04, 2019	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Dec. 01, 2019~ Dec. 04, 2019	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Dec. 01, 2019~ Dec. 04, 2019	N/A	Radiation (03CH13-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	Dec. 01, 2019~ Dec. 04, 2019	N/A	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 01, 2019	Dec. 01, 2019~ Dec. 04, 2019	Oct. 31, 2020	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-2700- 3000-18000-60 SS	SN2	3GHz High Pass Filter	Jul. 14, 2019	Dec. 01, 2019~ Dec. 04, 2019	Jul. 13, 2020	Radiation (03CH13-HY)
Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN12	1.53GHz Low Pass Filter	Sep. 16, 2019	Dec. 01, 2019~ Dec. 04, 2019	Sep. 15, 2020	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.0
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.4
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2019/11/27~2019/11/29	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.025	0.665	0.50	Pass
BLE	1Mbps	1	19	2440	1.025	0.671	0.50	Pass
BLE	1Mbps	1	39	2480	1.025	0.665	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.30	30.00	-1.34	3.96	36.00	Pass
BLE	1Mbps	1	19	2440	4.10	30.00	-1.34	2.76	36.00	Pass
BLE	1Mbps	1	39	2480	6.10	30.00	-1.34	4.76	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.20	-9.33	-1.34	8.00	Pass
BLE	1Mbps	1	19	2440	4.19	-10.27	-1.34	8.00	Pass
BLE	1Mbps	1	39	2480	6.15	-8.36	-1.34	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.030	1.147	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.030	1.155	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.030	1.147	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	5.30	30.00	-1.34	3.96	36.00	Pass
BLE5.0	2Mbps	1	19	2440	4.10	30.00	-1.34	2.76	36.00	Pass
BLE5.0	2Mbps	1	39	2480	6.10	30.00	-1.34	4.76	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	5.22	-12.93	-1.34	8.00	Pass
BLE5.0	2Mbps	1	19	2440	4.20	-13.91	-1.34	8.00	Pass
BLE5.0	2Mbps	1	39	2480	6.14	-12.02	-1.34	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	22~25℃
		Relative Humidity :	43~51%

EUT Information

Report NO : 9N2705
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	45.91	---	66.00	20.09	L1	OFF	19.5
0.150000	---	23.08	56.00	32.92	L1	OFF	19.5
0.190500	50.60	---	64.02	13.42	L1	OFF	19.5
0.190500	---	31.85	54.02	22.17	L1	OFF	19.5
0.192750	50.81	---	63.92	13.11	L1	OFF	19.5
0.192750	---	32.60	53.92	21.32	L1	OFF	19.5
0.208500	50.98	---	63.27	12.29	L1	OFF	19.5
0.208500	---	36.49	53.27	16.78	L1	OFF	19.5
0.250530	44.00	---	61.74	17.74	L1	OFF	19.5
0.250530	---	24.68	51.74	27.06	L1	OFF	19.5
0.353760	37.73	---	58.87	21.14	L1	OFF	19.5
0.353760	---	24.54	48.87	24.33	L1	OFF	19.5
0.500010	32.61	---	56.00	23.39	L1	OFF	19.5
0.500010	---	25.28	46.00	20.72	L1	OFF	19.5
0.566250	30.48	---	56.00	25.52	L1	OFF	19.5
0.566250	---	23.18	46.00	22.82	L1	OFF	19.5
6.369000	34.93	---	60.00	25.07	L1	OFF	19.6
6.369000	---	34.29	50.00	15.71	L1	OFF	19.6
7.965600	35.21	---	60.00	24.79	L1	OFF	19.6
7.965600	---	31.27	50.00	18.73	L1	OFF	19.6
10.349250	39.03	---	60.00	20.97	L1	OFF	19.7

10.349250	---	34.70	50.00	15.30	L1	OFF	19.7
-----------	-----	-------	-------	-------	----	-----	------

EUT Information

Report NO : 9N2705
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.181500	---	21.07	54.42	33.35	N	OFF	19.5
0.181500	41.18	---	64.42	23.24	N	OFF	19.5
0.253500	---	25.43	51.64	26.21	N	OFF	19.5
0.253500	43.53	---	61.64	18.11	N	OFF	19.5
0.345750	---	26.56	49.06	22.50	N	OFF	19.5
0.345750	37.86	---	59.06	21.20	N	OFF	19.5
0.494250	---	22.69	46.10	23.41	N	OFF	19.5
0.494250	32.04	---	56.10	24.06	N	OFF	19.5
8.748510	---	27.25	50.00	22.75	N	OFF	19.7
8.748510	32.75	---	60.00	27.25	N	OFF	19.7
10.349250	---	35.27	50.00	14.73	N	OFF	19.7
10.349250	39.51	---	60.00	20.49	N	OFF	19.7



Appendix C. Radiated Spurious Emission

Test Engineer :	Jesse Wang , JC Liang , Wilson Wu	Temperature :	21.5 ~ 23.5°C
		Relative Humidity :	46.5 ~ 49.5%

2.4GHz 2400~2483.5MHz BLE_1Mbps (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preampl Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2353.575	55.83	-18.17	74	41.44	27.79	13.89	27.29	372	223	P	H
		2348.01	46.39	-7.61	54	31.99	27.8	13.89	27.29	372	223	A	H
	*	2402	100.07	-	-	85.83	27.6	13.93	27.29	372	223	P	H
	*	2402	99.49	-	-	85.25	27.6	13.93	27.29	372	223	A	H
													H
													H
		2320.185	55.02	-18.98	74	40.59	27.86	13.87	27.3	278	164	P	V
		2321.34	45.9	-8.1	54	31.47	27.86	13.87	27.3	278	164	A	V
	*	2402	98.8	-	-	84.56	27.6	13.93	27.29	278	164	P	V
	*	2402	98.18	-	-	83.94	27.6	13.93	27.29	278	164	A	V
													V
													V
BLE CH 19 2440MHz		2328.9	55.47	-18.53	74	41.06	27.84	13.87	27.3	357	220	P	H
		2373.7	45.98	-8.02	54	31.65	27.71	13.91	27.29	357	220	A	H
	*	2440	96.23	-	-	82.03	27.52	13.96	27.28	357	220	P	H
	*	2440	95.73	-	-	81.53	27.52	13.96	27.28	357	220	A	H
		2492.37	55.33	-18.67	74	41.09	27.5	14.01	27.27	357	220	P	H
		2496.92	45.99	-8.01	54	31.75	27.5	14.01	27.27	357	220	A	H
		2379.3	55.75	-18.25	74	41.45	27.68	13.91	27.29	302	166	P	V
		2352.28	45.98	-8.02	54	31.59	27.79	13.89	27.29	302	166	A	V
	*	2440	94.79	-	-	80.59	27.52	13.96	27.28	302	166	P	V
	*	2440	94.28	-	-	80.08	27.52	13.96	27.28	302	166	A	V
		2494.75	55.87	-18.13	74	41.63	27.5	14.01	27.27	302	166	P	V
		2488.45	45.87	-8.13	54	31.63	27.5	14.01	27.27	302	166	A	V



BLE CH 39 2480MHz	*	2480	101.17	-	-	86.94	27.5	14	27.27	310	213	P	H
	*	2480	100.44	-	-	86.21	27.5	14	27.27	310	213	A	H
		2498.16	55.36	-18.64	74	41.12	27.5	14.01	27.27	310	213	P	H
		2496.96	45.81	-8.19	54	31.57	27.5	14.01	27.27	310	213	A	H
													H
													H
	*	2480	100.72	-	-	86.49	27.5	14	27.27	298	172	P	V
	*	2480	100.24	-	-	86.01	27.5	14	27.27	298	172	A	V
		2484.64	55.13	-18.87	74	40.9	27.5	14	27.27	298	172	P	V
		2488.04	45.69	-8.31	54	31.46	27.5	14	27.27	298	172	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE_1Mbps (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	36.71	-37.29	74	56.81	31.11	6.38	57.59	100	0	P	H
													H
													H
													H
		4804	36.35	-37.65	74	56.45	31.11	6.38	57.59	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	38.39	-35.61	74	58.04	31.2	6.59	57.44	100	0	P	H
		7320	42.97	-31.03	74	55.26	36.76	8.23	57.28	100	0	P	H
													H
													H
		4880	38.07	-35.93	74	57.72	31.2	6.59	57.44	100	0	P	V
		7320	43.75	-30.25	74	56.04	36.76	8.23	57.28	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	39.43	-34.57	74	58.53	31.36	6.82	57.28	100	0	P	H
		7440	42.6	-31.4	74	55.15	36.68	8.2	57.43	100	0	P	H
													H
													H
		4960	38.15	-35.85	74	57.25	31.36	6.82	57.28	100	0	P	V
		7440	43.65	-30.35	74	56.2	36.68	8.2	57.43	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE_1Mbps (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		31.94	23.37	-16.63	40	31.56	23.64	0.46	32.29	-	-	P	H
		125.06	28.25	-15.25	43.5	42.27	17.2	0.97	32.19	-	-	P	H
		220.12	29.76	-16.24	46	45.61	15.01	1.28	32.14	-	-	P	H
		338.46	28.24	-17.76	46	39.14	19.74	1.51	32.15	-	-	P	H
		718.7	37.9	-8.1	46	40.92	26.75	2.28	32.05	100	0	P	H
		952.47	33.66	-12.34	46	31.41	30.55	2.66	30.96	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
		34.85	31.51	-8.49	40	40.94	22.39	0.47	32.29	100	0	P	V
		91.11	24.1	-19.4	43.5	41.13	14.43	0.76	32.22	-	-	P	V
		120.21	28.01	-15.49	43.5	42.16	17.1	0.95	32.2	-	-	P	V
		169.68	25.14	-18.36	43.5	40.85	15.33	1.12	32.16	-	-	P	V
		862.26	31.98	-14.02	46	32.2	28.75	2.62	31.59	-	-	P	V
		953.44	33.13	-12.87	46	30.86	30.57	2.66	30.96	-	-	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



2.4GHz 2400~2483.5MHz

BLE_2Mbps (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2353.89	55.09	-18.91	74	40.71	27.78	13.89	27.29	108	208	P	H
		2316.825	47.5	-6.5	54	33.07	27.87	13.86	27.3	108	208	A	H
	*	2402	99.55	-	-	85.31	27.6	13.93	27.29	108	208	P	H
	*	2402	98.17	-	-	83.93	27.6	13.93	27.29	108	208	A	H
													H
													H
		2373.105	54.97	-19.03	74	40.64	27.71	13.91	27.29	110	84	P	V
		2321.025	47.68	-6.32	54	33.25	27.86	13.87	27.3	110	84	A	V
	*	2402	97.92	-	-	83.68	27.6	13.93	27.29	110	84	P	V
	*	2402	96.61	-	-	82.37	27.6	13.93	27.29	110	84	A	V
													V
													V
BLE CH 19 2440MHz		2324	54.94	-19.06	74	40.52	27.85	13.87	27.3	130	209	P	H
		2338.98	47.64	-6.36	54	33.24	27.82	13.88	27.3	130	209	A	H
	*	2440	96.94	-	-	82.74	27.52	13.96	27.28	130	209	P	H
	*	2440	95.68	-	-	81.48	27.52	13.96	27.28	130	209	A	H
		2491.67	55.45	-18.55	74	41.21	27.5	14.01	27.27	130	209	P	H
		2486.28	47.62	-6.38	54	33.39	27.5	14	27.27	130	209	A	H
		2360.12	55.65	-18.35	74	41.28	27.76	13.9	27.29	100	99	P	V
		2338.42	47.36	-6.64	54	32.96	27.82	13.88	27.3	100	99	A	V
	*	2440	94.64	-	-	80.44	27.52	13.96	27.28	100	99	P	V
	*	2440	93.29	-	-	79.09	27.52	13.96	27.28	100	99	A	V
		2492.3	54.52	-19.48	74	40.28	27.5	14.01	27.27	100	99	P	V
		2490.69	47.52	-6.48	54	33.28	27.5	14.01	27.27	100	99	A	V



BLE CH 39 2480MHz	*	2480	101.93	-	-	87.7	27.5	14	27.27	126	210	P	H
	*	2480	100.67	-	-	86.44	27.5	14	27.27	126	210	A	H
		2496.68	55.34	-18.66	74	41.1	27.5	14.01	27.27	126	210	P	H
		2484.92	47.6	-6.4	54	33.37	27.5	14	27.27	126	210	A	H
													H
													H
	*	2480	100.36	-	-	86.13	27.5	14	27.27	100	98	P	V
	*	2480	99.19	-	-	84.96	27.5	14	27.27	100	98	A	V
		2486.72	55.38	-18.62	74	41.15	27.5	14	27.27	100	98	P	V
		2492.48	47.82	-6.18	54	33.58	27.5	14.01	27.27	100	98	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE_2Mbps (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	36.16	-37.84	74	56.26	31.11	6.38	57.59	100	0	P	H
													H
													H
													H
		4804	36.87	-37.13	74	56.97	31.11	6.38	57.59	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	38.08	-35.92	74	57.73	31.2	6.59	57.44	100	0	P	H
		7320	43.82	-30.18	74	56.11	36.76	8.23	57.28	100	0	P	H
													H
													H
		4880	38.63	-35.37	74	58.28	31.2	6.59	57.44	100	0	P	V
		7320	42.37	-31.63	74	54.66	36.76	8.23	57.28	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	38.21	-35.79	74	57.31	31.36	6.82	57.28	100	0	P	H
		7440	43.54	-30.46	74	56.09	36.68	8.2	57.43	100	0	P	H
													H
													H
		4960	38.96	-35.04	74	58.06	31.36	6.82	57.28	100	0	P	V
		7440	43.03	-30.97	74	55.58	36.68	8.2	57.43	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE_2Mbps (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		119.24	29.84	-13.66	43.5	43.99	17.1	0.95	32.2	-	-	P	H
		216.24	30.56	-15.44	46	46.81	14.62	1.27	32.14	-	-	P	H
		265.71	29.24	-16.76	46	40.54	19.47	1.38	32.15	-	-	P	H
		329.73	27.83	-18.17	46	38.99	19.49	1.5	32.15	-	-	P	H
		871.96	32.18	-13.82	46	32.41	28.7	2.61	31.54	-	-	P	H
		944.71	33.9	-12.1	46	32.08	30.19	2.66	31.03	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		33.88	28.71	-11.29	40	37.61	22.92	0.47	32.29	100	0	P	V
		55.22	25.93	-14.07	40	45.58	12.08	0.55	32.28	-	-	P	V
		120.21	28.89	-14.61	43.5	43.04	17.1	0.95	32.2	-	-	P	V
		169.68	24.75	-18.75	43.5	40.46	15.33	1.12	32.16	-	-	P	V
		839.95	31.39	-14.61	46	31.91	28.6	2.58	31.7	-	-	P	V
		935.98	33.27	-12.73	46	31.96	29.76	2.65	31.1	-	-	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.







Appendix D. Radiated Spurious Emission Plots





Test Engineer :	Jesse Wang , JC Liang , Wilson Wu	Temperature :	21.5 ~ 23.5°C
		Relative Humidity :	46.5 ~ 49.5%

Note symbol





-L	Low channel location
-R	High channel location



2.4GHz 2400~2483.5MHz
BLE_1Mbps (Band Edge @ 3m)





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 16	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 16
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 16	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 16



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 16	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 16
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 16	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 16
Avg		











BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Level (dBuV/m) vs Frequency (MHz) plot for Peak Horizontal. The plot shows a sharp peak at 2440 MHz. The y-axis ranges from 17.5 to 140 dBuV/m, and the x-axis ranges from 2310 to 2450 MHz. A red line indicates the peak level at approximately 105 dBuV/m. Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17	 Level (dBuV/m) vs Frequency (MHz) plot for Peak Fundamental. The plot shows a sharp peak at 2440 MHz. The y-axis ranges from 17.5 to 140 dBuV/m, and the x-axis ranges from 2300 to 2500 MHz. A red line indicates the peak level at approximately 105 dBuV/m. Site : 03CH13-HV Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17
Avg.	 Level (dBuV/m) vs Frequency (MHz) plot for Avg Horizontal. The plot shows a sharp peak at 2440 MHz. The y-axis ranges from 17.5 to 140 dBuV/m, and the x-axis ranges from 2310 to 2450 MHz. A red line indicates the average level at approximately 105 dBuV/m. Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17	 Level (dBuV/m) vs Frequency (MHz) plot for Avg Fundamental. The plot shows a sharp peak at 2440 MHz. The y-axis ranges from 17.5 to 140 dBuV/m, and the x-axis ranges from 2300 to 2500 MHz. A red line indicates the average level at approximately 105 dBuV/m. Site : 03CH13-HV Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 17	Left blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 17	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 17

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 17	Left blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 17	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18
	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 18



2.4GHz 2400~2483.5MHz

BLE_1Mbps (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 16	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 16





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 17	Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 17











BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 1B	Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 1B





Emission below 1GHz
2.4GHz BLE_1Mbps (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH13-HY Condition : QP 3m BTL06_40103 HORIZONTAL Detector : Peak Project : 9H42705 Mode : 24	 Site : 03CH13-HY Condition : QP 3m BTL06_40103 VERTICAL Detector : Peak Project : 9H42705 Mode : 24



2.4GHz 2400~2483.5MHz
BLE_2Mbps (Band Edge @ 3m)





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 19	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 19
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 19	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 19



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 19	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 19
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 19	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 19





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20
	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20	 Site : 03CH13-HV Condition : AVG_54 3m HORN_9120D_1241 HORIZONTAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 20	Left blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 20	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : 20
Avg.		



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 20	Left blank
Avg.	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 20	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HV Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : Z1	 Site : 03CH13-HV Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : Z1
	 Site : 03CH13-HV Condition : AVG_BE_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : Z1	 Site : 03CH13-HV Condition : AVG_54 3m HORN_91200_1241 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 9N2705 Mode : Z1



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : Z1	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : Z1
	 Site : 03CH13-HY Condition : AVG_BE_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : Z1	 Site : 03CH13-HY Condition : AVG_54 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : Z1





2.4GHz 2400~2483.5MHz
BLE_2Mbps (Harmonic @ 3m)



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N42705 Mode : 19	 Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N42705 Mode : 19



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 20	 Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 20


BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL Detector : Peak Project : 9N2705 Mode : 21	 Site : 03CH13-4V Condition : PEAK_74 3m HORN_91200_1241 VERTICAL Detector : Peak Project : 9N2705 Mode : 21

Emission below 1GHz
2.4GHz BLE_2Mbps (LF)


BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH13-HY Condition : QP 3m BTL06_40103 HORIZONTAL Detector : Peak Project : 9H42705 Mode : 25	 Site : 03CH13-HY Condition : QP 3m BTL06_40103 VERTICAL Detector : Peak Project : 9H42705 Mode : 25

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth –LE_1Mbps	62.62	392	2.55	3kHz	2.03
Bluetooth –LE_2Mbps	32.59	204	4.90	10kHz	4.87

Bluetooth – LE_1Mbps


Date: 27.NOV.2019 22:57:36

Bluetooth – LE_2Mbps


Date: 27.NOV.2019 23:00:15