



# FCC RF Test Report

**APPLICANT** : Lenovo(Shanghai) Electronics Technology Co., Ltd.  
**EQUIPMENT** : Portable Tablet Computer  
**BRAND NAME** : Lenovo  
**MODEL NAME** : Lenovo PB-6505Y  
**FCC ID** : O57PB6505Y  
**STANDARD** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : (NII) Unlicensed National Information Infrastructure

The product was received on Mar. 29, 2019 and testing was completed on May 13, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*James Huang*

Approved by: James Huang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Product Feature of Equipment Under Test..... 5

    1.3 Product Specification of Equipment Under Test..... 6

    1.4 Modification of EUT ..... 7

    1.5 Testing Location ..... 7

    1.6 Applicable Standards..... 7

    1.7 Specification of Accessory..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Carrier Frequency and Channel ..... 9

    2.2 Test Mode ..... 10

    2.3 Connection Diagram of Test System..... 12

    2.4 Support Unit used in test configuration and system ..... 12

    2.5 EUT Operation Test Setup ..... 13

    2.6 Measurement Results Explanation Example..... 13

**3 TEST RESULT..... 14**

    3.1 26dB & 99% Occupied Bandwidth Measurement ..... 14

    3.2 Maximum Conducted Output Power Measurement ..... 16

    3.3 Power Spectral Density Measurement ..... 18

    3.4 Unwanted Emissions Measurement ..... 21

    3.5 AC Conducted Emission Measurement..... 26

    3.6 Automatically Discontinue Transmission ..... 28

    3.7 Antenna Requirements..... 29

**4 LIST OF MEASURING EQUIPMENT ..... 30**

**5 UNCERTAINTY OF EVALUATION ..... 31**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	2.1049 & 15.403(i)	26dB & 99% Bandwidth	-	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	Pass	Under limit 3.34 dB at 5149.760 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.11 dB at 0.499 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.

Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

## 1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	Lenovo PB-6505Y
FCC ID	O57PB6505Y
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40 Bluetooth BR/EDR/LE FM Receiver and GNSS
HW Version	Lenovo Tablet PB-6505Y
SW Version	PB-6505Y_RF01_190615
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5700 MHz
<b>Maximum Output Power to Antenna</b>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 15.33 dBm / 0.0341 W  802.11n HT20 : 15.18 dBm / 0.0330 W  802.11n HT40 : 15.59 dBm / 0.0362 W  802.11ac VHT20 : 15.14 dBm / 0.0327 W  802.11ac VHT40 : 15.93 dBm / 0.0392 W</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 15.32 dBm / 0.0340 W  802.11n HT20 : 15.08 dBm / 0.0322 W  802.11n HT40 : 15.57 dBm / 0.0361 W  802.11ac VHT20 : 15.04 dBm / 0.0319 W  802.11ac VHT40 : 15.94 dBm / 0.0393 W</p> <p><b>&lt;5500 MHz ~ 5700 MHz &gt;</b>  802.11a : 15.20 dBm / 0.0331 W  802.11n HT20 : 15.40 dBm / 0.0347 W  802.11n HT40 : 15.57 dBm / 0.0361 W  802.11ac VHT20 : 15.36 dBm / 0.0344 W  802.11ac VHT40 : 15.99 dBm / 0.0397 W</p>
<b>99% Occupied Bandwidth</b>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  802.11a : 18.28 MHz  802.11n HT20 : 19.08 MHz  802.11ac VHT40 : 36.56 MHz</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  802.11a : 18.28 MHz  802.11n HT20 : 19.23 MHz  802.11ac VHT40 : 36.66 MHz</p> <p><b>&lt;5500 MHz ~ 5700 MHz &gt;</b>  802.11a : 18.53 MHz  802.11n HT20 : 19.28 MHz  802.11ac VHT40 : 36.96 MHz</p>
<b>Antenna Gain / Gain</b>	<p><b>&lt;5180 MHz ~ 5240 MHz&gt;</b>  PIFA Antenna with gain -2.80 dBi</p> <p><b>&lt;5260 MHz ~ 5320 MHz&gt;</b>  PIFA Antenna with gain -2.60 dBi</p> <p><b>&lt;5500 MHz ~ 5700 MHz &gt;</b>  PIFA Antenna with gain -2.40 dBi</p>
<b>Type of Modulation</b>	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

**Note:**

1. WLAN operation in 5600 MHz ~ 5650 MHz is notched.
2. For 802.11an HT20 / ac VHT20 and 802.11an HT40 / ac VHT40 mode, the whole testing have assessed only 802.11an HT20/ ac VHT40 by referring to their maximum conducted power.



### 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.5 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-0512-57900158 FAX : +86-0512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

### 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

### 1.7 Specification of Accessory

Specification of Accessory				
AC Adapter 1 (US)	Brand Name	Lenovo (Salom)	Model Name	SC-41
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 1 (UK)	Brand Name	Lenovo (Salom)	Model Name	SC-43
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 1 (AR)	Brand Name	Lenovo (Salom)	Model Name	SC-46
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2 (US)	Brand Name	Lenovo (Acbel)	Model Name	SC-41
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2 (UK)	Brand Name	Lenovo (Acbel)	Model Name	SC-43
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
AC Adapter 2 (AR)	Brand Name	Lenovo (Acbel)	Model Name	SC-46
	Power Rating	I/P: 100 - 240 Vac, 300mA, O/P: 5Vdc, 2000mA		
Battery	Brand Name	Lenovo (NVT)	Model Name	L18D1P33
	Power Rating	3.85Vdc,5180mAh	Type	Li-ion
USB Cable 1	Brand Name	Lenovo (Leagtech)	Model Name	711300000371
	Signal Line	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	Brand Name	Lenovo (Chinapysind)	Model Name	711300000441
	Signal Line	1.0 meter, shielded cable, without ferrite core		



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
5260-5320 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
5500-5700 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	-	-	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

**Note:**

- 1. The above Frequency and Channel in "\*" were 802.11n HT40 and 802.11ac VHT40.



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11ac VHT40	MCS0

Test Cases	
<b>AC Conducted Emission</b>	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from adapter 1) + Earphone
<b>Remark:</b> For Radiated Test Cases, The tests were performed with Adapter 1, USB Cable 1 and Earphone.	




Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5700 MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140

Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5700 MHz
		802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140

Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5700 MHz
		802.11ac VHT40	802.11ac VHT40	802.11ac VHT40
L	Low	38	54	102
M	Middle	-	-	110
H	High	46	62	134

### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2 m	N/A



## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss

*Offset = RF cable loss*

Following shows an offset computation example with cable loss 6.8 dB

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 6.8 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 26dB & 99% Occupied Bandwidth Measurement

##### 3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
8. Measure and record the results in the test report.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



## 3.2 Maximum Conducted Output Power Measurement

### 3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm  $10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where x is the duty cycle.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.3.3 Test Procedures


The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.  
Section F) Maximum power spectral density.

#### # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW  $\geq$  3 MHz.
- Number of points in sweep  $\geq$  2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



**Note:** Average Power Density (dB) = Measured value+ Duty Factor



### 3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

#### 3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3



EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.3

**Note:** The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

$E_{Meas}$  is the field strength of the emission at the measurement distance, in dBµV/m

$d_{Meas}$  is the measurement distance, in m

### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.
  - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
    - RBW = 120 kHz
    - VBW = 300 kHz
    - Detector = Peak
    - Trace mode = max hold
  - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
    - RBW = 1 MHz
    - VBW  $\geq$  3 MHz
    - Detector = Peak
    - Sweep time = auto
    - Trace mode = max hold
  - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
    - RBW = 1 MHz
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq$  1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### 3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

### 3.4.7 Duty Cycle

Please refer to Appendix D.

### 3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.



### 3.5 AC Conducted Emission Measurement

#### 3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.5.4 Test Setup



### 3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.6 Automatically Discontinue Transmission**

### **3.6.1 Limit of Automatically Discontinue Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

### **3.6.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.6.3 Test Result of Automatically Discontinue Transmission**

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Apr. 27, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 11, 2018	Apr. 27, 2019	Oct. 10, 2019	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 14, 2019	Apr. 27, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Apr. 27, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz; Max 30dBm	Oct. 12, 2018	May 13, 2019	Oct. 11, 2019	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz~44GHz	Jun. 25, 2018	May 13, 2019	Jun. 24, 2019	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	May 13, 2019	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 28, 2018	May 13, 2019	Dec. 27, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	May 13, 2019	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	May 13, 2019	Jan. 04, 2020	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	May 13, 2019	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	May 13, 2019	Jan. 13, 2020	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2019	May 13, 2019	Apr. 16, 2020	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2019	May 13, 2019	Apr. 14, 2020	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 13, 2019	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 13, 2019	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 13, 2019	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2019	Apr. 28, 2019	Apr. 15, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Apr. 28, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Apr. 28, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Apr. 28, 2019	Oct. 11, 2019	Conduction (CO01-KS)



## 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.9dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------



## **Appendix A. Conducted Test Results**

Test Engineer:	Weller Liu	Temperature:	21~25	°C
Test Date:	2019/4/27	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**26dB and 99% OBW**

Band I										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)		
11a	6Mbps	1	36	5180	18.04	23.28	-	22.56		
11a	6Mbps	1	44	5220	18.28	23.64	-	22.62		
11a	6Mbps	1	48	5240	18.28	23.73	-	22.62		
HT20	MCS0	1	36	5180	19.03	23.73	-	22.79		
HT20	MCS0	1	44	5220	19.08	23.88	-	22.81		
HT20	MCS0	1	48	5240	19.03	23.83	-	22.79		
VHT40	MCS0	1	38	5190	36.56	44.33	-	23.01		
VHT40	MCS0	1	46	5230	36.46	44.69	-	23.01		

**TEST RESULTS DATA**  
**Average Power Table**

FCC Band I										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.59	15.05	24.00	-2.80		Pass
11a	6Mbps	1	44	5220	0.59	15.18	24.00	-2.80		Pass
11a	6Mbps	1	48	5240	0.59	15.33	24.00	-2.80		Pass
HT20	MCS0	1	36	5180	0.63	14.77	24.00	-2.80		Pass
HT20	MCS0	1	44	5220	0.63	14.86	24.00	-2.80		Pass
HT20	MCS0	1	48	5240	0.63	15.18	24.00	-2.80		Pass
HT40	MCS0	1	38	5190	0.65	15.46	24.00	-2.80		Pass
HT40	MCS0	1	46	5230	0.65	15.59	24.00	-2.80		Pass
VHT20	MCS0	1	36	5180	0.81	14.89	24.00	-2.80		Pass
VHT20	MCS0	1	44	5220	0.81	14.93	24.00	-2.80		Pass
VHT20	MCS0	1	48	5240	0.81	15.14	24.00	-2.80		Pass
VHT40	MCS0	1	38	5190	1.50	15.75	24.00	-2.80		Pass
VHT40	MCS0	1	46	5230	1.50	15.93	24.00	-2.80		Pass

**TEST RESULTS DATA**  
**Power Spectral Density**

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.59	2.83	11.00	-2.80		Pass
11a	6Mbps	1	44	5220	0.59	3.05	11.00	-2.80		Pass
11a	6Mbps	1	48	5240	0.59	3.53	11.00	-2.80		Pass
HT20	MCS0	1	36	5180	0.63	2.44	11.00	-2.80		Pass
HT20	MCS0	1	44	5220	0.63	2.52	11.00	-2.80		Pass
HT20	MCS0	1	48	5240	0.63	3.14	11.00	-2.80		Pass
VHT40	MCS0	1	38	5190	1.50	1.35	11.00	-2.80		Pass
VHT40	MCS0	1	46	5230	1.50	1.39	11.00	-2.80		Pass

**TEST RESULTS DATA**  
**26dB and 99% OBW**

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	52	5260	18.03	23.48	23.56	29.56	23.98	
11a	6M bps	1	60	5300	18.28	23.68	23.62	29.62	23.98	
11a	6M bps	1	64	5320	18.28	23.68	23.62	29.62	23.98	
HT20	MCS 0	1	52	5260	19.08	24.03	23.81	29.81	23.98	
HT20	MCS 0	1	60	5300	19.23	24.83	23.84	29.84	23.98	
HT20	MCS 0	1	64	5320	19.23	23.88	23.84	29.84	23.98	
VHT40	MCS 0	1	54	5270	36.56	44.96	23.98	30.00	23.98	
VHT40	MCS 0	1	62	5310	36.66	44.78	23.98	30.00	23.98	

**TEST RESULTS DATA**  
**Average Power Table**

FCC Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	52	5260	0.59	15.26	23.98	-2.60	26.99	Pass
11a	6M bps	1	60	5300	0.59	15.25	23.98	-2.60	26.99	Pass
11a	6M bps	1	64	5320	0.59	15.32	23.98	-2.60	26.99	Pass
HT20	MCS 0	1	52	5260	0.63	15.08	23.98	-2.60	26.99	Pass
HT20	MCS 0	1	60	5300	0.63	14.79	23.98	-2.60	26.99	Pass
HT20	MCS 0	1	64	5320	0.63	15.01	23.98	-2.60	26.99	Pass
HT40	MCS 0	1	54	5270	0.65	15.57	23.98	-2.60	26.99	Pass
HT40	MCS 0	1	62	5310	0.65	15.52	23.98	-2.60	26.99	Pass
VHT20	MCS 0	1	52	5260	0.81	15.03	23.98	-2.60	26.99	Pass
VHT20	MCS 0	1	60	5300	0.81	14.90	23.98	-2.60	26.99	Pass
VHT20	MCS 0	1	64	5320	0.81	15.04	23.98	-2.60	26.99	Pass
VHT40	MCS 0	1	54	5270	1.50	15.94	23.98	-2.60	26.99	Pass
VHT40	MCS 0	1	62	5310	1.50	15.81	23.98	-2.60	26.99	Pass

**TEST RESULTS DATA**  
**Power Spectral Density**

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	52	5260	0.59	3.66	11.00	-2.60		Pass
11a	6M bps	1	60	5300	0.59	3.43	11.00	-2.60		Pass
11a	6M bps	1	64	5320	0.59	3.72	11.00	-2.60		Pass
HT20	MCS 0	1	52	5260	0.63	3.06	11.00	-2.60		Pass
HT20	MCS 0	1	60	5300	0.63	3.02	11.00	-2.60		Pass
HT20	MCS 0	1	64	5320	0.63	2.83	11.00	-2.60		Pass
VHT40	MCS 0	1	54	5270	1.50	1.56	11.00	-2.60		Pass
VHT40	MCS 0	1	62	5310	1.50	1.17	11.00	-2.60		Pass

**TEST RESULTS DATA**  
**26dB and 99% OBW**

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	100	5500	18.53	23.58	23.68	29.68	23.98	
11a	6M bps	1	116	5580	18.53	23.88	23.68	29.68	23.98	
11a	6M bps	1	140	5700	18.38	23.68	23.64	29.64	23.98	
HT20	MCS 0	1	100	5500	19.18	24.03	23.83	29.83	23.98	
HT20	MCS 0	1	116	5580	19.28	23.88	23.85	29.85	23.98	
HT20	MCS 0	1	140	5700	19.18	23.83	23.83	29.83	23.98	
VHT40	MCS 0	1	102	5510	36.86	45.32	23.98	30.00	23.98	
VHT40	MCS 0	1	110	5550	36.86	46.57	23.98	30.00	23.98	
VHT40	MCS 0	1	134	5670	36.96	44.69	23.98	30.00	23.98	

**TEST RESULTS DATA**  
**Average Power Table**

FCC Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	100	5500	0.59	15.20	23.98	-2.40	26.99	Pass
11a	6M bps	1	116	5580	0.59	15.06	23.98	-2.40	26.99	Pass
11a	6M bps	1	140	5700	0.59	15.14	23.98	-2.40	26.99	Pass
HT20	MCS 0	1	100	5500	0.63	15.14	23.98	-2.40	26.99	Pass
HT20	MCS 0	1	116	5580	0.63	15.10	23.98	-2.40	26.99	Pass
HT20	MCS 0	1	140	5700	0.63	15.40	23.98	-2.40	26.99	Pass
HT40	MCS 0	1	102	5510	0.65	15.47	23.98	-2.40	26.99	Pass
HT40	MCS 0	1	110	5550	0.65	15.26	23.98	-2.40	26.99	Pass
HT40	MCS 0	1	134	5670	0.65	15.57	23.98	-2.40	26.99	Pass
VHT20	MCS 0	1	100	5500	0.81	15.20	23.98	-2.40	26.99	Pass
VHT20	MCS 0	1	116	5580	0.81	15.04	23.98	-2.40	26.99	Pass
VHT20	MCS 0	1	140	5700	0.81	15.36	23.98	-2.40	26.99	Pass
VHT40	MCS 0	1	102	5510	1.50	15.82	23.98	-2.40	26.99	Pass
VHT40	MCS 0	1	110	5550	1.50	15.65	23.98	-2.40	26.99	Pass
VHT40	MCS 0	1	134	5670	1.50	15.99	23.98	-2.40	26.99	Pass


**TEST RESULTS DATA**  
**Power Spectral Density**

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	100	5500	0.59	3.58	11.00	-2.40		Pass
11a	6M bps	1	116	5580	0.59	3.74	11.00	-2.40		Pass
11a	6M bps	1	140	5700	0.59	3.62	11.00	-2.40		Pass
HT20	MCS 0	1	100	5500	0.63	2.70	11.00	-2.40		Pass
HT20	MCS 0	1	116	5580	0.63	2.87	11.00	-2.40		Pass
HT20	MCS 0	1	140	5700	0.63	3.14	11.00	-2.40		Pass
VHT40	MCS 0	1	102	5510	1.50	1.07	11.00	-2.40		Pass
VHT40	MCS 0	1	110	5550	1.50	1.33	11.00	-2.40		Pass
VHT40	MCS 0	1	134	5670	1.50	1.31	11.00	-2.40		Pass



## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhao	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS  
 Condition : FCC PART 15E LISN-L-181119-060105 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.499	44.01	-12.00	56.01	33.61	0.17	10.23	QP
2 *	0.499	35.90	-10.11	46.01	25.50	0.17	10.23	Average
3	0.637	42.62	-13.38	56.00	32.20	0.18	10.24	QP
4	0.637	34.02	-11.98	46.00	23.60	0.18	10.24	Average
5	1.060	42.34	-13.66	56.00	31.91	0.20	10.23	QP
6	1.060	31.04	-14.96	46.00	20.61	0.20	10.23	Average
7	1.560	40.94	-15.06	56.00	30.50	0.21	10.23	QP
8	1.560	28.64	-17.36	46.00	18.20	0.21	10.23	Average
9	2.622	41.67	-14.33	56.00	31.20	0.23	10.24	QP
10	2.622	30.67	-15.33	46.00	20.20	0.23	10.24	Average
11	13.057	40.91	-19.09	60.00	30.30	0.23	10.38	QP
12	13.057	27.21	-22.79	50.00	16.60	0.23	10.38	Average



Test Engineer :	Amos Zhao	Temperature :	23.3~24.2°C
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS  
 Condition : FCC PART 15E LISN-N-181119-060105 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.567	40.68	-15.32	56.00	30.30	0.14	10.24	QP
2	0.567	28.98	-17.02	46.00	18.60	0.14	10.24	Average
3	1.203	41.97	-14.03	56.00	31.60	0.14	10.23	QP
4 *	1.203	32.67	-13.33	46.00	22.30	0.14	10.23	Average
5	2.567	40.69	-15.31	56.00	30.29	0.16	10.24	QP
6	2.567	29.59	-16.41	46.00	19.19	0.16	10.24	Average
7	11.933	42.01	-17.99	60.00	31.50	0.15	10.36	QP
8	11.933	29.11	-20.89	50.00	18.60	0.15	10.36	Average
9	13.057	43.71	-16.29	60.00	33.19	0.14	10.38	QP
10	13.057	29.41	-20.59	50.00	18.89	0.14	10.38	Average
11	13.989	42.72	-17.28	60.00	32.20	0.13	10.39	QP
12	13.989	29.12	-20.88	50.00	18.60	0.13	10.39	Average



## Appendix C. Radiated Spurious Emission

### Band 1 - 5150~5250MHz WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		5127.04	52.93	-21.07	74	46.23	35.06	8.14	36.5	296	334	P	H
		5127.52	44.29	-9.71	54	37.59	35.06	8.14	36.5	296	334	A	H
	*	5174	104.25	-	-	97.49	35.08	8.17	36.49	296	334	P	H
		5174	96.87	-	-	90.11	35.08	8.17	36.49	296	334	A	H
		5125.6	51.99	-22.01	74	45.29	35.06	8.14	36.5	400	14	P	V
		5127.68	42.86	-11.14	54	36.16	35.06	8.14	36.5	400	14	A	V
	*	5176	104.81	-	-	98.05	35.08	8.17	36.49	400	14	P	V
		5176	97.56	-	-	90.8	35.08	8.17	36.49	400	14	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		10360	43.28	-25.02	68.3	57	37.47	11.87	63.06	150	360	P	H
		10360	43.79	-24.51	68.3	57.51	37.47	11.87	63.06	150	360	P	V
802.11a CH 44 5220MHz		10440	43.14	-25.16	68.3	56.75	37.5	11.93	63.04	150	360	P	H
		10440	43.23	-25.07	68.3	56.84	37.5	11.93	63.04	150	360	P	V
802.11a CH 48 5240MHz		10480	42.41	-25.89	68.3	55.94	37.53	11.97	63.03	150	360	P	H
		10480	43.12	-25.18	68.3	56.65	37.53	11.97	63.03	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		5127.84	54.14	-19.86	74	47.44	35.06	8.14	36.5	297	333	P	H
		5128.32	45.47	-8.53	54	38.77	35.06	8.14	36.5	297	333	A	H
	*	5184	104.8	-	-	98.04	35.08	8.17	36.49	297	333	P	H
		5184	97.41	-	-	90.65	35.08	8.17	36.49	297	333	A	H
		5128	55.52	-18.48	74	48.82	35.06	8.14	36.5	337	13	P	V
		5128.32	45.91	-8.09	54	39.21	35.06	8.14	36.5	337	13	A	V
	*	5174	105.04	-	-	98.28	35.08	8.17	36.49	337	13	P	V
		5174	97.61	-	-	90.85	35.08	8.17	36.49	337	13	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for channels 36, 44, and 48 at frequencies 10360, 10440, and 10480 MHz.



**Band 1 5150~5250MHz**  
**WIFI 802.11ac VHT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
<b>802.11ac VHT40 CH 38 5190MHz</b>		5143.52	60.42	-13.58	74	53.72	35.06	8.14	36.5	100	323	P	H
		5149.76	50.66	-3.34	54	43.96	35.06	8.14	36.5	100	323	A	H
	*	5200	103.19	-	-	96.39	35.09	8.2	36.49	100	323	P	H
		5200	96.03	-	-	89.23	35.09	8.2	36.49	100	323	A	H
		5351.04	48.77	-25.23	74	41.76	35.16	8.3	36.45	100	323	P	H
		5384.88	40.12	-13.88	54	33.09	35.18	8.3	36.45	100	323	A	H
		5147.36	57.58	-16.42	74	50.88	35.06	8.14	36.5	332	348	P	V
		5149.98	47.67	-6.33	54	40.97	35.06	8.14	36.5	332	348	A	V
	*	5188	100.5	-	-	93.74	35.08	8.17	36.49	332	348	P	V
		5188	94.92	-	-	88.16	35.08	8.17	36.49	332	348	A	V
		5367.42	48.17	-25.83	74	41.15	35.17	8.3	36.45	332	348	P	V
		5370.3	39.82	-14.18	54	32.8	35.17	8.3	36.45	332	348	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 38 5190MHz		10380	41.28	-27.02	68.3	54.95	37.48	11.9	63.05	100	360	P	H
802.11ac VHT40 CH 46 5230MHz		10380	42.16	-26.14	68.3	55.83	37.48	11.9	63.05	100	360	P	V
802.11ac VHT40 CH 38 5190MHz		10460	42.31	-25.99	68.3	55.87	37.51	11.97	63.04	100	360	P	H
802.11ac VHT40 CH 46 5230MHz		10460	44.14	-24.16	68.3	57.7	37.51	11.97	63.04	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

Band 2 - 5250~5350MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 64 5320MHz		5372.4	50.52	-23.48	74	43.5	35.17	8.3	36.45	299	332	P	H
		5372.3	43.29	-10.71	54	36.27	35.17	8.3	36.45	299	332	A	H
	*	5316	103.97	-	-	97.01	35.15	8.27	36.46	299	332	P	H
		5316	96.69	-	-	89.73	35.15	8.27	36.46	299	332	A	H
		5350.7	51.16	-22.84	74	44.15	35.16	8.3	36.45	400	11	P	V
		5372.5	41.34	-12.66	54	34.32	35.17	8.3	36.45	400	11	A	V
	*	5314	104.76	-	-	97.8	35.15	8.27	36.46	400	11	P	V
		5314	97.48	-	-	90.52	35.15	8.27	36.46	400	11	A	V
Remark	<p>1. No other spurious found.</p> <p>2. All results are PASS against Peak and Average limit line.</p>												



Band 2 5250~5350MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 52 5260MHz		10520	43.18	-25.12	68.3	56.67	37.54	12	63.03	150	360	P	H
		10520	42.81	-25.49	68.3	56.3	37.54	12	63.03	150	360	P	V
802.11a CH 60 5300MHz		10600	42.53	-25.77	68.3	55.9	37.58	12.06	63.01	150	360	P	H
		10600	42.98	-25.32	68.3	56.35	37.58	12.06	63.01	150	360	P	V
802.11a CH 64 5320MHz		10640	43.68	-30.32	74	56.99	37.6	12.09	63	150	360	P	H
		10640	43.98	-30.02	74	57.29	37.6	12.09	63	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 64 5320MHz		5372.9	51.5	-22.5	74	44.48	35.17	8.3	36.45	299	330	P	H
		5371.7	44.18	-9.82	54	37.16	35.17	8.3	36.45	299	330	A	H
	*	5324	103.59	-	-	96.63	35.15	8.27	36.46	299	330	P	H
		5324	96.4	-	-	89.44	35.15	8.27	36.46	299	330	A	H
		5372.8	49.62	-24.38	74	42.6	35.17	8.3	36.45	357	10	P	V
		5371.7	42.62	-11.38	54	35.6	35.17	8.3	36.45	357	10	A	V
	*	5314	103.11	-	-	96.15	35.15	8.27	36.46	357	10	P	V
		5314	96.02	-	-	89.06	35.15	8.27	36.46	357	10	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 2 5250~5350MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 52 5260MHz		10520	43.17	-25.13	68.3	56.66	37.54	12	63.03	150	360	P	H
		10520	43	-25.3	68.3	56.49	37.54	12	63.03	150	360	P	V
802.11n HT20 CH 60 5300MHz		10600	43.33	-24.97	68.3	56.7	37.58	12.06	63.01	150	360	P	H
		10600	44.19	-24.11	68.3	57.56	37.58	12.06	63.01	150	360	P	V
802.11n HT20 CH 64 5320MHz		10640	42.91	-31.09	74	56.22	37.6	12.09	63	150	360	P	H
		10640	44.7	-29.3	74	58.01	37.6	12.09	63	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11ac VHT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 62 5310MHz		5131.68	50.42	-23.58	74	43.72	35.06	8.14	36.5	116	297	P	H
		5122.08	41.32	-12.68	54	34.64	35.05	8.14	36.51	116	297	A	H
	*	5298	102.83	-	-	95.91	35.14	8.25	36.47	116	297	P	H
		5298	95.26	-	-	88.34	35.14	8.25	36.47	116	297	A	H
		5354.46	58.2	-15.8	74	51.19	35.16	8.3	36.45	116	297	P	H
		5350.08	44.88	-9.12	54	37.87	35.16	8.3	36.45	116	297	A	H
		5144.48	50.79	-23.21	74	44.09	35.06	8.14	36.5	320	346	P	V
		5119.36	41.33	-12.67	54	34.65	35.05	8.14	36.51	320	346	A	V
	*	5304	99.3	-	-	92.38	35.14	8.25	36.47	320	346	P	V
		5304	91.95	-	-	85.03	35.14	8.25	36.47	320	346	A	V
		5353.38	52.49	-21.51	74	45.48	35.16	8.3	36.45	320	346	P	V
		5350.03	41.54	-12.46	54	34.53	35.16	8.3	36.45	320	346	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11ac VHT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 54 5270MHz		10540	43.54	-24.76	68.3	56.98	37.55	12.03	63.02	100	360	P	H
802.11ac VHT40 CH 62 5310MHz		10120	43.06	-25.24	68.3	57.12	37.36	11.69	63.11	100	360	P	V
802.11ac VHT40 CH 62 5310MHz		10620	44.27	-29.73	74	57.6	37.59	12.09	63.01	100	360	P	H
802.11ac VHT40 CH 62 5310MHz		10620	46.16	-27.84	74	59.49	37.59	12.09	63.01	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 2 5250~5350MHz**  
**Band 3 - 5470~5725MHz**  
**WIFI 802.11a (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 100 5500MHz		5447.44	50.97	-23.03	74	43.83	35.21	8.36	36.43	110	290	P	H
		5469.52	48.11	-20.19	68.3	40.92	35.22	8.4	36.43	110	290	P	H
		5447.76	44.28	-9.72	54	37.14	35.21	8.36	36.43	110	290	A	H
	*	5496	105.15	-	-	97.94	35.23	8.4	36.42	110	290	P	H
		5496	97.82	-	-	90.61	35.23	8.4	36.42	110	290	A	H
		5447.92	50.35	-23.65	74	43.21	35.21	8.36	36.43	353	11	P	V
		5470	50.26	-18.04	68.3	43.07	35.22	8.4	36.43	353	11	P	V
		5447.6	43.13	-10.87	54	35.99	35.21	8.36	36.43	353	11	A	V
	*	5498	104.6	-	-	97.38	35.24	8.4	36.42	353	11	P	V
		5498	97.41	-	-	90.19	35.24	8.4	36.42	353	11	A	V
802.11a CH 140 5700MHz		5725.32	59.92	-8.38	68.3	52.52	35.22	8.61	36.43	111	291	P	H
	*	5704	106.4	-	-	98.97	35.24	8.61	36.42	111	291	P	H
		5704	99.12	-	-	91.69	35.24	8.61	36.42	111	291	A	H
		5725.16	57.79	-10.51	68.3	50.39	35.22	8.61	36.43	362	51	P	V
	*	5694	104.37	-	-	96.96	35.25	8.58	36.42	362	51	P	V
		5694	96.7	-	-	89.29	35.25	8.58	36.42	362	51	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 100 5500MHz		11000	43.98	-30.02	74	56.78	37.76	12.37	62.93	150	360	P	H
		11000	45.18	-28.82	74	57.98	37.76	12.37	62.93	150	360	P	V
802.11a CH 116 5580MHz		11600	43.35	-30.65	74	55.26	38.08	12.82	62.81	150	360	P	H
		11600	44.19	-29.81	74	56.1	38.08	12.82	62.81	150	360	P	V
802.11a CH 140 5700MHz		11400	44.03	-29.97	74	56.25	37.95	12.68	62.85	150	360	P	H
		11400	46.04	-27.96	74	58.26	37.95	12.68	62.85	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**Band 3 - 5470~5725MHz**  
**WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		5446.8	50.64	-23.36	74	43.5	35.21	8.36	36.43	106	290	P	H
		5469.2	53.18	-15.12	68.3	45.99	35.22	8.4	36.43	106	290	P	H
		5448.24	43.82	-10.18	54	36.68	35.21	8.36	36.43	106	290	A	H
	*	5494	103.5	-	-	96.29	35.23	8.4	36.42	106	290	P	H
		5494	96.38	-	-	89.17	35.23	8.4	36.42	106	290	A	H
		5447.6	49.63	-24.37	74	42.49	35.21	8.36	36.43	372	9	P	V
		5467.92	48.61	-19.69	68.3	41.42	35.22	8.4	36.43	372	9	P	V
		5448.24	43.34	-10.66	54	36.2	35.21	8.36	36.43	372	9	A	V
	*	5496	104.91	-	-	97.7	35.23	8.4	36.42	372	9	P	V
		5496	97.41	-	-	90.2	35.23	8.4	36.42	372	9	A	V
802.11n HT20 CH 140 5700MHz		5726.28	61.68	-6.62	68.3	54.28	35.22	8.61	36.43	116	288	P	H
	*	5696	109.18	-	-	101.77	35.25	8.58	36.42	116	288	P	H
		5696	101.65	-	-	94.24	35.25	8.58	36.42	116	288	A	H
		5725.24	60.25	-8.05	68.3	52.85	35.22	8.61	36.43	364	50	P	V
	*	5692	105.29	-	-	97.88	35.25	8.58	36.42	364	50	P	V
	5692	98.25	-	-	90.84	35.25	8.58	36.42	364	50	A	V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for channels 100, 116, and 140 at various frequencies.



**Band 3 - 5470~5725MHz**  
**WIFI 802.11ac VHT40 (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 CH 102 5510MHz		5459.28	55.98	-18.02	74	48.84	35.21	8.36	36.43	122	294	P	H
		5469.52	62.41	-5.89	68.3	55.22	35.22	8.4	36.43	122	294	P	H
		5459.92	43.68	-10.32	54	36.54	35.21	8.36	36.43	122	294	A	H
	*	5518	105.02	-	-	97.76	35.24	8.44	36.42	122	294	P	H
		5518	97.93	-	-	90.67	35.24	8.44	36.42	122	294	A	H
		5753.24	51.41	-16.89	68.3	44.03	35.19	8.64	36.45	122	294	P	H
		5373.36	49.71	-24.29	74	42.69	35.17	8.3	36.45	386	46	P	V
		5470	53.99	-14.31	68.3	46.8	35.22	8.4	36.43	386	46	P	V
		5406.96	42.03	-11.97	54	34.96	35.19	8.32	36.44	386	46	A	V
	*	5522	103.36	-	-	96.1	35.24	8.44	36.42	386	46	P	V
		5522	95.86	-	-	88.6	35.24	8.44	36.42	386	46	A	V
		5736.84	50.61	-17.69	68.3	43.23	35.21	8.61	36.44	386	46	P	V
802.11ac VHT40 CH 134 5670MHz		5420.24	49.78	-24.22	74	42.71	35.19	8.32	36.44	337	285	P	H
		5461.68	49.17	-19.13	68.3	42.03	35.21	8.36	36.43	337	285	P	H
		5447.76	40.35	-13.65	54	33.21	35.21	8.36	36.43	337	285	A	H
	*	5662	106.26	-	-	98.8	35.28	8.58	36.4	337	285	P	H
		5662	98.53	-	-	91.07	35.28	8.58	36.4	337	285	A	H
		5725.96	58.75	-9.55	68.3	51.35	35.22	8.61	36.43	337	285	P	H
		5432.24	49.7	-24.3	74	42.58	35.2	8.36	36.44	393	36	P	V
		5460.88	47.99	-20.31	68.3	40.85	35.21	8.36	36.43	393	36	P	V
		5391.6	40.26	-13.74	54	33.21	35.18	8.32	36.45	393	36	A	V
	*	5658	104.24	-	-	96.81	35.28	8.55	36.4	393	36	P	V
		5658	96.8	-	-	89.37	35.28	8.55	36.4	393	36	A	V
		5725.64	51.07	-17.23	68.3	43.67	35.22	8.61	36.43	393	36	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11ac VHT40 (Harmonic @ 3m)

Table with 14 columns: WIFI Ant. 1, Note, Frequency (MHz), Level (dBµV/m), Over Limit (dB), Limit Line (dBµV/m), Read Level (dBµV), Antenna Factor (dB/m), Cable Loss (dB), Preamp Factor (dB), Ant Pos (cm), Table Pos (deg), Peak Avg. (P/A), Pol. (H/V). Rows include data for channels 102, 110, and 134.



Emission below 1GHz  
WIFI 802.11ac VHT40 (LF @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT40 LF		30	25.68	-14.32	40	31.82	25.2	0.64	31.98	100	0	P	H
		128.94	19.49	-24.01	43.5	32.36	17.79	1.28	31.94	-	-	P	H
		250.19	28.6	-17.4	46	39.9	18.8	1.86	31.96	-	-	P	H
		350.1	30	-16	46	39.38	20.6	2.1	32.08	-	-	P	H
		499.48	31.63	-14.37	46	37.15	24.18	2.56	32.26	-	-	P	H
		549.92	30.97	-15.03	46	35.18	25.5	2.63	32.34	-	-	P	H
		30	34.03	-5.97	40	40.17	25.2	0.64	31.98	100	0	P	V
		92.08	17.3	-26.2	43.5	32.93	15.18	1.11	31.92	-	-	P	V
		250.19	20.77	-25.23	46	32.07	18.8	1.86	31.96	-	-	P	V
		549.92	31.4	-14.6	46	35.61	25.5	2.63	32.34	-	-	P	V
		649.83	31.12	-14.88	46	33.97	26.6	2.91	32.36	-	-	P	V
		749.74	29.64	-16.36	46	30.25	28.5	3.14	32.25	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m) = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB) = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB) = 55.45 (dBμV/m)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m) = 55.45(dBμV/m) – 74(dBμV/m) = -18.55(dB)

**For Average Limit @ 2390MHz:**


- Level(dBμV/m) = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB) = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB) = 43.54 (dBμV/m)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m) = 43.54(dBμV/m) – 54(dBμV/m) = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

## Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.26	1.370	0.730	0.75kHz
802.11an HT20	86.49	1.280	0.781	0.82kHz
802.11ac VHT40	70.86	0.496	2.016	2.20kHz

### 802.11a





802.11n HT20



802.11ac VHT40

