

# FCC RF Test Report

**APPLICANT** : Lenovo (Shanghai) Electronics Technology Co., Ltd.  
**EQUIPMENT** : Tablet PC  
**BRAND NAME** : Vodafone  
**MODEL NAME** : Smart Tab III<sup>10</sup>  
**MARKETING NAME** : Vodafone Smart Tab III10  
**FCC ID** : O57S6000VDF3G  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DSS) Spread Spectrum Transmitter


The product was received on Mar. 07, 2013 and completely tested on Mar. 23, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Manager



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**



## TABLE OF CONTENTS

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>REVISION HISTORY .....</b>                                   | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                             | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION .....</b>                              | <b>5</b>  |
| 1.1 Applicant .....                                             | 5         |
| 1.2 Manufacturer .....                                          | 5         |
| 1.3 Feature of Equipment Under Test .....                       | 5         |
| 1.4 Product Specification of Equipment Under Test .....         | 5         |
| 1.5 Testing Site .....                                          | 6         |
| 1.6 Applied Standards .....                                     | 6         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>       | <b>7</b>  |
| 2.1 Descriptions of Test Mode .....                             | 7         |
| 2.2 Test Mode .....                                             | 8         |
| 2.3 Connection Diagram of Test System .....                     | 9         |
| 2.4 Support Unit used in test configuration and system .....    | 10        |
| 2.5 Description of RF Function Operation Test Setup .....       | 10        |
| 2.6 Measurement Results Explanation Example .....               | 11        |
| <b>3 TEST RESULT .....</b>                                      | <b>12</b> |
| 3.1 Number of Channel Measurement .....                         | 12        |
| 3.2 Hopping Channel Separation Measurement .....                | 14        |
| 3.3 Dwell Time Measurement .....                                | 21        |
| 3.4 20dB Bandwidth Measurement .....                            | 23        |
| 3.5 Peak Output Power Measurement .....                         | 30        |
| 3.6 Conducted Band Edges Measurement .....                      | 33        |
| 3.7 Conducted Spurious Emission Measurement .....               | 40        |
| 3.8 Radiated Band Edges and Spurious Emission Measurement ..... | 44        |
| 3.9 AC Conducted Emission Measurement .....                     | 56        |
| 3.10 Antenna Requirements .....                                 | 60        |
| <b>4 LIST OF MEASURING EQUIPMENT .....</b>                      | <b>61</b> |
| <b>5 UNCERTAINTY OF EVALUATION .....</b>                        | <b>62</b> |
| <b>APPENDIX A. PHOTOGRAPHS OF EUT</b>                           |           |
| <b>APPENDIX B. SETUP PHOTOGRAPHS</b>                            |           |

## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FR342901A  | Rev. 01 | Initial issue of report | Jul. 11, 2013 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule           | Description                                        | Limit                                                            | Result | Remark                                    |
|----------------|--------------------|----------------------------------------------------|------------------------------------------------------------------|--------|-------------------------------------------|
| 3.1            | 15.247(a)(1)       | Number of Channels                                 | $\geq 15\text{Chs}$                                              | Pass   | -                                         |
| 3.2            | 15.247(a)(1)       | Hopping Channel Separation                         | $\geq 2/3$ of 20dB BW                                            | Pass   | -                                         |
| 3.3            | 15.247(a)(1)       | Dwell Time of Each Channel                         | $\leq 0.4\text{sec}$ in 31.6sec period                           | Pass   | -                                         |
| 3.4            | 15.247(a)(1)       | 20dB Bandwidth                                     | NA                                                               | Pass   | -                                         |
| 3.5            | 15.247(b)(1)       | Peak Output Power                                  | $\leq 1\text{ w}$ for 1Mbps<br>$\leq 125\text{ Mw}$ for 2, 3Mbps | Pass   | -                                         |
| 3.6            | 15.247(d)          | Conducted Band Edges                               | $\leq 20\text{dBc}$                                              | Pass   | -                                         |
| 3.7            | 15.247(d)          | Conducted Spurious Emission                        | $\leq 20\text{dBc}$                                              | Pass   | -                                         |
| 3.8            | 15.247(d)          | Radiated Band Edges and Radiated Spurious Emission | 15.209(a) & 15.247(d)                                            | Pass   | Under limit<br>3.67 dB at<br>2483.500 MHz |
| 3.9            | 15.207             | AC Conducted Emission                              | 15.207(a)                                                        | Pass   | Under limit<br>5.72 dB at<br>0.430 MHz    |
| 3.10           | 15.203 & 15.247(b) | Antenna Requirement                                | N/A                                                              | Pass   | -                                         |

# 1 General Description

## 1.1 Applicant

**Lenovo (Shanghai) Electronics Technology Co., Ltd.**

No. 68 Building, 199 Fenju Road, Wai Gao Qiao FTZ, Shanghai, China

## 1.2 Manufacturer

**Lenovo PC HK Limited**

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

## 1.3 Feature of Equipment Under Test

| Product Feature                 |                                                              |
|---------------------------------|--------------------------------------------------------------|
| Equipment                       | Tablet PC                                                    |
| Brand Name                      | Vodafone                                                     |
| Model Name                      | Smart Tab III <sup>10</sup>                                  |
| Marketing Name                  | Vodafone Smart Tab III10                                     |
| FCC ID                          | O57S6000VDF3G                                                |
| EUT supports Radios application | GPRS/EGPRS/WCDMA/HSPA/HSPA+/WLAN 11bgn/<br>Bluetooth 3.0/4.0 |
| HW Version                      | H401                                                         |
| SW Version                      | S6000-S3                                                     |
| EUT Stage                       | Identical Prototype                                          |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

| Product Specification subjective to this standard |                                                                                                                                          |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Tx/Rx Frequency Range                             | 2402 MHz ~ 2480 MHz                                                                                                                      |
| Number of Channels                                | 79                                                                                                                                       |
| Carrier Frequency of Each Channel                 | 2402+n*1 MHz; n=0~78                                                                                                                     |
| Maximum Output Power to Antenna                   | Bluetooth BR (1Mbps) : 8.40 dBm (0.0069 W)<br>Bluetooth EDR (2Mbps) : 8.00 dBm (0.0063 W)<br>Bluetooth EDR (3Mbps) : 8.45 dBm (0.0070 W) |
| Antenna Type                                      | Fixed Internal Antenna with gain 3.10 dBi                                                                                                |
| Type of Modulation                                | Bluetooth BR (1Mbps) : GFSK<br>Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK<br>Bluetooth EDR (3Mbps) : 8-DPSK                                  |

## 1.5 Testing Site

|                           |                                                                                                                                                              |                                |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL INC.                                                                                                                                   |                                |
| <b>Test Site Location</b> | No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park,<br>Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.<br>TEL: +886-3-3273456 / FAX: +886-3-3284978 |                                |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                      | <b>FCC/IC Registration No.</b> |
|                           | 03CH07-HY                                                                                                                                                    | 722060/4086B-1                 |

|                           |                                                                                                                  |         |                                |
|---------------------------|------------------------------------------------------------------------------------------------------------------|---------|--------------------------------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL (KUNSHAN) INC.                                                                             |         |                                |
| <b>Test Site Location</b> | No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.<br>TEL: +86-0512-5790-0158<br>FAX: +86-0512-5790-0958 |         |                                |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                          |         | <b>FCC/IC Registration No.</b> |
|                           | TH01-KS                                                                                                          | CO01-KS | 149928/4086E-1                 |

The test site complies with ANSI C63.4 2003 requirement.

## 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC Public Notice DA 00-705
- ANSI C63.10-2009

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

| Channel | Frequency | Bluetooth RF Output Power |                |                 |
|---------|-----------|---------------------------|----------------|-----------------|
|         |           | Data Rate / Modulation    |                |                 |
|         |           | GFSK                      | $\pi/4$ -DQPSK | 8-DPSK          |
|         |           | 1Mbps                     | 2Mbps          | 3Mbps           |
| Ch00    | 2402MHz   | 7.27 dBm                  | 6.98 dBm       | 7.19 dBm        |
| Ch39    | 2441MHz   | 7.77 dBm                  | 7.41 dBm       | 7.60 dBm        |
| Ch78    | 2480MHz   | 8.40 dBm                  | 8.00 dBm       | <b>8.45 dBm</b> |

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
  2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals pursuant to ANSI C63.10-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (X plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


## 2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


| Summary table of Test Cases                                                                                                                                                                                                                                                                                                                                  |                                                                                                                |                                       |                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------|-------------------------------|
| Test Item                                                                                                                                                                                                                                                                                                                                                    | Data Rate / Modulation                                                                                         |                                       |                               |
|                                                                                                                                                                                                                                                                                                                                                              | Bluetooth BR 1Mbps<br>GFSK                                                                                     | Bluetooth EDR 2Mbps<br>$\pi/4$ -DQPSK | Bluetooth EDR 3Mbps<br>8-DPSK |
| Conducted<br>Test Cases                                                                                                                                                                                                                                                                                                                                      | Mode 1: CH00_2402 MHz                                                                                          | Mode 4: CH00_2402 MHz                 | Mode 7: CH00_2402 MHz         |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 2: CH39_2441 MHz                                                                                          | Mode 5: CH39_2441 MHz                 | Mode 8: CH39_2441 MHz         |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 3: CH78_2480 MHz                                                                                          | Mode 6: CH78_2480 MHz                 | Mode 9: CH78_2480 MHz         |
| Radiated<br>Test Cases                                                                                                                                                                                                                                                                                                                                       | Bluetooth EDR 3Mbps 8-DPSK                                                                                     |                                       |                               |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 1: CH00_2402 MHz                                                                                          |                                       |                               |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 2: CH39_2441 MHz                                                                                          |                                       |                               |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 3: CH78_2480 MHz                                                                                          |                                       |                               |
| AC<br>Conducted<br>Emission                                                                                                                                                                                                                                                                                                                                  | Mode 1 :GPRS850 Idle + Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone |                                       |                               |
|                                                                                                                                                                                                                                                                                                                                                              | Mode 2 :GPRS850 Idle + Bluetooth Link + WLAN Link + USB Cable 2 (Charging from Adapter) + Battery 2 + Earphone |                                       |                               |
| Remark:                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                |                                       |                               |
| 1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission. |                                                                                                                |                                       |                               |
| 2. The worst case of conducted emission is mode 1; only the test data of it was reported.                                                                                                                                                                                                                                                                    |                                                                                                                |                                       |                               |

## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

| Item | Equipment              | Trade Name | Model Name | FCC ID      | Data Cable | Power Cord                                                 |
|------|------------------------|------------|------------|-------------|------------|------------------------------------------------------------|
| 1.   | System Simulator       | R&S        | CMU 200    | N/A         | N/A        | Unshielded, 1.8 m                                          |
| 2.   | Bluetooth Base Station | R&S        | CBT        | FCC DoC     | N/A        | Unshielded, 1.8 m                                          |
| 3.   | Bluetooth Base Station | R&S        | CBT32      | FCC DoC     | N/A        | Unshielded, 1.8 m                                          |
| 4.   | DC Power Supply        | GWINSTEK   | GPS-3030D  | N/A         | N/A        | Unshielded, 1.8 m                                          |
| 5.   | WLAN AP                | D-Link     | DIR-855    | KA2DIR855A2 | N/A        | Unshielded, 1.8 m                                          |
| 6.   | Notebook               | Lenovo     | G480       | PPD-AR5B195 | N/A        | AC I/P:<br>Unshielded, 1.8 m<br>DC O/P:<br>Shielded, 1.8 m |
| 7.   | Bluetooth Earphone     | Lenovo     | LBH301     | N/A         | N/A        | N/A                                                        |

## 2.5 Description of RF Function Operation Test Setup

For Bluetooth function, turn on “Enter Engmode” software on the EUT directly. Then, the EUT will get into the engineering modes to contact with Bluetooth base station for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

### For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and 10dB attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and 10dB attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following table shows an offset computation example with cable loss 5.6 dB.

Example :

*Offset(dB) = RF cable loss(dB) + attenuator factor(dB).*

*= 5.6 + 10 = 15.6 (dB)*

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW  $\geq$  1% of the span; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.


##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency

| Test Mode :                    | 3Mbps                                   | Temperature :       | 23~24°C   |
|--------------------------------|-----------------------------------------|---------------------|-----------|
| Test Engineer :                | Lizy Li                                 | Relative Humidity : | 47~48%    |
| Number of Hopping<br>(Channel) | Adaptive Frequency<br>Hopping (Channel) | Limits<br>(Channel) | Pass/Fail |
| 79                             | $\geq 20$                               | $> 15$              | Pass      |

## Number of Hopping Channel Plot on Channel 00 - 78



Date: 16.MAR.2013 01:50:40



Date: 16.MAR.2013 01:54:56

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  $RBW \geq 1\%$  of the span;  
 $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation


|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 1Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 1.002                      | 0.6053                        | Pass      |
| 39      | 2441            | 1.002                      | 0.6053                        | Pass      |
| 78      | 2480            | 1.002                      | 0.5653                        | Pass      |


**Channel Separation Plot on Channel 00 - 01**



Date: 16.MAR.2013 01:21:22

**Channel Separation Plot on Channel 39 - 40**


Date: 16.MAR.2013 01:22:03

**Channel Separation Plot on Channel 77 - 78**



Date: 16.MAR.2013 01:22:45




|                 |         |                     |         |
|-----------------|---------|---------------------|---------|
| Test Mode :     | 2Mbps   | Temperature :       | 23~24°C |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48%  |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 1.002                      | 0.8520                        | Pass      |
| 39      | 2441            | 1.008                      | 0.8520                        | Pass      |
| 78      | 2480            | 1.002                      | 0.8440                        | Pass      |


Channel Separation Plot on Channel 00 - 01



Date: 16.MAR.2013 01:24:00

**Channel Separation Plot on Channel 39 - 40**


Date: 16.MAR.2013 01:24:39


**Channel Separation Plot on Channel 77 - 78**


Date: 16.MAR.2013 01:25:48




|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 3Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |


| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 1.002                      | 0.8560                        | Pass      |
| 39      | 2441            | 1.002                      | 0.8560                        | Pass      |
| 78      | 2480            | 1.002                      | 0.8560                        | Pass      |

**Channel Separation Plot on Channel 00 - 01**

Date: 16.MAR.2013 01:26:57

**Channel Separation Plot on Channel 39 - 40**


Date: 7.MAR.2013 10:39:13

**Channel Separation Plot on Channel 77 - 78**


Date: 7.MAR.2013 10:40:01

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Dwell Time


|                        |         |                            |         |
|------------------------|---------|----------------------------|---------|
| <b>Test Mode :</b>     | 3DH5    | <b>Temperature :</b>       | 23~24°C |
| <b>Test Engineer :</b> | Lizy Li | <b>Relative Humidity :</b> | 47~48%  |

| Mode   | Hopping Channel Number | Hops Over Occupancy Time(hops) | Package Transfer Time (msec) | Dwell Time (sec) | Limits (sec) | Pass/Fail |
|--------|------------------------|--------------------------------|------------------------------|------------------|--------------|-----------|
| Normal | 79                     | 106.67                         | 2.954                        | 0.32             | 0.4          | Pass      |
| AFH    | 20                     | 53.34                          | 2.954                        | 0.16             | 0.4          | Pass      |

**Remark:**

1. In normal mode, hopping rate is 1600hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.34 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

**Package Transfer Time Plot**


Date : 12.MAR.2013 10:47:28

### 3.4 20dB Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Measure and record the results in the test report.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 1Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 0.908                |
| 39      | 2441            | 0.908                |
| 78      | 2480            | 0.848                |


**20 dB Bandwidth Plot on Channel 00**



Date: 16.MAR.2013 01:29:04




### 20 dB Bandwidth Plot on Channel 39



Date: 16.MAR.2013 01:29:23


### 20 dB Bandwidth Plot on Channel 78




Date: 16.MAR.2013 01:29:41

|                        |         |                            |        |
|------------------------|---------|----------------------------|--------|
| <b>Test Mode :</b>     | 2Mbps   | <b>Temperature :</b>       | 23~24℃ |
| <b>Test Engineer :</b> | Lizy Li | <b>Relative Humidity :</b> | 47~48% |


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 1.278                |
| 39      | 2441            | 1.278                |
| 78      | 2480            | 1.266                |

**20 dB Bandwidth Plot on Channel 00**


Date: 16.MAR.2013 01:30:05

**20 dB Bandwidth Plot on Channel 39**



Date: 16.MAR.2013 01:30:26

**20 dB Bandwidth Plot on Channel 78**


Date: 16.MAR.2013 01:30:45

|                        |         |                            |        |
|------------------------|---------|----------------------------|--------|
| <b>Test Mode :</b>     | 3Mbps   | <b>Temperature :</b>       | 23~24℃ |
| <b>Test Engineer :</b> | Lizy Li | <b>Relative Humidity :</b> | 47~48% |


| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 1.284                |
| 39      | 2441            | 1.284                |
| 78      | 2480            | 1.284                |

**20 dB Bandwidth Plot on Channel 00**


Date: 16.MAR.2013 01:31:05




### 20 dB Bandwidth Plot on Channel 39



Date: 16.MAR.2013 01:31:25

### 20 dB Bandwidth Plot on Channel 78



Date: 16.MAR.2013 01:31:46

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup




### 3.5.5 Test Result of Peak Output Power

|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 3Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |


| Channel | Frequency (MHz) | RF Power (dBm) |                   |           |
|---------|-----------------|----------------|-------------------|-----------|
|         |                 | 8-DPSK         | Max. Limits (dBm) | Pass/Fail |
|         |                 | 3 Mbps         |                   |           |
| 00      | 2402            | 7.19           | 20.97             | Pass      |
| 39      | 2441            | 7.60           | 20.97             | Pass      |
| 78      | 2480            | 8.45           | 20.97             | Pass      |

**Peak Output Power Plot on Channel 00**




Date: 12.MAR.2013 10:39:44

### Peak Output Power Plot on Channel 39



Date: 12.MAR.2013 10:40:59

### Peak Output Power Plot on Channel 78



Date: 12.MAR.2013 10:54:39

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 300kHz ( $\geq 1\%$  span=30MHz ), VBW = 300kHz ( $\geq$  RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


### 3.6.4 Test Setup



### 3.6.5 Test Result of Conducted Band Edges


|                |           |                     |         |
|----------------|-----------|---------------------|---------|
| Test Mode :    | 1Mbps     | Temperature :       | 23~24℃  |
| Test Channel : | 00 and 78 | Relative Humidity : | 47~48%  |
|                |           | Test Engineer :     | Lizy Li |

#### Low Band Edge Plot on Channel 00



Date: 16.MAR.2013 01:32:40


#### High Band Edge Plot on Channel 78




Date: 16.MAR.2013 01:33:43



|                |           |                     |         |
|----------------|-----------|---------------------|---------|
| Test Mode :    | 2Mbps     | Temperature :       | 23~24℃  |
| Test Channel : | 00 and 78 | Relative Humidity : | 47~48%  |
|                |           | Test Engineer :     | Lizy Li |

**Low Band Edge Plot on Channel 00**


Date: 16.MAR.2013 02:06:59

**High Band Edge Plot on Channel 78**

Date: 16.MAR.2013 01:35:38


|                       |           |                            |         |
|-----------------------|-----------|----------------------------|---------|
| <b>Test Mode :</b>    | 3Mbps     | <b>Temperature :</b>       | 23~24℃  |
| <b>Test Channel :</b> | 00 and 78 | <b>Relative Humidity :</b> | 47~48%  |
|                       |           | <b>Test Engineer :</b>     | Lizy Li |

### Low Band Edge Plot on Channel 00



Date: 16.MAR.2013 01:36:29


### High Band Edge Plot on Channel 78




Date: 16.MAR.2013 02:10:06

### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 1Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |


**Hopping Mode Low Band Edge Plot on Channel 00**


Date: 16.MAR.2013 22:45:33


**Hopping Mode High Band Edge Plot on Channel 78**


Date: 16.MAR.2013 04:37:56

|                        |         |                            |        |
|------------------------|---------|----------------------------|--------|
| <b>Test Mode :</b>     | 2Mbps   | <b>Temperature :</b>       | 23~24℃ |
| <b>Test Engineer :</b> | Lizy Li | <b>Relative Humidity :</b> | 47~48% |

**Hopping Mode Low Band Edge Plot on Channel 00**



Date: 16.MAR.2013 22:44:18

**Hopping Mode High Band Edge Plot on Channel 78**



Date: 16.MAR.2013 04:36:40



|                 |         |                     |        |
|-----------------|---------|---------------------|--------|
| Test Mode :     | 3Mbps   | Temperature :       | 23~24℃ |
| Test Engineer : | Lizy Li | Relative Humidity : | 47~48% |

**Hopping Mode Low Band Edge Plot on Channel 00**

Date: 16.MAR.2013 22:40:46

**Hopping Mode High Band Edge Plot on Channel 78**

Date: 16.MAR.2013 04:35:14

### 3.7 Conducted Spurious Emission Measurement

#### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


#### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


#### 3.7.4 Test Setup



### 3.7.5 Test Results


|                |       |                     |         |
|----------------|-------|---------------------|---------|
| Test Mode :    | 3Mbps | Temperature :       | 23~24℃  |
| Test Channel : | 00    | Relative Humidity : | 47~48%  |
|                |       | Test Engineer :     | Lizy Li |

#### Conducted Spurious Emission Plot between 30MHz ~ 3 GHz




Date: 16.MAR.2013 01:43:52

#### Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz




Date: 16.MAR.2013 01:56:44

|                       |       |                            |         |
|-----------------------|-------|----------------------------|---------|
| <b>Test Mode :</b>    | 3Mbps | <b>Temperature :</b>       | 23~24°C |
| <b>Test Channel :</b> | 39    | <b>Relative Humidity :</b> | 47~48%  |
|                       |       | <b>Test Engineer :</b>     | Lizy Li |

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**



Date: 16.MAR.2013 01:44:57

**Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz**



Date: 16.MAR.2013 01:57:25



|                |       |                     |         |
|----------------|-------|---------------------|---------|
| Test Mode :    | 3Mbps | Temperature :       | 23~24℃  |
| Test Channel : | 78    | Relative Humidity : | 47~48%  |
|                |       | Test Engineer :     | Lizy Li |

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**

Date: 16.MAR.2013 01:46:01

**Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz**

Date: 16.MAR.2013 01:58:01

### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490      | 2400/F(kHz)                          | 300                              |
| 0.490 – 1.705      | 24000/F(kHz)                         | 30                               |
| 1.705 – 30.0       | 30                                   | 30                               |
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

#### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


### 3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines and fulfills ANSI C63.4-2003 and the guidelines in ANSI C63.10-2009 test site requirement.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
$$\text{On time} = N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$$
  
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Level = Peak Level + 20\*log(Duty cycle)
8. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.79dB) derived from 20log (dwell time/100ms).

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.8.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


### 3.8.6 Duty cycle correction factor for average measurement

#### 3DH5 on time (One Pulse) Plot on Channel 39



Date: 23.MAR.2013 16:06:37

#### 3DH5 on time (Count Pulses) Plot on Channel 39



Date: 23.MAR.2013 16:05:13

#### Note:

1. Duty cycle = on time/100 milliseconds = 2 \* 2.88 / 100 = 5.76 %
2. Duty cycle correction factor = 20\*log(Duty cycle) = -24.79 dB
3. 3DH5 has the highest duty cycle and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2$  hops

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

**3.8.7 Test Result of Radiated Band Edges**

|                       |                                                                       |                            |            |
|-----------------------|-----------------------------------------------------------------------|----------------------------|------------|
| <b>Test Mode :</b>    | 3Mbps + USB Cable 1 (Charging from Adapter) +<br>Battery 1 + Earphone | <b>Temperature :</b>       | 21~23°C    |
| <b>Test Channel :</b> | 00                                                                    | <b>Relative Humidity :</b> | 51~53%     |
|                       |                                                                       | <b>Test Engineer :</b>     | Beer Huang |

| ANTENNA POLARITY : HORIZONTAL |                     |                         |                             |                           |                             |                         |                            |                      |                         |         |
|-------------------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )          | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2386.41                       | 54.88               | -19.12                  | 74                          | 49.94                     | 32.3                        | 6.91                    | 34.27                      | 192                  | 305                     | Peak    |
| 2386.41                       | 30.09               | -23.91                  | 54                          | -                         | -                           | -                       | -                          | -                    | -                       | Average |

| ANTENNA POLARITY : VERTICAL |                     |                         |                             |                           |                             |                         |                            |                      |                         |         |
|-----------------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )        | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2385.69                     | 48.16               | -25.84                  | 74                          | 43.22                     | 32.3                        | 6.91                    | 34.27                      | 100                  | 239                     | Peak    |
| 2385.69                     | 23.37               | -30.63                  | 54                          | -                         | -                           | -                       | -                          | -                    | -                       | Average |

**Note:** The average levels were calculated from the peak level corrected with duty cycle correction factor (24.79dB) derived from  $20\log(\text{dwell time}/100\text{ms})$ .

For example: Average level = 54.88dBμV/m – 24.79 (dB) = 30.09dBμV/m.

|                       |                                                                       |                            |            |
|-----------------------|-----------------------------------------------------------------------|----------------------------|------------|
| <b>Test Mode :</b>    | 3Mbps + USB Cable 1 (Charging from Adapter) +<br>Battery 1 + Earphone | <b>Temperature :</b>       | 21~23°C    |
| <b>Test Channel :</b> | 78                                                                    | <b>Relative Humidity :</b> | 51~53%     |
|                       |                                                                       | <b>Test Engineer :</b>     | Beer Huang |

| ANTENNA POLARITY : HORIZONTAL |                     |                         |                             |                           |                             |                         |                            |                      |                         |         |
|-------------------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )          | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2483.5                        | 70.33               | -3.67                   | 74                          | 65.32                     | 32.38                       | 7.06                    | 34.43                      | 184                  | 346                     | Peak    |
| 2483.5                        | 45.54               | -8.46                   | 54                          | -                         | -                           | -                       | -                          | -                    | -                       | Average |

| ANTENNA POLARITY : VERTICAL |                     |                         |                             |                           |                             |                         |                            |                      |                         |         |
|-----------------------------|---------------------|-------------------------|-----------------------------|---------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| Frequency<br>( MHz )        | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
| 2483.5                      | 63.64               | -10.36                  | 74                          | 58.63                     | 32.38                       | 7.06                    | 34.43                      | 100                  | 226                     | Peak    |
| 2483.5                      | 38.85               | -15.15                  | 54                          | -                         | -                           | -                       | -                          | -                    | -                       | Average |

**3.8.8 Test Result of Radiated Emission (30 MHz ~ 10<sup>th</sup> Harmonic)**

|                        |                                                                                                                                                                                                                       |                            |            |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone                                                                                                                                                    | <b>Temperature :</b>       | 21~23°C    |
| <b>Test Channel :</b>  | 00                                                                                                                                                                                                                    | <b>Relative Humidity :</b> | 51~53%     |
| <b>Test Engineer :</b> | Beer Huang                                                                                                                                                                                                            | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 1. 2402 MHz is fundamental signal which can be ignored.<br>2. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. For example, 108.91dBμV/m - 20dB = 88.91 dBμV/m. |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2402                 | 108.91              | -                       | -                           | 104                     | 32.3                        | 6.91                    | 34.3                       | 192                  | 305                     | Peak    |
| 2402                 | 84.12               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4803                 | 41.43               | -32.57                  | 74                          | 56.17                   | 33.98                       | 8.75                    | 57.47                      | 100                  | 0                       | Peak    |
| 4803                 | 16.64               | -37.36                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7206                 | 42.06               | -46.85                  | 88.91                       | 53.65                   | 35.56                       | 10.81                   | 57.96                      | 100                  | 0                       | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |                                                                                                                                                                      |                            |          |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone                                                                                                   | <b>Temperature :</b>       | 21~23°C  |
| <b>Test Channel :</b>  | 00                                                                                                                                                                   | <b>Relative Humidity :</b> | 51~53%   |
| <b>Test Engineer :</b> | Beer Huang                                                                                                                                                           | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 1. 2402 MHz is fundamental signal which can be ignored.<br>2. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2402                 | 100.61              | -                       | -                           | 95.7                    | 32.3                        | 6.91                    | 34.3                       | 100                  | 239                     | Peak    |
| 2402                 | 75.82               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4803                 | 41.59               | -32.41                  | 74                          | 56.33                   | 33.98                       | 8.75                    | 57.47                      | 100                  | 0                       | Peak    |
| 4803                 | 16.8                | -37.2                   | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7206                 | 41.29               | -39.32                  | 80.61                       | 52.88                   | 35.56                       | 10.81                   | 57.96                      | 100                  | 0                       | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |                                                                                                                                                      |                            |            |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone                                                                                   | <b>Temperature :</b>       | 21~23°C    |
| <b>Test Channel :</b>  | 39                                                                                                                                                   | <b>Relative Humidity :</b> | 51~53%     |
| <b>Test Engineer :</b> | Beer Huang                                                                                                                                           | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 1. 2441 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2441                 | 107.86              | -                       | -                           | 102.91                  | 32.35                       | 6.99                    | 34.39                      | 155                  | 306                     | Peak    |
| 2441                 | 83.07               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4881                 | 41.27               | -32.73                  | 74                          | 55.95                   | 33.95                       | 8.85                    | 57.48                      | 100                  | 0                       | Peak    |
| 4881                 | 16.48               | -37.52                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7323                 | 40.69               | -33.31                  | 74                          | 52.29                   | 35.53                       | 10.91                   | 58.04                      | 100                  | 0                       | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |                                                                                                                                                      |                            |          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|----------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone                                                                                   | <b>Temperature :</b>       | 21~23°C  |
| <b>Test Channel :</b>  | 39                                                                                                                                                   | <b>Relative Humidity :</b> | 51~53%   |
| <b>Test Engineer :</b> | Beer Huang                                                                                                                                           | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 1. 2441 MHz is fundamental signal which can be ignored.<br>2. Average measurement was not performed if peak level went lower than the average limit. |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 2441                 | 100.27              | -                       | -                           | 95.32                   | 32.35                       | 6.99                    | 34.39                      | 100                  | 241                     | Peak    |
| 2441                 | 75.48               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4881                 | 40.72               | -33.28                  | 74                          | 55.4                    | 33.95                       | 8.85                    | 57.48                      | 100                  | 0                       | Peak    |
| 4881                 | 15.93               | -38.07                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7323                 | 41.54               | -32.46                  | 74                          | 53.14                   | 35.53                       | 10.91                   | 58.04                      | 100                  | 0                       | Peak    |

**Note:** Other harmonics are lower than background noise.

|                        |                                                                    |                            |            |
|------------------------|--------------------------------------------------------------------|----------------------------|------------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone | <b>Temperature :</b>       | 21~23°C    |
| <b>Test Channel :</b>  | 78                                                                 | <b>Relative Humidity :</b> | 51~53%     |
| <b>Test Engineer :</b> | Beer Huang                                                         | <b>Polarization :</b>      | Horizontal |
| <b>Remark :</b>        | 2480 MHz is fundamental signal which can be ignored.               |                            |            |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 42.96                | 24.1                | -15.9                   | 40                          | 43.51                   | 11.7                        | 0.64                    | 31.75                      | -                    | -                       | Peak    |
| 110.73               | 23.84               | -19.66                  | 43.5                        | 43.73                   | 10.8                        | 1.05                    | 31.74                      | -                    | -                       | Peak    |
| 194.97               | 24.63               | -18.87                  | 43.5                        | 45.59                   | 9.05                        | 1.3                     | 31.31                      | -                    | -                       | Peak    |
| 519.8                | 29.62               | -16.38                  | 46                          | 39.74                   | 18.43                       | 2.49                    | 31.04                      | -                    | -                       | Peak    |
| 584.9                | 27.84               | -18.16                  | 46                          | 36.41                   | 19.54                       | 2.65                    | 30.76                      | -                    | -                       | Peak    |
| 780.2                | 33.34               | -12.66                  | 46                          | 38.75                   | 21.79                       | 3.11                    | 30.31                      | 103                  | 96                      | Peak    |
| 2480                 | 108.56              | -                       | -                           | 103.55                  | 32.38                       | 7.06                    | 34.43                      | 184                  | 346                     | Peak    |
| 2480                 | 83.77               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4959                 | 40.27               | -33.73                  | 74                          | 54.93                   | 33.91                       | 8.92                    | 57.49                      | 100                  | 0                       | Peak    |
| 4959                 | 15.48               | -38.52                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7440                 | 40.19               | -33.81                  | 74                          | 51.76                   | 35.51                       | 11.04                   | 58.12                      | 100                  | 0                       | Peak    |
| 7440                 | 15.4                | -38.6                   | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |

**Note:** Other harmonics are lower than background noise.

|                        |                                                                    |                            |          |
|------------------------|--------------------------------------------------------------------|----------------------------|----------|
| <b>Test Mode :</b>     | 3Mbps + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone | <b>Temperature :</b>       | 21~23°C  |
| <b>Test Channel :</b>  | 78                                                                 | <b>Relative Humidity :</b> | 51~53%   |
| <b>Test Engineer :</b> | Beer Huang                                                         | <b>Polarization :</b>      | Vertical |
| <b>Remark :</b>        | 2480 MHz is fundamental signal which can be ignored.               |                            |          |

| Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>(dBμV) | Antenna<br>Factor<br>( dB ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Remark  |
|----------------------|---------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|----------------------------|----------------------|-------------------------|---------|
| 45.39                | 30.93               | -9.07                   | 40                          | 51.89                   | 10.1                        | 0.66                    | 31.72                      | 111                  | 54                      | Peak    |
| 75.36                | 20.53               | -19.47                  | 40                          | 44.36                   | 7.06                        | 0.86                    | 31.75                      | -                    | -                       | Peak    |
| 168.51               | 20.07               | -23.43                  | 43.5                        | 40.47                   | 9.66                        | 1.23                    | 31.29                      | -                    | -                       | Peak    |
| 389.6                | 16.75               | -29.25                  | 46                          | 30.3                    | 15.74                       | 2.12                    | 31.41                      | -                    | -                       | Peak    |
| 584.9                | 27.52               | -18.48                  | 46                          | 36.09                   | 19.54                       | 2.65                    | 30.76                      | -                    | -                       | Peak    |
| 780.2                | 27.99               | -18.01                  | 46                          | 33.4                    | 21.79                       | 3.11                    | 30.31                      | -                    | -                       | Peak    |
| 2480                 | 101.97              | -                       | -                           | 96.96                   | 32.38                       | 7.06                    | 34.43                      | 100                  | 226                     | Peak    |
| 2480                 | 77.18               | -                       | -                           | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 4959                 | 41.85               | -32.15                  | 74                          | 56.51                   | 33.91                       | 8.92                    | 57.49                      | 100                  | 0                       | Peak    |
| 4959                 | 17.06               | -36.94                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |
| 7440                 | 40.96               | -33.04                  | 74                          | 52.53                   | 35.51                       | 11.04                   | 58.12                      | 100                  | 0                       | Peak    |
| 7440                 | 16.17               | -37.83                  | 54                          | -                       | -                           | -                       | -                          | -                    | -                       | Average |

**Note:** Other harmonics are lower than background noise.

### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.9.3 Test Procedures


1. The test follows the guidelines in ANSI C63.10-2009 test site requirement.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

|                 |                                                                                                        |                     |        |
|-----------------|--------------------------------------------------------------------------------------------------------|---------------------|--------|
| Test Mode :     | Mode 1                                                                                                 | Temperature :       | 19~20℃ |
| Test Engineer : | Tom Wang                                                                                               | Relative Humidity : | 39~40% |
| Test Voltage :  | 120Vac / 60Hz                                                                                          | Phase :             | Line   |
| Function Type : | GPRS850 Idle + Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone |                     |        |




Site : C001-KS  
Condition: FCC PART15C LISN-L20130306 LINE

mode : Mode 1

|    | Freq | Level | Over   | Limit | Read  | LISN   | Cable |         |
|----|------|-------|--------|-------|-------|--------|-------|---------|
|    | MHz  | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  |
|    |      |       | dB     | dBuV  | dBuV  | dB     | dB    |         |
| 1  | 0.20 | 51.26 | -12.50 | 63.76 | 40.00 | 1.04   | 10.22 | QP      |
| 2  | 0.20 | 39.16 | -14.60 | 53.76 | 27.90 | 1.04   | 10.22 | Average |
| 3  | 0.21 | 39.59 | -13.46 | 53.05 | 28.40 | 0.97   | 10.22 | Average |
| 4  | 0.21 | 50.79 | -12.26 | 63.05 | 39.60 | 0.97   | 10.22 | QP      |
| 5  | 0.34 | 36.81 | -12.32 | 49.13 | 26.10 | 0.46   | 10.25 | Average |
| 6  | 0.34 | 51.11 | -8.02  | 59.13 | 40.40 | 0.46   | 10.25 | QP      |
| 7  | 0.36 | 51.16 | -7.62  | 58.78 | 40.50 | 0.41   | 10.25 | QP      |
| 8  | 0.36 | 37.46 | -11.32 | 48.78 | 26.80 | 0.41   | 10.25 | Average |
| 9  | 0.40 | 36.26 | -11.51 | 47.77 | 25.70 | 0.31   | 10.25 | Average |
| 10 | 0.40 | 48.86 | -8.91  | 57.77 | 38.30 | 0.31   | 10.25 | QP      |
| 11 | 0.42 | 34.94 | -12.57 | 47.51 | 24.40 | 0.29   | 10.25 | Average |
| 12 | 0.42 | 49.44 | -8.07  | 57.51 | 38.90 | 0.29   | 10.25 | QP      |
| 13 | 0.43 | 51.52 | -5.72  | 57.24 | 41.00 | 0.27   | 10.25 | QP      |
| 14 | 0.43 | 37.02 | -10.22 | 47.24 | 26.50 | 0.27   | 10.25 | Average |
| 15 | 0.53 | 33.96 | -12.04 | 46.00 | 23.50 | 0.20   | 10.26 | Average |
| 16 | 0.53 | 47.26 | -8.74  | 56.00 | 36.80 | 0.20   | 10.26 | QP      |
| 17 | 0.56 | 31.46 | -14.54 | 46.00 | 21.00 | 0.20   | 10.26 | Average |
| 18 | 0.56 | 47.06 | -8.94  | 56.00 | 36.60 | 0.20   | 10.26 | QP      |
| 19 | 0.58 | 47.06 | -8.94  | 56.00 | 36.60 | 0.20   | 10.26 | QP      |
| 20 | 0.58 | 31.56 | -14.44 | 46.00 | 21.10 | 0.20   | 10.26 | Average |
| 21 | 0.64 | 30.17 | -15.83 | 46.00 | 19.70 | 0.20   | 10.27 | Average |
| 22 | 0.64 | 46.27 | -9.73  | 56.00 | 35.80 | 0.20   | 10.27 | QP      |
| 23 | 0.74 | 43.66 | -12.34 | 56.00 | 33.20 | 0.19   | 10.27 | QP      |
| 24 | 0.74 | 28.86 | -17.14 | 46.00 | 18.40 | 0.19   | 10.27 | Average |



|                 |                                                                                                        |                     |         |
|-----------------|--------------------------------------------------------------------------------------------------------|---------------------|---------|
| Test Mode :     | Mode 1                                                                                                 | Temperature :       | 19~20°C |
| Test Engineer : | Tom Wang                                                                                               | Relative Humidity : | 39~40%  |
| Test Voltage :  | 120Vac / 60Hz                                                                                          | Phase :             | Neutral |
| Function Type : | GPRS850 Idle + Bluetooth Link + WLAN Link + USB Cable 1 (Charging from Adapter) + Battery 1 + Earphone |                     |         |



Site : C001-KS  
Condition: FCC PART15C LISN-N20130306 NEUTRAL

mode : Mode 1

|    | Freq | Level | Over   | Limit | Read  | LISN   | Cable | Remark  |
|----|------|-------|--------|-------|-------|--------|-------|---------|
|    | MHz  | dBuV  | Limit  | Line  | Level | Factor | Loss  |         |
|    |      |       | dB     | dBuV  | dBuV  | dB     | dB    |         |
| 1  | 0.15 | 32.57 | -23.30 | 55.87 | 20.50 | 1.87   | 10.20 | Average |
| 2  | 0.15 | 43.67 | -22.20 | 65.87 | 31.60 | 1.87   | 10.20 | QP      |
| 3  | 0.20 | 40.42 | -13.16 | 53.58 | 29.20 | 1.00   | 10.22 | Average |
| 4  | 0.20 | 53.32 | -10.26 | 63.58 | 42.10 | 1.00   | 10.22 | QP      |
| 5  | 0.21 | 37.60 | -15.63 | 53.23 | 26.40 | 0.98   | 10.22 | Average |
| 6  | 0.21 | 52.80 | -10.43 | 63.23 | 41.60 | 0.98   | 10.22 | QP      |
| 7  | 0.29 | 30.42 | -20.17 | 50.59 | 19.40 | 0.78   | 10.24 | Average |
| 8  | 0.29 | 45.82 | -14.77 | 60.59 | 34.80 | 0.78   | 10.24 | QP      |
| 9  | 0.34 | 33.59 | -15.68 | 49.27 | 22.79 | 0.55   | 10.25 | Average |
| 10 | 0.34 | 46.59 | -12.68 | 59.27 | 35.79 | 0.55   | 10.25 | QP      |
| 11 | 0.40 | 47.96 | -9.94  | 57.90 | 37.30 | 0.41   | 10.25 | QP      |
| 12 | 0.40 | 35.46 | -12.44 | 47.90 | 24.80 | 0.41   | 10.25 | Average |
| 13 | 0.43 | 34.52 | -12.77 | 47.29 | 23.90 | 0.37   | 10.25 | Average |
| 14 | 0.43 | 48.72 | -8.57  | 57.29 | 38.10 | 0.37   | 10.25 | QP      |
| 15 | 0.47 | 26.47 | -19.98 | 46.45 | 15.90 | 0.32   | 10.25 | Average |
| 16 | 0.47 | 41.07 | -15.38 | 56.45 | 30.50 | 0.32   | 10.25 | QP      |
| 17 | 0.52 | 38.75 | -17.25 | 56.00 | 28.20 | 0.29   | 10.26 | QP      |
| 18 | 0.52 | 26.25 | -19.75 | 46.00 | 15.70 | 0.29   | 10.26 | Average |
| 19 | 0.62 | 42.90 | -13.10 | 56.00 | 32.41 | 0.23   | 10.26 | QP      |
| 20 | 0.62 | 28.90 | -17.10 | 46.00 | 18.41 | 0.23   | 10.26 | Average |
| 21 | 0.64 | 44.99 | -11.01 | 56.00 | 34.50 | 0.22   | 10.27 | QP      |
| 22 | 0.64 | 29.99 | -16.01 | 46.00 | 19.50 | 0.22   | 10.27 | Average |
| 23 | 0.70 | 23.37 | -22.63 | 46.00 | 12.90 | 0.20   | 10.27 | Average |
| 24 | 0.70 | 39.07 | -16.93 | 56.00 | 28.60 | 0.20   | 10.27 | QP      |
| 25 | 0.80 | 26.34 | -19.66 | 46.00 | 15.89 | 0.17   | 10.28 | Average |
| 26 | 0.80 | 37.14 | -18.86 | 56.00 | 26.69 | 0.17   | 10.28 | QP      |
| 27 | 4.95 | 32.13 | -13.87 | 46.00 | 21.60 | 0.20   | 10.33 | Average |
| 28 | 4.95 | 37.63 | -18.37 | 56.00 | 27.10 | 0.20   | 10.33 | QP      |
| 29 | 6.52 | 35.55 | -14.45 | 50.00 | 25.00 | 0.20   | 10.35 | Average |
| 30 | 6.52 | 40.55 | -19.45 | 60.00 | 30.00 | 0.20   | 10.35 | QP      |

### **3.10 Antenna Requirements**

#### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### **3.10.2 Antenna Connected Construction**

Non-standard connector used.

#### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

| Instrument                        | Manufacturer    | Model No.                      | Serial No.    | Characteristics          | Calibration Date | Test Date                       | Due Date      | Remark                |
|-----------------------------------|-----------------|--------------------------------|---------------|--------------------------|------------------|---------------------------------|---------------|-----------------------|
| Spectrum Analyzer                 | R&S             | FSP40                          | 100319        | 9kHz~40GHz               | Dec. 29, 2012    | Mar. 07, 2013~<br>Mar. 16, 2013 | Dec. 28, 2013 | Conducted (TH01-KS)   |
| Power Meter                       | Agilent         | E4416A                         | MY45101555    | N/A                      | Aug. 22, 2012    | Mar. 07, 2013~<br>Mar. 16, 2013 | Aug. 21, 2013 | Conducted (TH01-KS)   |
| Power Sensor                      | Agilent         | E9327A                         | MY44421198    | N/A                      | Aug. 22, 2012    | Mar. 07, 2013~<br>Mar. 16, 2013 | Aug. 21, 2013 | Conducted (TH01-KS)   |
| Bilog Antenna                     | Schaffner       | CBL6111C                       | 2726          | 30MHz ~ 1GHz             | Oct. 06, 2012    | Mar. 23, 2013                   | Oct. 05, 2013 | Radiation (03CH07-HY) |
| Spectrum Analyzer                 | Rohde & Schwarz | FSP30                          | 101067        | 9kHz ~ 30GHz             | Nov. 30, 2012    | Mar. 23, 2013                   | Nov. 29, 2013 | Radiation (03CH07-HY) |
| Double Ridge Horn Antenna         | ESCO            | 3117                           | 00075962      | 1GHz ~ 18GHz             | Aug. 22, 2012    | Mar. 23, 2013                   | Aug. 21, 2013 | Radiation (03CH07-HY) |
| Preamplifier                      | Agilent         | 8449B                          | 3008A02362    | 1GHz~ 26.5GHz            | Dec. 01, 2012    | Mar. 23, 2013                   | Nov. 30, 2013 | Radiation (03CH07-HY) |
| Preamplifier                      | MITEQ           | AMF-7D-001<br>01800-30-10<br>P | 159088        | 1GHz ~ 18GHz             | Feb. 27, 2013    | Mar. 23, 2013                   | Feb. 26, 2014 | Radiation (03CH07-HY) |
| Preamplifier                      | COM-POWER       | PA-103A                        | 161241        | 10-1000MHz.<br>32dB.GAIN | Feb. 26, 2013    | Mar. 23, 2013                   | Feb. 25, 2014 | Radiation (03CH07-HY) |
| EMI Test Receiver                 | Rohde & Schwarz | ESCI 7                         | 100724        | 9kHz~7GHz                | Sep. 03, 2012    | Mar. 23, 2013                   | Sep. 02, 2013 | Radiation (03CH07-HY) |
| SHF-EHF Horn Antenna              | SCHWARZBECK     | BBHA 9170                      | BBHA9170251   | 15GHz ~ 40GHz            | Sep. 28, 2012    | Mar. 23, 2013                   | Sep. 27, 2013 | Radiation (03CH07-HY) |
| Loop Antenna                      | R&S             | HFH2-Z2                        | 860004/001    | 9kHz ~ 30MHz             | Jul. 03, 2012    | Mar. 23, 2013                   | Jul. 02, 2014 | Radiation (03CH07-HY) |
| Turn Table                        | chaintek        | T-200-S                        | 420/650/00    | 0 ~ 360 degree           | N/A              | Mar. 23, 2013                   | N/A           | Radiation (03CH07-HY) |
| Antenna Mast                      | chaintek        | M-400-0                        | 114/8000604/L | 1 m - 4 m                | N/A              | Mar. 23, 2013                   | N/A           | Radiation (03CH07-HY) |
| EMI Receiver                      | R&S             | ESCI7                          | 100768        | 9kHz~7GHz                | Jun. 01, 2012    | Mar. 22, 2013                   | May 31, 2013  | Conduction (CO01-KS)  |
| LISN<br>(for auxiliary equipment) | MessTec         | AN3016                         | 60103         | 9kHz~30MHz               | Dec. 29, 2012    | Mar. 22, 2013                   | Dec. 28, 2013 | Conduction (CO01-KS)  |
| LISN                              | MessTec         | AN3016                         | 60105         | 9kHz~30MHz               | Dec. 29, 2012    | Mar. 22, 2013                   | Dec. 28, 2013 | Conduction (CO01-KS)  |
| AC Power Source                   | Chroma          | 61602                          | ABP000000811  | N/A                      | Nov. 15, 2012    | Mar. 22, 2013                   | Nov. 14, 2013 | Conduction (CO01-KS)  |

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

|                                                                         |      |
|-------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 2.26 |
|-------------------------------------------------------------------------|------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                         |      |
|-------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 2.54 |
|-------------------------------------------------------------------------|------|

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

|                                                                         |      |
|-------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 4.72 |
|-------------------------------------------------------------------------|------|



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP342901 as below.