



BUREAU  
VERITAS

Test Report No.: PSU-NQN2407300316RF02



# FCC TEST REPORT (Part 15, Subpart C)


|            |  |
|------------|--|
| Applicant: | Lenovo (Shanghai) Electronics Technology Co., Ltd.   |
| Address:   | Section 304-305, Building No. 4, # 222, Meiyue Road,<br>China (Shanghai) Pilot Free Trade Zone |

|                           |  |
|---------------------------|--|
| Manufacturer or Supplier: | Lenovo PC HK Limited   |
| Address:                  | 23/F, Lincoln House, Taikoo Place<br>979 King's Road, Quarry Bay, Hong Kong, China |
| Product:                  | Portable Tablet Computer   |
| Brand Name:               | Lenovo   |
| Model Name:               | TB311FU  |
| FCC ID:                   | O57TB311FU   |
| Date of tests:            | Aug. 05, 2024 ~ Sep. 06, 2024  |

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247**
- ANSI C63.10-2020**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

|  |  |
|--|--|
| Prepared by Simon Wang<br>Engineer / Mobile Department   | Approved by Luke Lu<br>Manager / Mobile Department   |
| <br>Date: Sep. 06, 2024 | <br>Date: Sep. 06, 2024 |

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

BV 7Layers Communications Technology  
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,  
Zhaoshang Street, Nanshan District Shenzhen,  
Guangdong, People's Republic of China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.sw@bureauveritas.com](mailto:customerservice.sw@bureauveritas.com)



# TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>RELEASE CONTROL RECORD .....</b>                          | <b>4</b>  |
| <b>1 SUMMARY OF TEST RESULTS.....</b>                        | <b>5</b>  |
| 1.1 MEASUREMENT UNCERTAINTY .....                            | 6         |
| <b>2 GENERAL INFORMATION .....</b>                           | <b>7</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT .....                         | 7         |
| 2.2 DESCRIPTION OF TEST MODES .....                          | 10        |
| 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....               | 11        |
| 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... | 11        |
| 2.3 DUTY CYCLE OF TEST SIGNAL .....                          | 15        |
| 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS .....           | 16        |
| 2.5 DESCRIPTION OF SUPPORT UNITS .....                       | 16        |
| <b>3 TEST TYPES AND RESULTS.....</b>                         | <b>17</b> |
| 3.1 CONDUCTED EMISSION MEASUREMENT .....                     | 17        |
| 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....         | 17        |
| 3.1.2 TEST INSTRUMENTS.....                                  | 17        |
| 3.1.3 TEST PROCEDURES .....                                  | 18        |
| 3.1.4 DEVIATION FROM TEST STANDARD .....                     | 18        |
| 3.1.5 TEST SETUP .....                                       | 19        |
| 3.1.6 EUT OPERATING CONDITIONS .....                         | 19        |
| 3.1.7 TEST RESULTS .....                                     | 20        |
| 3.2 RADIATED EMISSION MEASUREMENT .....                      | 22        |
| 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....          | 22        |
| 3.2.2 TEST INSTRUMENTS.....                                  | 23        |
| 3.2.3 TEST PROCEDURES .....                                  | 24        |
| 3.2.4 DEVIATION FROM TEST STANDARD .....                     | 24        |
| 3.2.5 TEST SETUP .....                                       | 25        |
| 3.2.6 EUT OPERATING CONDITIONS .....                         | 26        |
| 3.2.7 TEST RESULTS .....                                     | 27        |
| 3.3 6 dB BANDWIDTH MEASUREMENT .....                         | 65        |
| 3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT .....              | 65        |
| 3.3.2 TEST INSTRUMENTS.....                                  | 65        |
| 3.3.3 TEST PROCEDURE.....                                    | 65        |
| 3.3.4 DEVIATION FROM TEST STANDARD .....                     | 66        |
| 3.3.5 TEST SETUP .....                                       | 66        |



**BUREAU  
VERITAS**

**Test Report No.: PSU-NQN2407300316RF02**

|          |  |           |
|----------|--|-----------|
| 3.3.6    | EUT OPERATING CONDITIONS .....   | 66        |
| 3.3.7    | TEST RESULTS .....   | 67        |
| 3.4      | CONDUCTED OUTPUT POWER.....  | 68        |
| 3.4.1    | LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....                           | 68        |
| 3.4.2    | TEST SETUP .....   | 68        |
| 3.4.3    | TEST INSTRUMENTS.....  | 68        |
| 3.4.4    | TEST PROCEDURES .....  | 68        |
| 3.4.5    | DEVIATION FROM TEST STANDARD .....   | 69        |
| 3.4.6    | EUT OPERATING CONDITIONS .....   | 69        |
| 3.4.7    | TEST RESULTS .....   | 70        |
| 3.5      | POWER SPECTRAL DENSITY MEASUREMENT .....                                     | 71        |
| 3.5.1    | LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....                           | 71        |
| 3.5.2    | TEST SETUP .....   | 71        |
| 3.5.3    | TEST INSTRUMENTS.....  | 71        |
| 3.5.4    | TEST PROCEDURE.....  | 71        |
| 3.5.5    | DEVIATION FROM TEST STANDARD .....   | 71        |
| 3.5.6    | EUT OPERATING CONDITION .....  | 71        |
| 3.5.7    | TEST RESULTS .....   | 72        |
| 3.6      | OUT OF BAND EMISSION MEASUREMENT .....                                       | 73        |
| 3.6.1    | LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....                             | 73        |
| 3.6.2    | TEST SETUP .....   | 73        |
| 3.6.3    | TEST INSTRUMENTS.....  | 73        |
| 3.6.4    | TEST PROCEDURE.....  | 73        |
| 3.6.5    | DEVIATION FROM TEST STANDARD .....   | 74        |
| 3.6.6    | EUT OPERATING CONDITION .....  | 74        |
| 3.6.7    | TEST RESULTS .....   | 74        |
| 3.7      | ANTENNA REQUIREMENTS.....  | 75        |
| 3.7.1    | STANDARD APPLICABLE .....  | 75        |
| 3.7.2    | ANTENNA CONNECTED CONSTRUCTION.....  | 75        |
| 3.7.3    | ANTENNA GAIN .....   | 75        |
| <b>4</b> | <b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>                           | <b>75</b> |
| <b>5</b> | <b>MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB</b> | <b>76</b> |
| <b>6</b> | <b>APPENDIX.....</b>   | <b>77</b> |



**BUREAU  
VERITAS**

Test Report No.: PSU-NQN2407300316RF02

## RELEASE CONTROL RECORD

| ISSUE NO.             | REASON FOR CHANGE | DATE ISSUED   |
|-----------------------|-------------------|---------------|
| PSU-NQN2407300316RF02 | Original release  | Sep. 06, 2024 |



## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) |                                  |            |
|---|----------------------------------|------------|
| STANDARD SECTION  | TEST TYPE AND LIMIT              | RESULT     |
| 15.207  | AC Power Conducted Emission      | Compliance |
| 15.205<br>15.209  | Radiated Emissions               | Compliance |
| 15.247(d)   | Out of band Emission Measurement | Compliance |
| 15.247(a)(2)  | 6dB bandwidth                    | Compliance |
| 15.247(b)   | Conducted Output power           | Compliance |
| 15.247(e)   | Power Spectral Density           | Compliance |
| 15.203  | Antenna Requirement              | Compliance |

**NOTE:** Except RSE, other data please refer to Appendix.



### 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT                       | UNCERTAINTY |
|-----------------------------------|-------------|
| AC Power Conducted emissions      | ±2.70dB     |
| Radiated emissions (9KHz~30MHz)   | ±2.68dB     |
| Radiated emissions (30MHz~1GHz)   | ±4.98dB     |
| Radiated emissions (1GHz ~6GHz)   | ±4.70dB     |
| Radiated emissions (6GHz ~18GHz)  | ±4.60dB     |
| Radiated emissions (18GHz ~40GHz) | ±4.12dB     |
| Conducted emissions               | ±4.01dB     |
| Occupied Channel Bandwidth        | ±43.58KHz   |
| Conducted Output power            | ±2.06dB     |
| Power Spectral Density            | ±0.85 dB    |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                            |   |
|----------------------------|---|
| <b>PRODUCT</b>             | Portable Tablet Computer  |
| <b>BRAND NAME</b>          | Lenovo  |
| <b>MODEL NAME</b>          | TB311FU   |
| <b>NOMINAL VOLTAGE</b>     | 5Vdc(adapter or host equipment)<br>3.9Vdc (Li-ion, battery)   |
| <b>MODULATION</b>          | DSSS, OFDM, GFSK  |
| <b>TRANSMISSION RATE</b>   | 802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps<br>802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps<br>802.11n(HT20): up to 144.4 Mbps<br>802.11n(HT40): up to 300 Mbps<br>BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps |
| <b>OPERATING FREQUENCY</b> | 2412-2462MHz for 11b/g/n(HT20/40)<br>2402-2480MHz for BT-LE(GFSK)   |
| <b>MAX. OUTPUT POWER</b>   | WLAN: 325.84mW (Maximum)<br>BT-LE: 2.35mW (Maximum)   |
| <b>ANTENNA TYPE</b>        | FPC Antenna with -0.24dBi gain for WIFI/ BT_LE  |
| <b>HW VERSION</b>          | TB311FU   |
| <b>SW VERSION</b>          | TB311FU_RF01_20240921   |
| <b>I/O PORTS</b>           | Refer to user's manual  |
| <b>CABLE SUPPLIED</b>      | USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter<br>USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter  |



**NOTE:**

1. For a more detailed features description, please refer to the manufacturer’s specifications or the user’s manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

| <b>MODULATION MODE</b> | <b>TX/RX FUNCTION</b> |
|------------------------|-----------------------|
| <b>802.11b</b>         | 1TX /1RX              |
| <b>802.11g</b>         | 1TX /1RX              |
| <b>802.11n(HT20)</b>   | 1TX /1RX              |
| <b>802.11n(HT40)</b>   | 1TX /1RX              |
| <b>BT_LE(1MHz)</b>     | 1TX /1RX              |
| <b>BT_LE(2MHz)</b>     | 1TX /1RX              |
| <b>BT_LE(S2)</b>       | 1TX /1RX              |
| <b>BT_LE(S8)</b>       | 1TX /1RX              |

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



**5. List of Accessory:**

| <b>ACCESSORIES</b>  | <b>BRAND</b> | <b>MANUFACTURER</b>                     | <b>MODEL</b> | <b>SPECIFICATION</b>  |
|---------------------|--------------|---|--------------|---|
| Battery 1           | N/A          | Zhejiang Sunwoda Electronic Co., Ltd.   | L24D1P32     | Nominal Energy: 19.55Wh,<br>Typical Energy: 19.95Wh   |
| Battery 2           | N/A          | Ningde AmpereX Technology Limited       | L24D1P32     | Nominal Energy: 19.55Wh,<br>Typical Energy: 19.95Wh   |
| AC Adapter 1        | Salcomp      | Salcomp (Shenzhen) Co., Ltd             | MC-201(US)   | I/P: 100-240V~, 50/60Hz, 0.7A,<br>O/P: 5.0Vdc 3.0A 15W<br>10Vdc 2.0A 20W<br>12Vdc 1.67A 20W |
| AC Adapter 2        | Aohai        | Jiangxi Jian Aohai Technology Co., Ltd. | MC-201(US)   | I/P: 100-240V~, 50/60Hz, 0.7A,<br>O/P: 5.0Vdc 3.0A 15W<br>10Vdc 2.0A 20W<br>12Vdc 1.67A 20W |
| USB Cable 1         | Jieye        | Jiangxi Jieye Electronics Co., LTD      | JY-C03-422   | Signal Line,1.0meter  |
| USB Cable 2         | Saibao       | Saibao (Jiangxi) Industrial Co., LTD    | SLQ-A263A    | Signal Line,1.0meter  |
| EARPHONE (optional) | Lenovo       | N/A                                     | E310         | -   |
| Pen(optional)       | Lenovo       | N/A                                     | passive pen  | -   |



## 2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 1       | 2412 MHz  | 7       | 2442 MHz  |
| 2       | 2417 MHz  | 8       | 2447 MHz  |
| 3       | 2422 MHz  | 9       | 2452 MHz  |
| 4       | 2427 MHz  | 10      | 2457 MHz  |
| 5       | 2432 MHz  | 11      | 2462 MHz  |
| 6       | 2437 MHz  |         |           |

7 channels are provided for 802.11n (HT40):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 3       | 2422 MHz  | 7       | 2442 MHz  |
| 4       | 2427 MHz  | 8       | 2447 MHz  |
| 5       | 2432 MHz  | 9       | 2452 MHz  |
| 6       | 2437 MHz  |         |           |

40 channels are provided for BT-LE (GFSK):

| CHANNEL | FREQ. (MHZ) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0       | 2402        | 10      | 2422        | 20      | 2442        | 30      | 2462        |
| 1       | 2404        | 11      | 2424        | 21      | 2444        | 31      | 2464        |
| 2       | 2406        | 12      | 2426        | 22      | 2446        | 32      | 2466        |
| 3       | 2408        | 13      | 2428        | 23      | 2448        | 33      | 2468        |
| 4       | 2410        | 14      | 2430        | 24      | 2450        | 34      | 2470        |
| 5       | 2412        | 15      | 2432        | 25      | 2452        | 35      | 2472        |
| 6       | 2414        | 16      | 2434        | 26      | 2454        | 36      | 2474        |
| 7       | 2416        | 17      | 2436        | 27      | 2456        | 37      | 2476        |
| 8       | 2418        | 18      | 2438        | 28      | 2458        | 38      | 2478        |
| 9       | 2420        | 19      | 2440        | 29      | 2460        | 39      | 2480        |



### 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

### 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | MODE |
|--------------------------|---------------|-------|-----|------|------|
|                          | RE<1G         | RE≥1G | PLC | APCM |      |
| -                        | √             | √     | √   | √    | -    |

Where **RE<1G**: Radiated Emission below 1GHz      **RE≥1G**: Radiated Emission above 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:** No need to concern of Conducted Emission due to the EUT is powered by battery.

### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

| MODE    | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|---------|-------------------|----------------|------------|------------------|
| 802.11g | 1 to 11           | 11             | OFDM       | 6.0              |
| BT-LE   | 0 to 39           | 39             | GFSK       | 0.125            |



**RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

| MODE         | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|--------------|-------------------|----------------|------------|------------------|
| 802.11b      | 1 to 11           | 1, 6, 11       | DSSS       | 1.0              |
| 802.11g      | 1 to 11           | 1, 6, 11       | OFDM       | 6.0              |
| 802.11n HT20 | 1 to 11           | 1, 6, 11       | OFDM       | MCS0             |
| 802.11n HT40 | 3 to 9            | 3,6,9          | OFDM       | MCS0             |
| BT-LE        | 0 to 39           | 0,19, 39       | GFSK       | 0.125&0.5&1.0    |
| BT-LE        | 1 to 38           | 1,19, 38       | GFSK       | 2.0              |

**POWER LINE CONDUCTED EMISSION TEST**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

| MODE    | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|---------|-------------------|----------------|------------|------------------|
| 802.11g | 1 to 11           | 11             | OFDM       | 6.0              |



**BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

| MODE         | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|--------------|-------------------|----------------|------------|------------------|
| 802.11b      | 1 to 11           | 1, 6, 11       | DSSS       | 1.0              |
| 802.11g      | 1 to 11           | 1, 6, 11       | OFDM       | 6.0              |
| 802.11n HT20 | 1 to 11           | 1, 6, 11       | OFDM       | MCS0             |
| 802.11n HT40 | 3 to 9            | 3,6,9          | OFDM       | MCS0             |
| BT-LE        | 0 to 39           | 0,19, 39       | GFSK       | 0.125&0.5&1.0    |
| BT-LE        | 1 to 38           | 1,19, 38       | GFSK       | 2.0              |



**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

| MODE         | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|--------------|-------------------|----------------|------------|------------------|
| 802.11b      | 1 to 11           | 1, 6, 11       | DSSS       | 1.0              |
| 802.11g      | 1 to 11           | 1, 6, 11       | OFDM       | 6.0              |
| 802.11n HT20 | 1 to 11           | 1, 6, 11       | OFDM       | MCS0             |
| 802.11n HT40 | 3 to 9            | 3,6,9          | OFDM       | MCS0             |
| BT-LE        | 0 to 39           | 0,19, 39       | GFSK       | 0.125&0.5&1.0    |
| BT-LE        | 1 to 38           | 1,19, 38       | GFSK       | 2.0              |

**TEST CONDITION:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE         | TESTED BY |
|---------------|--------------------------|----------------------|-----------|
| RE<1G         | 23deg. C, 70%RH          | DC 5V By Adapter     | Jace Hu   |
| RE≥1G         | 23deg. C, 70%RH          | DC 5V By Adapter     | Jace Hu   |
| PLC           | 25deg. C, 52%RH          | DC 5V By Adapter     | Carl Xie  |
| APCM          | 25deg. C, 60%RH          | DC 3.9V By DC Supply | James Fu  |



**BUREAU  
VERITAS**

**Test Report No.: PSU-NQN2407300316RF02**

## **2.3 DUTY CYCLE OF TEST SIGNAL**

Please Refer to Appendix Of this test report.



## 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v05r02**

**ANSI C63.10-2020**

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND  | MODEL NO.     | SERIAL NO. | FCC ID |
|-----|---------|--------|---------------|------------|--------|
| 1   | Desktop | Lenovo | M73 SFF       | PC04GRQV   | N/A    |
| 2   | Desktop | Lenovo | M73 SFF       | PC06CS27   | N/A    |
| 3   | Laptop  | Lenovo | ThinkPad T450 | PC-049PT1  | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| 1   | AC Line: Unshielded, Detachable 1.5m                |
| 2   | AC Line: Unshielded, Detachable 1.5m                |
| 3   | AC Line: Unshielded, Detachable 1.5m                |



### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dBµV) |          |
|-----------------------------|------------------------|----------|
|                             | Quasi-peak             | Average  |
| 0.15 ~ 0.5                  | 66 to 56               | 56 to 46 |
| 0.5 ~ 5                     | 56                     | 46       |
| 5 ~ 30                      | 60                     | 50       |

- NOTE:** 1.The lower limit shall apply at the transition frequencies.  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.  
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

##### 3.1.2 TEST INSTRUMENTS

| Equipment           | Manufacturer  | Model No. | Serial No. | Last Cal.  | Next Cal.  |
|---------------------|---------------|-----------|------------|------------|------------|
| EMI Test Receiver   | Rohde&Schwarz | ESR3      | 101900     | Feb. 14,24 | Feb. 13,25 |
| EMC32 test software | Rohde&Schwarz | EMC32     | NA         | NA         | NA         |
| LISN network        | Rohde&Schwarz | ENV216    | 101922     | Mar. 10,24 | Mar. 09,25 |

- NOTE:**  
1. The test was performed in CE shielded room.  
2. The calibration interval of the above test instruments is 12 months, and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated, and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



### 3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
  - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



### 3.1.7 TEST RESULTS


#### CONDUCTED WORST-CASE DATA:

|                        |                |   |                                       |
|------------------------|----------------|---|---------------------------------------|
| <b>Frequency Range</b> | 150KHz ~ 30MHz | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9 kHz |
| <b>Input Power</b>     | 120Vac, 60Hz   | <b>Environmental Conditions</b>                     | 26deg. C, 51%RH                       |
| <b>Tested By</b>       | Carl Xie       |   |                                       |

| Frequency (MHz) | QuasiPeak (dBUV) | CAverage (dBUV) | Limit (dBUV) | Margin (dB) | Line | Filter | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|------|--------|------------|
| 0.944000        | ---              | 21.96           | 46.00        | 24.04       | L1   | ON     | 9.8        |
| 0.944000        | 40.29            | ---             | 56.00        | 15.71       | L1   | ON     | 9.8        |
| 3.632000        | ---              | 27.23           | 46.00        | 18.77       | L1   | ON     | 9.8        |
| 3.632000        | 44.43            | ---             | 56.00        | 11.57       | L1   | ON     | 9.8        |
| 4.976000        | ---              | 31.69           | 46.00        | 14.31       | L1   | ON     | 9.7        |
| 4.976000        | 45.99            | ---             | 56.00        | 10.01       | L1   | ON     | 9.7        |
| 10.460000       | ---              | 38.19           | 50.00        | 11.81       | L1   | ON     | 10.5       |
| 10.460000       | 51.69            | ---             | 60.00        | 8.31        | L1   | ON     | 10.5       |
| 15.912000       | ---              | 41.66           | 50.00        | 8.34        | L1   | ON     | 10.9       |
| 15.912000       | 53.16            | ---             | 60.00        | 6.84        | L1   | ON     | 10.9       |
| 17.880000       | ---              | 38.11           | 50.00        | 11.89       | L1   | ON     | 11.1       |
| 17.880000       | 49.07            | ---             | 60.00        | 10.93       | L1   | ON     | 11.1       |

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Limit value -Emission level
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum





**BUREAU  
VERITAS**


**Test Report No.: PSU-NQN2407300316RF02**

|                        |                |   |                                       |
|------------------------|----------------|---|---------------------------------------|
| <b>Frequency Range</b> | 150KHz ~ 30MHz | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9 kHz |
| <b>Input Power</b>     | 120Vac, 60Hz   | <b>Environmental Conditions</b>                     | 26deg. C, 51%RH                       |
| <b>Tested By</b>       | Carl Xie       |   |                                       |

| Frequency (MHz) | QuasiPeak (dBUV) | CAverage (dBUV) | Limit (dBUV) | Margin (dB) | Line | Filter | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|------|--------|------------|
| 2.090000        | ---              | 22.57           | 46.00        | 23.43       | N    | ON     | 9.8        |
| 2.090000        | 39.25            | ---             | 56.00        | 16.75       | N    | ON     | 9.8        |
| 3.620000        | ---              | 29.25           | 46.00        | 16.75       | N    | ON     | 9.7        |
| 3.620000        | 45.14            | ---             | 56.00        | 10.86       | N    | ON     | 9.7        |
| 4.988000        | ---              | 31.74           | 46.00        | 14.26       | N    | ON     | 9.7        |
| 4.988000        | 46.83            | ---             | 56.00        | 9.17        | N    | ON     | 9.7        |
| 10.292000       | ---              | 37.64           | 50.00        | 12.36       | N    | ON     | 10.4       |
| 10.292000       | 51.95            | ---             | 60.00        | 8.05        | N    | ON     | 10.4       |
| 13.820000       | ---              | 44.55           | 50.00        | 5.45        | N    | ON     | 10.7       |
| 13.820000       | 55.46            | ---             | 60.00        | 4.54        | N    | ON     | 10.7       |
| 17.836000       | ---              | 42.12           | 50.00        | 7.88        | N    | ON     | 11.2       |
| 17.836000       | 51.46            | ---             | 60.00        | 8.54        | N    | ON     | 11.2       |

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Limit value -Emission level
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



BV 7Layers Communications Technology  
(Shenzhen) Co., Ltd

Room B37, Warehouse A5, No.3 Chiwan 4th Road,  
Zhaoshang Street, Nanshan District Shenzhen,  
Guangdong, People's Republic of China

Tel: +86 755 8869 6566  
Fax: +86 755 8869 6577  
Email: [customerservice.sw@bureauveritas.com](mailto:customerservice.sw@bureauveritas.com)



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.2.2 TEST INSTRUMENTS

| Equipment                  | Manufacturer | Model No.                   | Serial No.                  | Last Cal.  | Next Cal.  |
|----------------------------|--------------|-----------------------------|-----------------------------|------------|------------|
| 3m Semi-anechoic Chamber   | ETS-LINDGREN | 9m*6m*6m                    | Euroshieldpn-CT0001143-1216 | Nov. 14,23 | Nov. 13,26 |
| Bilog Antenna              | ETS-LINDGREN | 3143B                       | 00161965                    | Feb. 18,24 | Feb. 17,25 |
| Horn Antenna               | ETS-LINDGREN | 3117                        | 00168692                    | Feb. 18,24 | Feb. 17,25 |
| Horn Antenna (18GHz-40GHz) | N/A          | QWH-SL-18-40-K-SG/QMS-00361 | 15433                       | Sep.04, 23 | Sep.03, 24 |
| Horn Antenna (18GHz-40GHz) | N/A          | QWH-SL-18-40-K-SG/QMS-00361 | 15433                       | Sep.03, 24 | Sep.02, 25 |
| Test Software              | E3           | V 9.160323                  | N/A                         | N/A        | N/A        |
| Test Software              | JS1120-3     | 3.2.06                      | N/A                         | N/A        | N/A        |
| 10dB Attenuator            | JFW/USA      | 50HF-010-SMA                | N/A                         | May. 06,24 | May. 05,25 |
| MXE EMI Receiver           | KEYSIGHT     | N9038A-544                  | MY54450026                  | Mar. 28,24 | Mar. 27,25 |
| Signal Pre-Amplifier       | EMSI         | EMC 9135                    | 980249                      | May. 06,24 | May. 05,25 |
| Signal Pre-Amplifier       | EMSI         | EMC 012645B                 | 980257                      | May.10,24  | May.09,25  |
| Signal Pre-Amplifier       | EMSI         | EMC 184045B                 | 980259                      | Feb. 17,24 | Feb. 16,25 |
| DC Source                  | Kikusui/JP   | PMX18-5A                    | 0000001                     | Aug. 12,23 | Aug. 11,24 |
| DC Source                  | Kikusui/JP   | PMX18-5A                    | 0000001                     | Aug. 11,24 | Aug. 10,25 |
| Power Meter                | Anritsu      | ML2495A                     | 1506002                     | Feb. 14,24 | Feb. 13,25 |
| Power Sensor               | Anritsu      | MA2411B                     | 1339352                     | Feb. 14,24 | Feb. 13,25 |
| Loop Antenna               | Schwarzbeck  | FMZB 1519B                  | 00173                       | Sep.03,23  | Sep.02,24  |
| Loop Antenna               | Schwarzbeck  | FMZB 1519B                  | 00173                       | Sep.02,24  | Sep.01,25  |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months, and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Chamber.
  3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3-meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz, and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated, and the worst-case emissions are reported.


### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.5 TEST SETUP

#### <Frequency Range 9KHz~30MHz >




#### < Frequency Range 30MHz~1GHz >





### <Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



**3.2.7 TEST RESULTS**

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

**BELOW 1GHz WORST-CASE DATA:**

**30 MHz – 1GHz data:**


**802.11g**

|                        |               |                          |                 |
|------------------------|---------------|--------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz  |                          |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |        |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|--------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 34.850  | 25.14                   | 39.63             | 40.00          | -14.86      | 22.71                  | 0.20            | 37.40              | 100                 | 360                  | Peak   |
| 60.070  | 21.05                   | 42.05             | 40.00          | -18.95      | 16.07                  | 0.30            | 37.37              | 100                 | 360                  | Peak   |
| 136.700   | 24.28                   | 46.35             | 43.50          | -19.22      | 14.00                  | 0.70            | 36.77              | 100                 | 360                  | Peak   |
| 171.620   | 26.03                   | 46.30             | 43.50          | -17.47      | 15.56                  | 0.82            | 36.65              | 100                 | 360                  | Peak   |
| 324.880   | 23.63                   | 39.46             | 46.00          | -22.37      | 19.40                  | 1.38            | 36.61              | 100                 | 360                  | Peak   |
| 545.070   | 27.31                   | 35.19             | 46.00          | -18.69      | 27.20                  | 2.07            | 37.15              | 100                 | 360                  | Peak   |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.






|                        |               |                          |                 |
|------------------------|---------------|--------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz  |                          |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |        |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|--------|
| FREQ. (MHz)                                       | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 36.790  | 34.01                   | 49.42             | 40.00          | -5.99       | 21.78                  | 0.20            | 37.39              | 100                 | 0                    | Peak   |
| 72.680  | 28.90                   | 52.79             | 40.00          | -11.10      | 13.00                  | 0.40            | 37.29              | 100                 | 0                    | Peak   |
| 132.820   | 23.40                   | 45.81             | 43.50          | -20.10      | 13.68                  | 0.69            | 36.78              | 100                 | 0                    | Peak   |
| 178.410   | 24.59                   | 44.44             | 43.50          | -18.91      | 15.94                  | 0.84            | 36.63              | 100                 | 0                    | Peak   |
| 361.740   | 23.09                   | 36.43             | 46.00          | -22.91      | 21.83                  | 1.47            | 36.64              | 100                 | 0                    | Peak   |
| 555.740   | 27.04                   | 35.34             | 46.00          | -18.96      | 26.76                  | 2.10            | 37.16              | 100                 | 0                    | Peak   |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.





BUREAU VERITAS

Test Report No.: PSU-NQN2407300316RF02

ABOVE 1GHz WORST-CASE DATA:

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

802.11b

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 65.55                   | 73.12             | 74.00          | -8.45       | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Peak    |
| 2390.000    | 42.63                   | 50.20             | 54.00          | -11.37      | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Average |
| 2412.000    | 97.43                   | 104.39            | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Peak    |
| 2412.000    | 96.32                   | 103.28            | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Average |
| 2483.500    | 52.04                   | 57.78             | 74.00          | -21.96      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Peak    |
| 2483.500    | 40.99                   | 46.73             | 54.00          | -13.01      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Average |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 63.84                   | 69.85             | 74.00          | -10.16      | 32.36                  | 7.74            | 46.11              | 100                 | 240                  | Peak    |
| 2390.000    | 43.64                   | 49.65             | 54.00          | -10.36      | 32.36                  | 7.74            | 46.11              | 100                 | 240                  | Average |
| 2412.000    | 97.61                   | 104.04            | /              | /           | 31.91                  | 7.77            | 46.11              | 100                 | 240                  | Peak    |
| 2412.000    | 96.43                   | 102.86            | /              | /           | 31.91                  | 7.77            | 46.11              | 100                 | 240                  | Average |
| 2483.500    | 50.98                   | 57.86             | 74.00          | -23.02      | 31.33                  | 7.88            | 46.09              | 100                 | 240                  | Peak    |
| 2483.500    | 39.65                   | 46.53             | 54.00          | -14.35      | 31.33                  | 7.88            | 46.09              | 100                 | 240                  | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 48.77                         | 56.34                   | 74.00             | -25.23         | 30.80                        | 7.74                  | 46.11                    | 120                       | 40                         | Peak    |
| 2390.000  | 39.27                         | 46.84                   | 54.00             | -14.73         | 30.80                        | 7.74                  | 46.11                    | 120                       | 40                         | Average |
| 2437.000  | 97.70                         | 103.81                  | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 120                       | 40                         | Peak    |
| 2437.000  | 95.47                         | 101.58                  | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 120                       | 40                         | Average |
| 2483.500  | 51.16                         | 56.90                   | 74.00             | -22.84         | 32.47                        | 7.88                  | 46.09                    | 120                       | 40                         | Peak    |
| 2483.500  | 40.92                         | 46.66                   | 54.00             | -13.08         | 32.47                        | 7.88                  | 46.09                    | 120                       | 40                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.00                         | 56.01                   | 74.00             | -24.00         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Peak    |
| 2390.000  | 40.73                         | 46.74                   | 54.00             | -13.27         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Average |
| 2437.000  | 96.80                         | 103.78                  | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Peak    |
| 2437.000  | 94.43                         | 101.41                  | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Average |
| 2483.500  | 50.04                         | 56.92                   | 74.00             | -23.96         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Peak    |
| 2483.500  | 39.79                         | 46.67                   | 54.00             | -14.21         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 49.55                   | 57.12             | 74.00          | -24.45      | 30.80                  | 7.74            | 46.11              | 115                 | 40                   | Peak    |
| 2390.000    | 39.23                   | 46.80             | 54.00          | -14.77      | 30.80                  | 7.74            | 46.11              | 115                 | 40                   | Average |
| 2462.000    | 97.17                   | 102.88            | /              | /           | 32.55                  | 7.84            | 46.10              | 115                 | 40                   | Peak    |
| 2462.000    | 95.14                   | 100.85            | /              | /           | 32.55                  | 7.84            | 46.10              | 115                 | 40                   | Average |
| 2483.500    | 63.90                   | 69.64             | 74.00          | -10.10      | 32.47                  | 7.88            | 46.09              | 115                 | 40                   | Peak    |
| 2483.500    | 43.62                   | 49.36             | 54.00          | -10.38      | 32.47                  | 7.88            | 46.09              | 115                 | 40                   | Average |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 51.20                   | 57.21             | 74.00          | -22.80      | 32.36                  | 7.74            | 46.11              | 100                 | 270                  | Peak    |
| 2390.000    | 40.50                   | 46.51             | 54.00          | -13.50      | 32.36                  | 7.74            | 46.11              | 100                 | 270                  | Average |
| 2462.000    | 95.92                   | 103.06            | /              | /           | 31.12                  | 7.84            | 46.10              | 100                 | 270                  | Peak    |
| 2462.000    | 94.48                   | 101.62            | /              | /           | 31.12                  | 7.84            | 46.10              | 100                 | 270                  | Average |
| 2483.500    | 62.90                   | 69.78             | 74.00          | -11.10      | 31.33                  | 7.88            | 46.09              | 100                 | 270                  | Peak    |
| 2483.500    | 43.25                   | 50.13             | 54.00          | -10.75      | 31.33                  | 7.88            | 46.09              | 100                 | 270                  | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



802.11g

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 63.62                   | 71.19             | 74.00          | -10.38      | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Peak    |
| 2390.000    | 48.77                   | 56.34             | 54.00          | -5.23       | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Average |
| 2412.000    | 100.43                  | 107.39            | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Peak    |
| 2412.000    | 93.12                   | 100.08            | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Average |
| 2483.500    | 51.74                   | 57.48             | 74.00          | -22.26      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Peak    |
| 2483.500    | 41.86                   | 47.60             | 54.00          | -12.14      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Average |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 62.94                   | 68.95             | 74.00          | -11.06      | 32.36                  | 7.74            | 46.11              | 175                 | 185                  | Peak    |
| 2390.000    | 48.82                   | 54.83             | 54.00          | -5.18       | 32.36                  | 7.74            | 46.11              | 175                 | 185                  | Average |
| 2412.000    | 100.76                  | 107.19            | /              | /           | 31.91                  | 7.77            | 46.11              | 175                 | 185                  | Peak    |
| 2412.000    | 92.59                   | 99.02             | /              | /           | 31.91                  | 7.77            | 46.11              | 175                 | 185                  | Average |
| 2483.500    | 50.03                   | 56.91             | 74.00          | -23.97      | 31.33                  | 7.88            | 46.09              | 175                 | 185                  | Peak    |
| 2483.500    | 40.97                   | 47.85             | 54.00          | -13.03      | 31.33                  | 7.88            | 46.09              | 175                 | 185                  | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 48.37                   | 55.94             | 74.00          | -25.63      | 30.80                  | 7.74            | 46.11              | 145                 | 40                   | Peak    |
| 2390.000    | 41.49                   | 49.06             | 54.00          | -12.51      | 30.80                  | 7.74            | 46.11              | 145                 | 40                   | Average |
| 2437.000    | 100.43                  | 106.54            | /              | /           | 32.18                  | 7.81            | 46.10              | 145                 | 40                   | Peak    |
| 2437.000    | 94.40                   | 100.51            | /              | /           | 32.18                  | 7.81            | 46.10              | 145                 | 40                   | Average |
| 2483.500    | 50.59                   | 56.33             | 74.00          | -23.41      | 32.47                  | 7.88            | 46.09              | 145                 | 40                   | Peak    |
| 2483.500    | 42.76                   | 48.50             | 54.00          | -11.24      | 32.47                  | 7.88            | 46.09              | 145                 | 40                   | Average |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 50.07                   | 56.08             | 74.00          | -23.93      | 32.36                  | 7.74            | 46.11              | 120                 | 185                  | Peak    |
| 2390.000    | 42.62                   | 48.63             | 54.00          | -11.38      | 32.36                  | 7.74            | 46.11              | 120                 | 185                  | Average |
| 2437.000    | 100.14                  | 107.12            | /              | /           | 31.31                  | 7.81            | 46.10              | 120                 | 185                  | Peak    |
| 2437.000    | 93.85                   | 100.83            | /              | /           | 31.31                  | 7.81            | 46.10              | 120                 | 185                  | Average |
| 2483.500    | 49.51                   | 56.39             | 74.00          | -24.49      | 31.33                  | 7.88            | 46.09              | 120                 | 185                  | Peak    |
| 2483.500    | 41.69                   | 48.57             | 54.00          | -12.31      | 31.33                  | 7.88            | 46.09              | 120                 | 185                  | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 49.26                         | 56.83                   | 74.00             | -24.74         | 30.80                        | 7.74                  | 46.11                    | 100                       | 185                        | Peak    |
| 2390.000  | 40.58                         | 48.15                   | 54.00             | -13.42         | 30.80                        | 7.74                  | 46.11                    | 100                       | 185                        | Average |
| 2462.000  | 100.43                        | 106.14                  | /                 | /              | 32.55                        | 7.84                  | 46.10                    | 100                       | 185                        | Peak    |
| 2462.000  | 94.38                         | 100.09                  | /                 | /              | 32.55                        | 7.84                  | 46.10                    | 100                       | 185                        | Average |
| 2483.500  | 66.01                         | 71.75                   | 74.00             | -7.99          | 32.47                        | 7.88                  | 46.09                    | 100                       | 185                        | Peak    |
| 2483.500  | 50.73                         | 56.47                   | 54.00             | -3.27          | 32.47                        | 7.88                  | 46.09                    | 100                       | 185                        | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 51.35                         | 57.36                   | 74.00             | -22.65         | 32.36                        | 7.74                  | 46.11                    | 100                       | 100                        | Peak    |
| 2390.000  | 42.94                         | 48.95                   | 54.00             | -11.06         | 32.36                        | 7.74                  | 46.11                    | 100                       | 100                        | Average |
| 2462.000  | 98.54                         | 105.68                  | /                 | /              | 31.12                        | 7.84                  | 46.10                    | 100                       | 100                        | Peak    |
| 2462.000  | 91.11                         | 98.25                   | /                 | /              | 31.12                        | 7.84                  | 46.10                    | 100                       | 100                        | Average |
| 2483.500  | 62.53                         | 69.41                   | 74.00             | -11.47         | 31.33                        | 7.88                  | 46.09                    | 100                       | 100                        | Peak    |
| 2483.500  | 48.98                         | 55.86                   | 54.00             | -5.02          | 31.33                        | 7.88                  | 46.09                    | 100                       | 100                        | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



802.11n (20MHz)

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 58.21                   | 65.78             | 74.00          | -15.79      | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Peak    |
| 2390.000  | 47.34                   | 54.91             | 54.00          | -6.66       | 30.80                  | 7.74            | 46.11              | 170                 | 40                   | Average |
| 2412.000  | 97.10                   | 104.06            | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Peak    |
| 2412.000  | 89.94                   | 96.90             | /              | /           | 31.38                  | 7.77            | 46.11              | 170                 | 40                   | Average |
| 2483.500  | 50.51                   | 56.25             | 74.00          | -23.49      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Peak    |
| 2483.500  | 43.49                   | 49.23             | 54.00          | -10.51      | 32.47                  | 7.88            | 46.09              | 170                 | 40                   | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                        |                 |                    |                     |                      |         |
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 58.54                   | 64.55             | 74.00          | -15.46      | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Peak    |
| 2390.000  | 46.76                   | 52.77             | 54.00          | -7.24       | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Average |
| 2412.000  | 95.87                   | 102.30            | /              | /           | 31.91                  | 7.77            | 46.11              | 100                 | 185                  | Peak    |
| 2412.000  | 88.71                   | 95.14             | /              | /           | 31.91                  | 7.77            | 46.11              | 100                 | 185                  | Average |
| 2483.500  | 48.97                   | 55.85             | 74.00          | -25.03      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Peak    |
| 2483.500  | 42.53                   | 49.41             | 54.00          | -11.47      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2412MHz: Fundamental frequency.



|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
|----------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| 2390.000       | 49.87                         | 57.44                   | 74.00             | -24.13         | 30.80                        | 7.74                  | 46.11                    | 100                       | 40                         | Peak    |
| 2390.000       | 41.77                         | 49.34                   | 54.00             | -12.23         | 30.80                        | 7.74                  | 46.11                    | 100                       | 40                         | Average |
| 2437.000       | 95.81                         | 101.92                  | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 100                       | 40                         | Peak    |
| 2437.000       | 87.72                         | 93.83                   | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 100                       | 40                         | Average |
| 2483.500       | 52.07                         | 57.81                   | 74.00             | -21.93         | 32.47                        | 7.88                  | 46.09                    | 100                       | 40                         | Peak    |
| 2483.500       | 43.27                         | 49.01                   | 54.00             | -10.73         | 32.47                        | 7.88                  | 46.09                    | 100                       | 40                         | Average |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
|----------------|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| 2390.000       | 51.89                         | 57.90                   | 74.00             | -22.11         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Peak    |
| 2390.000       | 43.53                         | 49.54                   | 54.00             | -10.47         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Average |
| 2437.000       | 97.33                         | 104.31                  | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Peak    |
| 2437.000       | 89.98                         | 96.96                   | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Average |
| 2483.500       | 49.94                         | 56.82                   | 74.00             | -24.06         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Peak    |
| 2483.500       | 42.86                         | 49.74                   | 54.00             | -11.14         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2437MHz: Fundamental frequency.



|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

| <b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b> |  |                                  |                           |                        |                                       |                                |                                   |                                    |                                     |               |
|--|--|----------------------------------|---------------------------|------------------------|---------------------------------------|--------------------------------|-----------------------------------|------------------------------------|-------------------------------------|---------------|
| <b>FREQ.<br/>(MHz)</b>   | <b>EMISSION<br/>LEVEL<br/>(dBuV/m)</b> | <b>READ<br/>LEVEL<br/>(dBuV)</b> | <b>LIMIT<br/>(dBuV/m)</b> | <b>MARGIN<br/>(dB)</b> | <b>ANTENNA<br/>FACTOR<br/>(dB /m)</b> | <b>CABLE<br/>LOSS<br/>(dB)</b> | <b>PREAMP<br/>FACTOR<br/>(dB)</b> | <b>ANTENNA<br/>HEIGHT<br/>(cm)</b> | <b>TABLE<br/>ANGLE<br/>(Degree)</b> | <b>REMARK</b> |
| 2390.000   | 49.58                                  | 57.15                            | 74.00                     | -24.42                 | 30.80                                 | 7.74                           | 46.11                             | 165                                | 45                                  | Peak          |
| 2390.000   | 42.01                                  | 49.58                            | 54.00                     | -11.99                 | 30.80                                 | 7.74                           | 46.11                             | 165                                | 45                                  | Average       |
| 2462.000   | 95.88                                  | 101.59                           | /                         | /                      | 32.55                                 | 7.84                           | 46.10                             | 165                                | 45                                  | Peak          |
| 2462.000   | 88.29                                  | 94.00                            | /                         | /                      | 32.55                                 | 7.84                           | 46.10                             | 165                                | 45                                  | Average       |
| 2483.500   | 59.43                                  | 65.17                            | 74.00                     | -14.57                 | 32.47                                 | 7.88                           | 46.09                             | 165                                | 45                                  | Peak          |
| 2483.500   | 46.49                                  | 52.23                            | 54.00                     | -7.51                  | 32.47                                 | 7.88                           | 46.09                             | 165                                | 45                                  | Average       |
| <b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>   |  |                                  |                           |                        |                                       |                                |                                   |                                    |                                     |               |
| <b>FREQ.<br/>(MHz)</b>   | <b>EMISSION<br/>LEVEL<br/>(dBuV/m)</b> | <b>READ<br/>LEVEL<br/>(dBuV)</b> | <b>LIMIT<br/>(dBuV/m)</b> | <b>MARGIN<br/>(dB)</b> | <b>ANTENNA<br/>FACTOR<br/>(dB /m)</b> | <b>CABLE<br/>LOSS<br/>(dB)</b> | <b>PREAMP<br/>FACTOR<br/>(dB)</b> | <b>ANTENNA<br/>HEIGHT<br/>(cm)</b> | <b>TABLE<br/>ANGLE<br/>(Degree)</b> | <b>REMARK</b> |
| 2390.000   | 50.91                                  | 56.92                            | 74.00                     | -23.09                 | 32.36                                 | 7.74                           | 46.11                             | 100                                | 95                                  | Peak          |
| 2390.000   | 43.46                                  | 49.47                            | 54.00                     | -10.54                 | 32.36                                 | 7.74                           | 46.11                             | 100                                | 95                                  | Average       |
| 2462.000   | 94.33                                  | 101.47                           | /                         | /                      | 31.12                                 | 7.84                           | 46.10                             | 100                                | 95                                  | Peak          |
| 2462.000   | 86.65                                  | 93.79                            | /                         | /                      | 31.12                                 | 7.84                           | 46.10                             | 100                                | 95                                  | Average       |
| 2483.500   | 56.93                                  | 63.81                            | 74.00                     | -17.07                 | 31.33                                 | 7.88                           | 46.09                             | 100                                | 95                                  | Peak          |
| 2483.500   | 44.23                                  | 51.11                            | 54.00                     | -9.77                  | 31.33                                 | 7.88                           | 46.09                             | 100                                | 95                                  | Average       |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.



802.11n (40MHz)

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 57.64                   | 65.21             | 74.00          | -16.36      | 30.80                  | 7.74            | 46.11              | 100                 | 40                   | Peak    |
| 2390.000    | 49.01                   | 56.58             | 54.00          | -4.99       | 30.80                  | 7.74            | 46.11              | 100                 | 40                   | Average |
| 2422.000    | 92.54                   | 99.17             | /              | /           | 31.70                  | 7.78            | 46.11              | 100                 | 40                   | Peak    |
| 2422.000    | 84.71                   | 91.34             | /              | /           | 31.70                  | 7.78            | 46.11              | 100                 | 40                   | Average |
| 2483.500    | 52.40                   | 58.14             | 74.00          | -21.60      | 32.47                  | 7.88            | 46.09              | 100                 | 40                   | Peak    |
| 2483.500    | 43.37                   | 49.11             | 54.00          | -10.63      | 32.47                  | 7.88            | 46.09              | 100                 | 40                   | Average |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 55.81                   | 61.82             | 74.00          | -18.19      | 32.36                  | 7.74            | 46.11              | 100                 | 85                   | Peak    |
| 2390.000    | 48.55                   | 54.56             | 54.00          | -5.45       | 32.36                  | 7.74            | 46.11              | 100                 | 85                   | Average |
| 2422.000    | 94.43                   | 101.09            | /              | /           | 31.67                  | 7.78            | 46.11              | 100                 | 85                   | Peak    |
| 2422.000    | 86.93                   | 93.59             | /              | /           | 31.67                  | 7.78            | 46.11              | 100                 | 85                   | Average |
| 2483.500    | 50.32                   | 57.20             | 74.00          | -23.68      | 31.33                  | 7.88            | 46.09              | 100                 | 85                   | Peak    |
| 2483.500    | 43.11                   | 49.99             | 54.00          | -10.89      | 31.33                  | 7.88            | 46.09              | 100                 | 85                   | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2422MHz: Fundamental frequency.



**BUREAU  
VERITAS**

Test Report No.: PSU-NQN2407300316RF02

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.36                         | 57.93                   | 74.00             | -23.64         | 30.80                        | 7.74                  | 46.11                    | 100                       | 45                         | Peak    |
| 2390.000  | 42.30                         | 49.87                   | 54.00             | -11.70         | 30.80                        | 7.74                  | 46.11                    | 100                       | 45                         | Average |
| 2437.000  | 94.12                         | 100.23                  | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 100                       | 45                         | Peak    |
| 2437.000  | 86.25                         | 92.36                   | /                 | /              | 32.18                        | 7.81                  | 46.10                    | 100                       | 45                         | Average |
| 2483.500  | 52.64                         | 58.38                   | 74.00             | -21.36         | 32.47                        | 7.88                  | 46.09                    | 100                       | 45                         | Peak    |
| 2483.500  | 44.24                         | 49.98                   | 54.00             | -9.76          | 32.47                        | 7.88                  | 46.09                    | 100                       | 45                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.71                         | 56.72                   | 74.00             | -23.29         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Peak    |
| 2390.000  | 43.32                         | 49.33                   | 54.00             | -10.68         | 32.36                        | 7.74                  | 46.11                    | 100                       | 85                         | Average |
| 2437.000  | 95.15                         | 102.13                  | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Peak    |
| 2437.000  | 87.48                         | 94.46                   | /                 | /              | 31.31                        | 7.81                  | 46.10                    | 100                       | 85                         | Average |
| 2483.500  | 51.88                         | 58.76                   | 74.00             | -22.12         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Peak    |
| 2483.500  | 42.88                         | 49.76                   | 54.00             | -11.12         | 31.33                        | 7.88                  | 46.09                    | 100                       | 85                         | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2437MHz: Fundamental frequency.



|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 9 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 48.72                         | 56.29                   | 74.00             | -25.28         | 30.80                        | 7.74                  | 46.11                    | 100                       | 60                         | Peak    |
| 2390.000  | 42.03                         | 49.60                   | 54.00             | -11.97         | 30.80                        | 7.74                  | 46.11                    | 100                       | 60                         | Average |
| 2452.000  | 94.73                         | 100.41                  | /                 | /              | 32.59                        | 7.83                  | 46.10                    | 100                       | 60                         | Peak    |
| 2452.000  | 87.46                         | 93.14                   | /                 | /              | 32.59                        | 7.83                  | 46.10                    | 100                       | 60                         | Average |
| 2483.500  | 55.69                         | 61.43                   | 74.00             | -18.31         | 32.47                        | 7.88                  | 46.09                    | 100                       | 60                         | Peak    |
| 2483.500  | 44.60                         | 50.34                   | 54.00             | -9.40          | 32.47                        | 7.88                  | 46.09                    | 100                       | 60                         | Average |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                    | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.04                         | 56.05                   | 74.00             | -23.96         | 32.36                        | 7.74                  | 46.11                    | 100                       | 90                         | Peak    |
| 2390.000  | 43.64                         | 49.65                   | 54.00             | -10.36         | 32.36                        | 7.74                  | 46.11                    | 100                       | 90                         | Average |
| 2452.000  | 95.84                         | 103.09                  | /                 | /              | 31.02                        | 7.83                  | 46.10                    | 100                       | 90                         | Peak    |
| 2452.000  | 87.58                         | 94.83                   | /                 | /              | 31.02                        | 7.83                  | 46.10                    | 100                       | 90                         | Average |
| 2483.500  | 54.83                         | 61.71                   | 74.00             | -19.17         | 31.33                        | 7.88                  | 46.09                    | 100                       | 90                         | Peak    |
| 2483.500  | 45.06                         | 51.94                   | 54.00             | -8.94          | 31.33                        | 7.88                  | 46.09                    | 100                       | 90                         | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2452MHz: Fundamental frequency.



**BUREAU VERITAS** Test Report No.: PSU-NQN2407300316RF02


Worst case harmonic:

802.11g

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**


|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |            |
| 1    | 4927.000 | 45.71  | 47.52      | 74.00      | -28.29     | -1.81  | Peak   | Horizontal |
| 2 PP | 7386.000 | 46.76  | 44.45      | 74.00      | -27.24     | 2.31   | Peak   | Horizontal |





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|------|----------|--------|------------|------------|------------|--------|--------|-----------|
|      | MHz      | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |           |
| 1    | 4924.000 | 44.67  | 46.54      | 74.00      | -29.33     | -1.87  | Peak   | Vertical  |
| 2 PP | 7392.000 | 45.76  | 43.22      | 74.00      | -28.24     | 2.54   | Peak   | Vertical  |



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2462MHz: Fundamental frequency.
- For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



**BELOW 1GHz WORST-CASE DATA:**

30 MHz – 1GHz data:


BT-LE\_S8

|                        |               |                           |                 |
|------------------------|---------------|---------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>ODETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz  |                           |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |        |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|--------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 30.970  | 25.36                   | 38.04             | 40.00          | -14.64      | 24.61                  | 0.14            | 37.43              | 100                 | 360                  | Peak   |
| 71.710  | 20.97                   | 44.82             | 40.00          | -19.03      | 13.06                  | 0.39            | 37.30              | 100                 | 360                  | Peak   |
| 146.400   | 25.58                   | 46.91             | 43.50          | -17.92      | 14.64                  | 0.77            | 36.74              | 100                 | 360                  | Peak   |
| 191.020   | 27.98                   | 47.84             | 43.50          | -15.52      | 15.80                  | 0.93            | 36.59              | 100                 | 360                  | Peak   |
| 326.820   | 23.75                   | 39.52             | 46.00          | -22.25      | 19.47                  | 1.38            | 36.62              | 100                 | 360                  | Peak   |
| 552.830   | 27.12                   | 35.26             | 46.00          | -18.88      | 26.93                  | 2.09            | 37.16              | 100                 | 360                  | Peak   |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value






|                        |               |                          |                 |
|------------------------|---------------|--------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39 | <b>DETECTOR FUNCTION</b> | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz  |                          |                 |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |        |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|--------|
| FREQ. (MHz)                                       | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK |
| 31.940  | 32.10                   | 45.23             | 40.00          | -7.90       | 24.13                  | 0.16            | 37.42              | 100                 | 0                    | Peak   |
| 71.710  | 28.54                   | 52.39             | 40.00          | -11.46      | 13.06                  | 0.39            | 37.30              | 100                 | 0                    | Peak   |
| 87.230  | 29.95                   | 54.12             | 40.00          | -10.05      | 12.45                  | 0.48            | 37.10              | 100                 | 0                    | Peak   |
| 156.100   | 24.27                   | 43.18             | 43.50          | -19.23      | 17.00                  | 0.79            | 36.70              | 100                 | 0                    | Peak   |
| 258.920   | 20.76                   | 36.97             | 46.00          | -25.24      | 19.19                  | 1.18            | 36.58              | 100                 | 0                    | Peak   |
| 542.160   | 26.68                   | 34.68             | 46.00          | -19.32      | 27.09                  | 2.06            | 37.15              | 100                 | 0                    | Peak   |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





ABOVE 1GHz TEST DATA

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

BT-LE \_1M

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 0 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 49.14                   | 56.71             | 74.00          | -24.86      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Peak    |
| 2390.000  | 41.62                   | 49.19             | 54.00          | -12.38      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Average |
| 2402.000  | 87.93                   | 95.23             | /              | /           | 31.06                  | 7.75            | 46.11              | 100                 | 55                   | Peak    |
| 2402.000  | 87.08                   | 94.38             | /              | /           | 31.06                  | 7.75            | 46.11              | 100                 | 55                   | Average |
| 2483.500  | 50.46                   | 56.20             | 74.00          | -23.54      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Peak    |
| 2483.500  | 43.18                   | 48.92             | 54.00          | -10.82      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                        |                 |                    |                     |                      |         |
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 50.24                   | 56.25             | 74.00          | -23.76      | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Peak    |
| 2390.000  | 42.72                   | 48.73             | 54.00          | -11.28      | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Average |
| 2402.000  | 88.80                   | 95.01             | /              | /           | 32.15                  | 7.75            | 46.11              | 100                 | 185                  | Peak    |
| 2402.000  | 87.82                   | 94.03             | /              | /           | 32.15                  | 7.75            | 46.11              | 100                 | 185                  | Average |
| 2483.500  | 49.43                   | 56.31             | 74.00          | -24.57      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Peak    |
| 2483.500  | 42.18                   | 49.06             | 54.00          | -11.82      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| <b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b> |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|--|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)   | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000   | 47.64                         | 55.21                   | 74.00             | -26.36         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Peak    |
| 2390.000   | 41.29                         | 48.86                   | 54.00             | -12.71         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Average |
| 2440.000   | 86.77                         | 92.78                   | /                 | /              | 32.28                        | 7.81                  | 46.10                    | 100                       | 55                         | Peak    |
| 2440.000   | 85.71                         | 91.72                   | /                 | /              | 32.28                        | 7.81                  | 46.10                    | 100                       | 55                         | Average |
| 2483.500   | 49.89                         | 55.63                   | 74.00             | -24.11         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Peak    |
| 2483.500   | 42.77                         | 48.51                   | 54.00             | -11.23         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Average |
| <b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)   | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000   | 49.92                         | 55.93                   | 74.00             | -24.08         | 32.36                        | 7.74                  | 46.11                    | 100                       | 95                         | Peak    |
| 2390.000   | 42.84                         | 48.85                   | 54.00             | -11.16         | 32.36                        | 7.74                  | 46.11                    | 100                       | 95                         | Average |
| 2440.000   | 88.37                         | 95.42                   | /                 | /              | 31.24                        | 7.81                  | 46.10                    | 100                       | 95                         | Peak    |
| 2440.000   | 87.41                         | 94.46                   | /                 | /              | 31.24                        | 7.81                  | 46.10                    | 100                       | 95                         | Average |
| 2483.500   | 48.66                         | 55.54                   | 74.00             | -25.34         | 31.33                        | 7.88                  | 46.09                    | 100                       | 95                         | Peak    |
| 2483.500   | 41.97                         | 48.85                   | 54.00             | -12.03         | 31.33                        | 7.88                  | 46.09                    | 100                       | 95                         | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 48.69                   | 56.26             | 74.00          | -25.31      | 30.80                  | 7.74            | 46.11              | 100                 | 60                   | Peak    |
| 2390.000  | 41.69                   | 49.26             | 54.00          | -12.31      | 30.80                  | 7.74            | 46.11              | 100                 | 60                   | Average |
| 2480.000  | 85.35                   | 91.09             | /              | /           | 32.48                  | 7.87            | 46.09              | 100                 | 60                   | Peak    |
| 2480.000  | 84.40                   | 90.14             | /              | /           | 32.48                  | 7.87            | 46.09              | 100                 | 60                   | Average |
| 2483.500  | 51.21                   | 56.95             | 74.00          | -22.79      | 32.47                  | 7.88            | 46.09              | 100                 | 60                   | Peak    |
| 2483.500  | 43.04                   | 48.78             | 54.00          | -10.96      | 32.47                  | 7.88            | 46.09              | 100                 | 60                   | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                        |                 |                    |                     |                      |         |
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 51.07                   | 57.08             | 74.00          | -22.93      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Peak    |
| 2390.000  | 43.02                   | 49.03             | 54.00          | -10.98      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Average |
| 2480.000  | 86.85                   | 93.77             | /              | /           | 31.30                  | 7.87            | 46.09              | 100                 | 90                   | Peak    |
| 2480.000  | 85.79                   | 92.71             | /              | /           | 31.30                  | 7.87            | 46.09              | 100                 | 90                   | Average |
| 2483.500  | 49.59                   | 56.47             | 74.00          | -24.41      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Peak    |
| 2483.500  | 42.35                   | 49.23             | 54.00          | -11.65      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.



**BUREAU  
VERITAS**


Test Report No.: PSU-NQN2407300316RF02

Worst case harmonic:

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**


|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |            |
| 1    | 4808.000 | 45.27  | 47.11      | 74.00      | -28.73     | -1.84  | Peak   | Horizontal |
| 2 PP | 7206.000 | 45.40  | 43.65      | 74.00      | -28.60     | 1.75   | Peak   | Horizontal |





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
|   | MHz         | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |           |
| 1 | PP 4804.000 | 45.40  | 46.62      | 74.00      | -28.60     | -1.22  | Peak   | Vertical  |
| 2 | 7205.000    | 45.33  | 43.67      | 74.00      | -28.67     | 1.66   | Peak   | Vertical  |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



**BUREAU  
VERITAS**

Test Report No.: PSU-NQN2407300316RF02

**BT-LE\_2M**

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 49.92                         | 57.49                   | 74.00             | -24.08         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Peak    |
| 2390.000  | 41.03                         | 48.60                   | 54.00             | -12.97         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Average |
| 2404.000  | 85.05                         | 92.27                   | /                 | /              | 31.13                        | 7.76                  | 46.11                    | 100                       | 55                         | Peak    |
| 2404.000  | 83.22                         | 90.44                   | /                 | /              | 31.13                        | 7.76                  | 46.11                    | 100                       | 55                         | Average |
| 2483.500  | 51.22                         | 56.96                   | 74.00             | -22.78         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Peak    |
| 2483.500  | 43.24                         | 48.98                   | 54.00             | -10.76         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Average |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                    | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.83                         | 56.84                   | 74.00             | -23.17         | 32.36                        | 7.74                  | 46.11                    | 100                       | 185                        | Peak    |
| 2390.000  | 42.76                         | 48.77                   | 54.00             | -11.24         | 32.36                        | 7.74                  | 46.11                    | 100                       | 185                        | Average |
| 2404.000  | 85.57                         | 91.82                   | /                 | /              | 32.10                        | 7.76                  | 46.11                    | 100                       | 185                        | Peak    |
| 2404.000  | 83.73                         | 89.98                   | /                 | /              | 32.10                        | 7.76                  | 46.11                    | 100                       | 185                        | Average |
| 2483.500  | 50.51                         | 57.39                   | 74.00             | -23.49         | 31.33                        | 7.88                  | 46.09                    | 100                       | 185                        | Peak    |
| 2483.500  | 41.95                         | 48.83                   | 54.00             | -12.05         | 31.33                        | 7.88                  | 46.09                    | 100                       | 185                        | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2404MHz: Fundamental frequency.



|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 19 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 49.92                   | 57.49             | 74.00          | -24.08      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Peak    |
| 2390.000    | 41.15                   | 48.72             | 54.00          | -12.85      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Average |
| 2440.000    | 87.40                   | 93.41             | /              | /           | 32.28                  | 7.81            | 46.10              | 100                 | 55                   | Peak    |
| 2440.000    | 85.47                   | 91.48             | /              | /           | 32.28                  | 7.81            | 46.10              | 100                 | 55                   | Average |
| 2483.500    | 50.43                   | 56.17             | 74.00          | -23.57      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Peak    |
| 2483.500    | 42.98                   | 48.72             | 54.00          | -11.02      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Average |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
|-------------|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| 2390.000    | 50.23                   | 56.24             | 74.00          | -23.77      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Peak    |
| 2390.000    | 43.68                   | 49.69             | 54.00          | -10.32      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Average |
| 2440.000    | 88.57                   | 95.62             | /              | /           | 31.24                  | 7.81            | 46.10              | 100                 | 90                   | Peak    |
| 2440.000    | 86.64                   | 93.69             | /              | /           | 31.24                  | 7.81            | 46.10              | 100                 | 90                   | Average |
| 2483.500    | 49.90                   | 56.78             | 74.00          | -24.10      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Peak    |
| 2483.500    | 42.05                   | 48.93             | 54.00          | -11.95      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 38 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 48.76                         | 56.33                   | 74.00             | -25.24         | 30.80                        | 7.74                  | 46.11                    | 100                       | 60                         | Peak    |
| 2390.000  | 41.84                         | 49.41                   | 54.00             | -12.16         | 30.80                        | 7.74                  | 46.11                    | 100                       | 60                         | Average |
| 2478.000  | 85.99                         | 91.72                   | /                 | /              | 32.49                        | 7.87                  | 46.09                    | 100                       | 60                         | Peak    |
| 2478.000  | 84.11                         | 89.84                   | /                 | /              | 32.49                        | 7.87                  | 46.09                    | 100                       | 60                         | Average |
| 2483.500  | 50.33                         | 56.07                   | 74.00             | -23.67         | 32.47                        | 7.88                  | 46.09                    | 100                       | 60                         | Peak    |
| 2483.500  | 42.77                         | 48.51                   | 54.00             | -11.23         | 32.47                        | 7.88                  | 46.09                    | 100                       | 60                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 51.37                         | 57.38                   | 74.00             | -22.63         | 32.36                        | 7.74                  | 46.11                    | 100                       | 90                         | Peak    |
| 2390.000  | 43.13                         | 49.14                   | 54.00             | -10.87         | 32.36                        | 7.74                  | 46.11                    | 100                       | 90                         | Average |
| 2478.000  | 87.46                         | 94.40                   | /                 | /              | 31.28                        | 7.87                  | 46.09                    | 100                       | 90                         | Peak    |
| 2478.000  | 85.66                         | 92.60                   | /                 | /              | 31.28                        | 7.87                  | 46.09                    | 100                       | 90                         | Average |
| 2483.500  | 50.47                         | 57.35                   | 74.00             | -23.53         | 31.33                        | 7.88                  | 46.09                    | 100                       | 90                         | Peak    |
| 2483.500  | 42.29                         | 49.17                   | 54.00             | -11.71         | 31.33                        | 7.88                  | 46.09                    | 100                       | 90                         | Average |

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2478MHz: Fundamental frequency.



**BUREAU  
VERITAS**


Test Report No.: PSU-NQN2407300316RF02

**Worst case harmonic:**

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 19 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**


|      | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|----------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz      | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |            |
| 1    | 4880.000 | 44.84  | 46.76      | 74.00      | -29.16     | -1.92  | Peak   | Horizontal |
| 2 PP | 7324.000 | 45.19  | 43.00      | 74.00      | -28.81     | 2.19   | Peak   | Horizontal |





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
|   | MHz         | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |           |
| 1 | 4876.000    | 46.17  | 47.66      | 74.00      | -27.83     | -1.49  | Peak   | Vertical  |
| 2 | PP 7320.000 | 46.45  | 43.98      | 74.00      | -27.55     | 2.47   | Peak   | Vertical  |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2440MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet



**BUREAU  
VERITAS**

Test Report No.: PSU-NQN2407300316RF02

**BT-LE \_S2**

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
|---|-------------------------------|-------------------------|-------------------|----------------|------------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 48.38                         | 55.95                   | 74.00             | -25.62         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Peak    |
| 2390.000  | 41.27                         | 48.84                   | 54.00             | -12.73         | 30.80                        | 7.74                  | 46.11                    | 100                       | 55                         | Average |
| 2402.000  | 85.68                         | 92.98                   | /                 | /              | 31.06                        | 7.75                  | 46.11                    | 100                       | 55                         | Peak    |
| 2402.000  | 85.37                         | 92.67                   | /                 | /              | 31.06                        | 7.75                  | 46.11                    | 100                       | 55                         | Average |
| 2483.500  | 50.88                         | 56.62                   | 74.00             | -23.12         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Peak    |
| 2483.500  | 43.51                         | 49.25                   | 54.00             | -10.49         | 32.47                        | 7.88                  | 46.09                    | 100                       | 55                         | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                              |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB /m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390.000  | 50.71                         | 56.72                   | 74.00             | -23.29         | 32.36                        | 7.74                  | 46.11                    | 100                       | 185                        | Peak    |
| 2390.000  | 42.86                         | 48.87                   | 54.00             | -11.14         | 32.36                        | 7.74                  | 46.11                    | 100                       | 185                        | Average |
| 2402.000  | 86.77                         | 92.98                   | /                 | /              | 32.15                        | 7.75                  | 46.11                    | 100                       | 185                        | Peak    |
| 2402.000  | 85.95                         | 92.16                   | /                 | /              | 32.15                        | 7.75                  | 46.11                    | 100                       | 185                        | Average |
| 2483.500  | 49.66                         | 56.54                   | 74.00             | -24.34         | 31.33                        | 7.88                  | 46.09                    | 100                       | 185                        | Peak    |
| 2483.500  | 41.79                         | 48.67                   | 54.00             | -12.21         | 31.33                        | 7.88                  | 46.09                    | 100                       | 185                        | Average |

**REMARKS:**

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.



|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 19 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 49.54                   | 57.11             | 74.00          | -24.46      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Peak    |
| 2390.000  | 41.33                   | 48.90             | 54.00          | -12.67      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Average |
| 2440.000  | 87.52                   | 93.53             | /              | /           | 32.28                  | 7.81            | 46.10              | 100                 | 55                   | Peak    |
| 2440.000  | 86.87                   | 92.88             | /              | /           | 32.28                  | 7.81            | 46.10              | 100                 | 55                   | Average |
| 2483.500  | 50.16                   | 55.90             | 74.00          | -23.84      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Peak    |
| 2483.500  | 43.50                   | 49.24             | 54.00          | -10.50      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Average |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                         |                   |                |             |                        |                 |                    |                     |                      |         |
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 50.08                   | 56.09             | 74.00          | -23.92      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Peak    |
| 2390.000  | 43.23                   | 49.24             | 54.00          | -10.77      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Average |
| 2440.000  | 88.96                   | 96.01             | /              | /           | 31.24                  | 7.81            | 46.10              | 100                 | 90                   | Peak    |
| 2440.000  | 88.26                   | 95.31             | /              | /           | 31.24                  | 7.81            | 46.10              | 100                 | 90                   | Average |
| 2483.500  | 49.96                   | 56.84             | 74.00          | -24.04      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Peak    |
| 2483.500  | 42.75                   | 49.63             | 54.00          | -11.25      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2440MHz: Fundamental frequency.



|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 39 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 49.59                   | 57.16             | 74.00          | -24.41      | 30.80                  | 7.74            | 46.11              | 100                 | 60                   | Peak    |
| 2390.000  | 41.81                   | 49.38             | 54.00          | -12.19      | 30.80                  | 7.74            | 46.11              | 100                 | 60                   | Average |
| 2480.000  | 85.86                   | 91.60             | /              | /           | 32.48                  | 7.87            | 46.09              | 100                 | 60                   | Peak    |
| 2480.000  | 85.46                   | 91.20             | /              | /           | 32.48                  | 7.87            | 46.09              | 100                 | 60                   | Average |
| 2483.500  | 51.19                   | 56.93             | 74.00          | -22.81      | 32.47                  | 7.88            | 46.09              | 100                 | 60                   | Peak    |
| 2483.500  | 43.40                   | 49.14             | 54.00          | -10.60      | 32.47                  | 7.88            | 46.09              | 100                 | 60                   | Average |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                       | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 50.68                   | 56.69             | 74.00          | -23.32      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Peak    |
| 2390.000  | 43.23                   | 49.24             | 54.00          | -10.77      | 32.36                  | 7.74            | 46.11              | 100                 | 90                   | Average |
| 2480.000  | 86.56                   | 93.48             | /              | /           | 31.30                  | 7.87            | 46.09              | 100                 | 90                   | Peak    |
| 2480.000  | 86.03                   | 92.95             | /              | /           | 31.30                  | 7.87            | 46.09              | 100                 | 90                   | Average |
| 2483.500  | 49.72                   | 56.60             | 74.00          | -24.28      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Peak    |
| 2483.500  | 42.30                   | 49.18             | 54.00          | -11.70      | 31.33                  | 7.88            | 46.09              | 100                 | 90                   | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2480MHz: Fundamental frequency.




Worst case harmonic:

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 0 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**


|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|---|-------------|--------|------------|------------|------------|--------|--------|------------|
|   | MHz         | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |            |
| 1 | PP 4808.000 | 45.40  | 47.24      | 74.00      | -28.60     | -1.84  | Peak   | Horizontal |
| 2 | 7206.000    | 44.71  | 42.96      | 74.00      | -29.29     | 1.75   | Peak   | Horizontal |





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

|   | Freq        | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|-------------|--------|------------|------------|------------|--------|--------|-----------|
|   | MHz         | dBuV/m | dBuV       | dBuV/m     | dB         | dB/m   |        |           |
| 1 | PP 4804.000 | 45.47  | 46.69      | 74.00      | -28.53     | -1.22  | Peak   | Vertical  |
| 2 | 7205.000    | 44.16  | 42.50      | 74.00      | -29.84     | 1.66   | Peak   | Vertical  |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet



BUREAU VERITAS

Test Report No.: PSU-NQN2407300316RF02

BT-LE\_S8

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 0 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)   | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 49.29                   | 56.86             | 74.00          | -24.71      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Peak    |
| 2390.000  | 41.94                   | 49.51             | 54.00          | -12.06      | 30.80                  | 7.74            | 46.11              | 100                 | 55                   | Average |
| 2402.000  | 85.54                   | 92.84             | /              | /           | 31.06                  | 7.75            | 46.11              | 100                 | 55                   | Peak    |
| 2402.000  | 84.77                   | 92.07             | /              | /           | 31.06                  | 7.75            | 46.11              | 100                 | 55                   | Average |
| 2483.500  | 52.07                   | 57.81             | 74.00          | -21.93      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Peak    |
| 2483.500  | 43.12                   | 48.86             | 54.00          | -10.88      | 32.47                  | 7.88            | 46.09              | 100                 | 55                   | Average |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                         |                   |                |             |                        |                 |                    |                     |                      |         |
|---|-------------------------|-------------------|----------------|-------------|------------------------|-----------------|--------------------|---------------------|----------------------|---------|
| FREQ. (MHz)                                       | EMISSION LEVEL (dBuV/m) | READ LEVEL (dBuV) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA FACTOR (dB /m) | CABLE LOSS (dB) | PREAMP FACTOR (dB) | ANTENNA HEIGHT (cm) | TABLE ANGLE (Degree) | REMARK  |
| 2390.000  | 50.85                   | 56.86             | 74.00          | -23.15      | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Peak    |
| 2390.000  | 43.31                   | 49.32             | 54.00          | -10.69      | 32.36                  | 7.74            | 46.11              | 100                 | 185                  | Average |
| 2402.000  | 85.55                   | 91.76             | /              | /           | 32.15                  | 7.75            | 46.11              | 100                 | 185                  | Peak    |
| 2402.000  | 84.78                   | 90.99             | /              | /           | 32.15                  | 7.75            | 46.11              | 100                 | 185                  | Average |
| 2483.500  | 50.19                   | 57.07             | 74.00          | -23.81      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Peak    |
| 2483.500  | 42.75                   | 49.63             | 54.00          | -11.25      | 31.33                  | 7.88            | 46.09              | 100                 | 185                  | Average |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Emission level – Limit value.
- 2402MHz: Fundamental frequency.