



FCC Test Report

APPLICANT : Lenovo (Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : TB328XU
FCC ID : O57TB328XU
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Jan. 02, 2022 ~ Jan. 03, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 7

 1.7. Test Software 7

 1.8. Applicable Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 9

 2.3. Support Unit used in test configuration and system 10

 2.4. EUT Operation Test Setup 10

3. TEST RESULT 11

 3.1. Test of AC Conducted Emission Measurement 11

 3.2. Test of Radiated Emission Measurement 15

4. LIST OF MEASURING EQUIPMENT 20

5. UNCERTAINTY OF EVALUATION 21

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 8.26 dB at 0.151 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.54 dB at 712.880 MHz for Quasi-Peak

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. General Description

1.1. Applicant

Lenovo (Shanghai) Electronics Technology Co., Ltd.
Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2. Manufacturer

Lenovo PC HK Limited
23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	TB328XU
FCC ID	O57TB328XU
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE, GNSS
IMEI Code	Conduction: 860646060006227 for Sample 1 860646060006698 for Sample 2 860646060004263 for Sample 3 860646060004263 for Sample 4 Radiation: 860646060006383 for Sample 1 860646060004511 for Sample 2 860646060004396 for Sample 3 860646060007001 for Sample 4
HW Version	Lenovo Tablet TB328XU
SW Version	TB328XU_RF01_220118
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850MHz ~ 1910MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7 : 2500 MHz ~ 2570 MHz LTE Band 38 : 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz 802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Rx Frequency	GSM850: 869 MHz ~ 894 MHz GSM1900: 1930 MHz ~ 1990 MHz WCDMA Band II: 1930 MHz ~ 1990 MHz WCDMA Band V: 869 MHz ~ 894 MHz LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 7 : 2620 MHz ~ 2690 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz 802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz GNSS : 1559 MHz ~ 1610 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna
Type of Modulation	GSM/GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK



	Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : π/4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK
--	--

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH04-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Middle)+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+Camera(Rear) for Sample 1
	Mode 2: WCDMA 1900 Rx+USB Cable 2(Charging from Adapter2)+Earphone+Bluetooth Idle+WLAN Idle(5G)+Camera(Front) for Sample 1
	Mode 3: GSM 850 Rx(Low)+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+MP4 for Sample 1
	Mode 4: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 1
	Mode 5: LTE Band 7 Rx+ USB Cable 2(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(2.4G)+ GNSS Rx for Sample 1
	Mode 6: GSM 850 Rx(Middle)+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+Camera(Rear) for Sample 2
	Mode 7: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 2
	Mode 8: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 3
	Mode 9: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 4
Radiated Emissions	Mode 1: GSM 850 Rx(Middle)+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+Camera(Rear) for Sample 1
	Mode 2: WCDMA 1900 Rx+USB Cable 2(Charging from Adapter2)+Earphone+Bluetooth Idle+WLAN Idle(5G)+Camera(Front) for Sample 1
	Mode 3: GSM 850 Rx(Low)+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+MP4 for Sample 1
	Mode 4: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 1
	Mode 5: LTE Band 7 Rx+ USB Cable 2(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(2.4G)+ GNSS Rx for Sample 1
	Mode 6: WCDMA 1900 Rx+USB Cable 1(Charging from Adapter1)+Earphone+Bluetooth Idle+WLAN Idle(2.4G)+Camera(Rear) for Sample 2
	Mode 7: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 2
	Mode 8: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth

	<p>Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 3</p> <p>Mode 9: LTE Band 5 Rx(High)+ USB Cable 1(Data Link with Notebook)+ Earphone+ Bluetooth</p> <p>Idle+ WLAN Idle(5G)+ GNSS Rx for Sample 4</p>
<p>Remark:</p> <ol style="list-style-type: none"> 1. The worst case of AC is mode 4; only the test data of this mode is reported. 2. The worst case of RE is mode 4; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 4. After pre-scanned the L/M/H channel for all frequency band which operate within the frequency range of 30MHz ~ 960MHz (GSM850/WCDMA Band V/LTE Band 5); only the worst channel for them between 30MHz ~ 960MHz test data of this mode was reported. 	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	LTE Base Station	Anritus	MT8820C	N/A	N/A	Unshielded,1.8m
3.	Base Station	Anritus	MT8000A	N/A	N/A	Unshielded,1.8m
4.	Signal Generator	R&S	SMBV100A	N/A	N/A	Unshielded,1.8m
5.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
6.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
7.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
8.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
9.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
10.	Notebook	Lenovo	S730-13IWL	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
11.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
12.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
13.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
14.	SD Card	Kingston	8GB	N/A	N/A	N/A
15.	Earphone	N/A	N/A	N/A	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator’s paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-060105-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.150	56.09	-9.91	66.00	45.50	0.11	10.48	QP
2	0.150	42.79	-13.21	56.00	32.20	0.11	10.48	Average
3	0.161	54.76	-10.67	65.43	44.20	0.11	10.45	QP
4	0.161	34.86	-20.57	55.43	24.30	0.11	10.45	Average
5	0.189	50.69	-13.37	64.06	40.21	0.10	10.38	QP
6	0.189	31.79	-22.27	54.06	21.31	0.10	10.38	Average
7	0.206	46.66	-16.70	63.36	36.20	0.10	10.36	QP
8	0.206	30.49	-22.87	53.36	20.03	0.10	10.36	Average
9	2.167	34.27	-21.73	56.00	23.90	0.14	10.23	QP
10	2.167	28.57	-17.43	46.00	18.20	0.14	10.23	Average
11	2.500	35.48	-20.52	56.00	25.09	0.15	10.24	QP
12	2.500	29.68	-16.32	46.00	19.29	0.15	10.24	Average
13	2.854	34.89	-21.11	56.00	24.50	0.15	10.24	QP
14	2.854	28.59	-17.41	46.00	18.20	0.15	10.24	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC CLASS-B LISN-060105-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.151	57.70	-8.26	65.96	47.20	0.02	10.48	QP
2	0.151	43.40	-12.56	55.96	32.90	0.02	10.48	Average
3	0.184	49.63	-14.65	64.28	39.20	0.03	10.40	QP
4	0.184	32.93	-21.35	54.28	22.50	0.03	10.40	Average
5	0.209	47.20	-16.03	63.23	36.80	0.04	10.36	QP
6	0.209	32.30	-20.93	53.23	21.90	0.04	10.36	Average
7	0.329	37.57	-21.92	59.49	27.20	0.08	10.29	QP
8	0.329	26.57	-22.92	49.49	16.20	0.08	10.29	Average
9	0.502	32.94	-23.06	56.00	22.60	0.10	10.24	QP
10	0.502	25.64	-20.36	46.00	15.30	0.10	10.24	Average
11	2.765	32.99	-23.01	56.00	22.60	0.15	10.24	QP
12	2.765	27.29	-18.71	46.00	16.90	0.15	10.24	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Yoke SI	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03ch04-KS
 Condition : FCC CLASS-B 3m CBL6112D SN49922NEW HORIZONTAL

Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	167.74	38.10	-5.40	43.50	53.50	15.68	1.88	32.96	---	---	Peak
2	263.77	36.12	-9.88	46.00	46.83	19.68	2.38	32.77	---	---	Peak
3	487.84	38.57	-7.43	46.00	44.09	23.65	3.25	32.42	---	---	Peak
4	584.84	41.18	-4.82	46.00	44.87	25.58	3.56	32.83	---	---	Peak
5	712.88	42.46	-3.54	46.00	44.32	26.75	3.92	32.53	100	0	QP
6	889.42	39.42			38.14	29.14	4.36	32.22	---	---	Peak
7	974.78	39.38	-14.62	54.00	36.45	30.41	4.57	32.05	---	---	Peak
8	3992.00	42.16	-31.84	74.00	65.00	32.52	9.28	64.64	---	---	Peak
9	7477.00	43.11	-30.89	74.00	59.23	35.42	12.88	64.42	---	---	Peak
10	10027.00	44.53	-29.47	74.00	55.53	36.84	15.37	63.21	---	---	Peak
11	12288.00	45.63	-28.37	74.00	52.78	38.57	16.72	62.44	---	---	Peak
12	14515.00	46.02	-27.98	74.00	53.32	39.14	18.24	64.68	---	---	Peak
13	16725.00	46.86	-27.14	74.00	51.78	41.17	19.61	65.70	---	---	Peak



Test Engineer :	Yoke SI	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03ch04-KS
 Condition : FCC CLASS-B 3m CBL6112D SN49922NEW VERTICAL

Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	96.93	32.31	-11.19	43.50	48.28	15.55	1.46	32.98	---	Peak
2	167.74	33.90	-9.60	43.50	49.30	15.68	1.88	32.96	---	Peak
3	506.27	37.34	-8.66	46.00	42.36	24.22	3.31	32.55	---	Peak
4	584.84	38.29	-7.71	46.00	41.98	25.58	3.56	32.83	---	Peak
5	711.91	38.26	-7.74	46.00	40.13	26.73	3.92	32.52	---	Peak
6	889.42	38.90			37.62	29.14	4.36	32.22	---	Peak
7	974.78	38.64	-15.36	54.00	35.71	30.41	4.57	32.05	---	Peak
8	3125.00	41.19	-32.81	74.00	65.63	31.59	8.26	64.29	---	Peak
9	6763.00	43.78	-30.22	74.00	60.30	35.33	12.16	64.01	---	Peak
10	8888.00	42.69	-31.31	74.00	56.42	35.76	14.11	63.60	---	Peak
11	11523.00	45.63	-28.37	74.00	53.91	37.79	16.23	62.30	---	Peak
12	13988.00	46.16	-27.84	74.00	53.43	38.63	18.00	63.90	---	Peak
13	16725.00	46.86	-27.14	74.00	51.78	41.17	19.61	65.70	---	Peak

Note:

- Level(dBuV/m) = Read Level(dBuV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBuV/m) – Limit Line(dBuV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 21, 2021	Jan. 02, 2022	Apr. 20, 2022	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 17, 2021	Jan. 02, 2022	Oct. 16, 2022	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Oct. 17, 2021	Jan. 02, 2022	Oct. 16, 2022	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 17, 2021	Jan. 02, 2022	Oct. 16, 2022	Conduction (CO01-KS)
EMI Test Receiver	Keysight	N9038A	MY57290151	3Hz~8.5GHz;M ax 30dBm	Jul. 17, 2021	Jan. 03, 2022	Jul. 16, 2022	Radiation (03CH04-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 13, 2021	Jan. 03, 2022	Apr. 12, 2022	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 30, 2021	Jan. 03, 2022	May 29, 2022	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 18, 2021	Jan. 03, 2022	Apr. 17, 2022	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 9, 2021	Jan. 03, 2022	Nov. 08, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 07, 2021	Jan. 03, 2022	Jan. 06, 2022	Radiation (03CH04-KS)
Amplifier	Burgeon	BPA-530	102219	0.01MHz ~3000MHz	Oct. 30, 2021	Jan. 03, 2022	Oct. 29, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5G Hz	Oct. 13, 2021	Jan. 03, 2022	Oct. 12, 2022	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 03, 2022	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 03, 2022	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 03, 2022	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------