

Date: 2025-03-10

**01\_WCDMA V\_RMC 12.2Kbps\_Bottom Face\_0mm\_Ch4182**

Communication System: UMTS-FDD (DC-HSDPA); Frequency: 836.400 MHz; Duty Cycle: 1:1  
Medium: Head Simulating Liquid Medium parameters used:  $f = 836.400$  MHz;  $\sigma = 0.949$  S/m;  $\epsilon_r = 42.0$


Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(9.47, 9.3, 9.4); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: WCDMA, 10457-AAB

**Area Scan (80.0 mm x 300.0 mm):** Measurement Grid: 15.0 mm x 15.0 mm  
SAR (1g) = 0.460 W/kg; SAR (10g) = 0.266 W/kg;

**Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm):** Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm  
Power Drift = 0.08 dB  
SAR (1g) = 0.486 W/kg; SAR (10g) = 0.235 W/kg  
Smallest distance from peaks to all points 3 dB below = 6.8 mm  
Ratio of SAR at M2 to SAR at M1 = 70.9 %



Date: 2025-03-10

**02\_LTE Band 5\_10M\_QPSK\_1RB\_0Offset\_Bottom Face\_0mm\_Ch20525**


Communication System: LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK) RBPosition:Mid  
AntennaCfg:SISO; Frequency: 836.500 MHz; Duty Cycle: 1:1  
Medium: Head Simulating Liquid Medium parameters used:  $f = 836.500$  MHz;  $\sigma = 0.956$  S/m;  $\epsilon_r = 42.0$   
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(9.47, 9.3, 9.4); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: LTE-FDD, 10175-CAH

**Area Scan (100.0 mm x 300.0 mm):** Measurement Grid: 15.0 mm x 15.0 mm  
SAR (1g) = 0.199 W/kg; SAR (10g) = 0.127 W/kg;

**Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm):** Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm  
Power Drift = 0.01 dB  
SAR (1g) = 0.280 W/kg; SAR (10g) = 0.136 W/kg  
Smallest distance from peaks to all points 3 dB below = 6.6 mm  
Ratio of SAR at M2 to SAR at M1 = 73.1 %



Date: 2025-03-10

**03\_LTE Band 26\_15M\_QPSK\_1RB\_0Offset\_Bottom Face\_0mm\_Ch26865**


Communication System: LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK) RBPosition:Mid  
AntennaCfg:SISO; Frequency: 831.500 MHz; Duty Cycle: 1:1  
Medium: Head Simulating Liquid Medium parameters used:  $f= 831.500$  MHz;  $\sigma= 0.953$  S/m;  $\epsilon_r = 42.0$   
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(9.47, 9.3, 9.4); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: LTE-FDD, 10181-CAF

**Area Scan (100.0 mm x 300.0 mm):** Measurement Grid: 15.0 mm x 15.0 mm  
SAR (1g) = 0.333 W/kg; SAR (10g) = 0.194 W/kg;

**Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm):** Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm  
Power Drift = 0.02 dB  
SAR (1g) = 0.434 W/kg; SAR (10g) = 0.211 W/kg  
Smallest distance from peaks to all points 3 dB below = 6.0 mm  
Ratio of SAR at M2 to SAR at M1 = 71.6 %



Date: 2025-03-10

**04\_LTE Band 41\_20M\_QPSK\_1RB\_0Offset\_Bottom Face\_0mm\_Ch40620**


Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK) RBPosition:Mid  
AntennaCfg:SISO; Frequency: 2593.000 MHz; Duty Cycle: 1:1.59  
Medium: Head Simulating Liquid Medium parameters used:  $f= 2593.000$  MHz;  $\sigma= 2.01$  S/m;  $\epsilon_r = 40.7$   
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(7.96, 7.81, 7.89); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: LTE-TDD, 10172-CAH

**Area Scan (80.0 mm x 300.0 mm):** Measurement Grid: 12.0 mm x 10.0 mm  
SAR (1g) = 0.697 W/kg; SAR (10g) = 0.260 W/kg;

**Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm):** Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm  
Power Drift = 0.06 dB  
SAR (1g) = 0.828 W/kg; SAR (10g) = 0.260 W/kg  
Smallest distance from peaks to all points 3 dB below = 5.0 mm  
Ratio of SAR at M2 to SAR at M1 = 34.2 %



Date: 2025-03-11

**05\_LTE Band 42\_20M\_QPSK\_1RB\_0Offset\_Edge 3\_0mm\_Ch42590**


Communication System: LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK) RBPosition:Mid  
AntennaCfg:SISO; Frequency: 3500.000 MHz; Duty Cycle: 1:1.59  
Medium: Head Simulating Liquid Medium parameters used:  $f=3500.000$  MHz;  $\sigma=2.83$  S/m;  $\epsilon_r=39.1$   
Ambient Temperature: 23.3°C; Liquid Temperature: 22.8°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(7.13, 7.0, 7.07); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: LTE-TDD, 10172-CAH

**Area Scan (48.0 mm x 300.0 mm):** Measurement Grid: 8.0 mm x 10.0 mm  
SAR (1g) = 0.167 W/kg; SAR (10g) = 0.063 W/kg;

**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm  
Power Drift = 0.03 dB  
SAR (1g) = 0.185 W/kg; SAR (10g) = 0.064 W/kg  
Smallest distance from peaks to all points 3 dB below = 5.9 mm  
Ratio of SAR at M2 to SAR at M1 = 70.8 %



Date: 2025-03-11

**06\_FR1 n77 Part 27O HPUE\_100M\_QPSK\_135RB\_69Offset\_Bottom Face\_0mm\_Ch656000**


Communication System: 5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)  
RBPosition:Mid AntennaCfg:SISO; Frequency: 3840.000 MHz; Duty Cycle: 1:2  
Medium: Head Simulating Liquid Medium parameters used:  $f= 3840.000$  MHz;  $\sigma= 3.24$  S/m;  $\epsilon_r = 38.4$   
Ambient Temperature: 23.3°C; Liquid Temperature: 22.8°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(6.97, 6.83, 6.91); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: 5G NR FR1 TDD, 10917-AAD

**Area Scan (80.0 mm x 300.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm  
SAR (1g) = 0.656 W/kg; SAR (10g) = 0.219 W/kg;

**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm  
Power Drift = 0.01 dB  
SAR (1g) = 0.781 W/kg; SAR (10g) = 0.230 W/kg  
Smallest distance from peaks to all points 3 dB below = 5.4 mm  
Ratio of SAR at M2 to SAR at M1 = 67.5 %



Date: 2025-03-12

**07\_WLAN2.4GHz\_802.11b 1Mbps\_Bottom Face\_0mm\_Ch1**


Communication System: IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps); Frequency: 2412.000 MHz; Duty Cycle: 1:1  
Medium: Head Simulating Liquid Medium parameters used:  $f = 2412.000$  MHz;  $\sigma = 1.82$  S/m;  $\epsilon_r = 39.2$   
Ambient Temperature: 23.2°C; Liquid Temperature: 22.9°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(7.87, 7.72, 7.8); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: WLAN, 10012-CAB

**Area Scan (216.0 mm x 300.0 mm):** Measurement Grid: 12.0 mm x 10.0 mm  
SAR (1g) = 0.434 W/kg; SAR (10g) = 0.176 W/kg;

**Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm):** Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm  
Power Drift = 0.02 dB  
SAR (1g) = 0.463 W/kg; SAR (10g) = 0.169 W/kg  
Smallest distance from peaks to all points 3 dB below = 5.2 mm  
Ratio of SAR at M2 to SAR at M1 = 70.9 %



Date: 2025-03-12

**08\_Bluetooth\_1Mbps\_Bottom Face\_0mm\_Ch78**


Communication System: IEEE 802.15.1 Bluetooth (GFSK, DH5); Frequency: 2480.000 MHz;  
Duty Cycle: 1:1.302  
Medium: Head Simulating Liquid Medium parameters used:  $f = 2480.000$  MHz;  $\sigma = 1.84$  S/m;  $\epsilon_r = 39.1$   
Ambient Temperature: 23.2°C; Liquid Temperature: 22.9°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(7.87, 7.72, 7.8); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: Bluetooth, 10032-CAA

**Area Scan (100.0 mm x 300.0 mm):** Measurement Grid: 12.0 mm x 10.0 mm  
SAR (1g) = 0.302 W/kg; SAR (10g) = 0.128 W/kg;

**Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm):** Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm  
Power Drift = -0.06 dB  
SAR (1g) = 0.347 W/kg; SAR (10g) = 0.127 W/kg  
Smallest distance from peaks to all points 3 dB below = 6.0 mm  
Ratio of SAR at M2 to SAR at M1 = 70.6 %



Date: 2025-03-12

**09\_WLAN5GHz\_802.11n-HT40 MCS0\_Bottom Face\_19mm\_Ch54**


Communication System: IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle);  
Frequency: 5270.000 MHz; Duty Cycle: 1:1.058  
Medium: Head Simulating Liquid Medium parameters used:  $f = 5270.000$  MHz;  $\sigma = 4.64$  S/m;  $\epsilon_r = 36.6$   
Ambient Temperature: 23.1°C; Liquid Temperature: 22.7°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(5.98, 5.87, 5.93); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: WLAN, 10599-AAD

**Area Scan (70.0 mm x 280.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm  
SAR (1g) = 0.619 W/kg; SAR (10g) = 0.256 W/kg;

**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm  
Power Drift = 0.01 dB  
SAR (1g) = 0.632 W/kg; SAR (10g) = 0.269 W/kg  
Smallest distance from peaks to all points 3 dB below = 13.6 mm  
Ratio of SAR at M2 to SAR at M1 = 64.2 %



Date: 2025-03-12

**10\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Face\_19mm\_Ch138**


Communication System: IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle); Frequency: 5690.000 MHz; Duty Cycle: 1:1.112  
Medium: Head Simulating Liquid Medium parameters used:  $f= 5690.000$  MHz;  $\sigma= 5.10$  S/m;  $\epsilon_r = 35.8$   
Ambient Temperature: 23.4°C; Liquid Temperature: 22.7°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(5.44, 5.34, 5.4); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: WLAN, 10626-AAD

**Area Scan (70.0 mm x 280.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm  
SAR (1g) = 0.620 W/kg; SAR (10g) = 0.255 W/kg;

**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm  
Power Drift = 0.01 dB  
SAR (1g) = 0.559 W/kg; SAR (10g) = 0.258 W/kg  
Smallest distance from peaks to all points 3 dB below = 14.2 mm  
Ratio of SAR at M2 to SAR at M1 = 62.4 %



Date: 2025-03-12

**11\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Face\_19mm\_Ch155**

Communication System: IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle); Frequency: 5775.000 MHz; Duty Cycle: 1:1.112  
Medium: Head Simulating Liquid Medium parameters used:  $f= 5775.000$  MHz;  $\sigma= 5.23$  S/m;  $\epsilon_r = 35.6$   
Ambient Temperature: 23.4°C; Liquid Temperature: 22.7°C

**DASY8 Configuration:**

- Probe: EX3DV4 - SN7764; ConvF(5.44, 5.34, 5.4); Calibrated: 2024-09-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1691; Calibrated: 2024-04-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2151
- Measurement Software: 16.4.0.5005
- UID: WLAN, 10626-AAD

**Area Scan (70.0 mm x 280.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm  
SAR (1g) = 0.517 W/kg; SAR (10g) = 0.212 W/kg;

**Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm):** Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm  
Power Drift = 0.07 dB  
SAR (1g) = 0.560 W/kg; SAR (10g) = 0.231 W/kg  
Smallest distance from peaks to all points 3 dB below = 14.9 mm  
Ratio of SAR at M2 to SAR at M1 = 59.9 %

