



# FCC RF Test Report

**APPLICANT** : Lenovo (Shanghai) Electronics  
Technology Co., Ltd.  
**EQUIPMENT** : Portable Tablet Computer  
**BRAND NAME** : Lenovo  
**MODEL NAME** : TB352FU  
**FCC ID** : O57TB352FU  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System  
**TEST DATE(S)** : Nov. 30, 2024 ~ Dec. 10, 2024

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (ShenZhen)**

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 5

    1.5 Modification of EUT ..... 6

    1.6 Testing Location ..... 6

    1.7 Test Software ..... 6

    1.8 Applicable Standards..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 8**

    2.1 Carrier Frequency Channel ..... 8

    2.2 Test Mode ..... 9

    2.3 Connection Diagram of Test System ..... 10

    2.4 Support Unit used in test configuration and system ..... 11

    2.5 EUT Operation Test Setup ..... 11

    2.6 Measurement Results Explanation Example..... 11

**3 TEST RESULT ..... 12**

    3.1 6dB and 99% Bandwidth Measurement ..... 12

    3.2 Output Power Measurement..... 19

    3.3 Power Spectral Density Measurement ..... 20

    3.4 Conducted Band Edges and Spurious Emission Measurement ..... 27

    3.5 Radiated Band Edges and Spurious Emission Measurement ..... 36

    3.6 AC Conducted Emission Measurement..... 40

    3.7 Antenna Requirements ..... 42

**4 LIST OF MEASURING EQUIPMENT ..... 43**

**5 MEASUREMENT UNCERTAINTY ..... 44**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR411806-08B	Rev. 01	Initial issue of report	Dec. 16, 2024



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.28 dB at 30.97 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.19 dB at 13.62 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

<b>Conformity Assessment Condition:</b>
1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"
<b>Disclaimer:</b>
The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

**Lenovo (Shanghai) Electronics Technology Co., Ltd.**

Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

## 1.2 Manufacturer

**Lenovo PC HK Limited**

23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	TB352FU
FCC ID	O57TB352FU
SN Code	Conducted: HA234E3D for sample 1 Conduction/ Radiation: HA2343EV for sample 1
HW Version	TB352FU
SW Version	TB352FU_RF01_241110
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are four types of EUT, the differences could be referred to the TB352FU\_Operational Description of Product Equality Declaration which is exhibit separately. After evaluation, we chose sample 1 to full test, sample 2 is verified the worst case of sample 1 for CE/RSE among the Part 15C reports.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 125Kbps: 9.87 dBm (0.0097 W) BLE 500Kbps: 9.63 dBm (0.0092 W) BLE 1Mbps: 9.52 dBm (0.0090 W) BLE 2Mbps: 9.87 dBm (0.0097 W)
99% Occupied Bandwidth	BLE 125Kbps: 1.065MHz BLE 2Mbps: 2.085MHz
Antenna Type / Gain	FPC Antenna with gain -3 dBi
Type of Modulation	Bluetooth LE : GFSK

**Note:** For BLE 125kbps & 500kbps & 1Mbps & 2Mbps mode, the whole testing has assessed BLE



125kbps / 2Mbps mode by referring to the higher conducted power.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International Inc. (Shenzhen)		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CN1256	421272

<b>Test Firm</b>	Sporton International Inc. (Shenzhen)		
<b>Test Site Location</b>	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO02-SZ ; 03CH01-SZ	CN1256	421272

### 1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO02-SZ	AUDIX	E3	6.120613b



## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	



## 2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 125Kbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 125Kbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 125Kbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 125Kbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 4: Bluetooth Tx CH00_2404 MHz_BLE 2Mbps
	Mode 5: Bluetooth Tx CH39_2478 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: Bluetooth Link+ WLAN (2.4G) Link+ USB Cable 1(Charging from Adapter 1)+ Battery1
<b>Remark:</b> For Radiated Test Cases, The tests were performed with Adapter 1 and USB Cable 1.	

## 2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,2.7m with Core
2.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A

## 2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the Bluetooth Earphone under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 1.3 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 1.3 + 10 = 11.3 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

##### 3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


#### BLE 125kbps

#### 6 dB Bandwidth Plot on Channel 00



Date: 6 DEC.2024 23:44:54


#### 6 dB Bandwidth Plot on Channel 19



Date: 6 DEC.2024 23:51:24




### 6 dB Bandwidth Plot on Channel 39



Date: 6 DEC.2024 23:54:21

### BLE 2Mbps


### 6 dB Bandwidth Plot on Channel 00



Date: 6 DEC.2024 23:58:44




6 dB Bandwidth Plot on Channel 19



Date: 7.DEC.2024 00:01:22

6 dB Bandwidth Plot on Channel 39



Date: 7.DEC.2024 00:04:09




### 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


#### BLE 125kbps

#### 99% Occupied Bandwidth Plot on Channel 00



Date: 7.DEC.2024 00:21:32


#### 99% Occupied Bandwidth Plot on Channel 19



Date: 7.DEC.2024 00:20:33




99% Occupied Bandwidth Plot on Channel 39



Date: 7.DEC.2024 00:19:38

BLE 2Mbps


99% Occupied Bandwidth Plot on Channel 00



Date: 7.DEC.2024 00:15:30




99% Occupied Bandwidth Plot on Channel 19



Date: 7.DEC.2024 00:16:26

99% Occupied Bandwidth Plot on Channel 39



Date: 7.DEC.2024 00:17:10

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


BLE 125kbps

PSD 100kHz Plot on Channel 00



Date: 6 DEC. 2024 23:45:38


PSD 100kHz Plot on Channel 19



Date: 6 DEC. 2024 23:52:05




PSD 100kHz Plot on Channel 39



Date: 6 DEC.2024 23:55:02

BLE 2Mbps


PSD 100kHz Plot on Channel 00



Date: 6 DEC.2024 23:59:13




PSD 100kHz Plot on Channel 19



Date: 7.DEC.2024 00:02:02

PSD 100kHz Plot on Channel 39




Date: 7.DEC.2024 00:04:42



### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)


BLE 125kbps

PSD 3kHz Plot on Channel 00



Date: 6 DEC. 2024 23:45:16


PSD 3kHz Plot on Channel 19



Date: 6 DEC. 2024 23:51:41




### PSD 3kHz Plot on Channel 39



Date: 6 DEC.2024 23:54:40

### BLE 2Mbps


### PSD 3kHz Plot on Channel 00



Date: 6 DEC.2024 23:58:54




PSD 3kHz Plot on Channel 19



Date: 7.DEC.2024 00:01:39

PSD 3kHz Plot on Channel 39



Date: 7.DEC.2024 00:04:21

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

### 3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots


#### BLE 1Mbps

#### Low Band Edge Plot on Channel 00



Date: 6 DEC.2024 23:46:35

#### High Band Edge Plot on Channel 39




Date: 6 DEC.2024 23:55:58




BLE 2Mbps

Low Band Edge Plot on Channel 00




High Band Edge Plot on Channel 39






### 3.4.6 Test Result of Conducted Spurious Emission Plots

#### Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 00



Date: 6 DEC.2024 23:46:00


#### Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 00



Date: 6 DEC.2024 23:46:18




### Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 19



Date: 6 DEC.2024 23:52:25


### Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 19



Date: 6 DEC.2024 23:52:42




Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 39



Date: 6 DEC.2024 23:55:25


Conducted Spurious Emission Plot on Bluetooth LE 125kbps GFSK Channel 39



Date: 6 DEC.2024 23:55:41




### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 7.DEC.2024 00:11:48


### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 00



Date: 7.DEC.2024 00:12:05




Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 7.DEC.2024 00:02:20


Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 19



Date: 7.DEC.2024 00:02:39




### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 7.DEC.2024 00:07:25

### Conducted Spurious Emission Plot on Bluetooth LE 2Mbps GFSK Channel 39



Date: 7.DEC.2024 00:09:54



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




### 3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.5.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C.

### **3.5.7 Duty Cycle**

Please refer to Appendix D.

### **3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)**

Please refer to Appendix C.



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Dec. 06, 2024~ Dec. 07, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 29, 2023	Dec. 06, 2024~ Dec. 07, 2024	Dec. 28, 2024	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA24440A	11707	50MHz~40GHz	Dec. 27, 2023	Dec. 06, 2024~ Dec. 07, 2024	Dec. 26, 2024	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY522601 85	20Hz~26.5GHz	Dec. 27, 2023	Nov. 30, 2024~ Dec. 10, 2024	Dec. 26, 2024	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 13	10Hz~44GHz	Jul. 03, 2024	Nov. 30, 2024~ Dec. 10, 2024	Jul. 02, 2025	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 29, 2023	Nov. 30, 2024~ Dec. 10, 2024	Dec. 28, 2024	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Nov. 30, 2024~ Dec. 10, 2024	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Nov. 30, 2024~ Dec. 10, 2024	Jul. 03, 2025	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 09, 2024	Nov. 30, 2024~ Dec. 10, 2024	Apr. 08, 2025	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 09, 2024	Nov. 30, 2024~ Dec. 10, 2024	Apr. 08, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Nov. 30, 2024~ Dec. 10, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY532701 05	0.5GHz~26.5GHz	Oct. 14, 2024	Nov. 30, 2024~ Dec. 10, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2024	Nov. 30, 2024~ Dec. 10, 2024	Jul. 02, 2025	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001 985	N/A	Oct. 14, 2024	Nov. 30, 2024~ Dec. 10, 2024	Oct. 13, 2025	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 30, 2024~ Dec. 10, 2024	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 30, 2024~ Dec. 10, 2024	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 03, 2024	Dec. 08, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2024	Dec. 08, 2024	Jul. 02, 2025	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002 470	100Vac~250Vac	Dec. 25, 2022	Dec. 08, 2024	Dec. 24, 2024	Conduction (CO02-SZ)

NCR: No Calibration Required



## 5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

### Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.3dB
---	-------

----- THE END -----



## **Appendix A. Conducted Test Results**

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Sam Zheng	Temperature:	21~25	°C
Test Date:	2024/12/6~2024/12/7	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	125kbps	1	0	2402	1.065	0.696	0.50	Pass
BLE	125kbps	1	19	2440	1.064	0.706	0.50	Pass
BLE	125kbps	1	39	2480	1.062	0.704	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	-	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	125kbps	1	0	2402	9.23	-	30.00	-3.00	6.23	36.00	Pass
BLE	125kbps	1	19	2440	9.87	-	30.00	-3.00	6.87	36.00	Pass
BLE	125kbps	1	39	2480	8.56	-	30.00	-3.00	5.56	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	-	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	125kbps	1	0	2402	0.83	8.60	-	30.00	-3.00	5.60	36.00	Pass
BLE	125kbps	1	19	2440	0.83	9.00	-	30.00	-3.00	6.00	36.00	Pass
BLE	125kbps	1	39	2480	0.83	8.00	-	30.00	-3.00	5.00	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	125kbps	1	0	2402	5.38	2.75	-3.00	8.00	Pass
BLE	125kbps	1	19	2440	5.92	3.32	-3.00	8.00	Pass
BLE	125kbps	1	39	2480	4.69	1.97	-3.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

**TEST RESULTS DATA****Peak Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	500kbps	1	0	2402	9.18	30.00	-3.00	6.18	36.00	Pass
BLE	500kbps	1	19	2440	9.63	30.00	-3.00	6.63	36.00	Pass
BLE	500kbps	1	39	2480	8.36	30.00	-3.00	5.36	36.00	Pass

**TEST RESULTS DATA****Average Power Table**

Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	500kbps	1	0	2402	2.44	8.50	30.00	-3.00	5.50	36.00	Pass
BLE	500kbps	1	19	2440	2.44	8.90	30.00	-3.00	5.90	36.00	Pass
BLE	500kbps	1	39	2480	2.44	7.90	30.00	-3.00	4.90	36.00	Pass

**TEST RESULTS DATA****Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	9.14	30.00	-3.00	6.14	36.00	Pass
BLE	1Mbps	1	19	2440	9.52	30.00	-3.00	6.52	36.00	Pass
BLE	1Mbps	1	39	2480	8.22	30.00	-3.00	5.22	36.00	Pass

**TEST RESULTS DATA****Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	2.20	8.50	30.00	-3.00	5.50	36.00	Pass
BLE	1Mbps	1	19	2440	2.20	8.90	30.00	-3.00	5.90	36.00	Pass
BLE	1Mbps	1	39	2480	2.20	7.90	30.00	-3.00	4.90	36.00	Pass

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.085	1.344	0.50	Pass
BLE	2Mbps	1	19	2440	2.085	1.344	0.50	Pass
BLE	2Mbps	1	39	2480	2.085	1.336	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	9.17	30.00	-3.00	6.17	36.00	Pass
BLE	2Mbps	1	19	2440	9.87	30.00	-3.00	6.87	36.00	Pass
BLE	2Mbps	1	39	2480	8.59	30.00	-3.00	5.59	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	5.14	8.20	30.00	-3.00	5.20	36.00	Pass
BLE	2Mbps	1	19	2440	5.14	8.80	30.00	-3.00	5.80	36.00	Pass
BLE	2Mbps	1	39	2480	5.14	7.70	30.00	-3.00	4.70	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	7.14	-9.68	-3.00	8.00	Pass
BLE	2Mbps	1	19	2440	7.85	-8.91	-3.00	8.00	Pass
BLE	2Mbps	1	39	2480	6.58	-10.25	-3.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



## Appendix B. AC Conducted Emission Test Results

Test Engineer :	TaoZhang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO02-SZ  
 Condition : FCC 15C\_QP LISN\_2024-L-1 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.17	29.29	-25.65	54.94	9.61	9.67	10.01	Average
2	0.17	38.49	-26.45	64.94	18.81	9.67	10.01	QP
3	0.25	28.34	-23.35	51.69	8.60	9.70	10.04	Average
4	0.25	41.14	-20.55	61.69	21.40	9.70	10.04	QP
5	0.90	25.56	-20.44	46.00	5.70	9.67	10.19	Average
6	0.90	39.66	-16.34	56.00	19.80	9.67	10.19	QP
7	4.20	29.60	-16.40	46.00	9.70	9.63	10.27	Average
8	4.20	41.80	-14.20	56.00	21.90	9.63	10.27	QP
9	8.06	36.04	-13.96	50.00	16.01	9.61	10.42	Average
10	8.06	46.04	-13.96	60.00	26.01	9.61	10.42	QP
11	13.62	39.81	-10.19	50.00	19.50	9.55	10.76	Average
12 *	13.62	49.31	-10.69	60.00	29.00	9.55	10.76	QP



Test Engineer :	TaoZhang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO02-SZ  
 Condition : FCC 15C\_QP LISN\_2024-N-1 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.19	30.82	-23.16	53.98	11.10	9.70	10.02	Average
2	0.19	44.42	-19.56	63.98	24.70	9.70	10.02	QP
3	0.30	25.72	-24.43	50.15	6.00	9.67	10.05	Average
4	0.30	40.12	-20.03	60.15	20.40	9.67	10.05	QP
5	2.53	24.90	-21.10	46.00	4.90	9.68	10.32	Average
6	2.53	38.60	-17.40	56.00	18.60	9.68	10.32	QP
7	3.86	29.85	-16.15	46.00	9.90	9.67	10.28	Average
8	3.86	41.25	-14.75	56.00	21.30	9.67	10.28	QP
9	7.69	34.13	-15.87	50.00	14.10	9.63	10.40	Average
10	7.69	44.03	-15.97	60.00	24.00	9.63	10.40	QP
11	16.66	38.70	-11.30	50.00	18.30	9.60	10.80	Average
12 *	16.66	48.90	-11.10	60.00	28.50	9.60	10.80	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



## Appendix C. Radiated Spurious Emission

Test Engineer :	HuaCong Liang	Relative Humidity :	50%
		Temperature :	20-24°C





### Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 5	2400-2483.5	Bluetooth-LE	00	2402	125Kbps	-	-
Mode 6	2400-2483.5	Bluetooth-LE	19	2440	125Kbps	-	-
Mode 7	2400-2483.5	Bluetooth-LE	39	2480	125Kbps	-	-
Mode 8	2400-2483.5	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 9	2400-2483.5	Bluetooth-LE	39	2480	2Mbps	-	-
Mode 10	2400-2483.5	Bluetooth-LE	39	2480	125Kbps	-	LF

### Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
5	Bluetooth-LE	00	2357.84	38.14	54.00	-15.86	V	AVERAGE	Pass	Band Edge
5	Bluetooth-LE	00	4804.00	40.80	74.00	-33.20	V	Peak	Pass	Harmonic
6	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
6	Bluetooth-LE	19	7320.00	44.86	74.00	-29.14	H	Peak	Pass	Harmonic
7	Bluetooth-LE	39	2485.54	38.67	54.00	-15.33	H	AVERAGE	Pass	Band Edge
7	Bluetooth-LE	39	7440	44.01	74	-29.99	H	Peak	Pass	Harmonic
8	Bluetooth-LE	00	2368.97	38.16	54.00	-15.84	V	AVERAGE	Pass	Band Edge
8	Bluetooth-LE	00	-	-	-	-	-	-	-	Harmonic
9	Bluetooth-LE	39	2484.04	38.55	54.00	-15.45	V	AVERAGE	Pass	Band Edge
9	Bluetooth-LE	39	-	-	-	-	-	-	-	Harmonic
10	Bluetooth-LE	39	30.97	33.72	40	-6.28	V	Peak	Pass	LF



Mode	5																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																																									
Pol.	Horizontal	Fundamental																																																																																								
Peak	 <p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2384.89</td> <td>48.99</td> <td>74.00</td> <td>-25.01</td> <td>47.48</td> <td>30.43</td> <td>4.79</td> <td>33.71</td> <td>218</td> <td>53</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB							cm	deg	1	2384.89	48.99	74.00	-25.01	47.48	30.43	4.79	33.71	218	53	PEAK	 <p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>96.73</td> <td>-----</td> <td>-----</td> <td>95.16</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>218</td> <td>53</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB							cm	deg	1	2402.00	96.73	-----	-----	95.16	30.44	4.81	33.68	218	53	PEAK
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																			
						cm	deg																																																																																			
1	2384.89	48.99	74.00	-25.01	47.48	30.43	4.79	33.71	218	53	PEAK																																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																			
						cm	deg																																																																																			
1	2402.00	96.73	-----	-----	95.16	30.44	4.81	33.68	218	53	PEAK																																																																															
Avg	 <p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2372.19</td> <td>38.12</td> <td>54.00</td> <td>-15.88</td> <td>36.66</td> <td>30.42</td> <td>4.78</td> <td>33.74</td> <td>218</td> <td>53</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB							cm	deg	1	2372.19	38.12	54.00	-15.88	36.66	30.42	4.78	33.74	218	53	AVERAGE	 <p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> <tr> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>95.44</td> <td>-----</td> <td>-----</td> <td>93.87</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>218</td> <td>53</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB							cm	deg	1	2402.00	95.44	-----	-----	93.87	30.44	4.81	33.68	218	53	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																			
						cm	deg																																																																																			
1	2372.19	38.12	54.00	-15.88	36.66	30.42	4.78	33.74	218	53	AVERAGE																																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																			
						cm	deg																																																																																			
1	2402.00	95.44	-----	-----	93.87	30.44	4.81	33.68	218	53	AVERAGE																																																																															



		5																																																																								
Mode	Band Edge																																																																									
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																									
Pol.	Vertical	Fundamental																																																																								
Peak	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2335.76</td> <td>49.28</td> <td>74.00</td> <td>-24.72</td> <td>47.94</td> <td>30.40</td> <td>4.74</td> <td>33.80</td> <td>400</td> <td>10</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2335.76	49.28	74.00	-24.72	47.94	30.40	4.74	33.80	400	10	PEAK	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>85.06</td> <td>-----</td> <td>-----</td> <td>83.49</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>400</td> <td>10</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2402.00	85.06	-----	-----	83.49	30.44	4.81	33.68	400	10	PEAK
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2335.76	49.28	74.00	-24.72	47.94	30.40	4.74	33.80	400	10	PEAK																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2402.00	85.06	-----	-----	83.49	30.44	4.81	33.68	400	10	PEAK																																																															
Avg	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2357.84</td> <td>38.14</td> <td>54.00</td> <td>-15.86</td> <td>36.72</td> <td>30.42</td> <td>4.76</td> <td>33.76</td> <td>400</td> <td>10</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2357.84	38.14	54.00	-15.86	36.72	30.42	4.76	33.76	400	10	AVERAGE	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>83.73</td> <td>-----</td> <td>-----</td> <td>82.16</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>400</td> <td>10</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2402.00	83.73	-----	-----	82.16	30.44	4.81	33.68	400	10	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2357.84	38.14	54.00	-15.86	36.72	30.42	4.76	33.76	400	10	AVERAGE																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2402.00	83.73	-----	-----	82.16	30.44	4.81	33.68	400	10	AVERAGE																																																															



Mode	5																																																																											
	Harmonic																																																																											
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																											
Pol.	Horizontal	Vertical																																																																										
Peak Avg	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4804.00</td> <td>40.70</td> <td>74.00 -33.30</td> <td>64.36</td> <td>33.82</td> <td>7.74</td> <td>65.22</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	40.70	74.00 -33.30	64.36	33.82	7.74	65.22	--	--	Peak	<table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4804.00</td> <td>40.80</td> <td>74.00 -33.20</td> <td>64.46</td> <td>33.82</td> <td>7.74</td> <td>65.22</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	40.80	74.00 -33.20	64.46	33.82	7.74	65.22	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																			
1	4804.00	40.70	74.00 -33.30	64.36	33.82	7.74	65.22	--	--	Peak																																																																		
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																			
1	4804.00	40.80	74.00 -33.20	64.46	33.82	7.74	65.22	--	--	Peak																																																																		



Mode	6																																																																																																			
	Harmonic																																																																																																			
	2400-2483.5_Bluetooth-LE_CH19_2440MHz																																																																																																			
Pol.	Horizontal	Vertical																																																																																																		
Peak Avg	<p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4880.00</td> <td>41.36</td> <td>74.00</td> <td>-32.64</td> <td>64.99</td> <td>33.85</td> <td>7.77</td> <td>65.25</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7320.00</td> <td>44.86</td> <td>74.00</td> <td>-29.14</td> <td>64.24</td> <td>36.30</td> <td>8.96</td> <td>64.64</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4880.00	41.36	74.00	-32.64	64.99	33.85	7.77	65.25	--	--	Peak	2	7320.00	44.86	74.00	-29.14	64.24	36.30	8.96	64.64	--	--	Peak	<p>Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4880.00</td> <td>41.25</td> <td>74.00</td> <td>-32.75</td> <td>64.88</td> <td>33.85</td> <td>7.77</td> <td>65.25</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7320.00</td> <td>44.16</td> <td>74.00</td> <td>-29.84</td> <td>63.54</td> <td>36.30</td> <td>8.96</td> <td>64.64</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4880.00	41.25	74.00	-32.75	64.88	33.85	7.77	65.25	--	--	Peak	2	7320.00	44.16	74.00	-29.84	63.54	36.30	8.96	64.64	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																												
Freq	Level	Line Margin	Level	Factor	Loss Factor																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																												
1	4880.00	41.36	74.00	-32.64	64.99	33.85	7.77	65.25	--	--	Peak																																																																																									
2	7320.00	44.86	74.00	-29.14	64.24	36.30	8.96	64.64	--	--	Peak																																																																																									
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level	Factor	Loss Factor																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																												
1	4880.00	41.25	74.00	-32.75	64.88	33.85	7.77	65.25	--	--	Peak																																																																																									
2	7320.00	44.16	74.00	-29.84	63.54	36.30	8.96	64.64	--	--	Peak																																																																																									



7

Mode

Band Edge


2400-2483.5\_Bluetooth-LE\_CH39\_2480MHz

Pol.


Horizontal

Fundamental

Peak




1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	
			Freq								Level
	2497.62	49.38	74.00	-24.62	47.45	30.50	4.94	33.51	207	35	PEAK




1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark
			Freq							
	2480.00	95.77	-----	93.90	30.49	4.92	33.54	207	35	PEAK

Avg



1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	
			Freq								Level
	2485.54	38.67	54.00	-15.33	36.79	30.49	4.92	33.53	207	35	AVERAGE



1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark
			Freq							
	2480.00	94.48	-----	92.61	30.49	4.92	33.54	207	35	AVERAGE



7

Mode

Band Edge


2400-2483.5\_Bluetooth-LE\_CH39\_2480MHz

Pol.


Vertical

Fundamental

Peak




1	Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark		
	Freq	Level								Line	Margin
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	2488.94	49.75	74.00	-24.25	47.84	30.50	4.93	33.52	400	25	PEAK




1	Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	
	Freq	Level								Line
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg
1	2480.00	85.85	83.98	1.87	30.49	4.92	33.54	400	25	PEAK

Avg



1	Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark		
	Freq	Level								Line	Margin
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	2497.54	38.55	54.00	-15.45	36.62	30.50	4.94	33.51	400	25	AVERAGE



1	Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	
	Freq	Level								Line
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg
1	2480.00	84.52	82.65	1.87	30.49	4.92	33.54	400	25	AVERAGE



Mode	7																																																																																																			
	Harmonic																																																																																																			
	2400-2483.5_Bluetooth-LE_CH39_2480MHz																																																																																																			
Pol.	Horizontal	Vertical																																																																																																		
Peak Avg	<p>Date: 2024-12-10</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>41.18</td> <td>74.00</td> <td>-32.82</td> <td>64.77</td> <td>33.89</td> <td>7.81</td> <td>65.29</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>44.01</td> <td>74.00</td> <td>-29.99</td> <td>63.06</td> <td>36.30</td> <td>9.19</td> <td>64.54</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4960.00	41.18	74.00	-32.82	64.77	33.89	7.81	65.29	--	--	Peak	2	7440.00	44.01	74.00	-29.99	63.06	36.30	9.19	64.54	--	--	Peak	<p>Date: 2024-12-10</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>4960.00</td> <td>41.57</td> <td>74.00</td> <td>-32.43</td> <td>65.16</td> <td>33.89</td> <td>7.81</td> <td>65.29</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> <tr> <td>2</td> <td>7440.00</td> <td>43.05</td> <td>74.00</td> <td>-30.95</td> <td>62.10</td> <td>36.30</td> <td>9.19</td> <td>64.54</td> <td>--</td> <td>--</td> <td>Peak</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	4960.00	41.57	74.00	-32.43	65.16	33.89	7.81	65.29	--	--	Peak	2	7440.00	43.05	74.00	-30.95	62.10	36.30	9.19	64.54	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																												
Freq	Level	Line Margin	Level	Factor	Loss Factor																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																												
1	4960.00	41.18	74.00	-32.82	64.77	33.89	7.81	65.29	--	--	Peak																																																																																									
2	7440.00	44.01	74.00	-29.99	63.06	36.30	9.19	64.54	--	--	Peak																																																																																									
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level	Factor	Loss Factor																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																												
1	4960.00	41.57	74.00	-32.43	65.16	33.89	7.81	65.29	--	--	Peak																																																																																									
2	7440.00	43.05	74.00	-30.95	62.10	36.30	9.19	64.54	--	--	Peak																																																																																									



		8																																																																														
Mode	Band Edge																																																																															
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																															
Pol.	Horizontal		Fundamental																																																																													
Peak	<table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th></th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2388.75</td> <td>48.73</td> <td>74.00</td> <td>-25.27</td> <td>47.22</td> <td>30.43</td> <td>4.79</td> <td>33.71</td> <td>222</td> <td>54 PEAK</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2388.75	48.73	74.00	-25.27	47.22	30.43	4.79	33.71	222	54 PEAK	<table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th></th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>97.26</td> <td>-----</td> <td>-----</td> <td>95.69</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>222</td> <td>54 PEAK</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	97.26	-----	-----	95.69	30.44	4.81	33.68	222	54 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																							
1	2388.75	48.73	74.00	-25.27	47.22	30.43	4.79	33.71	222	54 PEAK																																																																						
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																							
1	2402.00	97.26	-----	-----	95.69	30.44	4.81	33.68	222	54 PEAK																																																																						
Avg	<table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th></th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2361.24</td> <td>38.16</td> <td>54.00</td> <td>-15.84</td> <td>36.73</td> <td>30.42</td> <td>4.77</td> <td>33.76</td> <td>222</td> <td>54 AVERAGE</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2361.24	38.16	54.00	-15.84	36.73	30.42	4.77	33.76	222	54 AVERAGE	<table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th></th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th></th> <th></th> <th></th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>92.91</td> <td>-----</td> <td>-----</td> <td>91.34</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>222</td> <td>54 AVERAGE</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2402.00	92.91	-----	-----	91.34	30.44	4.81	33.68	222	54 AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																							
1	2361.24	38.16	54.00	-15.84	36.73	30.42	4.77	33.76	222	54 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																							
1	2402.00	92.91	-----	-----	91.34	30.44	4.81	33.68	222	54 AVERAGE																																																																						



		8																																																																								
Mode	Band Edge																																																																									
	2400-2483.5_Bluetooth-LE_CH00_2402MHz																																																																									
Pol.	Vertical	Fundamental																																																																								
Peak	<p style="text-align: right;">Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2379.74</td> <td>48.33</td> <td>74.00</td> <td>-25.67</td> <td>46.83</td> <td>30.43</td> <td>4.79</td> <td>33.72</td> <td>381</td> <td>2</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2379.74	48.33	74.00	-25.67	46.83	30.43	4.79	33.72	381	2	PEAK	<p style="text-align: right;">Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>89.73</td> <td>-----</td> <td>-----</td> <td>88.16</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>381</td> <td>2</td> <td>PEAK</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2402.00	89.73	-----	-----	88.16	30.44	4.81	33.68	381	2	PEAK
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2379.74	48.33	74.00	-25.67	46.83	30.43	4.79	33.72	381	2	PEAK																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2402.00	89.73	-----	-----	88.16	30.44	4.81	33.68	381	2	PEAK																																																															
Avg	<p style="text-align: right;">Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2368.97</td> <td>38.16</td> <td>54.00</td> <td>-15.84</td> <td>36.71</td> <td>30.42</td> <td>4.77</td> <td>33.74</td> <td>381</td> <td>2</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2368.97	38.16	54.00	-15.84	36.71	30.42	4.77	33.74	381	2	AVERAGE	<p style="text-align: right;">Date: 2024-11-30</p> <table border="1"> <thead> <tr> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>85.35</td> <td>-----</td> <td>-----</td> <td>83.78</td> <td>30.44</td> <td>4.81</td> <td>33.68</td> <td>381</td> <td>2</td> <td>AVERAGE</td> </tr> </tbody> </table>	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	2402.00	85.35	-----	-----	83.78	30.44	4.81	33.68	381	2	AVERAGE
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2368.97	38.16	54.00	-15.84	36.71	30.42	4.77	33.74	381	2	AVERAGE																																																															
Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																			
1	2402.00	85.35	-----	-----	83.78	30.44	4.81	33.68	381	2	AVERAGE																																																															



9

Mode

Band Edge


2400-2483.5\_Bluetooth-LE\_CH39\_2480MHz

Pol.


Horizontal

Fundamental

Peak




Limit Freq	Level	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Loss	APos	TPos	Remark	
										MHz
1	2499.18	50.55	74.00	-23.45	48.62	30.50	4.94	33.51	211	49 PEAK




Limit Freq	Level	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Loss	APos	TPos	Remark	
										MHz
1	2480.00	94.87	-----	-----	93.00	30.49	4.92	33.54	211	49 PEAK

Avg



Limit Freq	Level	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Loss	APos	TPos	Remark	
										MHz
1	2492.00	38.51	54.00	-15.49	36.60	30.50	4.93	33.52	211	49 AVERAGE



Limit Freq	Level	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Loss	APos	TPos	Remark	
										MHz
1	2480.00	90.40	-----	-----	88.53	30.49	4.92	33.54	211	49 AVERAGE



9

Mode

Band Edge


2400-2483.5\_Bluetooth-LE\_CH39\_2480MHz

Pol.


Vertical

Fundamental

Peak




1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	
			Freq								Level
	2497.28	49.23	74.00	-24.77	47.30	30.50	4.94	33.51	400	25	PEAK




1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark
			Freq							
	2480.00	86.14	-----	84.27	30.49	4.92	33.54	400	25	PEAK

Avg





1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	
			Freq								Level
	2484.04	38.55	54.00	-15.45	36.67	30.49	4.92	33.53	400	25	AVERAGE



1	MHz	dBuV/m	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark
			Freq							
	2480.00	81.57	-----	79.70	30.49	4.92	33.54	400	25	AVERAGE




Mode	10																																																																																																																																																																															
	LF																																																																																																																																																																															
	2400-2483.5_Bluetooth-LE_CH39_2480MHz																																																																																																																																																																															
Pol.	Horizontal	Vertical																																																																																																																																																																														
Peak	 <p>Date: 2024-11-30 FCC CLASS-B -6dB</p> <table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th></th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>46.49</td> <td>19.48</td> <td>40.00</td> <td>-20.52</td> <td>34.17</td> <td>19.62</td> <td>0.69</td> <td>35.00</td> <td>-- -- Peak</td> </tr> <tr> <td>2</td> <td>149.31</td> <td>22.05</td> <td>43.50</td> <td>-21.45</td> <td>36.57</td> <td>18.90</td> <td>1.28</td> <td>34.70</td> <td>-- -- Peak</td> </tr> <tr> <td>3</td> <td>209.45</td> <td>24.01</td> <td>43.50</td> <td>-19.49</td> <td>40.91</td> <td>16.29</td> <td>1.51</td> <td>34.70</td> <td>-- -- Peak</td> </tr> <tr> <td>4</td> <td>254.07</td> <td>27.14</td> <td>46.00</td> <td>-18.86</td> <td>42.49</td> <td>17.69</td> <td>1.65</td> <td>34.69</td> <td>-- -- Peak</td> </tr> <tr> <td>5</td> <td>445.16</td> <td>25.36</td> <td>46.00</td> <td>-20.64</td> <td>35.01</td> <td>22.62</td> <td>2.23</td> <td>34.50</td> <td>-- -- Peak</td> </tr> <tr> <td>6</td> <td>774.96</td> <td>32.84</td> <td>46.00</td> <td>-13.16</td> <td>36.48</td> <td>27.72</td> <td>2.99</td> <td>34.35</td> <td>-- -- Peak</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	46.49	19.48	40.00	-20.52	34.17	19.62	0.69	35.00	-- -- Peak	2	149.31	22.05	43.50	-21.45	36.57	18.90	1.28	34.70	-- -- Peak	3	209.45	24.01	43.50	-19.49	40.91	16.29	1.51	34.70	-- -- Peak	4	254.07	27.14	46.00	-18.86	42.49	17.69	1.65	34.69	-- -- Peak	5	445.16	25.36	46.00	-20.64	35.01	22.62	2.23	34.50	-- -- Peak	6	774.96	32.84	46.00	-13.16	36.48	27.72	2.99	34.35	-- -- Peak	 <p>Date: 2024-11-30 FCC CLASS-B -6dB</p> <table border="1"> <thead> <tr> <th></th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line</th> <th>Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th></th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>30.97</td> <td>33.72</td> <td>40.00</td> <td>-6.28</td> <td>50.16</td> <td>17.78</td> <td>0.55</td> <td>34.77</td> <td>-- -- Peak</td> </tr> <tr> <td>2</td> <td>149.31</td> <td>23.86</td> <td>43.50</td> <td>-19.64</td> <td>38.38</td> <td>18.90</td> <td>1.28</td> <td>34.70</td> <td>-- -- Peak</td> </tr> <tr> <td>3</td> <td>269.59</td> <td>22.16</td> <td>46.00</td> <td>-23.84</td> <td>36.94</td> <td>18.18</td> <td>1.70</td> <td>34.66</td> <td>-- -- Peak</td> </tr> <tr> <td>4</td> <td>469.41</td> <td>24.82</td> <td>46.00</td> <td>-21.18</td> <td>34.05</td> <td>22.98</td> <td>2.29</td> <td>34.50</td> <td>-- -- Peak</td> </tr> <tr> <td>5</td> <td>644.98</td> <td>27.82</td> <td>46.00</td> <td>-18.18</td> <td>33.41</td> <td>26.23</td> <td>2.69</td> <td>34.51</td> <td>-- -- Peak</td> </tr> <tr> <td>6</td> <td>773.99</td> <td>33.27</td> <td>46.00</td> <td>-12.73</td> <td>36.92</td> <td>27.71</td> <td>2.99</td> <td>34.35</td> <td>-- -- Peak</td> </tr> </tbody> </table>		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	30.97	33.72	40.00	-6.28	50.16	17.78	0.55	34.77	-- -- Peak	2	149.31	23.86	43.50	-19.64	38.38	18.90	1.28	34.70	-- -- Peak	3	269.59	22.16	46.00	-23.84	36.94	18.18	1.70	34.66	-- -- Peak	4	469.41	24.82	46.00	-21.18	34.05	22.98	2.29	34.50	-- -- Peak	5	644.98	27.82	46.00	-18.18	33.41	26.23	2.69	34.51	-- -- Peak	6	773.99	33.27	46.00	-12.73	36.92	27.71	2.99	34.35	-- -- Peak
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																																																																								
1	46.49	19.48	40.00	-20.52	34.17	19.62	0.69	35.00	-- -- Peak																																																																																																																																																																							
2	149.31	22.05	43.50	-21.45	36.57	18.90	1.28	34.70	-- -- Peak																																																																																																																																																																							
3	209.45	24.01	43.50	-19.49	40.91	16.29	1.51	34.70	-- -- Peak																																																																																																																																																																							
4	254.07	27.14	46.00	-18.86	42.49	17.69	1.65	34.69	-- -- Peak																																																																																																																																																																							
5	445.16	25.36	46.00	-20.64	35.01	22.62	2.23	34.50	-- -- Peak																																																																																																																																																																							
6	774.96	32.84	46.00	-13.16	36.48	27.72	2.99	34.35	-- -- Peak																																																																																																																																																																							
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																																																																																								
1	30.97	33.72	40.00	-6.28	50.16	17.78	0.55	34.77	-- -- Peak																																																																																																																																																																							
2	149.31	23.86	43.50	-19.64	38.38	18.90	1.28	34.70	-- -- Peak																																																																																																																																																																							
3	269.59	22.16	46.00	-23.84	36.94	18.18	1.70	34.66	-- -- Peak																																																																																																																																																																							
4	469.41	24.82	46.00	-21.18	34.05	22.98	2.29	34.50	-- -- Peak																																																																																																																																																																							
5	644.98	27.82	46.00	-18.18	33.41	26.23	2.69	34.51	-- -- Peak																																																																																																																																																																							
6	773.99	33.27	46.00	-12.73	36.92	27.71	2.99	34.35	-- -- Peak																																																																																																																																																																							



## Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 2Mbps	30.65	0.19	5.263	10kHz
Bluetooth LE 125Kbps	82.67	3.10	0.323	1kHz

### Bluetooth LE 2Mbps





Bluetooth LE 125kbps

