

FCC/IC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Portable Tablet Computer

ISSUED TO
LENOVO (SHANGHAI) ELECTRONICS TECHNOLOGY CO
LTD

NO 68 BUILDING 199 FENJU RD, CHINA (SHANGHAI) PILOT FREE
TRADE ZONE, SHANGHAI, 200131 CHINA



Tested by:

Cao Shaodong
(Engineer)

Date: Mar. 8, 2016

Approved by:

Wei Yanquan
(Chief Engineer)

Date: Mar. 8, 2016

Report No.: BL-SZ1610062-602

EUT Type: Portable Tablet Computer

Model Name: Lenovo TB3-X70F

Brand Name: Lenovo

Test Standard: 47 CFR Part 15 Subpart C

IC RSS-Gen (Issue 4, November 2014)

IC RSS-247 (Issue 1, May 2015)

FCC ID: O57TB3X70F

IC Number: 10407A-TB3X70F

Test conclusion: Pass

Test Date: Jan. 7, 2016 ~ Feb. 5, 2016

Date of Issue: Mar. 8, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055

TEL: +86-755-66850100, FAX: +86-755-61824271

Email: info@baluntek.com

www.baluntek.com

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Feb. 2, 2016</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Feb. 15, 2016</u>	<u>The Second Issue</u>
<u>Rev. 03</u>	<u>Mar. 2, 2016</u>	<u>The Third Issue</u>
Rev. 04	Mar. 8, 2016	Updated chapter 2.7

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)5

 1.1 Identification of the Testing Laboratory5

 1.2 Identification of the Responsible Testing Location5

 1.3 Laboratory Condition5

 1.4 Announce5

2 PRODUCT INFORMATION7

 2.1 Applicant Information7

 2.2 Manufacturer Information7

 2.3 Factory Information7

 2.4 General Description for Equipment under Test (EUT)7

 2.5 Ancillary Equipment9

 2.6 Technical Information10

 2.7 Additional Instructions12

3 SUMMARY OF TEST RESULTS13

 3.1 Test Standards13

 3.2 Verdict13

4 GENERAL TEST CONFIGURATIONS14

 4.1 Test Environments14

 4.2 Test Equipment List14

 4.3 Description of Test Setup15

 4.3.1 For Antenna Port Test15

 4.3.2 For AC Power Supply Port Test15

 4.3.3 For Radiated Test (Below 30 MHz)16

 4.3.4 For Radiated Test (30 MHz-1 GHz)16

 4.3.5 For Radiated Test (Above 1 GHz)17

5	TEST ITEMS.....	18
5.1	Antenna Requirements.....	18
5.1.1	Standard Applicable	18
5.1.2	Antenna Anti-Replacement Construction	18
5.1.3	Antenna Gain	19
5.2	Output Power	20
5.2.1	Test Limit.....	20
5.2.2	Test Setup	20
5.2.3	Test Procedure.....	20
5.2.4	Test Result	21
5.3	6dB Bandwidth	22
5.3.1	Limit.....	22
5.3.2	Test Setup	22
5.3.3	Test Procedure.....	22
5.3.4	Test Result	22
5.4	Conducted Spurious Emission	23
5.4.1	Limit.....	23
5.4.2	Test Setup	23
5.4.3	Test Procedure.....	23
5.4.4	Test Result	24
5.5	Band Edge (Authorized-band band-edge).....	25
5.5.1	Limit.....	25
5.5.2	Test Setup	25
5.5.3	Test Procedure.....	25
5.5.4	Test Result	25
5.6	Conducted Emission	26
5.6.1	Limit.....	26
5.6.2	Test Setup	26
5.6.3	Test Procedure.....	26
5.6.4	Test Result	26
5.7	Radiated Spurious Emission	27
5.7.1	Limit.....	27

5.7.2	Test Setup	27
5.7.3	Test Procedure	27
5.7.4	Test Result	30
5.9	Power Spectral density (PSD)	31
5.9.1	Limit	31
5.9.2	Test Setup	31
5.9.3	Test Procedure	31
5.9.4	Test Result	31
5.10	Receiver Spurious Emissions	32
5.10.1	Limit	32
5.10.2	Test Setup	32
5.10.3	Test Procedure	32
5.10.4	Test Result	32
ANNEX A	TEST RESULT	33
A.1	Output Power	33
A.2	Bandwidth	35
A.3	Conducted Spurious Emissions	38
A.4	Band Edge (Authorized-band band-edge)	47
A.5	Conducted Emissions	54
A.6	Radiated Emission	58
A.7	Power Spectral Density (PSD)	104
A.8	Receiver Spurious Emissions	107
ANNEX B	TEST SETUP PHOTOS	111
ANNEX C	EUT EXTERNAL PHOTOS	111
ANNEX D	EUT INTERNAL PHOTOS	111

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory has met the requirements of the IAS Accreditation Criteria for Testing Laboratories (AC89), has demonstrated compliance with ISO/IEC Standard 17025:2005. The accreditation certificate number is TL-588.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v3.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	LENOVO (SHANGHAI) ELECTRONICS TECHNOLOGY CO LTD
Address	NO 68 BUILDING 199 FENJU RD, CHINA (SHANGHAI) PILOT FREE TRADE ZONE, SHANGHAI, 200131 CHINA

2.2 Manufacturer Information

Manufacturer	Lenovo PC HK Limited.
Address	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong

2.3 Factory Information

Factory 1	BYD Precision Manufacture Co., Ltd.
Address 1	No.3001, Baohe Road, Baolong Industrial, Longgang, Shenzhen, P.R. China
Factory 2	Motorola (Wuhan) Mobility Technologies Communication Co., Ltd
Address 2	No.19, Gaoxin 4th Road, Wuhan East Lake High-tech Zone, Wuhan, China
Factory 3	Dong Guan Huabel Electronic Technology Co., Ltd
Address 3	No.9 Industrial Northern Road, National High-Tech Industrial Development Zone, SongShan Lake, Dong Guan City, China

2.4 General Description for Equipment under Test (EUT)

EUT Type	Portable Tablet Computer
Model Name Under Test	Lenovo TB3-X70F
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	A6604_MB_PCB_V2.0
Software Version	TB3-X70F_160108
Dimensions (Approx.)	247.4 mm × 171.5 mm × 9.4 mm
Weight (Approx.)	500 g(with battery)
Network and Wireless connectivity	Bluetooth 3.0, Bluetooth 4.0 Low Energy (BLE), WIFI 802.11a,802.11b, 802.11g and 802.11n (HT20/40), 802.11ac, GPS, GLONASS, NFC

EUT	Hardware	Manufacturer
Configuration A	LCD display	BOE TECHNOLOGY GROUP CO., LTD.
	Battery	Sunwoda Electronic Co.,Ltd.
Configuration B	LCD display	Innolux corporation
	Battery	SCUD (Fujian) Electronics Co.,Ltd.

Note: The EUT have two sample which Configuration A is OF display with XWD battery and Configuration B is AUO display with ATL battery), the internal structure and circuit electrical parameters are the same; but the LCD display and battery are different. All of them were tested in this report, the Configuration A sample as the main for tested and the Configuration B sample as confirmatory test. In Spurious Emissions test, only the Configuration A + C-P35 (HUNTKEY) and Configuration B + C-P35 (Acbel) were shown in this report.

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery 1	
	Brand Name	Lenovo
	Model No.	L14D2P31
	Serial No.	N/A
	Capacitance	7000 mAh
	Rated Voltage	3.8 V
	Limit Charge Voltage	4.35 V
	Manufacturer	Sunwoda Electronic Co. Ltd
Ancillary Equipment 2	Battery 2	
	Brand Name	Lenovo
	Model No.	L14D2P31
	Serial No.	N/A
	Capacitance	7000 mAh
	Rated Voltage	3.8 V
	Limit Charge Voltage	SCUD (Fujian) Electronics Co., Ltd.
Ancillary Equipment 3	Charger 1	
	Brand Name	Lenovo
	Model Name	C-P35
	Rated Input	100-240 V ~, 50/60 Hz, 0.5 A
	Rated Output	5.2 V =, 2.0 A
	Manufacturer	SHENZHEN HUNTKEY ELECTRIC CO LTD
Ancillary Equipment 4	Charger 2	
	Brand Name	Lenovo
	Model Name	C-P35
	Rated Input	100-240 V ~, 50/60 Hz, 0.3 A
	Rated Output	5.2 V =, 2.0 A
	Manufacturer	Acbel Polytech Inc.
Ancillary Equipment 5	USB Cable 1 ^{Note 1}	
	Length(Approx.)	102 cm
	Manufacturer	SHIN AN WIRE&CABLE CO., LTD.
Ancillary Equipment 6	USB Cable 2 ^{Note 1}	
	Length(Approx.)	102 cm
	Manufacturer	SAIBO ELECTRON TECHNOLOGY (HK) CO., LTD.

Note 1: There tow USB cable only the manufacturer is different. All the USB cable were tested, but only the USB cable 1 was shown in this report.

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

TX/ RX Operating Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11. 802.11n(40 MHz): 2.422 GHz - 2.452 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 3 to 9.
Modulation Type	DSSS, OFDM
Product Type	Mobile and portable
Antenna Type	PIFA Antenna
Antenna Gain	0.49 dBi
Antenna System(MIMO Smart Antenna)	N/A
About the Product	The equip.ment is Portable Tablet Computer, it contains WIFI and Bluetooth Modules operating at 2.4 GHz ISM band.

Modulation technology	Modulation Type	Transfer Rate (Mbps)	The Frequency Equal to the Transmission Rate of Modulation Signal
DSSS (802.11b)	DBPSK	1	1 MHz
	DQPSK	2	
	CCK	5.5/ 11	1.375 MHz
OFDM (802.11g)	BPSK	6 / 9	1 MHz
	QPSK	12 / 18	
	16QAM	24 / 36	
	64QAM	48 / 54	
OFDM (802.11n-20MHz)	BPSK	6.5	1 MHz
	QPSK	13/19.5	
	16QAM	26/39	
	64QAM	52/58.5/65	
OFDM (802.11n-40MHz)	BPSK	13.5	1 MHz
	QPSK	27/40.5	
	16QAM	54/81/108	
	64QAM	121.5/135	

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
6dB Bandwidth	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.7 Additional Instructions

EUT Software Settings:


Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

EUT Software Settings:

Power level setup in software		
Test Software Version	Test software is set by engineering instruction“*##3646633#*##” in engineering mode	
Mode	Channel	Soft Set
802.11 b	All	19
802.11 g	All	17
802.11 n20	All	17
802.11 n40	All	17

Run software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-14 Edition)	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v03r03	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
3	ANSI C63.4-2014	American National Standard for Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
4	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
5	IC RSS-Gen (Issue 4, Nov. 2014)	General Requirements for Compliance of Radio Apparatus
6	IC RSS-247 (Issue 1, May 2015)	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices

3.2 Verdict

No.	Description	Part No.	Test Result	Verdict
1	Antenna Requirement	RSS-247, 5.4 (6); 15.203; 15.247(b)	Note1	Pass
2	Output Power	RSS-247, 5.4 (4); 15.247(b)	ANNEX A.1	Pass
3	6dB Bandwidth	RSS-GEN, 6.6; RSS-247, 5.2 (1); 15.247(a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	RSS-247, 5.5; 15.247(d)	ANNEX A.3	Pass
5	Band Edge	RSS-GEN, 8.9; RSS-247, 5.5; 5.209; 15.247(d)	ANNEX A.4	Pass
6	Radiated Spurious Emission	RSS-247, 5.5; 15.209; 15.247(d)	ANNEX A.5	Pass
7	Conducted Emission	RSS-GEN, 8.8; 15.207	ANNEX A.6	Pass
8	Power spectral density (PSD)	RSS-247, 5.2 (2); 15.247(e)	ANNEX A.7	Pass
9	Receiver Spurious Emissions	RSS-Gen, 7.1.2	ANNEX A.8	Pass
Note 1: Please refer to section 5.1				

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:


Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.8 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2015.07.16	2016.07.15
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2015.07.16	2016.07.15
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2015.07.01	2016.06.30
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2015.07.16	2016.07.15
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.15	2016.10.14
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2015.07.14	2016.07.13
LISN	SCHWARZBECK	NSLK 8127	8127-687	2015.07.14	2016.07.13
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2015.07.16	2016.07.15
Power Splitter	KMW	DCPD-LDC	1305003215	2015.07.01	2016.06.30
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2015.07.21	2016.07.20
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2015.07.17	2016.07.16
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2015.08.07	2016.08.06
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2016.02.27
Shielded Enclosure	ChangNing	CN-130701	130703	--	--


4.3 Description of Test Setup

4.3.1 For Antenna Port Test




(Diagram 1)

4.3.2 For AC Power Supply Port Test




(Diagram 2)

4.3.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.3.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.3.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	An embedded-in antenna design is used.

Reference Documents	Item
Photo	



5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (4)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 6dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.2-4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW ≥ 3 x RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Receiver Spurious Emissions

5.10.1 Limit

IC RSS-Gen, 7.1.2

Radiated spurious emission measurements shall be performed with the receiver antenna connected to the receiver antenna terminals. Spurious emissions from receivers shall not exceed the radiated limits shown in the table below:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

5.10.2 Test Setup

See section 4.4.3-5 (Diagram 3-5) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Test Plots for the Whole Measurement Frequency Range:

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.10.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	Duty Cycle	T (ms)	1/T(kHz)
802.11b	1.00	8.383	0.119289037
802.11g	0.97	1.380	0.724637681
802.11n-20 MHz	0.97	1.287	0.777000777
802.11n-40 MHz	0.92	0.630	1.587301587

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.54	35.81	30	1000	Pass
Middle	15.52	35.65			Pass
High	15.18	32.96			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	11.89	15.45	30	1000	Pass
Middle	13.65	23.17			Pass
High	11.54	14.26			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	12.15	16.41	30	1000	Pass
Middle	12.98	19.86			Pass
High	11.32	13.55			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.04	10.09	30	1000	Pass
Middle	13.78	23.88			Pass
High	9.42	8.75			Pass

A.2 Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	9.100	13.6944	≥500
Middle	9.092	13.6512	≥500
High	8.099	13.6641	≥500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	15.259	16.3897	≥500
Middle	15.952	16.3803	≥500
High	14.811	16.3771	≥500

802.11n-20MHz Mode:


Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.843	17.5705	≥500
Middle	16.846	17.5854	≥500
High	16.829	17.5685	≥500

802.11n-40MHz Mode:


Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	35.268	35.8692	≥500
Middle	35.274	35.9134	≥500
High	35.284	35.8513	≥500

Test plots


802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




802.11 n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-42.22	7.55	-12.45	Pass
Middle	-42.07	7.36	-12.64	Pass
High	-41.71	7.44	-12.56	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-54.19	1.16	-18.84	Pass
Middle	-50.86	2.97	-17.03	Pass
High	-51.46	0.90	-19.10	Pass

802.11n-20MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-54.81	1.20	-18.80	Pass
Middle	-52.18	2.09	-17.91	Pass
High	-54.52	1.12	-18.88	Pass

802.11n-40MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-55.16	-4.15	-24.15	Pass
Middle	-49.17	-0.20	-20.20	Pass
High	-54.00	-4.01	-24.01	Pass

Test Plots


802.11b LOW CHANNEL CARRIER LEVEL




802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11b MIDDLE CHANNEL CARRIER LEVEL



802.11b MIDDLE CHANNEL, SPURIOUS
30 MHz ~ 3 GHz




802.11b MIDDLE CHANNEL, SPURIOUS
2 GHz ~ 25 GHz




802.11b HIGH CHANNEL CARRIER LEVEL




802.11b HIGH CHANNEL, SPURIOUS
30 MHz ~ 3 GHz




802.11b HIGH CHANNEL, SPURIOUS
2 GHz ~ 25 GHz




802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz





802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz






802.11g MIDDLE CHANNEL CARRIER LEVEL




802.11g MIDDLE CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11g MIDDLE CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz



802.11g HIGH CHANNEL CARRIER LEVEL


 802.11g HIGH CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11g HIGH CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz



802.11n-20 MHz LOW CHANNEL CARRIER LEVEL




802.11n-20 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz





802.11n-20 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz






802.11n-20 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz



802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL


 802.11n-20 MHz HIGH CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11n-20 MHz HIGH CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz



802.11n-40 MHz LOW CHANNEL CARRIER LEVEL




802.11n-40 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz





802.11n-40 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz






802.11n-40 MHz MIDDLE CHANNEL CARRIER LEVEL



802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz


802.11n-40 MHz HIGH CHANNEL CARRIER LEVEL


 802.11-n40 MHz HIGH CHANNEL, SPURIOUS
 30 MHz ~ 3 GHz

 802.11n-40 MHz HIGH CHANNEL, SPURIOUS
 2 GHz ~ 25 GHz


A.4 Band Edge (Authorized-band band-edge)

Test Data

The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-28.97	7.55	-12.45	Pass
High Channel	-49.74	7.44	-12.56	Pass

802.11g Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-27.00	1.16	-18.84	Pass
High Channel	-43.39	0.90	-19.10	Pass

802.11n-20 MHz Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-27.00	1.20	-18.80	Pass
High Channel	-40.41	1.12	-18.88	Pass

802.11n-40 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-30.14	-4.15	-24.15	Pass
High Channel	-34.81	-4.01	-24.01	Pass

Test Plots


802.11b LOW CHANNEL, Carrier level




802.11b LOW CHANNEL, Reference level




802.11b LOW CHANNEL, Band Edge




802.11b HIGH CHANNEL, Carrier level




802.11b HIGH CHANNEL, Reference level




802.11b HIGH CHANNEL, Band Edge




802.11g LOW CHANNEL, Carrier level




802.11g LOW CHANNEL, Band Edge




802.11g LOW CHANNEL, Reference level




802.11g HIGH CHANNEL, Carrier level




802.11g HIGH CHANNEL, Reference level



802.11g HIGH CHANNEL, Band Edge





802.11n-20 MHz LOW CHANNEL, Carrier level




802.11n-20 MHz LOW CHANNEL, Reference level

802.11n-20 MHz LOW CHANNEL, Band Edge





802.11n-20 MHz HIGH CHANNEL, Carrier level




802.11n-20 MHz HIGH CHANNEL, Reference level


802.11n-20 MHz HIGH CHANNEL, Band Edge




802.11n-40 MHz LOW CHANNEL, Carrier level




802.11n-40 MHz LOW CHANNEL, Reference level



802.11n-40 MHz LOW CHANNEL, Band Edge





802.11n-40 MHz HIGH CHANNEL, Carrier level



802.11n-40 MHz HIGH CHANNEL, Reference level

802.11n-40 MHz HIGH CHANNEL, Band Edge




A.5 Conducted Emissions

Note: All configurations have been tested, only the worst configuration (802.11b High Channel) shown here.

Test Data and Plots


CONFIGURATION A+ C-P35 (Huntkey)

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.22	38.2	13.00	64.1	25.90	Peak	L Line	Pass
1**	0.22	24.9	13.00	54.1	29.20	AV	L Line	Pass
2	0.66	37.7	13.00	56.0	18.30	Peak	L Line	Pass
2**	0.66	26.2	13.00	46.0	19.80	AV	L Line	Pass
3	2.78	42.7	13.00	56.0	13.30	Peak	L Line	Pass
3**	2.78	26.9	13.00	46.0	19.10	AV	L Line	Pass
4	4.18	37.9	13.00	56.0	18.10	Peak	L Line	Pass
4**	4.18	25.9	13.00	46.0	20.10	AV	L Line	Pass
5	12.84	38.8	13.00	60.0	21.20	Peak	L Line	Pass
5**	12.84	27.0	13.00	50.0	23.00	AV	L Line	Pass
6	17.83	45.6	13.00	60.0	14.40	Peak	L Line	Pass
6**	17.83	39.9	13.00	50.0	10.10	AV	L Line	Pass

PHASE N




No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.16	41.0	13.00	65.6	24.60	Peak	N Line	Pass
1**	0.16	31.9	13.00	55.6	23.70	AV	N Line	Pass
2	0.62	41.8	13.00	56.0	14.20	Peak	N Line	Pass
2**	0.62	29.4	13.00	46.0	16.60	AV	N Line	Pass
3	2.13	36.6	13.00	56.0	19.40	Peak	N Line	Pass
3**	2.13	23.3	13.00	46.0	22.70	AV	N Line	Pass
4	3.52	40.6	13.00	56.0	15.40	Peak	N Line	Pass
4**	3.52	29.1	13.00	46.0	16.90	AV	N Line	Pass
5	6.20	37.9	13.00	60.0	22.10	Peak	N Line	Pass
5**	6.20	25.4	13.00	50.0	24.60	AV	N Line	Pass
6	16.55	45.3	13.00	60.0	14.70	Peak	N Line	Pass
6**	16.55	32.5	13.00	50.0	17.50	AV	N Line	Pass

CONFIGURATION B+ C-P35 (Acbel)

PHASE L


CE Test case_FCC_CE_FCC PART 15_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.20	56.7	13.00	64.5	7.80	Peak	L Line	Pass
1**	0.20	27.8	13.00	54.5	26.70	AV	L Line	Pass
2	0.43	50.9	13.00	58.1	7.20	Peak	L Line	Pass
2**	0.43	24.4	13.00	48.1	23.70	AV	L Line	Pass
3	0.68	47.0	13.00	56.0	9.00	Peak	L Line	Pass
3**	0.68	23.1	13.00	46.0	22.90	AV	L Line	Pass
4	2.82	45.3	13.00	56.0	10.70	Peak	L Line	Pass
4**	2.82	29.2	13.00	46.0	16.80	AV	L Line	Pass
5	9.09	38.0	13.00	60.0	22.00	Peak	L Line	Pass
5**	9.09	26.0	13.00	50.0	24.00	AV	L Line	Pass
6	16.71	49.5	13.00	60.0	10.50	Peak	L Line	Pass
6**	16.71	33.6	13.00	50.0	16.40	AV	L Line	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.18	57.0	13.00	65.0	8.00	Peak	N Line	Pass
1**	0.18	28.4	13.00	55.0	26.60	AV	N Line	Pass
2	0.31	51.2	13.00	61.5	10.30	Peak	N Line	Pass
2**	0.31	27.1	13.00	51.5	24.40	AV	N Line	Pass
3	0.62	46.7	13.00	56.0	9.30	Peak	N Line	Pass
3**	0.62	28.0	13.00	46.0	18.00	AV	N Line	Pass
4	1.03	43.8	13.00	56.0	12.20	Peak	N Line	Pass
4**	1.03	22.6	13.00	46.0	23.40	AV	N Line	Pass
5	4.05	42.6	13.00	56.0	13.40	Peak	N Line	Pass
5**	4.05	31.1	13.00	46.0	14.90	AV	N Line	Pass
6	17.19	48.4	13.00	60.0	11.60	Peak	N Line	Pass
6**	17.19	35.1	13.00	50.0	14.90	AV	N Line	Pass

A.6 Radiated Emission

Note: Below the 1 GHz, all configurations have been tested, only the worst configuration (802.11b: Low channel) shown here.

Antenna-port Conducted test data

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + The appropriate maximum ground reflection factor (dB)

Note: All configure were tested but only the worst data (802.11b Low Channel) was reported in this report.

The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.


Note 4: The harmonic (2th, 3th, 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise

LOW 1GHz


Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Remark	Verdict
0.010175	-81.53	6	3	2	QP	21.73	79.87	58.14	Note 2	Pass
20	-65.86	6	3	2	QP	37.40	79.87	42.47	Note 2	Pass
471.4	-81.66	4.7	3	2	QP	20.30	79.87	59.57	Note 2	Pass
830.2	-81.13	4.7	3	2	QP	20.83	79.87	59.04	Note 2	Pass

Test Plots


LOW CHANNEL, SPURIOUS 9 kHz ~ 150 kHz



LOW CHANNEL, SPURIOUS 150 kHz ~ 30 MHz



LOW CHANNEL, SPURIOUS 30 MHz ~ 1 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11b: LOW CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4826	-45.72	0	3	2	PK	51.54	74.00	22.46	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
13696.3	-45.38	0	3	2	PK	51.88	87.54	35.66	Note 2	Pass
	N/A		3	2	AV	N/A	67.54	N/A	Note 3	Pass
2411	10.28	0	3	2	PK	107.54	N/A	N/A	Note 1	N/A
	-14.57		3	2	AV	82.69	N/A	N/A		N/A

Test Plots

LOW CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11b: MIDDLE CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4875.5	-46.91	0	3	2	PK	50.35	74.00	23.65	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14213.3	-45.24	0	3	2	PK	52.02	87.46	35.44	Note 2	Pass
	N/A		3	2	AV	N/A	67.46	N/A	Note 3	Pass
2436	10.2	0	3	2	PK	107.46	N/A	N/A	Note 1	N/A
	-14.65		3	2	AV	82.61	N/A	N/A		N/A

Test Plots

MIDDLE CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11b: HIGH CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4925	-46.63	0	3	2	PK	50.63	74.00	23.37	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
13080.3	-45.2	0	3	2	PK	52.06	87.39	35.33	Note 2	Pass
	N/A		3	2	AV	N/A	67.39	N/A	Note 3	Pass
2461	10.13	0	3	2	PK	107.39	N/A	N/A	Note 1	N/A
	-14.72		3	2	AV	82.54	N/A	N/A		N/A

Test Plots

HIGH CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11g: LOW CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4826	-46.46	0	3	2	PK	50.80	74.00	23.20	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
13696.3	-45.47	0	3	2	PK	51.79	85.63	33.84	Note 2	Pass
	N/A		3	2	AV	N/A	65.63	N/A	Note 3	Pass
2410.5	8.37	0	3	2	PK	105.63	N/A	N/A	Note 1	N/A
	-16.48		3	2	AV	80.78	N/A	N/A		N/A

Test Plots

LOW CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th, 3th, 4th...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11g: MIDDLE CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
21480	-44.67	0	3	2	PK	52.59	86.99	34.40	Note 3	Pass
	N/A		3	2	AV	N/A	66.99	N/A		Pass
14191.3	-44.84	0	3	2	PK	52.42	86.99	34.57	Note 2	Pass
	N/A		3	2	AV	N/A	66.99	N/A	Note 3	Pass
2436	9.73	0	3	2	PK	106.99	N/A	N/A	Note 1	N/A
	-15.12		3	2	AV	82.14	N/A	N/A		N/A

Test Plots

MIDDLE CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11g: HIGH CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4919.5	-46.17	0	3	2	PK	51.09	74.00	22.91	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14202.3	-46.4	0	3	2	PK	50.86	85.10	34.24	Note 2	Pass
	N/A		3	2	AV	N/A	65.10	N/A	Note 3	Pass
2461	7.84	0	3	2	PK	105.10	N/A	N/A	Note 1	N/A
	-17.01		3	2	AV	80.25	N/A	N/A		N/A

Test Plots

HIGH CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11n20: LOW CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4815	-46.71	0	3	2	PK	50.55	74.00	23.45	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14202.3	-44.93	0	3	2	PK	52.33	85.24	32.91	Note 2	Pass
	N/A		3	2	AV	N/A	65.24	N/A	Note 3	Pass
2410	7.98	0	3	2	PK	105.24	N/A	N/A	Note 1	N/A
	-16.87		3	2	AV	80.39	N/A	N/A		N/A

Test Plots

LOW CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11n20: MIDDLE CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4875.5	-46.43	0	3	2	PK	50.83	74.00	23.17	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14746.8	-48.75	0	3	2	PK	48.51	86.75	38.24	Note 2	Pass
	N/A		3	2	AV	N/A	66.75	N/A	Note 3	Pass
2435.5	9.49	0	3	2	PK	106.75	N/A	N/A	Note 1	N/A
	-15.36		3	2	AV	81.90	N/A	N/A		N/A

Test Plots

MIDDLE CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.



Note 4: The harmonic (2th, 3th, 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise

802.11n20: HIGH CHANNEL										
Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
21298.5	-45.7	0	3	2	PK	51.56	74.00	22.44	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14207.8	-45.5	0	3	2	PK	51.76	84.84	33.08	Note 2	Pass
	N/A		3	2	AV	N/A	64.84	N/A	Note 3	Pass
2460.5	7.58	0	3	2	PK	104.84	N/A	N/A	Note 1	N/A
	-17.27		3	2	AV	79.99	N/A	N/A		N/A

Test Plots

HIGH CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th, 3th, 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11n40: LOW CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
21271	-46.98	0	3	2	PK	50.28	74.00	23.72	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14730.3	-44.96	0	3	2	PK	52.30	80.58	28.28	Note 2	Pass
	N/A		3	2	AV	N/A	60.58	N/A	Note 3	Pass
2419.5	3.32	0	3	2	PK	100.58	N/A	N/A	Note 1	N/A
	-21.53		3	2	AV	75.73	N/A	N/A		N/A

Test Plots

LOW CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.

Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (3th, 4th, 5th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise



802.11n40: MIDDLE CHANNEL

Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
4870	-46.56	0	3	2	PK	50.70	74.00	23.30	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
13690.8	-48.74	0	3	2	PK	48.52	84.46	35.94	Note 2	Pass
	N/A		3	2	AV	N/A	64.46	N/A	Note 3	Pass
2439.5	7.2	0	3	2	PK	104.46	N/A	N/A	Note 1	N/A
	-17.65		3	2	AV	79.61	N/A	N/A		N/A

Test Plots

MIDDLE CHANNEL, SPURIOUS 1 GHz ~ 3 GHz

MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



The EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2dBi, whichever is greater.

And the maximum in-band gain of the antenna is 0.49 dBi.

Note 1: The frequency is fundamental signal which can be ignored.

Note 2: Which frequency is not within a restricted band, and its limit line is 20dB below the highest emission level.


Note 3: Average measurement was not performed if peak level went lower than the average limit.

Note 4: The harmonic (2th, 3th, 4th,...etc.) and other spurious are not reported, because those levels are lower than average limit line and background noise


802.11n40: HIGH CHANNEL										
Frequency (MHz)	Value (dBm)	Ground Reflection Factor (dB)	D (m)	Max gain (dBi)	Detector	E (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Verdict
22019	-46.51	0	3	2	PK	50.75	74.00	23.25	Note 3	Pass
	N/A		3	2	AV	N/A	54.00	N/A		Pass
14213.3	-44.47	0	3	2	PK	52.79	84.46	31.67	Note 2	Pass
	N/A		3	2	AV	N/A	64.46	N/A	Note 3	Pass
2454.5	7.2	0	3	2	PK	104.46	N/A	N/A	Note 1	N/A
	-17.65		3	2	AV	79.61	N/A	N/A		N/A

Test Plots

HIGH CHANNEL, SPURIOUS 1 GHz ~ 3 GHz



HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Cabinet Radiated spurious emission test

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: Based on the 1-25GHz test, the below 1GHz test data only reported the worst data in this report.


Note 5: Both model of the charger were tested in this report. The C-P35 (Huntkey) is the main test model, and the C-P35 (Acbel) only retest the below 1GHz in this report which choose the low test channel in the GFSK mode.

Test Data and Plots

CONFIGURATION A+ C-P35 (Huntkey)


Note 1: Based on the 1-25GHz test, the below 1GHz test data only reported the worst data(802.11b Low Channel) in this report.

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	53.27	21.51	-18.80	40.0	18.49	Peak	3.40	100	Horizontal	Pass
2	79.94	23.22	-24.48	40.0	16.78	Peak	8.10	100	Horizontal	Pass
3	171.83	23.05	-22.53	43.5	20.45	Peak	303.20	100	Horizontal	Pass
4	257.65	22.71	-18.70	46.0	23.29	Peak	37.30	100	Horizontal	Pass
5	349.78	27.63	-16.24	46.0	18.37	Peak	283.30	100	Horizontal	Pass
6	437.06	32.50	-14.59	46.0	13.50	Peak	100.40	100	Horizontal	Pass


30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	38.73	22.53	-20.05	40.0	17.47	Peak	133.40	100	Vertical	N/A
2	61.52	23.30	-20.23	40.0	16.70	Peak	88.00	100	Vertical	Pass
3	78.49	23.61	-24.62	40.0	16.39	Peak	318.40	100	Vertical	N/A
4	188.07	21.23	-21.37	43.5	22.27	Peak	0.80	100	Vertical	Pass
5	252.32	25.80	-18.85	46.0	20.20	Peak	102.80	100	Vertical	Pass
6	431.48	40.67	-14.65	46.0	5.33	Peak	28.00	100	Vertical	Pass

1 GHz to 25 GHz, ANT V 802.11b Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2404.15	48.95	-0.28	74.0	25.05	Peak	349.50	100	Vertical	PASS
2	4412.65	51.68	12.43	74.0	22.32	Peak	315.50	100	Vertical	PASS
3	5666.33	53.02	15.42	74.0	20.98	Peak	132.70	100	Vertical	PASS
4	7931.78	47.29	14.71	74.0	26.71	Peak	333.50	100	Vertical	PASS
5	12502.91	51.41	20.20	74.0	22.59	Peak	129.80	100	Vertical	PASS
6	21975.04	49.99	12.44	74.0	24.01	Peak	358.30	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11b Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1830.79	44.91	-3.41	74.0	29.09	Peak	357.10	100	Horizontal	PASS
2	2832.04	49.51	1.78	74.0	24.49	Peak	181.60	100	Horizontal	PASS
3	5666.33	53.02	15.42	74.0	20.98	Peak	132.70	100	Horizontal	PASS
4	7931.78	47.29	14.71	74.0	26.71	Peak	333.50	100	Horizontal	PASS
5	12323.21	51.70	20.64	74.0	22.30	Peak	343.90	100	Horizontal	PASS
6	21885.19	49.65	12.61	74.0	24.35	Peak	326.00	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11b Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	45.81	-2.40	74.0	28.19	Peak	317.40	100	Vertical	PASS
2	2832.04	50.40	1.78	74.0	23.60	Peak	183.10	100	Vertical	PASS
3	4805.55	52.64	13.79	74.0	21.36	Peak	58.10	100	Vertical	PASS
4	8358.57	47.43	15.05	74.0	26.57	Peak	118.40	100	Vertical	PASS
5	12233.36	51.70	20.65	74.0	22.30	Peak	0.30	100	Vertical	PASS
6	22204.66	49.75	12.11	74.0	24.25	Peak	169.10	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11b Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1267.43	44.91	-5.02	74.0	29.09	Peak	73.80	100	Horizontal	PASS
2	2737.07	49.60	1.76	74.0	24.40	Peak	342.50	100	Horizontal	PASS
3	4847.54	52.52	13.62	74.0	21.48	Peak	295.90	100	Horizontal	PASS
4	8358.57	47.43	15.05	74.0	26.57	Peak	118.40	100	Horizontal	PASS
5	12233.36	51.70	20.65	74.0	22.30	Peak	0.30	100	Horizontal	PASS
6	19309.48	51.21	13.46	74.0	22.79	Peak	57.20	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11b High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	46.10	-2.40	74.0	27.90	Peak	318.20	100	Vertical	PASS
2	2832.04	50.26	1.78	74.0	23.74	Peak	182.10	100	Vertical	PASS
3	4805.55	52.60	13.79	74.0	21.40	Peak	57.60	100	Vertical	PASS
4	8358.57	47.43	15.05	74.0	26.57	Peak	118.40	100	Vertical	PASS
5	12233.36	51.70	20.65	74.0	22.30	Peak	0.30	100	Vertical	PASS
6	19309.48	51.21	13.46	74.0	22.79	Peak	57.20	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11b High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1267.43	45.61	-5.02	74.0	28.39	Peak	73.40	100	Horizontal	PASS
2	2404.65	49.47	-0.31	74.0	24.53	Peak	347.90	100	Horizontal	PASS
3	4738.81	52.95	13.53	74.0	21.05	Peak	287.80	100	Horizontal	PASS
4	8785.36	47.70	16.37	74.0	26.30	Peak	5.00	100	Horizontal	PASS
5	11975.04	51.81	20.76	74.0	22.19	Peak	69.00	100	Horizontal	PASS
6	19169.72	50.73	14.01	74.0	23.27	Peak	335.20	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11g Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1823.79	44.89	-3.42	74.0	29.11	Peak	278.90	100	Vertical	PASS
2	2832.04	50.38	1.78	74.0	23.62	Peak	182.40	100	Vertical	PASS
3	4732.82	53.10	13.68	74.0	20.90	Peak	356.30	100	Vertical	PASS
4	8425.96	47.20	15.06	74.0	26.80	Peak	71.50	100	Vertical	PASS
5	11649.33	52.11	20.41	74.0	21.89	Peak	0.20	100	Vertical	PASS
6	22124.79	49.79	12.22	74.0	24.21	Peak	56.90	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11g Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2002.75	46.46	-2.35	74.0	27.54	Peak	265.00	100	Horizontal	PASS
2	2737.07	49.58	1.76	74.0	24.42	Peak	343.20	100	Horizontal	PASS
3	4738.81	52.56	13.53	74.0	21.44	Peak	287.80	100	Horizontal	PASS
4	8425.96	47.20	15.06	74.0	26.80	Peak	71.50	100	Horizontal	PASS
5	11975.04	51.74	20.76	74.0	22.26	Peak	69.40	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11g Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	46.16	-2.40	74.0	27.84	Peak	316.90	100	Vertical	PASS
2	2831.54	49.27	1.81	74.0	24.73	Peak	183.10	100	Vertical	PASS
3	4732.82	53.05	13.68	74.0	20.95	Peak	357.40	100	Vertical	PASS
4	8425.96	47.20	15.06	74.0	26.80	Peak	71.50	100	Vertical	PASS
5	11649.33	52.10	20.41	74.0	21.90	Peak	0.30	100	Vertical	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11g Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1600.85	44.02	-4.33	74.0	29.98	Peak	29.60	100	Horizontal	PASS
2	2404.65	49.55	-0.31	74.0	24.45	Peak	348.90	100	Horizontal	PASS
3	4805.55	52.69	13.79	74.0	21.31	Peak	58.00	100	Horizontal	PASS
4	8785.36	47.71	16.37	74.0	26.29	Peak	5.20	100	Horizontal	PASS
5	12008.74	51.82	20.87	74.0	22.18	Peak	311.70	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11g High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1603.35	44.40	-4.38	74.0	29.60	Peak	359.60	100	Vertical	PASS
2	2399.65	49.17	-0.35	74.0	24.83	Peak	348.80	100	Vertical	PASS
3	4732.82	53.06	13.68	74.0	20.94	Peak	356.00	100	Vertical	PASS
4	8425.96	47.60	15.06	74.0	26.40	Peak	71.70	100	Vertical	PASS
5	11649.33	52.11	20.41	74.0	21.89	Peak	-0.50	100	Vertical	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11g High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2002.75	46.39	-2.35	74.0	27.61	Peak	265.30	100	Horizontal	PASS
2	2832.04	50.21	1.78	74.0	23.79	Peak	182.10	100	Horizontal	PASS
3	5666.33	52.51	15.42	74.0	21.49	Peak	132.10	100	Horizontal	PASS
4	8841.51	47.64	16.58	74.0	26.36	Peak	307.10	100	Horizontal	PASS
5	12323.21	52.11	20.64	74.0	21.89	Peak	344.00	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n20 Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	46.23	-2.40	74.0	27.77	Peak	316.50	100	Vertical	PASS
2	2831.54	49.75	1.81	74.0	24.25	Peak	183.20	100	Vertical	PASS
3	4732.82	52.81	13.68	74.0	21.19	Peak	356.30	100	Vertical	PASS
4	8358.57	47.43	15.05	74.0	26.57	Peak	119.00	100	Vertical	PASS
5	12323.21	52.11	20.64	74.0	21.89	Peak	344.00	100	Vertical	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11n20 Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1267.43	45.32	-5.02	74.0	28.68	Peak	73.40	100	Horizontal	PASS
2	2401.15	48.94	-0.23	74.0	25.06	Peak	348.70	100	Horizontal	PASS
3	4652.59	52.34	13.09	74.0	21.66	Peak	118.60	100	Horizontal	PASS
4	8358.57	47.43	15.05	74.0	26.57	Peak	119.00	100	Horizontal	PASS
5	12323.21	52.11	20.64	74.0	21.89	Peak	344.00	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n20 Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	46.04	-2.40	74.0	27.96	Peak	316.50	100	Vertical	PASS
2	2832.04	49.55	1.78	74.0	24.45	Peak	182.00	100	Vertical	PASS
3	4732.82	52.70	13.68	74.0	21.30	Peak	356.40	100	Vertical	PASS
4	8785.36	47.17	16.37	74.0	26.83	Peak	5.00	100	Vertical	PASS
5	12132.28	51.82	20.73	74.0	22.18	Peak	136.00	100	Vertical	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11n20 Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	46.04	-2.40	74.0	27.96	Peak	316.50	100	Horizontal	PASS
2	2831.54	49.51	1.81	74.0	24.49	Peak	183.20	100	Horizontal	PASS
3	4805.55	52.64	13.79	74.0	21.36	Peak	58.80	100	Horizontal	PASS
4	8425.96	47.63	15.06	74.0	26.37	Peak	71.90	100	Horizontal	PASS
5	12008.74	51.97	20.87	74.0	22.03	Peak	311.00	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n20 High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1830.79	44.81	-3.41	74.0	29.19	Peak	356.10	100	Vertical	PASS
2	2404.15	48.91	-0.28	74.0	25.09	Peak	348.70	100	Vertical	PASS
3	4805.55	52.64	13.79	74.0	21.36	Peak	58.80	100	Vertical	PASS
4	8785.36	47.78	16.37	74.0	26.22	Peak	3.90	100	Vertical	PASS
5	12233.36	51.77	20.65	74.0	22.23	Peak	-0.70	100	Vertical	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11n20 High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1603.35	44.50	-4.38	74.0	29.50	Peak	359.40	100	Horizontal	PASS
2	2405.15	49.40	-0.24	74.0	24.60	Peak	329.80	100	Horizontal	PASS
3	5666.33	53.13	15.42	74.0	20.87	Peak	132.10	100	Horizontal	PASS
4	8358.57	47.35	15.05	74.0	26.65	Peak	118.70	100	Horizontal	PASS
5	12008.74	52.06	20.87	74.0	21.94	Peak	311.90	100	Horizontal	PASS
6	19309.48	50.93	13.46	74.0	23.07	Peak	56.40	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n40 Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1830.79	44.81	-3.41	74.0	29.19	Peak	357.00	100	Vertical	PASS
2	2832.04	50.15	1.78	74.0	23.85	Peak	183.10	100	Vertical	PASS
3	4738.81	52.99	13.53	74.0	21.01	Peak	288.30	100	Vertical	PASS
4	8425.96	46.93	15.06	74.0	27.07	Peak	71.10	100	Vertical	PASS
5	11975.04	51.78	20.76	74.0	22.22	Peak	69.20	100	Vertical	PASS
6	19219.63	50.85	14.00	74.0	23.15	Peak	357.90	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11n40 Low Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1410.40	44.54	-4.62	74.0	29.46	Peak	253.00	100	Horizontal	PASS
2	2401.15	49.30	-0.23	74.0	24.70	Peak	348.50	100	Horizontal	PASS
3	4738.81	52.99	13.53	74.0	21.01	Peak	288.30	100	Horizontal	PASS
4	8358.57	47.38	15.05	74.0	26.62	Peak	117.90	100	Horizontal	PASS
5	12323.21	52.20	20.64	74.0	21.80	Peak	344.60	100	Horizontal	PASS
6	19309.48	51.11	13.46	74.0	22.89	Peak	58.10	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n40 Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2002.75	46.49	-2.35	74.0	27.51	Peak	264.20	100	Vertical	PASS
2	2831.54	49.83	1.81	74.0	24.17	Peak	183.40	100	Vertical	PASS
3	4733.57	52.59	13.61	74.0	21.41	Peak	355.90	100	Vertical	PASS
4	11121.46	51.48	20.22	74.0	22.52	Peak	200.30	100	Vertical	PASS
5	16181.78	48.84	11.19	74.0	25.16	Peak	118.90	100	Vertical	PASS
6	19309.48	51.11	13.46	74.0	22.89	Peak	58.10	100	Vertical	PASS

1 GHz to 25 GHz, ANT H 802.11n40 Middle Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1921.77	45.75	-2.40	74.0	28.25	Peak	318.00	100	Horizontal	PASS
2	2832.04	50.38	1.78	74.0	23.62	Peak	183.00	100	Horizontal	PASS
3	4733.57	52.59	13.61	74.0	21.41	Peak	355.90	100	Horizontal	PASS
4	9964.64	49.99	19.25	74.0	24.01	Peak	226.50	100	Horizontal	PASS
5	16327.37	48.51	11.70	74.0	25.49	Peak	155.80	100	Horizontal	PASS
6	19149.75	50.70	13.93	74.0	23.30	Peak	356.50	100	Horizontal	PASS

1 GHz to 25 GHz, ANT V 802.11n40 High Channel


RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1239.44	43.23	-5.19	74.0	30.77	Peak	227.00	100	Vertical	Pass
2	2785.05	48.52	1.62	74.0	25.48	Peak	198.00	100	Vertical	Pass
3	4699.07	51.62	13.27	74.0	22.38	Peak	86.00	100	Vertical	Pass
4	8819.05	47.49	16.51	74.0	26.51	Peak	265.00	100	Vertical	Pass
5	12019.97	50.79	20.86	74.0	23.21	Peak	11.00	100	Vertical	Pass
6	21915.14	49.17	12.55	74.0	24.83	Peak	246.00	100	Vertical	Pass

1 GHz to 25 GHz, ANT H 802.11n40 High Channel

RE Test case_FCC 15C 1GHz-25GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1219.94	43.76	-5.21	74.0	30.24	Peak	103.00	100	Horizontal	Pass
2	2195.20	46.40	-0.56	74.0	27.60	Peak	351.00	100	Horizontal	Pass
3	4504.12	51.16	12.69	74.0	22.84	Peak	296.00	100	Horizontal	Pass
4	9279.53	47.84	16.96	74.0	26.16	Peak	94.00	100	Horizontal	Pass
5	12109.82	50.94	20.76	74.0	23.06	Peak	212.00	100	Horizontal	Pass
6	18989.60	49.64	13.30	74.0	24.36	Peak	222.00	100	Horizontal	Pass

Test Frequency: 25 GHz ~ 40 GHz


Note: Only noise floor was seen above 25 GHz and not reported.

Restricted-band band-edge


802.11b LOW CHANNEL , PEAK




802.11b HIGH CHANNEL , PEAK




802.11g LOW CHANNEL , PEAK




802.11g HIGH CHANNEL , PEAK



802.11n-20 LOW CHANNEL , PEAK




802.11n-20 HIGH CHANNEL , PEAK




802.11n-40 LOW CHANNEL , PEAK

802.11n-40 HIGH CHANNEL , PEAK



Date: 22.JAN.2016 09:18:37




Date: 22.JAN.2016 09:20:53

CONFIGURATION B+ C-P35 (Acbel)

Note 1: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note 2: Based on the test result of EUT 1, the EUT 2 only retest the worst mode (802.11b Low Channel) in this report.

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	33.15	26.96	-23.06	40.0	13.04	Peak	327.10	100	Horizontal	Pass
2	49.88	26.04	-20.13	40.0	13.96	Peak	321.70	100	Horizontal	Pass
3	54.73	24.26	-20.36	40.0	15.74	Peak	252.30	100	Horizontal	Pass
4	127.46	28.82	-25.03	43.5	14.68	Peak	111.10	100	Horizontal	Pass
5	199.71	29.42	-22.77	43.5	14.08	Peak	4.50	100	Horizontal	Pass
6	414.51	28.01	-18.45	46.0	17.99	Peak	215.80	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	33.15	27.30	-23.06	40.0	12.70	Peak	326.30	100	Vertical	Pass
2	49.88	25.77	-20.13	40.0	14.23	Peak	321.20	100	Vertical	Pass
3	127.46	27.53	-25.03	43.5	15.97	Peak	111.50	100	Vertical	Pass
4	199.71	29.26	-22.77	43.5	14.24	Peak	3.50	100	Vertical	Pass
5	414.27	27.47	-18.42	46.0	18.53	Peak	217.00	100	Vertical	Pass
6	696.95	26.74	-14.01	46.0	19.26	Peak	0.60	100	Vertical	Pass

Note 1: All configuration were pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 2: Based on the test result of EUT 1, the EUT 2 only retest the worst mode (802.11b Low Channel) in this report.


1 GHz to 25 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1221.94	44.11	-5.16	74.0	29.89	Peak	207.90	100	Vertical	Pass
2	2756.06	48.42	1.87	74.0	25.58	Peak	199.70	100	Vertical	Pass
3	4500.37	52.68	12.69	74.0	21.32	Peak	205.20	100	Vertical	Pass
4	5954.26	51.93	15.89	74.0	22.07	Peak	170.60	100	Vertical	Pass
5	12053.66	52.47	20.82	74.0	21.53	Peak	205.80	100	Vertical	Pass
6	19139.77	50.75	13.90	74.0	23.25	Peak	195.50	100	Vertical	Pass

1 GHz to 25 GHz, ANT H

RE Test case_FCC 15C 1GHz-25GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	2467.13	48.34	-0.47	74.0	25.66	Peak	8.00	100	Horizontal	PASS
2	4828.04	51.95	13.74	74.0	22.05	Peak	359.40	100	Horizontal	PASS
3	5981.26	52.00	15.81	74.0	22.00	Peak	117.20	100	Horizontal	PASS
4	11020.38	51.46	20.14	74.0	22.54	Peak	285.90	100	Horizontal	PASS
5	12042.43	51.52	20.83	74.0	22.48	Peak	216.60	100	Horizontal	PASS
6	19209.65	49.93	14.06	74.0	24.07	Peak	30.20	100	Horizontal	PASS

Test Frequency: 25 GHz ~ 40 GHz

Note: Only noise floor was seen above 25 GHz and not reported.

A.7 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-10.50	8
Middle	-10.35	8
High	-10.08	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-15.21	8
Middle	-12.74	8
High	-15.58	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-14.63	8
Middle	-14.40	8
High	-16.05	8

802.11n-40 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-19.55	8
Middle	-13.82	8
High	-18.45	8

Test plots

802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




802.11 n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL




A.8 Receiver Spurious Emissions

Note: Based on the worst test results of CONFIGURATION A and CONFIGURATION B, the CONFIGURATION A (802.11b model) were recorded in this report.


Test Data and Plots

30 MHz to 1 GHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	38.73	22.53	-20.05	40.0	17.47	Peak	133.40	100	Vertical	Pass
2	61.52	23.30	-20.23	40.0	16.70	Peak	88.00	100	Vertical	Pass
3	78.49	23.61	-24.62	40.0	16.39	Peak	318.40	100	Vertical	Pass
4	188.07	21.23	-21.37	43.5	22.27	Peak	0.80	100	Vertical	Pass
5	252.32	25.80	-18.85	46.0	20.20	Peak	102.80	100	Vertical	Pass
6	431.48	40.67	-14.65	46.0	5.33	Peak	28.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	53.27	21.51	-18.80	40.0	18.49	Peak	3.40	100	Horizontal	Pass
2	79.94	23.22	-24.48	40.0	16.78	Peak	8.10	100	Horizontal	Pass
3	171.83	23.05	-22.53	43.5	20.45	Peak	303.20	100	Horizontal	Pass
4	257.65	22.71	-18.70	46.0	23.29	Peak	37.30	100	Horizontal	Pass
5	349.78	27.63	-16.24	46.0	18.37	Peak	283.30	100	Horizontal	Pass
6	437.06	32.50	-14.59	46.0	13.50	Peak	100.40	100	Horizontal	Pass

1 GHz to 6 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1183.95	44.66	-5.55	74.0	29.34	Peak	124.70	100	Vertical	Pass
2	1649.84	42.69	-4.05	74.0	31.31	Peak	143.90	100	Vertical	Pass
3	2203.70	47.50	-0.40	74.0	26.50	Peak	169.30	100	Vertical	Pass
4	2958.51	47.85	2.44	74.0	26.15	Peak	16.70	100	Vertical	Pass
5	3836.04	47.96	10.95	74.0	26.04	Peak	352.20	100	Vertical	Pass
6	4670.58	53.01	13.09	74.0	20.99	Peak	107.20	100	Vertical	Pass

1 GHz to 6 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1261.43	43.84	-5.17	74.0	30.16	Peak	207.50	100	Horizontal	Pass
2	1767.81	44.12	-3.77	74.0	29.88	Peak	99.30	100	Horizontal	Pass
3	2283.18	47.21	-0.58	74.0	26.79	Peak	169.30	100	Horizontal	Pass
4	2712.57	48.60	1.46	74.0	25.40	Peak	99.30	100	Horizontal	Pass
5	3602.85	48.12	9.95	74.0	25.88	Peak	111.60	100	Horizontal	Pass
6	4483.13	51.89	12.62	74.0	22.11	Peak	297.40	100	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1610062-AR.pdf".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1610062-AW.pdf".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1610062-AI.pdf".

--END OF REPORT--