



FCC Test Report

APPLICANT : Lenovo(Shanghai) Electronics
Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
MODEL NAME : Lenovo TB-7305X
FCC ID : O57TB7305X
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jul. 16, 2019 and testing was completed on Aug. 13, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 7

 1.7. Applicable Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system 10

 2.4. EUT Operation Test Setup 11

3. TEST RESULT 12

 3.1. Test of AC Conducted Emission Measurement 12

 3.2. Test of Radiated Emission Measurement 16

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC971618	Rev. 01	Initial issue of report	Aug. 27, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 7.24 dB at 0.486 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.12 dB at 959.900 MHz for Quasi-Peak



1. General Description

1.1. Applicant

Lenovo(Shanghai) Electronics Technology Co., Ltd.
Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

1.2. Manufacturer

Lenovo PC HK Limited
23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong P.R.China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Portable Tablet Computer
Brand Name	Lenovo
Model Name	Lenovo TB-7305X
FCC ID	O57TB7305X
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth BR/EDR/LE GNSS/FM Receiver
IMEI Code	Conduction: 861235040006207 for Sample1 861235040010092 for Sample2 861235040006389 for Sample3 Radiation: 861235040005860 for Sample1 861235040009813 for Sample2 861235040006405 for Sample3
HW Version	Lenovo Tablet TB-7305X
SW Version	TB-7305X_RF01_190806
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are three types of EUT: sample 1, sample 2 and sample 3, for change note, please refer the product equality declaration exhibit submitted. According to the difference, we evaluate the sample 1 to full test and the sample 2/3 is verified difference.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM: 88 MHz - 108 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna FM : External Earphone Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (Uplink) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

Note:

1. GNSS Rx = GLONASS + GPS
2. WLAN operation in 5600 MHz ~ 5650 MHz is notched.



1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-KS CO01-KS	CN1257	314309

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Rx(Middle channel) + USB Cable 1(Charging from Adapter 1)+ Earphone + Bluetooth Idle + Camera(Rear) + WLAN (2.4G) Idle + Battery 1 for Sample 1
	Mode 2: PCS1900 Rx + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + Camera(Front) + WLAN (5G) Idle + Battery 1 for Sample 1
	Mode 3: WCDMA Band II Rx + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + MPEG4 + WLAN (2.4G) Idle + Battery 1 for Sample 1
	Mode 4: WCDMA Band V Rx(Low channel) + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + FM Rx(98MHz) + WLAN (5G) Idle + Battery 1 for Sample 1
	Mode 5: LTE Band 4 Rx + USB Cable 1(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (2.4G) Idle + Battery 1 for Sample 1
	Mode 6: LTE Band 7 Rx + USB Cable 2(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (5G) Idle + Battery 1 for Sample 1
	Mode 7: PCS1900 Rx + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + Camera(Front) + WLAN (5G) Idle + Battery 2 for Sample 2
	Mode 8: LTE Band 7 Rx + USB Cable 2(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (5G) Idle + Battery 2 for Sample 2
	Mode 9: LTE Band 7 Rx + USB Cable 2(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (5G) Idle + Battery 1 for Sample 3

Radiated Emissions	<p>Mode 1: GSM850 Rx(Middle channel) + USB Cable 1(Charging from Adapter 1)+ Earphone + Bluetooth Idle + Camera(Rear) + WLAN (2.4G) Idle + Battery 1 for Sample 1</p> <p>Mode 2: PCS1900 Rx + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + Camera(Front) + WLAN (5G) Idle + Battery 1 for Sample 1</p> <p>Mode 3: WCDMA Band II Rx + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + MPEG4 + WLAN (2.4G) Idle + Battery 1 for Sample 1</p> <p>Mode 4: WCDMA Band V Rx(Low channel) + USB Cable 2(Charging from Adapter 2)+ Earphone + Bluetooth Idle + FM Rx(88MHz) + WLAN (5G) Idle + Battery 1 for Sample 1</p> <p>Mode 5: LTE Band 4 Rx + USB Cable 1(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (2.4G) Idle + Battery 1 for Sample 1</p> <p>Mode 6: LTE Band 7 Rx + USB Cable 2(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (5G) Idle + Battery 1 for Sample 1</p> <p>Mode 7: LTE Band 4 Rx + USB Cable 1(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (2.4G) Idle + Battery 2 for Sample 2</p> <p>Mode 8: LTE Band 4 Rx + USB Cable 1(Data Link with Notebook)+ Earphone + Bluetooth Idle + Camera(Front) + WLAN (2.4G) Idle + Battery 2 for Sample 2</p> <p>Mode 9: LTE Band 4 Rx + USB Cable 1(Data Link with Notebook)+ Earphone + Bluetooth Idle + GNSS Rx + WLAN (2.4G) Idle + Battery 1 for Sample 3</p>
<p>Remark:</p> <ol style="list-style-type: none"> 1. The worst case of AC is mode 7; only the test data of this mode is reported. 2. The worst case of RE is mode 8; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 4. Pre-scanned Low/Middle/High channel for GSM850/WCDMA Band V, FM Rx, the worst channel was recorded in this report 	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
4.	WLAN AP	D-Link	DIR-618	N/A	N/A	Unshielded, 1.8m
5.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded, 1.8m
6.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
7.	Notebook	Dell	Latitude3440	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
8.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
9.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
10.	Earphone	Lenovo	P121	N/A	N/A	Unshielded, 1.2m
11.	Hard disk	Lenovo	FH310	Fcc DoC	Shielded, 1.2m	N/A
12.	SD Card	Kingston	8GB	N/A	N/A	N/A
13.	SD Card	SanDisk	Ultra	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.
5. Turn on FM receiver function to make the EUT receive continuous signals from FM station.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup






3.1.5 Test Result of AC Conducted Emission





Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-181119-060105 NEUTRAL
 Project : (FC) 971618
 mode : Mode 7

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.486	48.99	-7.24	56.23	38.60	0.15	10.24	QP
2	0.486	36.69	-9.54	46.23	26.30	0.15	10.24	Average
3	0.518	35.98	-20.02	56.00	25.59	0.15	10.24	QP
4	0.518	22.58	-23.42	46.00	12.19	0.15	10.24	Average
5	0.601	41.88	-14.12	56.00	31.50	0.14	10.24	QP
6	0.601	30.58	-15.42	46.00	20.20	0.14	10.24	Average
7	1.043	37.56	-18.44	56.00	27.20	0.13	10.23	QP
8	1.043	23.86	-22.14	46.00	13.50	0.13	10.23	Average
9	1.636	37.97	-18.03	56.00	27.60	0.14	10.23	QP
10	1.636	27.27	-18.73	46.00	16.90	0.14	10.23	Average
11	2.513	35.89	-20.11	56.00	25.49	0.16	10.24	QP
12	2.513	25.29	-20.71	46.00	14.89	0.16	10.24	Average



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.1.6 Test Result of Radiated Emission

Test Engineer :	Carl Ni	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 49922-3M HORIZONTAL
 Project : (FC)971618
 Mode : 8

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBUV/m	Limit	Line	Level	Factor	Loss	Factor	cm	deg	
			dB	dBUV/m	dBuV	dB/m	dB	dB			
1	191.99	29.47	-14.03	43.50	44.35	15.43	1.60	31.91	---	---	Peak
2	223.03	29.47	-16.53	46.00	42.90	16.76	1.74	31.93	---	---	Peak
3	359.80	33.31	-12.69	46.00	42.42	20.85	2.13	32.09	---	---	Peak
4 !	480.08	42.88	-3.12	46.00	48.93	23.70	2.49	32.24	---	---	Peak
5	659.53	33.12	-12.88	46.00	35.93	26.62	2.93	32.36	---	---	Peak
6 !	959.90	42.21	-3.79	46.00	38.72	30.82	3.56	30.89	100	26	QP
7	3816.00	43.48	-30.52	74.00	34.62	33.63	7.24	32.01	---	---	Peak
8	5856.00	44.26	-29.74	74.00	31.81	34.90	9.02	31.47	---	---	Peak
9	6432.00	44.68	-29.32	74.00	31.55	35.18	9.54	31.59	---	---	Peak
10	7160.00	44.96	-29.04	74.00	30.77	35.58	10.07	31.46	---	---	Peak
11	7784.00	45.04	-28.96	74.00	30.12	36.14	10.80	32.02	---	---	Peak
12	8472.00	45.51	-28.49	74.00	29.77	36.49	11.20	31.95	---	---	Peak



Test Engineer :	Carl Ni	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 49922-3M VERTICAL
 Project : (FC)971618
 Mode : 8

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	45.52	27.70	-12.30	40.00	42.23	16.63	0.78	31.94	---	---	Peak
2	384.05	30.34	-15.66	46.00	38.75	21.49	2.20	32.10	---	---	Peak
3 !	480.08	42.45	-3.55	46.00	48.50	23.70	2.49	32.24	100	65	QP
4	645.95	36.37	-9.63	46.00	39.28	26.55	2.90	32.36	---	---	Peak
5	659.53	38.19	-7.81	46.00	41.00	26.62	2.93	32.36	---	---	Peak
6 !	959.90	42.88	-3.12	46.00	39.39	30.82	3.56	30.89	100	62	QP
7	3800.00	42.66	-31.34	74.00	33.83	33.62	7.22	32.01	---	---	Peak
8	5056.00	44.22	-29.78	74.00	33.03	33.96	8.44	31.21	---	---	Peak
9	5528.00	44.35	-29.65	74.00	32.00	34.55	8.84	31.04	---	---	Peak
10	6840.00	44.82	-29.18	74.00	31.05	35.30	9.90	31.43	---	---	Peak
11	7232.00	45.74	-28.26	74.00	31.48	35.73	10.12	31.59	---	---	Peak
12	8256.00	45.69	-28.31	74.00	30.33	36.31	11.05	32.00	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 16, 2019	Aug. 13, 2019	Apr. 15, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Aug. 13, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Aug. 13, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Aug. 13, 2019	Oct. 11, 2019	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max x 30dBm	Aug. 05, 2019	Aug. 09, 2019	Aug. 04, 2020	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2019	Aug. 09, 2019	Apr. 16, 2020	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Dec. 29, 2018	Aug. 09, 2019	Dec. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Aug. 09, 2019	Jan. 26, 2020	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Aug. 09, 2019	Jan. 04, 2020	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2019	Aug. 09, 2019	Aug. 05, 2020	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5G Hz	Apr. 15, 2019	Aug. 09, 2019	Apr. 14, 2020	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Jan. 14, 2019	Aug. 09, 2019	Jan. 13, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 09, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 09, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 09, 2019	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------