

EMC TEST REPORT

Applicant:	Lenovo(Shanghai) Electronics Technology Co., Ltd.
Address:	NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

Manufacturer or Supplier:	Lenovo PC HK Limited
Address:	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong
Product:	Portable Tablet Computer
Brand Name:	Lenovo
Model Name:	Lenovo TB-X705F
FCC ID:	O57TBX705F
Date of tests:	Jul. 25, 2018 ~ Sep. 27, 2018

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☒ **FCC Part 15, Subpart B, Class B**
- ☒ **ANSI C63.4:2014**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Issued by Alex Chen Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department
	
Date: Sep. 28, 2018	Date: Sep. 28, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT.....	4
1.2 SUMMARY OF TEST RESULTS.....	6
1.3 MEASUREMENT UNCERTAINTY.....	7
1.4 DESCRIPTION OF TEST MODES.....	8
1.5 DESCRIPTION OF SUPPORT UNITS.....	9
2 EMISSION TEST	10
2.1 CONDUCTED EMISSION MEASUREMENT.....	10
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
2.1.2 TEST INSTRUMENTS.....	10
2.1.3 TEST PROCEDURES	11
2.1.4 DEVIATION FROM TEST STANDARD	11
2.1.5 TEST SETUP.....	12
2.1.6 EUT OPERATING CONDITIONS	12
2.1.7 TEST RESULTS	13
2.2 RADIATED EMISSION MEASUREMENT.....	15
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
2.2.2 TEST INSTRUMENTS.....	17
2.2.3 TEST PROCEDURE.....	18
2.2.4 DEVIATION FROM TEST STANDARD	19
2.2.5 TEST SETUP.....	20
2.2.6 EUT OPERATING CONDITIONS	20
2.2.7 TEST RESULTS	21
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	25



Test Report No.: FV180927W004R1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FC180528C19	Original release	Jun. 14, 2018
FV180927W004	Based on the original report FC180528C19 remove two adapters, add Lenovo Smart Dock and its adapter	Sep. 28, 2018

Remarks: Original release FC180528C19 Reporting and testing conducted in Taiwan

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Portable Tablet Computer	
BRAND NAME	Lenovo	
MODEL NAME	Lenovo TB-X705F	
NOMINAL VOLTAGE	5.0Vdc from Dock 3.85Vdc (Li-ion)	
MODULATION TYPE	WLAN	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
	BT_LE	BT-LE(GFSK) for DTS
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	GPS/ GLONASS	C/A code
	FM	FSK
OPERATING FREQUENCY	WLAN	2412-2472MHz for 11b/g/n(HT20) 2422-2462MHz for 11n(HT40) 5180 ~ 5320MHz, 5500 ~ 5700, 5745 ~ 5825MHz for 11a/n(HT20)/n(HT40)/ac(80MHz)
	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	GPS	1575.42MHz
	GLONASS	1602MHz
	FM	87.5MHz ~ 108MHz
HW VERSION	Lenovo Tablet TB-X705F	
SW VERSION	TB-X705F_RF01_20180518	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable: shielded, detachable, 1.0meter	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



2. There were Sample A, B, C and D for this project, the difference is as below:

SAMPLE	EUT CONFIGURATION INFORMATION
A	LCD Panel 1+Photo Camera 1+Photo Camera 3+CPU1+EMMC1+DDR1+speaker
B	LCD Panel 1+Photo Camera 1+Photo Camera 3+CPU1+EMMC3+DDR3+speaker
C	LCD Panel 2+Photo Camera 2+Photo Camera 4+CPU 1+EMMC2+DDR2+speaker
D	LCD Panel 2+Photo Camera 2+Photo Camera 4+CPU 1+EMMC4+DDR4+speaker

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

LIST OF ACCESSORIES:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery 1	SCUD	L16D2P31	Rating: 3.85Vdc, 7000mAh
Battery 2	Celxpert	L16D2P31	Rating: 3.85Vdc, 7000mAh
LCD Panel1	BOE	TV101WUM-LL0/TV101WUM-LL1	10.1 "
LCD Panel2	INNOLUX	P101KZD-AF0/P101KZD-AF1	10.1 "
EMMC1+DDR1	SAMSUNG	KMGD6001BM-B421(3+32)	32G
EMMC2+DDR2	HYNIX	H9TQ26ADFTBCUR-KUM(3+32)	32G
EMMC3+DDR3	SAMSUNG	KMRH60014A-B614(4+64)	64G
EMMC4+DDR4	HYNIX	H9TQ52ACLTMCUR-KUM(4+64)	64G
Speaker	Keysound	QM171219AM48	-
motor1	AWA	YK2455R	-
Motor2	Baolong	BLX-431320S	-
Photo Camera 1	O-film	L8856A00	8M AF
Photo Camera 2	Q-tech	F8856CB	8M AF
Photo Camera 3	Lcetron	LE5132FM	5M AF
Photo Camera 4	Holitech	MF80G	5M AF
CPU	Qualcomm	SDA-450-A-792NSP-TR-01-0-AA	792nsp
Main Broad 1	huashen	W92ME1B3-3-03	-
Main Broad 2	yilianda	W92ME1B3-3-05	-
BT/WLAN Module	Qualcomm	WCN-3680B-0-79BWLNSP	-
AC Adapter 1 (For Dock)	XinSPower	A241-1202000B, A241-1202000E	I/P:100-240Vac, 800mA O/P: 12Vdc, 2000mA
Lenovo Smart Dock	Lenovo	Lenovo HA-200	I/P:12Vac, 2000mA O/P: 5Vdc, 1500mA
USB Cable 1(White)	LiQi	LQ-02300039	1.0m shielded cable w/o core
USB Cable 2(Black)	LiQi	LQ-02300040	1.0m shielded cable w/o core

Remark: USB cabel 1 and USB cable 2 is identical, difference models are for color distinguished. Therefore, only USB cable 1 is as a representative for final test.



Test Report No.: FV180927W004R1

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B				
Standard Section	Test Item	Result	Remark	Test Lab*
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	PASS	Meets limits minimum passing margin is -22.08dB at 7.776000MHz.	A
	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -12.28dB at 43.1442MHz	B
	Radiated Emission Test (Above 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -12.04dB at 3250MHz	A

*Test Lab Information Reference

Lab A:

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Address:

No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Accredited Test Lab Cert 3939.01

Lab B:

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch.

Lab Address:

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Accredited Test Lab Cert 2951.01

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	+/-2.66dB
Radiated emissions	30MHz ~ 1GHz	+/-3.26dB
	1GHz ~ 18GHz	+/-4.48dB

1.4 DESCRIPTION OF TEST MODES

For Radiated Emission evaluation, 230Vac/50Hz & 120/60Hz had been covered during the pre-test. The worst data was found at **230Vac/50Hz** and recorded in the applied test report.

For Conducted Emission evaluation, 230Vac/50Hz & 120/60Hz had been covered during the pre-test. The worst data was found at **230Vac/50Hz** and recorded in the applied test report.

Test Mode	Test Condition
Radiated emission test	
1	AC Adapter 1(For Dock) + Sample A# + Front Camera On + Earphone + BT Idel + WIFI 2.4g Idel + GPS Rx +Dock
2	AC Adapter 1(For Dock) + Sample B# + Back Camera On + Earphone + BT Idle + WIFI 5g Idle+ Glonass Rx +Dock
3	AC Adapter 1(For Dock) + Sample C# + MPG4 + Earphone + BT Idel + WIFI 2.4g Idel + Glonass Rx +Dock
4	AC Adapter 1(For Dock) + Sample D# + FM RX + Earphone + BT Idel + WIFI 5g Idel + GPS Rx +Dock
5	USB Link+ PC To EUT(Sample B)+Data Trasmission +Glonass Rx+ BT Idel+ WIFI 2.4G Idel+ Earphone
6	USB Link+ EUT To PC(Sample D)+ Data Trasmission +GPS Rx+ BT Idel+ WIFI 5G Idel+ Earphone
Conducted emission test	
1	AC Adapter 1(For Dock) + Sample A# + Front Camera On + Earphone + BT Idel + WIFI 2.4g Idel + GPS Rx +Dock
2	AC Adapter 1(For Dock) + Sample B# + Back Camera On + Earphone + BT Idle + WIFI 5g Idle+ Glonass Rx +Dock
3	AC Adapter 1(For Dock) + Sample C# + MPG4 + Earphone + BT Idel + WIFI 2.4g Idel + Glonass Rx +Dock
4	AC Adapter 1(For Dock) + Sample D# + FM RX + Earphone + BT Idel + WIFI 5g Idel + GPS Rx +Dock
5	USB Link+ PC To EUT(Sample B)+Data Trasmission +Glonass Rx+ BT Idel+ WIFI 2.4G Idel+ Earphone
6	USB Link+ EUT To PC(Sample D)+ Data Trasmission +GPS Rx+ BT Idel+ WIFI 5G Idel+ Earphone
NOTE: - For conducted emission test, test mode 1 was the worst case and only this mode was presented in this report. - For radiated emission test, test mode 5 was the worst case and only this mode was presented in this report.	

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR EMISSION TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Wireless AP	ABOCOM	WR224GR	060500749P	N/A
2	Bluetooth Earphone	FAP00	H6080	12098	N/A
3	GPS Simulator	Spetctracom/USA	GSG-5	200782	N/A
4	FM signal generator	Rohde&Schwarz	SMB100A	109279	N/A
5	Earphone	Nokia	WH-108	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	N/A
3	N/A
4	N/A
5	1.5m ,unshielded

2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 15,18	Mar. 14,19
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

NOTE: 1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.




2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	24deg. C, 43RH	TESTED BY	John Wen

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.170000	---	17.94	54.96	-37.02	L1	ON	9.7
0.170000	38.04	---	64.96	-26.92	L1	ON	9.7
0.304000	---	13.28	50.13	-36.85	L1	ON	9.7
0.304000	27.00	---	60.13	-33.13	L1	ON	9.7
3.512000	---	14.64	46.00	-31.36	L1	ON	9.7
3.512000	21.01	---	56.00	-34.99	L1	ON	9.7
5.916000	---	27.67	50.00	-22.33	L1	ON	9.8
5.916000	34.45	---	60.00	-25.55	L1	ON	9.8
9.136000	---	27.26	50.00	-22.74	L1	ON	9.9
9.136000	34.30	---	60.00	-25.70	L1	ON	9.9
13.840000	---	27.65	50.00	-22.35	L1	ON	9.9
13.840000	34.86	---	60.00	-25.14	L1	ON	9.9

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum




TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	24deg. C, 43RH	TESTED BY	John Wen

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.232000	---	20.22	52.38	-32.16	N	ON	9.9
0.232000	35.41	---	62.38	-26.97	N	ON	9.9
0.618000	---	17.90	46.00	-28.10	N	ON	10.1
0.618000	29.39	---	56.00	-26.61	N	ON	10.1
0.900000	---	12.87	46.00	-33.13	N	ON	9.9
0.900000	22.64	---	56.00	-33.36	N	ON	9.9
1.304000	---	17.75	46.00	-28.25	N	ON	9.9
1.304000	30.79	---	56.00	-25.21	N	ON	9.9
4.360000	---	15.95	46.00	-30.05	N	ON	9.8
4.360000	29.39	---	56.00	-26.61	N	ON	9.8
7.776000	---	27.92	50.00	-22.08	N	ON	9.8
7.776000	35.55	---	60.00	-24.45	N	ON	9.8

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 10 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B/ ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	39	29.5	40	30
88-216	43.5	33.1		
216-230	46.4	35.6		
230-960			47	37
960-1000	49.5	43.5		
1000-3000	Avg: 49.5	Avg: 43.5	Not defined	Not defined
3000+	Peak: 69.5	Peak: 63.5	Not defined	Not defined

Radiated Emissions Limits at 3 meters (dBμV/m)				
Frequencies (MHz)	FCC 15B / ICES-003, Class A	FCC 15B / ICES-003, Class B	CISPR 22, Class A	CISPR 22, Class B
30-88	49.5	40	50.5	40.5
88-216	54	43.5		
216-230	56.9	46		
230-960				
960-1000	60	54	57.5	47.5
1000-3000	Avg: 60 Peak: 80	Avg: 54 Peak: 74	Avg: 56 Peak: 76	Avg: 50 Peak: 70
3000+			Avg: 60 Peak: 80	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI 3	101418	Jan. 02,18	Jan. 01,19
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Jan. 18,18	Jan. 17,19
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-555	Nov. 10, 17	Nov. 09, 18
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 10, 17	Dec. 09, 18
Preamplifier	EMCI	EMC1135	980378	Mar. 19,18	Mar. 18,19
Preamplifier	EMCI	EMC1135	980423	Mar. 19,18	Mar. 18,19
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated V8.7.07	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in Dongguan 10m Semi-anechoic Chamber

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Apr. 21,18	Apr. 20,19
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 10,16	Nov. 09,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 09,18	Jul. 08,19

- NOTE:** 1. The test was performed in 3m chamber.
2. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The FCC Site Registration No. is 525120.

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
3. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
4. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
5. $\text{Margin value} = \text{Emission level} - \text{Limit value}$.

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 10Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
5. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
6. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)
7. $\text{Margin value} = \text{Emission level} - \text{Limit value}$.

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS


Same as 2.1.6

2.2.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Luke		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M

No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower cm	Table deg
1	123.9687	-23.76	34.19	10.43	30.00	-19.57	400	43
2	147.7337	-22.48	33.76	11.28	30.00	-18.72	400	83
3	434.8537	-17.91	35.29	17.38	37.00	-19.62	200	11
4	553.4362	-14.92	34.63	19.71	37.00	-17.29	200	78
*	5	610.0600	-13.29	34.02	20.73	-16.27	200	28
	6	638.4325	-13.24	33.89	20.65	-16.35	400	97




- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.

TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Luke		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M

No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower cm	Table deg
* 1	43.1442	-22.90	40.62	17.72	30.00	-12.28	100	132
2	120.7965	-23.11	37.95	14.84	30.00	-15.16	100	94
3	170.2205	-21.70	32.56	10.86	30.00	-19.14	100	317
4	228.4234	-22.69	33.71	11.02	30.00	-18.98	100	265
5	294.5807	-20.07	32.64	12.57	37.00	-24.43	100	109
6	553.2927	-13.54	33.48	19.94	37.00	-17.06	300	125




- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.

Note: Radiated Emission below 1GHz Test was performed in **Lab B**.

TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Vincent Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
1780	34.6	43.25	54	-19.4	30.49	6.95	46.09	100	64	Average
1780	44.95	53.6	74	-29.05	30.49	6.95	46.09	100	64	Peak
2275	37.13	42.96	54	-16.87	32.17	7.95	45.95	100	215	Average
2275	46.47	52.3	74	-27.53	32.17	7.95	45.95	100	215	Peak
3318	40.63	43.82	54	-13.37	32.96	9.68	45.83	100	136	Average
3318	51.46	54.65	74	-22.54	32.96	9.68	45.83	100	136	Peak

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 18GHz.
 4. Only emissions significantly above equipment noise floor are reported.




TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Vincent Chen		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
1365	38.28	49.63	54	-15.72	28.84	6	46.19	100	96	Average
1365	46.64	57.99	74	-27.36	28.84	6	46.19	100	0	Peak
2485	41.19	46.37	54	-12.81	32.39	8.32	45.89	100	268	Average
2485	49.05	54.23	74	-24.95	32.39	8.32	45.89	100	0	Peak
3250	41.96	45.26	54	-12.04	32.95	9.58	45.83	100	295	Average
3250	49.68	52.98	74	-24.32	32.95	9.58	45.83	100	0	Peak

REMARKS:

1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 18GHz.
4. Only emissions significantly above equipment noise floor are reported.



3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---