

Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radio frequency Radiation

Radar Type: RA41C
FCC ID: O5VRB715A
Manufacturer: Koden Electronics Co., Ltd

Reference:

Sec. 1.1310 Radio frequency radiation exposure limits
Table 1--Limits for Maximum Permissible Exposure (MPE)
(A) Limits for Occupational/Controlled Exposures

1500-100,000MHz 5mW/cm²

Calculation:

(1) Average Output Power (Pav)

Peak Output Power	4kW (4000W)
Repetition Frequency	600Hz
Pulse Width	0.8 us (0.0000008s)
Average Output Power	= $4000(W) \times 600(Hz) \times 0.0000008(s)$ = 1.92 (W)

Horizontal Beam Width 3.9 deg. (Continuously Rotating with 360 deg.)

Pav = $1.92 \times 3.9/360$
= 0.0208 (W)

(2) Antenna Gain (Ga) 24.1dB (256)

(3) Wave Length (Lw) 0.0319 (m)

(4) Power Density Limit (Plim) 50 (W) ; 5mW/cm² = 50W/m²

Range of Limits (m) = $((Pav \times Ga \times Lw^2) / ((4 \times \pi)^2 \times Plim))$
= $((0.0208 \times 256 \times (0.0319)^2) / ((4 \times \pi)^2 \times 50))$
= **0.00083 (m)**

According to above calculation, this radar is comply with " Sec. 1.1310 Radio frequency radiation exposure limits ".