

Evaluating Compliance with FCC-Specified Guidelines for Human Exposure
to Radio frequency Radiation

Radar Type: RA54

FCC ID: 05VRB718A

Manufacturer: Koden Electronics Co., Ltd

Reference:

Sec. 1.1310 Radio frequency radiation exposure limits

Table 1--Limits for Maximum Permissible Exposure (MPE)

(B) Limits for General Population/Uncontrolled Exposures

1500-100,000MHz 1mW/cm²

Calculation:

(1) Average Output Power (Pav)

-1 Pulse duty factor

Peak Output Power 12kW (12000W)

Repetition Frequency 500Hz

Pulse Width 1.0 us (0.000001s)

Average Output Power = 12000(W) x 500(Hz) x 0.000001(s)

Po = 6.0 (W)

-2 Mechanical scanning duty factor

Horizontal Beam Width 1.8 deg.

(Continuously Rotating with 360 deg.)

Pav = Po x 1.8(deg.) / 360(deg.)

= 3.0 x 1.8(deg.) / 360(deg.)

= 0.03 (W)

(2) Antenna Gain (Ga) 28.0dB (631)

(3) Power Density Limit (Plim) 10 (W) ; 1mW/cm² = 10W/m²

(4) K (Factor of Ground Reflection) 4

Range of Limits (m) = SQR((Pav x Ga x K)/(4 x PI x Plim))

= SQR((0.03 x 631 x 4)/(4 x PI x 10))

= 0.776 (m)

According to above calculation, this radar is comply with " Sec. 1.1310
Radio frequency radiation exposure limits ".