



EMC - Test Report

Model : FY-2000/R

Product type	Digital MP3 Player	Serial No.	-
Applicant	Kedcom Co., Ltd.		
Address	#1122-5, Shingil-Dong, Ansan-City, Kyunggi-Do, Korea, 425-125		
Manufacturer	Kedcom Co., Ltd.		
Address	#1122-5, Shingil-Dong, Ansan-City, Kyunggi-Do, Korea, 425-125		
Test specification : FCC Part15 Subpart B Class B (Standard)			
Test Result : Pass			
Tested by (Test engineer)		Reviewed by (EMC Manager)	
2000-08-08	Young Joon, Park	2000-08-08	James, Hong
Date	Name	Date	Name
Signature		Signature	
Definition Pass: Test passed, Fail : Test failed, ☒ : Applicable, ☐ : Not Applicable, N/A : Not Applicable, - : Not Applicable			

No single part of this document may be reproduced without permission from Certitek Standards Laboratory Co., Ltd.

Tel: +82-31-339-9970, Fax: +82-31-339-9972

CERTITEK STANDARDS LABORATORY CO., LTD.



Table of contents

1. EUT description	3
Introduction	3
Identification	3
Electrical rating	3
2. Test Set-up.....	4
Test Mode	4
Cable configuration	4
Cable description	5
Auxiliary equipment	5
Test software	5
Measurement Procedures	6
3. Test Result	7
Test summary	7
Radiated emission	8
Conducted emission	9
4. Photographs	11
EUT (Front / Rear)	11
Main Board (Front / Rear)	12
Memory Board (Front / Rear)	13
Label	14
Radiated emission	15
Conducted emission	16



1. EUT description

Introduction

FY-2000/R is a Digital MP3 Player.

Identification

Model : FY-2000/R

FCC ID : O5YFY-2000R

Manufacturer : Kedcom Co., Ltd.

Address : #1122-5, Shingil-Dong, Ansan-City, Kyunggi-Do, Korea, 425-125

Contact person : Myung-hoe, Kim

Telephone : +82 - 31 - 492 - 0111

Serial No : -

EUT size : 60mm(W), 65mm(H), 17mm(D)

Peripheral Device Ports

Port name	Description
Earphone	Connect to Earphone
Download	Connect to PC' s Parallel Port

Electrical rating

Input : AA Size DC 1.5V Battery.

Output : -




2. Test Set-up

Test Mode

Play mode & Data transfer mode.

Cable configuration



**Cable description**

	Port name (start / end)	Type	Length (m)	Remark
A	EUT's Earphone / Earphone	Unshielded	1.0	Connected Earphone
B	EUT's Download / PC's Parallel	Shielded (With Ferrite Core)	1.2	Connected to PC's Parallel port
C	PC's Serial / Mouse	Shielded	1.6	Connected Serial Mouse
D	PC's USB / Mouse	Shielded	1.6	Connected USB Mouse
E	PC's Keyboard / Keyboard	Shielded	1.5	Connected PS/2 Keyboard
F	PC's Mouse / Mouse	Shielded	1.6	Connected PS/2 Mouse
G	PC's Sound (Speaker / Mic / Line in) / Headset & Cable	Unshielded	2.0	Connected Headset & Cable
H	PC's Game Port / Game pad	Unshielded	2.0	Connected Game pad
I	PC's Video / Monitor	Shielded (With Ferrite Core)	1.8	Connected Monitor

Auxiliary equipment

	Description	Model name	Serial No.	Manufacturer
1	Earphone (for EUT)	-	-	-
2	PC	DTPC-17	G1703009	HEWLETT PACKARD
3	Monitor	PG17HS	301661	SAMSUNG
4	Keyboard	SK-2502C	M000351491	HEWLETT PACKARD
5	Mouse (PS/2)	M-S48	LZA84601000	LOGITECH
6	Mouse (USB)	M-BB48	LZE93853176	LOGITECH
7	Mouse (Serial)	M-S48	LZA91153127	SOTEC
8	Game pad	Side Winder	03421317	Microsoft Corporation
9	Headset	Hi-sonic	-	-

Test software

Software name	Manufacturer	Version	Description
-	-	-	-



Measurement Procedures

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested.

Final AC power line conducted emissions test was performed shielded room. (Location is same as Preliminary test)

Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

* Measurement procedures was In accordance with ANSI C63.4-1992 7.2.3, 7.2.4 and 8.3.1.1, 8.3.1.2



3. Test Result

Test summary

Test	Result	Remark
Emission test (EMI)		
Radiated emission	Pass	
Conducted emission	Not applicable	

The tested FY-2000/R fully meets the Requirements of ANSI C63.4-1992, when operated as described in this report.

President of Certitek standards laboratory.

2000-08-08

Date

Kedin, Lyoun

Name

Signature

**Radiated emission**Test result: **Pass**

Date of testing : 2000/08/03

Ambient temperature: 26°C, Relative humidity: 52%, Atmospheric pressure: 1003hPa(mbar)

Test site type: Open area test site

Reference Standard: FCC Part15 Subpart B , Class B

Test and measurement equipment (Main equipment)

Model name	Manufacturer	Description	Serial No.
BBA9106	Schwarzbeck	Biconical antenna	41-00210
UHALP9107	Schwarzbeck	Log-periodic antenna	1452
ESVS30	Rohde Schwarz	Field strength meter	826638/008
-	-	-	-

Frequency Band 30MHz - 1000MHz

Antenna distance 10m (From the EUT)

Test data sheet

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
49.26	19.0	H	4.0	9.80	1.30	40.0	30.10	9.90
82.36	20.7	V	1.0	9.23	1.80	40.0	31.73	8.27
132.69	15.8	H	3.6	11.90	2.30	43.5	30.00	13.50
155.48	17.7	V	1.0	12.55	2.50	43.5	32.75	10.75
185.21	16.1	H	4.0	12.85	2.60	43.5	31.55	11.95
204.69	15.3	V	1.8	15.45	2.80	43.5	33.55	9.95
248.15	18.7	H	3.2	18.43	3.10	46.0	40.23	5.77
337.69	14.6	V	1.4	15.14	3.90	46.0	33.64	12.36
383.77	15.8	V	2.0	15.40	4.10	46.0	35.30	10.70
428.92	19.9	H	3.0	16.26	4.20	46.0	40.36	5.64
475.10	19.7	V	1.0	17.42	4.40	46.0	41.52	4.48
702.15	14.5	H	2.2	21.60	5.70	46.0	41.80	4.20

Comment: -

**Conducted emission**Test result: **Not applicable**

Date of testing : -

Ambient temperature: -°C, Relative humidity: -%, Atmospheric pressure: -hPa(mbar)

Test site type: Shielded room

Reference Standard: FCC Part15 Subpart B , Class B

Test and measurement equipment (Main equipment)

Model name	Manufacturer	Description	Serial No.
3825/2	EMCO	LISN	9206-1971
ESHS30	Rohde Schwarz	Field strength meter	828144/002
-	-	-	-

Test data sheet

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
				Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
	LISN	Cable		[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]

Comment: -



Test data graphic

Not applicable

Not applicable





4. Photographs

EUT (Front / Rear)







Main Board (Front / Rear)






Memory Board (Front / Rear)






Label





Radiated emission





Conducted emission

Not applicable

Not applicable