

TEST REPORT

of

FCC Part 15 Subpart C

New Application; Class I PC; Class II PC

Product : **Bluetooth Speaker**

Brand: **GDMALL**

Model: **BT1000**

Model Difference: **N/A**

FCC ID: **O6TGDMALLBT1000**

FCC Rule Part: **§15.247, Cat: DSS**

Applicant: **Global Digitech Co., Ltd**

Address: **1F, N025, Aly. 56, Ln.245, Sec. 4, Bade Rd.,
Taipei 105, Taiwan**

Test Performed by:

International Standards Laboratory

<Lung-Tan LAB>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-3;

*Address:

No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd.

Lung-Tan Hsiang, Tao Yuan County 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: **ISL-12LR051FC**

Issue Date : **2012/06/13**

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.



VERIFICATION OF COMPLIANCE**Applicant:** Global Digitech Co., Ltd**Product Description:** Bluetooth Speaker**Brand Name:** GDMALL**Model No.:** BT1000**Model Difference:** N/A**FCC ID:** O6TGDMALLBT1000**FCC Rule Part:** §15.247, Cat: DSS**Date of test:** April. 18, 2012 –April. 20, 2012**Date of EUT Received:** 2012/4/17**We hereby certify that:**

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:**Date:**

2012/06/13

*Dion Chang / Engineer***Prepared By:****Date:**

2012/06/13

*Eva Kao / Technical Supervisor***Approved By:****Date:**

2012/06/13

Vincent Su / Technical Manager

Version

| Version No. | Date | Description |
|-------------|------------|------------------------------|
| 00 | 2012/06/13 | Initial creation of document |
| | | |
| | | |

Table of Contents

| | |
|-----------------------------------------------------------|-----------|
| 1. GENERAL INFORMATION | 7 |
| 1.1. Product Description | 7 |
| 1.2. Related Submittal(s) / Grant (s) | 8 |
| 1.3. Test Methodology | 8 |
| 1.4. Test Facility..... | 8 |
| 1.5. Special Accessories..... | 8 |
| 1.6. Equipment Modifications..... | 8 |
| 2. SYSTEM TEST CONFIGURATION..... | 9 |
| 2.1. EUT Configuration | 9 |
| 2.2. EUT Exercise | 9 |
| 2.3. Test Procedure..... | 9 |
| 2.4. Configuration of Tested System..... | 10 |
| 3. SUMMARY OF TEST RESULTS | 11 |
| 4. DESCRIPTION OF TEST MODES | 11 |
| 5. AC POWER LINE CONDUCTED EMISSION TEST | 12 |
| 5.1. Standard Applicable: | 12 |
| 5.2. Measurement Equipment Used:..... | 12 |
| 5.3. EUT Setup:..... | 12 |
| 5.4. Measurement Procedure: | 13 |
| 5.5. Measurement Result: | 13 |
| 6. PEAK OUTPUT POWER MEASUREMENT..... | 16 |
| 6.1. Standard Applicable: | 16 |
| 6.2. Measurement Equipment Used: | 16 |
| 6.3. .Test Set-up: | 16 |
| 6.4. Measurement Procedure: | 16 |
| 6.5. Measurement Result: | 17 |
| 7. 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT..... | 24 |
| 7.1. Standard Applicable: | 24 |
| 7.2. Measurement Equipment Used: | 24 |
| 7.3. Conducted Emission at antenna port:..... | 24 |
| 7.4. 7.2.2. Radiated emission: | 24 |
| 7.5. Test SET-UP:..... | 25 |
| 7.6. Conducted Emission at antenna port:..... | 25 |
| 7.7. Radiated emission: | 25 |
| 7.8. Measurement Procedure: | 26 |
| 7.9. Field Strength Calculation | 26 |
| 7.10. Measurement Result: | 26 |

| | |
|-------------------------------------------------|-----------|
| 8. SPURIOUS EMISSION TEST | 29 |
| 8.1. Standard Applicable: | 29 |
| 8.2. Measurement Equipment Used: | 29 |
| 8.3. Test SET-UP: | 29 |
| 8.4. Measurement Procedure: | 29 |
| 8.5. Field Strength Calculation | 30 |
| 8.6. Measurement Result: | 30 |
| 9. FREQUENCY SEPARATION | 40 |
| 9.1. Standard Applicable: | 40 |
| 9.2. Measurement Equipment Used: | 40 |
| 9.3. Test Set-up: | 40 |
| 9.4. Measurement Procedure: | 40 |
| 9.5. Measurement Result: | 40 |
| 10. NUMBER OF HOPPING FREQUENCY | 42 |
| 10.1. Standard Applicable: | 42 |
| 10.2. Measurement Equipment Used: | 42 |
| 10.3. Test Set-up: | 42 |
| 10.4. Measurement Procedure: | 42 |
| 10.5. Measurement Result: | 42 |
| 11. TIME OF OCCUPANCY (DWELL TIME) | 44 |
| 11.1. Standard Applicable: | 44 |
| 11.2. Measurement Equipment Used: | 44 |
| 11.3. Test Set-up: | 44 |
| 11.4. Measurement Procedure: | 44 |
| 11.5. Measurement Result: | 44 |
| 12. 20dB Bandwidth..... | 50 |
| 12.1. Standard Applicable: | 50 |
| 12.2. Measurement Equipment Used: | 50 |
| 12.3. Test Set-up: | 50 |
| 12.4. Measurement Procedure: | 50 |
| 12.5. Measurement Result: | 51 |
| 13. ANTENNA REQUIREMENT | 58 |
| 13.1. Standard Applicable: | 58 |
| 13.2. Antenna Connected Construction: | 58 |

1. GENERAL INFORMATION

1.1. Product Description

General:

| | |
|------------------|----------------------------------------------------|
| Product Name | Bluetooth Speaker |
| Brand Name | GDMALL |
| Model Name | BT1000 |
| Model Difference | N/A |
| Power Supply | 3.7V dc from Li-ion Battery or 5V dc from USB Port |

Bluetooth:

| | |
|----------------------|-------------------------------------------|
| Frequency Range: | 2402 – 2480MHz |
| Bluetooth Version: | V2.1 + EDR (GFSK + $\pi/4$ DQPSK + 8DPSK) |
| Channel number: | 79 channels |
| Modulation type: | Frequency Hopping Spread Spectrum |
| Transmit Power: | 6.03 dBm |
| Dwell Time: | <= 0.4s |
| Operating Mode: | Point-to-Point |
| Antenna Designation: | Printed Antenna 0.22 dBi. |

The EUT is compliance with Bluetooth 2.1 + EDR Standard.

1.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: O6TGDMALLBT1000** filing to comply with Section 15.247 of the FCC Part 15C, Subpart C Rules.

1.3. Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2003). Radiated testing was performed at an antenna to EUT distance 3 meters.

Tested in accordance with FCC Public Notice DA 00-705

1.4. Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory** <Lung-Tan LAB> No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd., Lung-Tan Hsiang, Tao Yuan County 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number is: TW1036, Canada Registration Number: 4067B-3.

1.5. Special Accessories

Not available for this EUT intended for grant.

1.6. Equipment Modifications

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT (Transmitter) was tested with a test program to fix the Tx/RX frequency that was for the purpose of the measurements. For more information please see test data and APPENDIX 1 for set-up photographs.

2.3. Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7, 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna. according to the requirements in Section 8 and 13 of ANSI C63.4-2003 and DA 00-705.

2.4. Configuration of Tested System

Fig. 2-1 Configuration of Tested System (Fixed channel)




Table 2-1 Equipment Used in Tested System

| Item | Equipment | Mrf/Brand | Model name | Series No | Data Cable | Power Cable |
|------|---------------|-----------|---------------|-----------|------------|-------------|
| 1 | Notebook | DELL NB | Latitude D620 | N/A | Shield | Non-shield |
| 2 | Test Software | CSR | Bluesuit | N/A | N/A | N/A |

3. SUMMARY OF TEST RESULTS

| FCC Rules | Description Of Test | Result |
|---------------------|-------------------------------------------|-----------|
| §15.207(a) | AC Power line Conducted Emission | N/A |
| §15.247(b)(1) | Peak Output Power | Compliant |
| §15.247(d) | 100 KHz Bandwidth Of Frequency Band Edges | Compliant |
| §15.247(c) | Spurious Emission | Compliant |
| §15.247(a)(1) | Frequency Separation | Compliant |
| §15.247(a)(1)(iii) | Number of hopping frequency | Compliant |
| §15.247(a)(1)(ii) | Time of Occupancy | Compliant |
| §15.247 | Peak Power Density | Compliant |
| §15.247(a)(1) | 20dB Bandwidth | Compliant |
| §15.203, §15.247(c) | Antenna Requirement | Compliant |

4. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz)、mid (2441MHz) and high (2480MHz) with highest data rate are chosen for full testing.

5. AC POWER LINE CONDUCTED EMISSION TEST

5.1. Standard Applicable:

According to §15.207, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

| Frequency range MHz | Limits dB(uV) | |
|------------------------|------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Note

1. The lower limit shall apply at the transition frequencies

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

5.2. Measurement Equipment Used:

| AC Power Line Test Site | | | | | |
|---------------------------|--------------------|--------------------------|------------------|--------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Conduction 03 -1 Cable | WOKEN | CFD 300-NL | Conduction 0-1 | 06/27/2011 | 06/27/2012 |
| EMI Receiver 12 | ROHDE & SCHWARZ | ESCI | 100804 | 06/25/2011 | 06/25/2012 |
| LISN 07 | FCC Inc. | FCC-LISN-50-100-4 -02 | 07040 | 06/02/2011 | 06/02/2012 |
| LISN 08 | FCC | FCC-LISN50-25-2-0 1 | 07039 | 06/25/2011 | 06/25/2012 |

5.3. EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2003.
2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4. Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.5. Measurement Result:


N/A, The power supply is 3.7V dc from Li-ion Battery or 5V dc from USB Port.

AC POWER LINE CONDUCTED EMISSION TEST DATA

| | | | |
|-----------------|----------------|------------|------------|
| Operation Mode: | Operation Mode | Test Date: | 2012/04/19 |
| Test By: | Dino | | |



Address: No.120, Lane 180, San Ho Tsuen, Hsin Ho Road, Lung-Tan Hsiang,
 Tao Yuan County, Taiwan R.O.C.
 Tel: 03-4071718




| Site Conduction 04 | | | | Phase: L1 | | | | Temperature: 26 °C | | | | |
|----------------------------------------|---------|----------------------|-------|----------------|--------------------|-------|--------------|--------------------|-------------|-------|--------|---------|
| Condition : CISPR22 Class B Conduction | | | | | | | | Humidity: 54 % | | | | |
| No. | Freq. | Reading_Level (dBuV) | | Correct Factor | Measurement (dBuV) | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
| | | Peak | QP | | Peak | QP | Avg | P/Q | Avg | P/Q | | |
| 1 | 0.1900 | 40.13 | 38.54 | 24.81 | 0.07 | 40.20 | 38.61 | 24.88 | 64.04 | 54.04 | -25.43 | -29.16 |
| 2 | 0.2460 | 39.06 | 32.65 | 23.18 | 0.07 | 39.13 | 32.72 | 23.25 | 61.89 | 51.89 | -29.17 | -28.64 |
| 3 | 0.4260 | 40.22 | 36.72 | 30.82 | 0.07 | 40.29 | 36.79 | 30.89 | 57.33 | 47.33 | -20.54 | -16.44 |
| 4 | 0.9820 | 37.08 | 34.61 | 30.12 | 0.07 | 37.15 | 34.68 | 30.19 | 56.00 | 46.00 | -21.32 | -15.81 |
| 5 | 4.5100 | 33.11 | 26.69 | 18.84 | 0.14 | 33.25 | 26.83 | 18.98 | 56.00 | 46.00 | -29.17 | -27.02 |
| 6 * | 15.8700 | 38.28 | 36.94 | 34.33 | 0.23 | 38.51 | 37.17 | 34.56 | 60.00 | 50.00 | -22.83 | -15.44 |

*:Maximum data x:Over limit !:over margin



Address: No.120, Lane 180, San Ho Tsuen, Hsin Ho Road, Lung-Tan Hsiang,
 Tao Yuan County, Taiwan R.O.C.
 Tel: 03-4071718



Site Conduction 04

 Phase: **N**

Temperature: 26 °C

Condition: CISPR22 Class B Conduction

Humidity: 54 %

| No. | Freq. | Reading_Level (dBuV) | | | Correct Factor | Measurement (dBuV) | | | Limit (dBuV) | | | Margin (dB) | | |
|-----|---------|-------------------------|-------|-------|-------------------|-----------------------|-------|-------|-----------------|-------|--------|----------------|-----|-----|
| | | MHz | Peak | QP | Avg | dB | peak | QP | Avg | P/Q | Avg | P/Q | Avg | P/F |
| 1 | 0.1780 | 42.39 | 38.13 | 24.50 | 0.08 | 42.47 | 38.21 | 24.58 | 64.58 | 54.58 | -26.37 | -30.00 | | |
| 2 | 0.2060 | 40.17 | 32.62 | 21.68 | 0.07 | 40.24 | 32.69 | 21.75 | 63.37 | 53.37 | -30.68 | -31.62 | | |
| 3 | 0.4300 | 40.01 | 36.47 | 30.67 | 0.07 | 40.08 | 36.54 | 30.74 | 57.25 | 47.25 | -20.71 | -16.51 | | |
| 4 * | 0.9780 | 37.70 | 34.93 | 29.78 | 0.07 | 37.77 | 35.00 | 29.85 | 56.00 | 46.00 | -21.00 | -16.15 | | |
| 5 | 4.6660 | 33.55 | 28.06 | 18.60 | 0.14 | 33.69 | 28.20 | 18.74 | 56.00 | 46.00 | -27.80 | -27.26 | | |
| 6 | 15.7380 | 39.69 | 36.09 | 32.12 | 0.23 | 39.92 | 36.32 | 32.35 | 60.00 | 50.00 | -23.68 | -17.65 | | |

*:Maximum data x:Over limit !:over margin

6. PEAK OUTPUT POWER MEASUREMENT


6.1. Standard Applicable:

According to §15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850MHz band: 1Watt. For all other frequency hopping systems in the 2400 – 2483.5MHz band: 0.125 Watts.

6.2. Measurement Equipment Used:

| Conducted Emission Test Site | | | | | |
|------------------------------|---------|--------------|---------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Power Meter 05 | Anritsu | ML2495A | 1116010 | 04/22/2012 | 04/21/2013 |
| Power Sensor 05 | Anritsu | MA2411B | 34NKF50 | 04/22/2012 | 04/21/2013 |
| Spectrum Analyzer 19 | R&S | FSP40 | 100116 | 10/18/2011 | 10/18/2012 |
| Spectrum Analyzer | Agilent | N9030A | MY51360021 | 03/11/2012 | 03/10/2013 |
| Temperature Chamber | KSON | THS-B4H100 | 2287 | 03/03/2012 | 03/03/2013 |
| DC Power supply | ABM | 51850 | N/A | 06/17/2011 | 06/16/2012 |

6.3. Test Set-up:



6.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Channel power function, RBW= 1MHz (1 % of Bandwidth.) for BDR mode; 1.5MHz(1 % of Bandwidth.) for EDR mode, VBW = 3MHz(1 % of Bandwidth.) for BDR mode /5MHz(1 % of Bandwidth.) for EDR mode)
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.5. Measurement Result:
BDR Mode

| Frequency (MHz) | Reading Power (dBm) | Cable Loss | Output Power (dBm) | Output Power (W) | Limit (W) |
|-----------------|---------------------|------------|--------------------|------------------|-----------|
| 2402.00 | 6.03 | 0.00 | 6.03 | 0.00401 | 1 |
| 2441.00 | 5.05 | 0.00 | 5.05 | 0.00320 | 1 |
| 2480.00 | 3.85 | 0.00 | 3.85 | 0.00243 | 1 |

EDR 2M Mode

| Frequency (MHz) | Reading Power (dBm) | Cable Loss | Output Power (dBm) | Output Power (W) | Limit (W) |
|-----------------|---------------------|------------|--------------------|------------------|-----------|
| 2402.00 | 5.00 | 0.00 | 5.00 | 0.00317 | 1 |
| 2441.00 | 3.99 | 0.00 | 3.99 | 0.00251 | 1 |
| 2480.00 | 2.65 | 0.00 | 2.65 | 0.00184 | 1 |


EDR 3M Mode

| Frequency (MHz) | Reading Power (dBm) | Cable Loss | Output Power (dBm) | Output Power (W) | Limit (W) |
|-----------------|---------------------|------------|--------------------|------------------|-----------|
| 2402.00 | 5.24 | 0.00 | 5.24 | 0.00334 | 1 |
| 2441.00 | 4.17 | 0.00 | 4.17 | 0.00261 | 1 |
| 2480.00 | 2.88 | 0.00 | 2.88 | 0.00194 | 1 |


offset: 9.5dB

Note: Refer to next page for plots.


Peak Power Output Data Plot (CH Low) (BDR mode)




Peak Power Output Data Plot (CH Mid) (BDR mode)




Peak Power Output Data Plot (CH High) (BDR mode)




Peak Power Output Data Plot (CH Low) (EDR 2M Mode)



Peak Power Output Data Plot (CH Mid) (EDR 2M Mode)



Peak Power Output Data Plot (CH High) (EDR 2M Mode)



Peak Power Output Data Plot (CH-Low) (EDR 3M Mode)



Peak Power Output Data Plot (CH-Mid) (EDR 3M Mode)



Peak Power Output Data Plot (CH-High) (EDR 3M Mode)



7. 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

7.1. Standard Applicable:

According to §15.247(d), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

7.2. Measurement Equipment Used:

7.3. Conducted Emission at antenna port:

Refer to section 6.2 for details.

7.4. 7.2.2. Radiated emission:

| Chamber 14(966) | | | | | |
|----------------------|--------------------------------|---------------|---------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Spectrum Analyzer 21 | Agilent | N9010A | MY49060537 | 07/18/2011 | 07/17/2012 |
| Spectrum Analyzer 19 | R&S | FSP40 | 100116 | 10/18/2010 | 10/17/2011 |
| Spectrum Analyzer 20 | Agilent | E4443A | MY48250315 | 05/12/2011 | 05/11/2012 |
| Short Dipole antenna | Schwarzbeck Mess-Elektronik | VHAA9110 | NA | 07/17/2011 | 07/16/2012 |
| Dipole antenna | SCHWARZBECK | VHAP&HUA P | NA | 07/17/2011 | 07/16/2012 |
| Dipole antenna | SCHWARZBECK | UHA9105 | NA | 07/17/2011 | 07/16/2012 |
| Loop Antenna | A.H.SYSTEM | SAS-564 | 294 | 02/28/2012 | 02/27/2013 |
| Bilog Antenna | Schaffner | CBL 6111D | 22612 | 03/30/2012 | 03/29/2013 |
| Horn antenna(06) | EMCO | 3117 | 0006665 | 09/28/2010 | 09/27/2011 |
| Horn antenna(05) | Com-power | AH-640 | 100A | 01/11/2011 | 01/10/2013 |
| Horn antenna(04) | Com-power | AH-826 | 081001 | 05/04/2011 | 05/03/2013 |
| Horn antenna(02) | EMCO | AH118 | 0006665 | 02/15/2012 | 02/14/2013 |
| Preamplifier | HP | 8447F | NA | 05/04/2011 | 05/03/2012 |
| Preamplifier 15 | Agilent | 8449B | 3008A2471 | 02/16/2012 | 02/15/2013 |
| Cable | Huber Suhner | Sucoflex 106 | NA | 02/09/2012 | 02/08/2013 |
| Cable | Pacific | 8D-FB | NA | 10/18/2011 | 10/17/2012 |
| Signal Generator | R&S | SMU200A | NA | 10/12/2011 | 10/11/2012 |


7.5. Test SET-UP:

7.6. Conducted Emission at antenna port:


Refer to section 6.3 for details.

7.7. Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



7.8. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW=100KHz, VBW=300KHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

7.9. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:


$$FS = RA + AF - CL - AG$$

| | | |
|-------|------------------------|--------------------------------------------|
| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |


7.10. Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

(Worst case BDR Mode)
Band Edges Test Data CH-Low



Band Edges Test Data CH-High



Radiated Emission: (BDR mode)

| | | | |
|-----------------------|-----------|-----------|------------|
| Operation Mode | TX CH Low | Test Date | 2012/04/18 |
| Fundamental Frequency | 2402 MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 2390.00 | 57.01 | -11.48 | 45.53 | 74.00 | -28.47 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2390.00 | 58.49 | -11.48 | 47.01 | 74.00 | -26.99 | Peak | HORIZONTAL |

| | | | |
|-----------------------|------------|-----------|------------|
| Operation Mode | TX CH High | Test Date | 2012/04/18 |
| Fundamental Frequency | 2480 MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 57.33 | -11.25 | 46.08 | 54.00 | -7.92 | Average | VERTICAL |
| 2 | 2483.50 | 65.40 | -11.25 | 54.15 | 74.00 | -19.85 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 63.29 | -11.25 | 52.04 | 54.00 | -1.96 | Average | HORIZONTAL |
| 2 | 2483.50 | 72.66 | -11.25 | 61.41 | 74.00 | -12.59 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- 4 Measurement of data within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 6 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

8. SPURIOUS EMISSION TEST

8.1. Standard Applicable:

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

8.2. Measurement Equipment Used:

8.2.1. Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2. Radiated emission:

Refer to section 7.2 for details.

8.3. Test SET-UP:

8.3.1. Conducted Emission at antenna port:

Refer to section 6.3 for details.

8.3.2. Radiated emission:

Refer to section 7.3 for details.

8.4. Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

8.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:


$$\mathbf{FS = RA + AF - CL - AG}$$

| | | |
|-------|------------------------|--------------------------------------------|
| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |


8.6. Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.


Conducted Spurious Emission Measurement Result (worst case: BDR Mode)
Ch Low 30MHz – 3GHz




Ch Low 3GHz – 26.5GHz




Ch Mid 30MHz – 3GHz




Ch Mid 3GHz – 26.5GHz



Ch High 30MHz – 3GHz



Ch High 3GHz – 26.5GHz



Radiated Spurious Emission Measurement Result (below 1GHz) (BDR mode)

| | | | |
|-----------------------|-----------|-----------|------------|
| Operation Mode | TX CH Low | Test Date | 2012/04/18 |
| Fundamental Frequency | 2402MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 47.46 | 51.44 | -16.91 | 34.53 | 40.00 | -5.47 | Peak | VERTICAL |
| 2 | 111.48 | 49.88 | -14.06 | 35.82 | 43.50 | -7.68 | Peak | VERTICAL |
| 3 | 257.95 | 47.55 | -12.18 | 35.37 | 46.00 | -10.63 | Peak | VERTICAL |
| 4 | 387.93 | 48.73 | -9.82 | 38.91 | 46.00 | -7.09 | Peak | VERTICAL |
| 5 | 451.95 | 42.22 | -9.21 | 33.01 | 46.00 | -12.99 | Peak | VERTICAL |
| 6 | 644.98 | 38.05 | -6.85 | 31.20 | 46.00 | -14.80 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 30.97 | 45.65 | -7.66 | 37.99 | 40.00 | -2.01 | Peak | HORIZONTAL |
| 2 | 106.63 | 49.33 | -14.56 | 34.77 | 43.50 | -8.73 | Peak | HORIZONTAL |
| 3 | 159.98 | 47.88 | -15.68 | 32.20 | 43.50 | -11.30 | Peak | HORIZONTAL |
| 4 | 388.90 | 44.71 | -9.81 | 34.90 | 46.00 | -11.10 | Peak | HORIZONTAL |
| 5 | 515.00 | 43.16 | -8.45 | 34.71 | 46.00 | -11.29 | Peak | HORIZONTAL |
| 6 | 795.33 | 35.72 | -5.47 | 30.25 | 46.00 | -15.75 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak / QP detector mode.
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

| | | | |
|-----------------------|-----------|-----------|------------|
| Operation Mode | TX CH Mid | Test Date | 2012/04/18 |
| Fundamental Frequency | 2441MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 47.46 | 45.49 | -16.91 | 28.58 | 40.00 | -11.42 | Peak | VERTICAL |
| 2 | 95.96 | 48.28 | -16.24 | 32.04 | 43.50 | -11.46 | Peak | VERTICAL |
| 3 | 111.48 | 46.97 | -14.06 | 32.91 | 43.50 | -10.59 | Peak | VERTICAL |
| 4 | 258.92 | 40.77 | -12.10 | 28.67 | 46.00 | -17.33 | Peak | VERTICAL |
| 5 | 453.89 | 39.44 | -9.20 | 30.24 | 46.00 | -15.76 | Peak | VERTICAL |
| 6 | 517.91 | 35.06 | -8.39 | 26.67 | 46.00 | -19.33 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 35.82 | 38.24 | -10.63 | 27.61 | 40.00 | -12.39 | Peak | HORIZONTAL |
| 2 | 106.63 | 45.02 | -14.56 | 30.46 | 43.50 | -13.04 | Peak | HORIZONTAL |
| 3 | 143.49 | 43.89 | -14.72 | 29.17 | 43.50 | -14.33 | Peak | HORIZONTAL |
| 4 | 193.93 | 46.58 | -16.16 | 30.42 | 43.50 | -13.08 | Peak | HORIZONTAL |
| 5 | 388.90 | 37.82 | -9.81 | 28.01 | 46.00 | -17.99 | Peak | HORIZONTAL |
| 6 | 905.91 | 35.16 | -4.27 | 30.89 | 46.00 | -15.11 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak / QP detector mode.
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz)

| | | | |
|-----------------------|------------|-----------|------------|
| Operation Mode | TX CH High | Test Date | 2012/04/18 |
| Fundamental Frequency | 2480MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| v | 95.96 | 49.87 | -16.24 | 33.63 | 43.50 | -9.87 | Peak | VERTICAL |
| 2 | 111.48 | 45.57 | -14.06 | 31.51 | 43.50 | -11.99 | Peak | VERTICAL |
| 3 | 299.66 | 40.48 | -11.76 | 28.72 | 46.00 | -17.28 | Peak | VERTICAL |
| 4 | 453.89 | 40.91 | -9.20 | 31.71 | 46.00 | -14.29 | Peak | VERTICAL |
| 5 | 518.88 | 36.19 | -8.37 | 27.82 | 46.00 | -18.18 | Peak | VERTICAL |
| 6 | 647.89 | 33.10 | -6.82 | 26.28 | 46.00 | -19.72 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 35.82 | 38.43 | -10.63 | 27.80 | 40.00 | -12.20 | Peak | HORIZONTAL |
| 2 | 106.63 | 43.12 | -14.56 | 28.56 | 43.50 | -14.94 | Peak | HORIZONTAL |
| 3 | 157.07 | 46.09 | -15.52 | 30.57 | 43.50 | -12.93 | Peak | HORIZONTAL |
| 4 | 192.96 | 46.36 | -16.22 | 30.14 | 43.50 | -13.36 | Peak | HORIZONTAL |
| 5 | 453.89 | 37.67 | -9.20 | 28.47 | 46.00 | -17.53 | Peak | HORIZONTAL |
| 6 | 944.71 | 33.63 | -3.64 | 29.99 | 46.00 | -16.01 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak / QP detector mode.
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz)

| | | | |
|-----------------------|-----------|-----------|------------|
| Operation Mode | TX CH Low | Test Date | 2012/04/18 |
| Fundamental Frequency | 2402 MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1602.00 | 57.51 | -15.02 | 42.49 | 74.00 | -31.51 | Peak | VERTICAL |
| 2 | 4804.00 | 54.12 | -2.65 | 51.47 | 74.00 | -22.53 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 1602.00 | 65.78 | -15.02 | 50.76 | 74.00 | -23.24 | Peak | HORIZONTAL |
| 2 | 4804.00 | 55.32 | -2.65 | 52.67 | 74.00 | -21.33 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- 4 Measurement of data within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 6 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz)

| | | | |
|-----------------------|-----------|-----------|------------|
| Operation Mode | TX CH Mid | Test Date | 2012/04/18 |
| Fundamental Frequency | 2441 MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 4882.00 | 50.45 | -2.40 | 48.05 | 54.00 | -5.95 | Average | VERTICAL |
| 2 | 4882.00 | 56.72 | -2.40 | 54.32 | 74.00 | -19.68 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 4882.00 | 51.13 | -2.40 | 48.73 | 54.00 | -5.27 | Average | HORIZONTAL |
| 2 | 4882.00 | 56.46 | -2.40 | 54.06 | 74.00 | -19.94 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- 4 Measurement of data within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 6 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz)

| | | | |
|-----------------------|------------|-----------|------------|
| Operation Mode | TX CH High | Test Date | 2012/04/18 |
| Fundamental Frequency | 2480 MHz | Test By | Dino |
| Temperature | 25 °C | Humidity | 60 % |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 4960.00 | 50.25 | -2.13 | 48.12 | 54.00 | -5.88 | Average | VERTICAL |
| 2 | 4960.00 | 56.62 | -2.13 | 54.49 | 74.00 | -19.51 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 4960.00 | 49.60 | -2.13 | 47.47 | 54.00 | -6.53 | Average | HORIZONTAL |
| 2 | 4960.00 | 56.67 | -2.13 | 54.54 | 74.00 | -19.46 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 "F" denotes fundamental frequency; "H" denotes harmonics frequency. "S" denotes spurious frequency.
- 4 Measurement of data within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 6 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

9. FREQUENCY SEPARATION

9.1. Standard Applicable:

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 20dB bandwidth of the hopping channel, whichever is greater.

9.2. Measurement Equipment Used:

Refer to section 6.2 for details.

9.3. Test Set-up:

Refer to section 6.3 for details.

9.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel .
4. Set the spectrum analyzer as RBW=100KHz,VBW=300KHz, Adjust Span to 3MHz.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

9.5. Measurement Result:

| Channel separation (MHz) | Limit | Result |
|-----------------------------|----------------------------------------|--------|
| 1 | >=25KHz or 2/3 times 20dB bandwidth | PASS |

Note: Refer to next page for plots.

Frequency Separation Test Data



10. NUMBER OF HOPPING FREQUENCY

10.1. Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

10.2. Measurement Equipment Used:

Refer to section 6.2 for details.

10.3. Test Set-up:

Refer to section 6.3 for details.


10.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441MHz and Start=2441MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW=100KHz, VBW=300KHz
5. Max hold, view and count how many channel in the band.


10.5. Measurement Result:

Note: Refer to next page for plots.

Channel Number
2.4 GHz – 2.441GHz



2.441 GHz – 2.4835GHz



11. TIME OF OCCUPANCY (DWELL TIME)

11.1. Standard Applicable:

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

11.2. Measurement Equipment Used:

Refer to section 6.2 for details.

11.3. Test Set-up:

Refer to section 6.3 for details.

11.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW / VBW =1MHz, Span = 0Hz , Adjust Sweep = auto
5. Repeat above procedures until all frequency measured were complete.

11.5. Measurement Result:

A period time = 0.4 (ms) * 79 = 31.6 (s)

CH Low DH1 time slot = 0.400 (ms) * (1600/2/79) * 31.6 = 128.00 (ms)

 DH3 time slot = 1.655 (ms) * (1600/4/79) * 31.6 = 264.80 (ms)

 DH5 time slot = 2.878 (ms) * (1600/6/79) * 31.6 = 306.99 (ms)

CH Mid DH1 time slot = 0.400 (ms) * (1600/2/79) * 31.6 = 128.00 (ms)

 DH3 time slot = 1.645 (ms) * (1600/4/79) * 31.6 = 263.20 (ms)


 DH5 time slot = 2.893 (ms) * (1600/6/79) * 31.6 = 308.59 (ms)

CH High DH1 time slot = 0.402 (ms) * (1600/2/79) * 31.6 = 128.64 (ms)


 DH3 time slot = 1.645 (ms) * (1600/4/79) * 31.6 = 263.20 (ms)

 DH5 time slot = 2.900 (ms) * (1600/6/79) * 31.6 = 309.33 (ms)



Note: Refer to next page for plots.

CH-Low
 DH1



DH3




DH5



 CH-Mid
 DH1


DH3




DH5




CH-High
 DH1


DH3



DH5



12. 20dB Bandwidth

12.1. Standard Applicable:

According to §15.247(a)(1) for frequency hopping systems operating in the 2400MHz-2483.5 MHz no limit for 20dB bandwidth.

12.2. Measurement Equipment Used:

Refer to section 6.2 for details.

12.3. Test Set-up:

Refer to section 6.3 for details.

12.4. Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=10KHz (1 % of Bandwidth.) for BDR mode; 30KHz (1 % of Bandwidth.) for EDR mode, Span= 3MHz, Sweep= auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

12.5. Measurement Result:
20dB Bandwidth
BDR Mode

| CH | Bandwidth (MHz) |
|--------|--------------------|
| Lower | 0.9647 |
| Mid | 0.8977 |
| Higher | 0.8924 |

EDR 2M Mode

| CH | Bandwidth (MHz) | 2/3 Bandwidth (MHz) |
|--------|--------------------|------------------------|
| Lower | 1.252 | 0.835 |
| Mid | 1.266 | 0.844 |
| Higher | 1.239 | 0.826 |

EDR 3M Mode

| CH | Bandwidth (MHz) | 2/3 Bandwidth (MHz) |
|--------|--------------------|------------------------|
| Lower | 1.267 | 0.845 |
| Mid | 1.264 | 0.843 |
| Higher | 1.267 | 0.845 |

Note: Refer to next page for plots.

BDR Mode


20dB Bandwidth Test Data CH-Low



20dB Bandwidth Test Data CH-Mid




20dB Bandwidth Test Data CH-High



2M EDR Mode


20dB Bandwidth Test Data CH-Low



20dB Bandwidth Test Data CH-Mid



20dB Bandwidth Test Data CH-High



EDR Mode


20dB Bandwidth Test Data CH-Low



20dB Bandwidth Test Data CH-Mid



20dB Bandwidth Test Data CH-High



13. ANTENNA REQUIREMENT

13.1. Standard Applicable:

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

And according to §15.246(1), if transmitting antennas of directional gain greater than 6dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2. Antenna Connected Construction:

The directional gains of antenna used for transmitting is 0.22dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.