



ADDENDUM TO WAVETREND TEST REPORT FC08-026

FOR THE

RFID ACTIVE TAG, L-TG 100 & W-TG 100

**FCC PART 15 SUBPART C SECTIONS 15.209 & 15.231
AND RSS-210 ISSUE 7**

TESTING

DATE OF ISSUE: JULY 15, 2008

PREPARED FOR:

Wavetrend
4000 Legato Road
Fairfax, VA 22033

P.O. No.: 218
W.O. No.: 87492

PREPARED BY:

Mary Ellen Clayton
CKC Laboratories, Inc.
5046 Sierra Pines Drive
Mariposa, CA 95338

Date of test: January 17 - March 20, 2008

Report No.: FC08-026A

This report contains a total of 31 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of CKC Laboratories, Inc. The results in this report apply only to the items tested, as identified herein.

TABLE OF CONTENTS

Administrative Information	3
Approvals	3
Summary of Results	4
Conditions During Testing	4
FCC 15.33(a) Frequency Ranges Tested	5
FCC 15.35 Analyzer Bandwidth Settings	5
EUT Operating Frequency	5
Temperature And Humidity During Testing	5
Equipment Under Test (EUT) Description	5
Equipment Under Test	5
Peripheral Devices	5
Report of Emissions Measurements	6
Testing Parameters	6
FCC 15.231/15.209 Spurious Emissions	8
FCC 15.231(a)(2) Activation	13
FCC 15.231(b) Emissions Limitations	16
FCC 15.231(c)/RSS-210 99% Bandwidth	21
FCC 15.231(e) Alternative Limit	23
FCC 15.231(e) Duration Between Transmission	28
Duty Cycle Correction	30

ADMINISTRATIVE INFORMATION

DATE OF TEST: January 17 –
March 20, 2008

DATE OF RECEIPT: January 17, 2008

REPRESENTATIVE: Ed Gonsalves

MANUFACTURER:

Wavetrend
4000 Legato Road
Fairfax, VA 22033

TEST LOCATION:

CKC Laboratories, Inc.
5046 Sierra Pines Drive
Mariposa, CA 95338

TEST METHOD: ANSI C63.4 (2003), RSS-210 Issue 7 and RSS-GEN Issue 2

PURPOSE OF TEST:

Original Report: To perform the testing of the RFID Active Tag, L-TG 100 & W-TG 100 with the requirements for FCC 15.209 & 15.231 and RSS-210 Issue 7 devices.

Addendum A: To correct the test equipment lists with no new testing.

APPROVALS

QUALITY ASSURANCE:

Steve Behm, Director of Engineering Services

TEST PERSONNEL:

A handwritten signature in black ink, appearing to read "Mike Wilkinson".

Mike Wilkinson, EMC Engineer/Lab
Manager

A handwritten signature in black ink, appearing to read "Randy Clark".

Randy Clark, EMC Engineer

SUMMARY OF RESULTS

Test	Specification/Method	Results
Spurious Emissions	FCC 15.209/15.231/ANSI C63.4(2003)	Pass
Activation	FCC 15.231(a)(2)/ANSI C63.4(2003)	Pass
Emissions Limitations	FCC 15.231(b)/ ANSI C63.4(2003)	Pass
99% Bandwidth	FCC 15.231(c) & RSS-210/ ANSI C63.4(2003) & RSS-GEN	Pass
Alternative Limit	FCC 15.231(e)/ ANSI C63.4(2003)	Pass
Duration Between Transmission	FCC 15.231(e)/ ANSI C63.4(2003)	Pass
Duty Cycle Correction	ANSI C63.4(2003)	Pass
Site File No.	FCC 784962 & IC 3082A-1	

CONDITIONS DURING TESTING

No modifications to the EUT were necessary during testing.

FCC 15.33(a) Frequency Ranges Tested

15.231 Emissions: 30 MHz – 4500 MHz

FCC SECTION 15.35: ANALYZER BANDWIDTH SETTINGS PER FREQUENCY RANGE			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz
RADIATED EMISSIONS	1000 MHz	4.5 GHz	1 MHz

EUT Operating Frequency

The EUT was operating at 433.9 MHz.

Temperature And Humidity During Testing

The temperature during testing was within +15°C and + 35°C.

The relative humidity was between 20% and 75%.

EQUIPMENT UNDER TEST (EUT) DESCRIPTION

The customer declares the EUT tested by CKC Laboratories was representative of a production unit.

EQUIPMENT UNDER TEST

RFID Active Tag

Manuf: Wavetrend
Model: L-TG 100
Serial: None
FCC ID: O6XL-TG100

RFID Active Tag

Manuf: Wavetrend
Model: W-TG 100
Serial: None
FCC ID: O6XL-TG100

PERIPHERAL DEVICES

The EUT was not tested with peripheral devices.

REPORT OF EMISSIONS MEASUREMENTS

TESTING PARAMETERS

The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in dB μ V/m, the spectrum analyzer reading in dB μ V was corrected by using the following formula. This reading was then compared to the applicable specification limit.

SAMPLE CALCULATIONS		
	Meter reading	(dB μ V)
+	Antenna Factor	(dB)
+	Cable Loss	(dB)
-	Distance Correction	(dB)
-	Preamplifier Gain	(dB)
=	Corrected Reading	(dB μ V/m)

SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "Peak" mode. Whenever a "Quasi-Peak" or "Average" reading is listed as one of the highest readings, this is indicated as a "QP" or an "Ave" on the appropriate rows of the data sheets. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

Peak

In this mode, the spectrum analyzer/receiver emissions readings were recorded at their peak value as the frequency band selected was scanned. By combining this function with another feature of the measuring device called "peak hold," the measuring device had the ability to measure transients or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

Quasi-Peak

When the true peak values exceeded or were within 2 dB of the specification limit, quasi-peak measurements were taken using the quasi-peak detector.

Average

For certain frequencies, average measurements may be made using the spectrum analyzer/receiver. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.

FCC 15.231/15.209 SPURIOUS EMISSIONS

Test Setup Photos



Test Data Sheets

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**

Specification: **FCC 15.231/15.209**

Work Order #: **87490**

Date: 3/3/2008

Test Type: **Maximized Emissions**

Time: 16:33:13

Equipment: **RFID Active Tag**

Sequence#: 2

Manufacturer: Wavetrend

Tested By: Mike Wilkinson

Model: L-TG 100

S/N: None

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	L-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was 30-4500 MHz. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 7.5 ms pulse on time in 100ms and calculated as follows: $20\log 0.075 = -22.5\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=ANT AN00327 900MHz-18.5GHz	T4=Cable WL Gore 10' 40 GHz AN P004290
T5=CAB-AN03008-40GHZ-2FT	T6=CAB-AN03011-40GHZ-2FT
T7=CAB-SITED3M1 9k - 20G	T8=Amp HF - AN02010
T9=22.5 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1 T5 T9	T2 T6	T3 T7	T4 T8	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	dB	dB	dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	867.749M	42.2	+22.6 +0.3	-27.5 +0.3	+0.0 +2.7	+1.6 +0.0	+0.0	42.2	46.0	-3.8	Horiz
2	2169.391M	47.2	+0.0 +0.4 +0.0	+0.0 +0.4	+27.8 +4.4	+2.5 -34.6	+0.0	48.1	54.0	-5.9	Horiz
3	2602.501M	44.9	+0.0 +0.4 +0.0	+0.0 +0.4	+29.0 +4.8	+2.8 -34.8	+0.0	47.5	54.0	-6.5	Horiz
4	2169.375M	45.2	+0.0 +0.4 +0.0	+0.0 +0.4	+27.8 +4.4	+2.5 -34.6	+0.0	46.1	54.0	-7.9	Vert
5	2603.241M	42.8	+0.0 +0.4 +0.0	+0.0 +0.4	+29.0 +4.8	+2.8 -34.8	+0.0	45.4	54.0	-8.6	Vert
6	867.773M	36.1	+22.6 +0.3	-27.5 +0.3	+0.0 +2.7	+1.6 +0.0	+0.0	36.1	46.0	-9.9	Vert
7	1301.808M	48.2	+0.0 +0.3 +0.0	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	42.8	54.0	-11.2	Vert
8	1301.691M Ave	59.9	+0.0 +0.3 -22.5	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	32.0	54.0	-22.0	Horiz
^	1301.691M	59.9	+0.0 +0.3	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	54.5	54.0	+0.5	Horiz

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**

Specification: **FCC 15.231/15.209**

Work Order #: **87490**

Test Type: **Maximized Emissions**

Equipment: **RFID Active Tag**

Manufacturer: Wavetrend

Model: W-TG 100

S/N: None

Date: 3/3/2008

Time: 16:22:29

Sequence#: 4

Tested By: Mike Wilkinson

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	W-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was 30-4500 MHz. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 3 ms pulse on time in 100ms and calculated as follows: $20\log 0.03 = -30.1\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=ANT AN00327 900MHz-18.5GHz	T4=Cable WL Gore 10' 40 GHz AN P004290
T5=CAB-AN03008-40GHZ-2FT	T6=CAB-AN03011-40GHZ-2FT
T7=CAB-SITED3M1 9k - 20G	T8=Amp HF - AN02010
T9=30.1 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1 T5 T9	T2 T6	T3 T7	T4 T8	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	dB	dB	dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	867.896M	43.6	+22.6 +0.3 +0.0	-27.5 +0.3	+0.0 +2.7	+1.6 +0.0	+0.0	43.6	46.0	-2.4	Horiz
2	2169.858M	50.5	+0.0 +0.4 +0.0	+0.0 +0.4	+27.8 +4.4	+2.5 -34.6	+0.0	51.4	54.0	-2.6	Horiz
3	2169.843M	48.0	+0.0 +0.4 +0.0	+0.0 +0.4	+27.8 +4.4	+2.5 -34.6	+0.0	48.9	54.0	-5.1	Vert
4	1735.681M	50.3	+0.0 +0.4 +0.0	+0.0 +0.4	+26.2 +3.7	+2.2 -35.0	+0.0	48.2	54.0	-5.8	Vert
5	2603.474M	45.3	+0.0 +0.4 +0.0	+0.0 +0.4	+29.0 +4.8	+2.8 -34.8	+0.0	47.9	54.0	-6.1	Horiz
6	2603.388M	44.9	+0.0 +0.4 +0.0	+0.0 +0.4	+29.0 +4.8	+2.8 -34.8	+0.0	47.5	54.0	-6.5	Vert
7	1735.730M	47.3	+0.0 +0.4 +0.0	+0.0 +0.4	+26.2 +3.7	+2.2 -35.0	+0.0	45.2	54.0	-8.8	Horiz
8	1301.699M	50.4	+0.0 +0.3 +0.0	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	45.0	54.0	-9.0	Vert
9	867.917M	35.0	+22.6 +0.3 +0.0	-27.5 +0.3	+0.0 +2.7	+1.6 +0.0	+0.0	35.0	46.0	-11.0	Vert
10	1301.838M	62.9	+0.0 +0.3 -30.1	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	27.4	54.0	-26.6	Horiz
^	1301.838M	62.9	+0.0 +0.3 +0.0	+0.0 +0.3	+24.3 +3.2	+1.9 -35.4	+0.0	57.5	54.0	+3.5	Horiz

FCC 15.231(a)(2) ACTIVATION

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)
 Customer: **Wavetrend**
 Specification: **FCC 15.231(a)(2)**
 Work Order #: **87492** Date: 3/20/2008
 Test Type: **Maximized Emissions** Time: 10:27:08
 Equipment: **RFID Active Tag** Sequence#: 1
 Manufacturer: Wavetrend Tested By: Randal Clark
 Model: L-TG100
 W-TG100
 S/N: None

Test Equipment:

Asset	Name	Manufacturer	Model	Serial	Cal Date	Cal Due
02616	Diode Detector, Low-barrier Schottky	HP	8472B		4/6/2006	4/6/2008
02713	Oscilloscope	HP	54616C	US37340242	7/20/2007	7/20/2009
P00494	Oscilloscope Probe, 10x	Tektronics	P6133		NCR	NCR

NCR = No Cal Required


Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	L-TG100	None
RFID Active Tag*	Wavetrend	W-TG 100	None


Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. A trigger output is connected to the external trigger input of the oscilloscope. A Crystal Diode Detector is used to receive RF energy using a near-field probe at the antenna of the equipment. The device is triggered (via manual manipulation) which results in a mode change to 15.231(a) operation. The first pulse is at the trigger event. The equipment was then tested to ensure cessation of transmission in this mode within 5 seconds. EUT is powered by internal battery only. Frequency range investigated was Carrier. The temperature was 70°F and the humidity was 40%.


Test Setup Photos



Plots



L-TG 100



W-TG 100

FCC 15.231(b) EMISSIONS LIMITATIONS

Test Setup Photos



Test Data Sheets

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**

Specification: **FCC 15.231(b) Fundamental**

Work Order #: **87490**

Date: 3/3/2008

Test Type: **Maximized Emissions**

Time: 15:27:08

Equipment: **RFID Active Tag**

Sequence#: 1

Manufacturer: Wavetrend

Tested By: Mike Wilkinson

Model: L-TG 100

S/N: None

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	L-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was Carrier. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 7.5 ms pulse on time in 100ms and calculated as follows: $20\log 0.075 = -22.5\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=Cable WL Gore 10' 40 GHz AN P004290	T4=CAB-AN03008-40GHZ-2FT
T5=CAB-AN03011-40GHZ-2FT	T6=CAB-SITED3M1 9k - 20G
T7=22.5 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1 T5	T2 T6	T3 T7	T4	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	dB	dB	dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	433.878M	73.3	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	66.0	80.5	-14.5	Vert
2	433.880M	87.3	+16.7 +0.2	-27.4 +1.9	+1.1 -22.5	+0.2	+0.0	57.5	80.5	-23.0	Horiz
^	433.880M	87.3	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	80.0	80.5	-0.5	Horiz

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**

Specification: **FCC 15.231(b) Fundamental**

Work Order #: **87490**

Date: 3/3/2008

Test Type: **Maximized Emissions**

Time: 16:00:50

Equipment: **RFID Active Tag**

Sequence#: 3

Manufacturer: Wavetrend

Tested By: Mike Wilkinson

Model: W-TG 100

S/N: None

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	W-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was Carrier. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 3 ms pulse on time in 100ms and calculated as follows: $20\log 0.03 = -30.1\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=Cable WL Gore 10' 40 GHz AN P004290	T4=CAB-AN03008-40GHZ-2FT
T5=CAB-AN03011-40GHZ-2FT	T6=CAB-SITED3M1 9k - 20G
T7=30.1 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	T5 dB	T6 dB	T7 dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	433.937M	76.4	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	69.1	80.5	-11.4	Vert
2	433.948M	88.2	+16.7 +0.2	-27.4 +1.9	+1.1 -30.1	+0.2	+0.0	50.8	80.5	-29.7	Horiz
^	433.948M	88.2	+16.7 +0.2	-27.4 +1.9	+1.1	+0.2	+0.0	80.9	80.5	+0.4	Horiz

FCC 15.231(c)/RSS-210 99% BANDWIDTH


Test Equipment

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660


Test Conditions

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side.


Test Setup Photos



Plots



L-TG 100



W-TG 100

FCC 15.231(e) ALTERNATIVE LIMIT

Test Setup Photos



Test Data Sheets

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**

Specification: **FCC 15.231(e) Fundamental**

Work Order #: **87490**

Date: 3/3/2008

Test Type: **Maximized Emissions**

Time: 15:27:08

Equipment: **RFID Active Tag**

Sequence#: 1

Manufacturer: Wavetrend

Tested By: Mike Wilkinson

Model: L-TG 100

S/N: None

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	L-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was Carrier. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 7.5 ms pulse on time in 100ms and calculated as follows: $20\log 0.075 = -22.5\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=Cable WL Gore 10' 40 GHz AN P004290	T4=CAB-AN03008-40GHZ-2FT
T5=CAB-AN03011-40GHZ-2FT	T6=CAB-SITED3M1 9k - 20G
T7=22.5 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1 T5	T2 T6	T3 T7	T4	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	dB	dB	dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	433.878M	73.3	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	66.0	72.6	-6.6	Vert
2	433.880M	87.3	+16.7 +0.2	-27.4 +1.9	+1.1 -22.5	+0.2	+0.0	57.5	72.6	-15.1	Horiz
^	433.880M	87.3	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	80.0	72.6	+7.4	Horiz

Test Location: CKC Laboratories, Inc. • 4933 Sierra Pines Dr. • Mariposa, CA 95338 • 1-800-500-4EMC (4362)

Customer: **Wavetrend**
 Specification: **FCC 15.231(e) Fundamental**
 Work Order #: **87490** Date: 3/3/2008
 Test Type: **Maximized Emissions** Time: 16:00:50
 Equipment: **RFID Active Tag** Sequence#: 3
 Manufacturer: Wavetrend Tested By: Mike Wilkinson
 Model: W-TG 100
 S/N: None

Test Equipment:

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660
10M SITE CBL MAST CBL	N/A	03/23/2007	03/23/2009	CAB-SITED10M
HP 8447D Preamp	1937A02604	03/14/2007	03/14/2009	00099
Chase CBL6111C Bilog	2456	12/30/2006	12/30/2008	01991
EMCO 3115 Horn Antenna	8006-3413	03/17/2007	03/17/2009	00327
HP 8449B Preamp	3008A00301	12/13/2006	12/13/2008	2010
Cable, Pasternack 36"	NA	04/24/2007	04/24/2009	P05202
Cable, Pasternack 48"	NA	04/24/2007	04/24/2009	P05203
EMCO Loop Antenna	1074	05/01/2007	05/01/2009	00226

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
RFID Active Tag*	Wavetrend	W-TG 100	None

Support Devices:

Function	Manufacturer	Model #	S/N
----------	--------------	---------	-----

Test Conditions / Notes:

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side. Frequency range investigated was Carrier. The temperature was 70°F and the humidity was 40%. Averaged readings reflect the application of a duty cycle correction factor derived from measurements that show 3 ms pulse on time in 100ms and calculated as follows: $20\log 0.03 = -30.1\text{dB}$.

Transducer Legend:

T1=ANT AN01991 25-1000MHz	T2=AMP AN00099
T3=Cable WL Gore 10' 40 GHz AN P004290	T4=CAB-AN03008-40GHZ-2FT
T5=CAB-AN03011-40GHZ-2FT	T6=CAB-SITED3M1 9k - 20G
T7=30.1 dB15.35 Duty Cycle Correction	

Measurement Data:

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1 T5	T2 T6	T3 T7	T4	Dist	Corr	Spec	Margin	Polar
	MHz	dB μ V	dB	dB	dB	dB	Table	dB μ V/m	dB μ V/m	dB	Ant
1	433.937M	76.4	+16.7 +0.2	-27.4 +1.9	+1.1 +0.0	+0.2	+0.0	69.1	72.6	-3.5	Vert
2	433.948M	88.2	+16.7 +0.2	-27.4 +1.9	+1.1 -30.1	+0.2	+0.0	50.8	72.6	-21.8	Horiz
^	433.948M	88.2	+16.7 +0.2	-27.4 +1.9	+1.1	+0.2	+0.0	80.9	72.6	+8.3	Horiz

FCC 15.231(e) DURATION BETWEEN TRANSMISSION


Test Equipment

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660

Test Conditions


EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side.

Test Setup Photos




Plots

DURATION BETWEEN TRANSMISSION = 16.85 Sec



L-TG 100

DURATION BETWEEN TRANSMISSION - 15.35 Sec



W-TG 100

DUTY CYCLE CORRECTION


Test Equipment

Function	S/N	Calibration Date	Cal Due Date	Asset #
Agilent E4446A SA	US44300407	01/03/2007	01/03/2009	02660


Test Conditions

EUT is a 433.92 MHz RFID transmitter operating under 15.231a & 15.231e. EUT is set to transmit continuously. EUT is powered by internal battery only. EUT was placed on the test site in the worst case position, which was the side.


Test Setup Photos



Plots



L-TG 100



W-TG 100