

FCC TEST REPORT (15.247)

REPORT NO.: RF931026L19

MODEL NO.: WL UD 2554 17A

RECEIVED: Oct. 21, 2004

TESTED: Oct. 21 ~ Dec. 20, 2004

ISSUED: Dec. 21, 2004

APPLICANT: GLOBAL SUN TECHNOLOGY INC.

ADDRESS: No. 281, Sinhu 3RD., Neihu District, Taipei
City 114, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen,
Kwei Shan Hsiang, Taoyuan Hsien 333,
Taiwan, R.O.C.

This test report consists of 120 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



No. 2177-01

Table of Contents

1.	CERTIFICATION	5
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT uncertainty	7
3.	GENERAL INFORMATION	8
3.1	GENERAL DESCRIPTION OF EUT	8
3.2	DESCRIPTION OF TEST MODES	9
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	10
3.2.2	TEST MODE APPLICABILITY:	11
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	13
3.4	DESCRIPTION OF SUPPORT UNITS	14
4.	TEST TYPES AND RESULTS (802.11b & g 2412~2462MHZ BAND)	15
4.1	CONDUCTED EMISSION MEASUREMENT	15
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	15
4.1.2	TEST INSTRUMENTS	15
4.1.3	TEST PROCEDURES	16
4.1.4	DEVIATION FROM TEST STANDARD	16
4.1.5	TEST SETUP	17
4.1.6	EUT OPERATING CONDITIONS	17
4.1.7	TEST RESULTS	18
4.2	RADIATED EMISSION MEASUREMENT	24
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	24
4.2.2	TEST INSTRUMENTS	25
4.2.3	TEST PROCEDURES	26
4.2.4	DEVIATION FROM TEST STANDARD	26
4.2.5	TEST SETUP	27
4.2.6	EUT OPERATING CONDITIONS	27
4.2.7	TEST RESULTS	28
4.3	6dB BANDWIDTH MEASUREMENT	37
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	37
4.3.2	TEST INSTRUMENTS	37
4.3.3	TEST PROCEDURE	38
4.3.4	DEVIATION FROM TEST STANDARD	38
4.3.5	TEST SETUP	38
4.3.6	EUT OPERATING CONDITIONS	38
4.3.7	TEST RESULTS	39
4.4	MAXIMUM PEAK OUTPUT POWER	47
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47
4.4.2	INSTRUMENTS	47



4.4.3	TEST PROCEDURES	48
4.4.4	DEVIATION FROM TEST STANDARD	48
4.4.5	TEST SETUP	48
4.4.6	EUT OPERATING CONDITIONS	48
4.4.7	TEST RESULTS	49
4.5	POWER SPECTRAL DENSITY MEASUREMENT	51
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	51
4.5.2	TEST INSTRUMENTS	51
4.5.3	TEST PROCEDURE	52
4.5.4	DEVIATION FROM TEST STANDARD	52
4.5.5	TEST SETUP	52
4.5.6	EUT OPERATING CONDITION	52
4.5.7	TEST RESULTS	53
4.6	BAND EDGES MEASUREMENT	61
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	61
4.6.2	TEST INSTRUMENTS	61
4.6.3	TEST PROCEDURE	61
4.6.4	DEVIATION FROM TEST STANDARD	61
4.6.5	EUT OPERATING CONDITION	61
4.6.6	TEST RESULTS	62
4.7	ANTENNA REQUIREMENT	74
4.7.1	STANDARD APPLICABLE	74
4.7.2	ANTENNA CONNECTED CONSTRUCTION	74
5.	TEST TYPES AND RESULTS (802.11a 5725~5850MHZ BAND)	75
5.1	CONDUCTED EMISSION MEASUREMENT	75
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	75
5.1.2	TEST INSTRUMENTS	75
5.1.3	TEST PROCEDURES	76
5.1.4	DEVIATION FROM TEST STANDARD	76
5.1.5	TEST SETUP	77
5.1.6	EUT OPERATING CONDITIONS	77
5.1.7	TEST RESULTS	78
5.2	RADIATED EMISSION MEASUREMENT	80
5.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	80
5.2.2	TEST INSTRUMENTS	81
5.2.3	TEST PROCEDURES	82
5.2.4	DEVIATION FROM TEST STANDARD	82
5.2.5	TEST SETUP	83
5.2.6	EUT OPERATING CONDITIONS	83
5.2.7	TEST RESULTS	84
5.3	6dB BANDWIDTH MEASUREMENT	91
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	91



5.3.2	TEST INSTRUMENTS.....	91
5.3.3	TEST PROCEDURE.....	92
5.3.4	DEVIATION FROM TEST STANDARD	92
5.3.5	TEST SETUP	92
5.3.6	EUT OPERATING CONDITIONS	92
5.3.7	TEST RESULTS	93
5.4	MAXIMUM PEAK OUTPUT POWER	98
5.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	98
5.4.2	INSTRUMENTS.....	98
5.4.3	TEST PROCEDURES	99
5.4.4	DEVIATION FROM TEST STANDARD	99
5.4.5	TEST SETUP	99
5.4.6	EUT OPERATING CONDITIONS	99
5.4.7	TEST RESULTS	100
5.5	POWER SPECTRAL DENSITY MEASUREMENT.....	102
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	102
5.5.2	TEST INSTRUMENTS.....	102
5.5.3	TEST PROCEDURE.....	103
5.5.4	DEVIATION FROM TEST STANDARD	103
5.5.5	TEST SETUP	103
5.5.6	EUT OPERATING CONDITION	103
5.5.7	TEST RESULTS	104
5.6	BAND EDGES MEASUREMENT	109
5.6.1	LIMITS OF BAND EDGES MEASUREMENT	109
5.6.2	TEST INSTRUMENTS.....	109
5.6.3	TEST PROCEDURE.....	109
5.6.4	DEVIATION FROM TEST STANDARD	109
5.6.5	EUT OPERATING CONDITION	110
5.6.6	TEST RESULTS	110
5.7	ANTENNA REQUIREMENT	117
5.7.1	STANDARD APPLICABLE	117
5.7.2	ANTENNA CONNECTED CONSTRUCTION.....	117
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	118
7.	INFORMATION ON THE TESTING LABORATORIES	120



1. CERTIFICATION

PRODUCT: 802.11 a+g Wireless USB Dongle
BRAND NAME: GLOBAL SUN
MODEL NO.: WL UD 2554 17A
APPLICANT: GLOBAL SUN TECHNOLOGY INC.
TEST SAMPLE: Engineering Sample
TESTED: Oct. 21 ~ Dec. 20, 2004
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Windy Chou , **DATE:** Dec. 21, 2004
(Windy Chou)

TECHNICAL
ACCEPTANCE : Gary Chang , **DATE:** Dec. 21, 2004
Responsible for
RF (Gary Chang)

APPROVED BY : Cody Chang , **DATE:** Dec. 21, 2004
(Cody Chang, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -15.61dB at 0.203MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.71dB at 9748.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	802.11 a+g Wireless USB Dongle
MODEL NO.	WL UD 2554 17A
POWER SUPPLY	5.0Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 108Mbps *see Note 2) 802.11a: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 108Mbps *see Note 2)
FREQUENCY RANGE	802.11b & 802.11g: 2.412 ~ 2.462GHz 802.11a: 5.150 ~ 5.350GHz and 5.725 ~ 5.850GHz
NUMBER OF CHANNEL	802.11b & 802.11g: 11 for Normal mode / 1 for Turbo mode 802.11a: 13 for Normal mode / 5 for Turbo mode
CHANNEL SPACING	802.11b & 802.11g: 5MHz 802.11a: 20MHz for Normal mode / 40MHz for Turbo mode
OUTPUT POWER	52.481mW for 802.11b 44.875mW for 802.11g 41.210mW for 5.150 ~ 5.350GHz 41.305mW for 5.725 ~ 5.850GHz
ANTENNA TYPE	802.11b & 802.11g: Chip antenna with 2.0dBi gain 802.11a:Chip antenna with 4.0dBi gain
DATA CABLE	NA
I/O PORTS	USB
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT operates in both the 5GHz and 2.4GHz Bands and compatibility with 802.11a and 802.11b, 802.11g technology.
2. This EUT is capable of providing data rates of up to 108 Mbps in Turbo mode depending upon reception quality.
3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g: Eleven channels are provided to this EUT for normal mode.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

For 802.11g: One channel is provided to this EUT for turbo mode.

Channel	Frequency
6	2437 MHz

Operated in 5725 ~ 5850MHz band:


For 802.11a: Five channels are provided to this EUT for normal mode.

Channel	Frequency
1	5745 MHz
2	5765 MHz
3	5785 MHz
4	5805 MHz
5	5825 MHz

For 802.11a: Two channels are provided to this EUT for turbo mode.

Channel	Frequency
1	5760 MHz
2	5800 MHz

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
1	X	X	X	X	

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11a	1 to 5	3	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6
802.11a	1 to 5	3	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	BPSK	12
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6
802.11a Turbo	1 to 2	1, 2	OFDM	BPSK	12



Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	BPSK	12
802.11a	1 to 5	1, 5	OFDM	BPSK	6
802.11a Turbo	1 to 2	1, 2	OFDM	BPSK	12

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g Turbo	6	6	OFDM	BPSK	12
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6
802.11a Turbo	1 to 2	1, 2	OFDM	BPSK	12



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 802.11 a+g Wireless USB Dongle. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Compaq	N800C	470048-515	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY054147	FCC DoC Approved
3	600Ω Load	NA	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m shielded cable without core
3	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS (802.11b & g 2412~2462MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Mar. 02, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Mar. 03, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Mar. 02, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to a Notebook system placed on a testing table.
- b. The Notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The Notebook system sent "H" messages to its screen.
- d. The Notebook system sent "H" messages to printer, and the printer printed them on paper.
- e. Steps c ~ d were repeated.


4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.203	0.12	47.75	-	47.87	-	63.48	53.48	-15.61	-
2	0.306	0.12	38.43	-	38.55	-	60.07	50.07	-21.52	-
3	0.502	0.13	32.19	-	32.32	-	56.00	46.00	-23.68	-
4	3.891	0.20	32.46	-	32.66	-	56.00	46.00	-23.34	-
5	14.379	0.72	37.71	-	38.43	-	60.00	50.00	-21.57	-
6	22.426	1.09	29.04	-	30.13	-	60.00	50.00	-29.87	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.217	0.11	45.92	-	46.03	-	62.95	52.95	-16.92	-
2	0.318	0.11	38.07	-	38.18	-	59.76	49.76	-21.58	-
3	1.668	0.16	33.00	-	33.16	-	56.00	46.00	-22.84	-
4	3.762	0.20	31.93	-	32.13	-	56.00	46.00	-23.87	-
5	14.711	0.62	35.45	-	36.07	-	60.00	50.00	-23.93	-
6	19.969	0.71	28.70	-	29.41	-	60.00	50.00	-30.59	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.232	0.12	45.43	-	45.55	-	62.38	52.38	-16.83	-
2	0.353	0.13	36.85	-	36.98	-	58.89	48.89	-21.91	-
3	0.591	0.13	33.33	-	33.46	-	56.00	46.00	-22.54	-
4	2.336	0.17	33.09	-	33.26	-	56.00	46.00	-22.74	-
5	15.219	0.79	33.89	-	34.68	-	60.00	50.00	-25.32	-
6	22.750	1.10	27.84	-	28.94	-	60.00	50.00	-31.06	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.231	0.11	44.62	-	44.73	-	62.42	52.42	-17.69	-
2	0.345	0.11	36.14	-	36.25	-	59.08	49.08	-22.82	-
3	1.773	0.16	33.48	-	33.64	-	56.00	46.00	-22.36	-
4	3.887	0.20	30.39	-	30.59	-	56.00	46.00	-25.41	-
5	14.637	0.61	34.62	-	35.23	-	60.00	50.00	-24.77	-
6	21.504	0.70	28.54	-	29.24	-	60.00	50.00	-30.76	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.232	0.12	43.30	-	43.42	-	62.38	52.38	-18.96	-
2	0.357	0.13	38.10	-	38.23	-	58.80	48.80	-20.57	-
3	0.595	0.13	34.80	-	34.93	-	56.00	46.00	-21.07	-
4	2.375	0.17	31.60	-	31.77	-	56.00	46.00	-24.23	-
5	13.918	0.68	36.41	-	37.09	-	60.00	50.00	-22.91	-
6	23.098	1.11	26.99	-	28.10	-	60.00	50.00	-31.90	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.224	0.11	43.24	-	43.35	-	62.66	52.66	-19.31	-
2	0.377	0.12	35.65	-	35.77	-	58.35	48.35	-22.59	-
3	0.600	0.12	34.44	-	34.56	-	56.00	46.00	-21.44	-
4	2.027	0.16	31.66	-	31.82	-	56.00	46.00	-24.18	-
5	14.887	0.63	33.04	-	33.67	-	60.00	50.00	-26.33	-
6	22.746	0.69	25.99	-	26.68	-	60.00	50.00	-33.32	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	$2400/F(\text{kHz})$	300
0.490-1.705	$24000/F(\text{kHz})$	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 \log$ Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Jan. 13, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 21, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2005
Preamplifier Agilent	8449B	3008A01961	Nov. 09, 2005
Preamplifier Agilent	8447D	2944A10629	Nov. 09, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 1.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC4924-2.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	115.53	37.75 QP	43.50	-5.75	1.50 H	46	25.17	12.57
2	168.02	32.41 QP	43.50	-11.09	1.50 H	241	18.29	14.12
3	199.12	35.30 QP	43.50	-8.20	1.50 H	268	23.84	11.46
4	249.66	28.14 QP	46.00	-17.86	1.00 H	268	14.93	13.22
5	356.57	32.81 QP	46.00	-13.19	1.00 H	277	17.02	15.79
6	455.71	30.38 QP	46.00	-15.62	2.00 H	79	12.23	18.15
7	500.42	33.13 QP	46.00	-12.87	1.50 H	337	14.39	18.74
8	533.47	27.38 QP	46.00	-18.62	1.50 H	16	8.01	19.37
9	599.56	33.18 QP	46.00	-12.82	1.50 H	82	12.18	21.00
10	667.60	31.89 QP	46.00	-14.11	1.50 H	220	9.99	21.90
11	731.74	33.95 QP	46.00	-12.05	1.00 H	310	10.86	23.08
12	760.90	33.57 QP	46.00	-12.43	2.00 H	49	9.98	23.59
13	799.78	32.89 QP	46.00	-13.11	1.00 H	43	9.07	23.82
14	863.93	34.51 QP	46.00	-11.49	2.50 H	64	10.06	24.45
15	961.12	34.07 QP	54.00	-19.93	1.50 H	247	8.39	25.68

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	70.82	31.40 QP	40.00	-8.60	1.00 V	301	19.04	12.37
2	117.47	29.15 QP	43.50	-14.35	1.50 V	217	16.38	12.77
3	156.35	28.38 QP	43.50	-15.12	1.00 V	97	13.58	14.80
4	171.90	29.10 QP	43.50	-14.40	1.00 V	181	15.36	13.74
5	249.66	25.47 QP	46.00	-20.53	1.50 V	337	12.25	13.22
6	346.85	27.34 QP	46.00	-18.66	2.00 V	328	11.76	15.58
7	399.34	34.06 QP	46.00	-11.94	1.00 V	13	17.32	16.74
8	455.71	34.84 QP	46.00	-11.16	1.00 V	13	16.69	18.15
9	533.47	31.26 QP	46.00	-14.74	1.00 V	1	11.89	19.37
10	605.39	35.23 QP	46.00	-10.77	1.50 V	331	14.15	21.08
11	665.65	31.15 QP	46.00	-14.85	1.00 V	301	9.28	21.87
12	731.74	31.43 QP	46.00	-14.57	2.00 V	10	8.35	23.08
13	797.84	31.60 QP	46.00	-14.40	2.00 V	4	7.79	23.81
14	863.93	32.89 QP	46.00	-13.11	2.00 V	349	8.45	24.45
15	933.91	33.80 QP	46.00	-12.20	1.00 V	25	8.33	25.47

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value

802.11b DSSS modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	58.10 PK	74.00	-15.90	1.09 H	360	26.39	31.71
1	2360.00	37.59 AV	54.00	-16.41	1.09 H	360	5.88	31.71
2	2386.00	57.15 PK	74.00	-16.85	1.06 H	21	25.36	31.79
2	2386.00	49.45 AV	54.00	-4.55	1.06 H	21	17.66	31.79
3	*2412.00	111.34 PK			1.06 H	21	79.47	31.87
3	*2412.00	103.64 AV			1.06 H	21	71.77	31.87
4	4824.00	56.77 PK	74.00	-17.23	1.01 H	204	18.66	38.11
4	4824.00	49.56 AV	54.00	-4.44	1.01 H	204	11.45	38.11
5	9648.00	56.48 PK	74.00	-17.52	1.22 H	190	14.20	42.28
5	9648.00	49.53 AV	54.00	-4.47	1.22 H	190	7.25	42.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	52.61 PK	74.00	-21.39	1.09 V	34	20.90	31.71
1	2360.00	34.83 AV	54.00	-19.17	1.09 V	34	3.12	31.71
2	2386.00	49.70 PK	74.00	-24.30	1.03 V	258	17.91	31.79
2	2386.00	41.99 AV	54.00	-12.01	1.03 V	258	10.20	31.79
3	*2412.00	103.89 PK			1.03 V	258	72.02	31.87
3	*2412.00	96.18 AV			1.03 V	258	64.31	31.87
4	4824.00	54.86 PK	74.00	-19.14	1.07 V	265	16.75	38.11
4	4824.00	46.74 AV	54.00	-7.26	1.07 V	265	8.63	38.11
5	9648.00	57.85 PK	74.00	-16.15	1.14 V	121	15.57	42.28
5	9648.00	50.44 AV	54.00	-3.56	1.14 V	121	8.16	42.28

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. “ * ” : Fundamental frequency

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	50.31 PK	74.00	-23.69	1.09 H	26	18.60	31.71
1	2360.00	40.86 AV	54.00	-13.14	1.09 H	26	9.15	31.71
2	*2437.00	111.43 PK			1.05 H	19	79.48	31.95
2	*2437.00	103.82 AV			1.05 H	19	71.87	31.95
3	4874.00	57.34 PK	74.00	-16.66	1.15 H	87	19.06	38.28
3	4874.00	50.03 AV	54.00	-3.97	1.15 H	87	11.75	38.28
4	9748.00	56.49 PK	74.00	-17.51	1.10 H	98	17.98	38.51
4	9748.00	52.29 AV	54.00	-1.71	1.10 H	98	13.78	38.51

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	46.20 PK	74.00	-27.80	1.00 V	258	14.49	31.71
1	2360.00	36.03 AV	54.00	-17.97	1.00 V	258	4.32	31.71
2	*2437.00	103.61 PK			1.00 V	341	71.66	31.95
2	*2437.00	95.92 AV			1.00 V	341	63.97	31.95
3	4874.00	56.76 PK	74.00	-17.24	1.07 V	118	18.48	38.28
3	4874.00	49.22 AV	54.00	-4.78	1.07 V	118	10.94	38.28
4	9748.00	54.91 PK	74.00	-19.09	1.03 V	175	16.40	38.51
4	9748.00	49.83 AV	54.00	-4.17	1.03 V	175	11.32	38.51

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	111.06 PK			1.03 H	21	79.04	32.02
1	*2462.00	103.21 AV			1.03 H	21	71.19	32.02
2	2487.00	56.56 PK	74.00	-17.44	1.03 H	21	24.46	32.10
2	2487.00	48.71 AV	54.00	-5.29	1.03 H	21	16.61	32.10
3	2688.00	49.20 PK	74.00	-24.80	1.24 H	151	16.30	32.90
3	2688.00	43.18 AV	54.00	-10.82	1.24 H	151	10.28	32.90
4	4924.00	55.61 PK	74.00	-18.39	1.02 H	186	17.12	38.49
4	4924.00	48.13 AV	54.00	-5.87	1.02 H	186	9.64	38.49
5	9848.00	53.38 PK	74.00	-20.62	1.22 H	219	18.05	35.33
5	9848.00	49.14 AV	54.00	-4.86	1.22 H	219	13.81	35.33

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.61 PK			1.00 V	258	71.59	32.02
1	*2462.00	96.11 AV			1.00 V	258	64.09	32.02
2	2487.00	49.77 PK	74.00	-24.23	1.00 V	258	17.67	32.10
2	2487.00	41.61 AV	54.00	-12.39	1.00 V	258	9.51	32.10
3	2688.00	45.42 PK	74.00	-28.58	1.17 V	360	12.52	32.90
3	2688.00	39.01 AV	54.00	-14.99	1.17 V	360	6.11	32.90
4	4924.00	56.90 PK	74.00	-17.10	1.00 V	199	18.41	38.49
4	4924.00	50.43 AV	54.00	-3.57	1.00 V	199	11.94	38.49
5	9848.00	54.33 PK	74.00	-19.67	1.26 V	168	19.00	35.33
5	9848.00	50.99 AV	54.00	-3.01	1.26 V	168	15.66	35.33

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

802.11g OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	49.33 PK	74.00	-24.67	1.11 H	360	17.62	31.71
1	2360.00	38.12 AV	54.00	-15.88	1.11 H	360	6.41	31.71
2	2390.00	58.85 PK	74.00	-15.15	1.06 H	21	27.05	31.80
2	2390.00	48.72 AV	54.00	-5.28	1.06 H	21	16.92	31.80
3	*2412.00	108.16 PK			1.06 H	21	76.29	31.87
3	*2412.00	98.03 AV			1.06 H	21	66.16	31.87
4	4824.00	50.56 PK	74.00	-23.44	1.19 H	263	12.45	38.11
4	4824.00	38.15 AV	54.00	-15.85	1.19 H	263	0.04	38.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	48.84 PK	74.00	-25.16	1.03 V	257	17.04	31.80
1	2390.00	38.86 AV	54.00	-15.14	1.03 V	257	7.06	31.80
2	*2412.00	98.15 PK			1.03 V	257	66.28	31.87
2	*2412.00	88.17 AV			1.03 V	257	56.30	31.87
3	4824.00	51.20 PK	74.00	-22.80	1.12 V	213	13.09	38.11
3	4824.00	38.50 AV	54.00	-15.50	1.12 V	213	0.39	38.11

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	54.76 PK	74.00	-19.24	1.11 H	360	23.05	31.71
1	2360.00	40.07 AV	54.00	-13.93	1.11 H	360	8.36	31.71
2	*2437.00	108.13 PK			1.05 H	360	76.18	31.95
2	*2437.00	98.07 AV			1.05 H	360	66.12	31.95
3	4874.00	50.61 PK	74.00	-23.39	1.16 H	158	12.33	38.28
3	4874.00	38.03 AV	54.00	-15.97	1.16 H	158	-0.25	38.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	48.06 PK	74.00	-25.94	1.00 V	315	16.35	31.71
1	2360.00	34.73 AV	54.00	-19.27	1.00 V	315	3.02	31.71
2	*2437.00	100.70 PK			1.00 V	298	68.75	31.95
2	*2437.00	91.09 AV			1.00 V	298	59.14	31.95
3	4874.00	51.48 PK	74.00	-22.52	1.14 V	236	13.20	38.28
3	4874.00	38.40 AV	54.00	-15.60	1.14 V	236	0.12	38.28

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.34 PK			1.04 H	12	74.32	32.02
1	*2462.00	96.32 AV			1.04 H	12	64.30	32.02
2	2483.50	62.02 PK	74.00	-11.98	1.04 H	12	29.93	32.09
2	2483.50	51.80 AV	54.00	-2.20	1.04 H	12	19.71	32.09
3	2688.00	47.43 PK	74.00	-26.57	1.00 H	360	14.53	32.90
3	2688.00	41.64 AV	54.00	-12.36	1.00 H	360	8.74	32.90
4	4924.00	52.12 PK	74.00	-21.88	1.00 H	127	13.63	38.49
4	4924.00	39.86 AV	54.00	-14.14	1.00 H	127	1.37	38.49

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	101.20 PK			1.12 V	257	69.18	32.02
1	*2462.00	91.78 AV			1.12 V	257	59.76	32.02
2	2483.50	56.88 PK	74.00	-17.12	1.12 V	257	24.79	32.09
2	2483.50	47.46 AV	54.00	-6.54	1.12 V	257	15.37	32.09
3	2688.00	45.33 PK	74.00	-28.67	1.18 V	342	12.43	32.90
3	2688.00	35.20 AV	54.00	-18.80	1.18 V	342	2.30	32.90
4	4924.00	52.28 PK	74.00	-21.72	1.00 V	194	13.79	38.49
4	4924.00	39.49 AV	54.00	-14.51	1.00 V	194	1.00	38.49

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

802.11g Turbo OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	TESTED BY	Rush Kao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	49.44 PK	74.00	-24.56	1.00 H	304	17.83	31.61
1	2390.00	39.67 AV	54.00	-14.33	1.00 H	304	8.06	31.61
2	*2437.00	97.31 PK			1.00 H	304	65.46	31.85
2	*2437.00	87.54 AV			1.00 H	304	55.69	31.85
3	2483.50	47.87 PK	74.00	-26.13	1.00 H	304	15.74	32.13
3	2483.50	38.10 AV	54.00	-15.90	1.00 H	304	5.97	32.13
4	2688.00	46.07 PK	74.00	-27.93	1.28 H	196	13.37	32.70
4	2688.00	42.69 AV	54.00	-11.31	1.28 H	196	9.99	32.70
5	4874.00	48.68 PK	74.00	-25.32	1.14 H	10	11.02	37.66
5	4874.00	34.91 AV	54.00	-19.09	1.14 H	10	-2.75	37.66

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	46.85 PK	74.00	-27.15	1.18 V	197	15.24	31.61
1	2390.00	37.87 AV	54.00	-16.13	1.18 V	197	6.26	31.61
2	*2437.00	94.72 PK			1.18 V	197	62.87	31.85
2	*2437.00	85.74 AV			1.18 V	197	53.89	31.85
3	2483.50	45.28 PK	74.00	-28.72	1.18 V	197	13.15	32.13
3	2483.50	36.30 AV	54.00	-17.70	1.18 V	197	4.17	32.13
4	2688.00	40.17 PK	74.00	-33.83	1.19 V	47	7.47	32.70
4	2688.00	32.44 AV	54.00	-21.56	1.19 V	47	-0.26	32.70
5	4874.00	46.18 PK	74.00	-27.82	1.19 V	11	8.52	37.66
5	4874.00	33.91 AV	54.00	-20.09	1.19 V	11	-3.75	37.66

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK 30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.7 TEST RESULTS

802.11b DSSS modulation


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.24	0.5	PASS
6	2437	12.40	0.5	PASS
11	2462	11.80	0.5	PASS


CH 1



CH 6



CH 11




802.11g OFDM modulation


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.44	0.5	PASS
6	2437	16.40	0.5	PASS
11	2462	16.44	0.5	PASS


CH 1



CH 6



CH 11




**802.11g Turbo OFDM modulation**

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
6	2437	32.79	0.5	PASS

CH 6





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 31, 2005
TEKTRONIX OSCILLOSCOPE	TDS 1012	C019167	Feb. 01, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23deg.C, 67%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	51.286	17.10	30	PASS
6	2437	52.481	17.20	30	PASS
11	2462	50.119	17.00	30	PASS

802.11g OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23deg.C, 67%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	44.875	16.52	30	PASS
6	2437	44.771	16.51	30	PASS
11	2462	39.811	16.00	30	PASS

802.11g Turbo OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	23deg.C, 67%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
6	2437	43.652	16.40	30	PASS



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




4.5.7 TEST RESULTS

802.11b DSSS modulation


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-8.38	8	PASS
6	2437	-8.13	8	PASS
11	2462	-8.64	8	PASS

CH 1




CH 6





CH 11




**802.11g OFDM modulation**


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.76	8	PASS
6	2437	-13.63	8	PASS
11	2462	-14.03	8	PASS

CH 1




CH 6





CH 11




**802.11g Turbo OFDM modulation**

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
6	2437	-18.33	8	PASS

CH 6



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



4.6.6 TEST RESULTS

The spectrum plots are attached on the following 18 images. D2 line indicates the highest level, and D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS modulation

NOTE 1: The band edge emission plot on page 65 shows 48.12dBc between carrier maximum power and local maximum emission in restrict band (2.3858GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 111.34dBuV/m (Peak), so the maximum field strength in restrict band is $111.34 - 48.12 = 63.22$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of on page 65 shows 53.16dBc between carrier maximum power and local maximum emission in restrict band (2.3872GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.64dBuV/m (Average), so the maximum field strength in restrict band is $103.64 - 53.16 = 50.48$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 66 shows 50.99dBc between carrier maximum power and local maximum emission in restrict band (2.4869GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 111.06dBuV/m (Peak), so the maximum field strength in restrict band is $111.06 - 50.99 = 60.07$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 67 shows 55.33dBc between carrier maximum power and local maximum emission in restrict band (2.4861GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 103.21dBuV/m (Average), so the maximum field strength in restrict band is $103.21 - 55.33 = 47.88$ dBuV/m which is under 54dBuV/m limit.



802.11g OFDM modulation

NOTE 1: The band edge emission plot on page 68 shows 46.92dBc between carrier maximum power and local maximum emission in restrict band (2.3896GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 108.16dBuV/m (Peak), so the maximum field strength in restrict band is $108.16 - 46.92 = 61.24$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of on page 68 shows 48.71dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 98.03dBuV/m (Average), so the maximum field strength in restrict band is $98.03 - 48.71 = 49.32$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 69 shows 45.39dBc between carrier maximum power and local maximum emission in restrict band (2.4849GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.34dBuV/m (Peak), so the maximum field strength in restrict band is $106.34 - 45.39 = 60.95$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 70 shows 50.34dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 96.32dBuV/m (Average), so the maximum field strength in restrict band is $96.32 - 50.34 = 45.98$ dBuV/m which is under 54dBuV/m limit.





802.11g Turbo OFDM modulation



NOTE 1: The band edge emission plot on page 71 shows 47.68dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 97.31dBuV/m (Peak), so the maximum field strength in restrict band is $97.31 - 47.68 = 49.63$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of on page 71 shows 53.26dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 87.54dBuV/m (Average), so the maximum field strength in restrict band is $87.54 - 53.26 = 34.28$ dBuV/m which is under 54dBuV/m limit.



NOTE 2: The band edge emission plot on page 72 shows 57.48dBc between carrier maximum power and local maximum emission in restrict band (2.4859GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 97.31dBuV/m (Peak), so the maximum field strength in restrict band is $97.31 - 57.48 = 39.83$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 73 shows 55.37dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 87.54dBuV/m (Average), so the maximum field strength in restrict band is $87.54 - 55.37 = 32.17$ dBuV/m which is under 54dBuV/m limit.



802.11b DSSS modulation











802.11g OFDM modulation





802.11g Turbo OFDM modulation







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip antenna without connector. The maximum Gain of the antenna is 2.0dBi.