

FCC TEST REPORT (15.407)

REPORT NO.: RF931026L19

MODEL NO.: WL UD 2554 17A

RECEIVED: Oct. 21, 2004

TESTED: Oct. 21 ~ Dec. 20, 2004

ISSUED: Dec. 21, 2004

APPLICANT: GLOBAL SUN TECHNOLOGY INC.

ADDRESS: No. 281, Sinhu 3RD., Neihu District, Taipei
City 114, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen,
Kwei Shan Hsiang, Taoyuan Hsien 333,
Taiwan, R.O.C.

This test report consists of 79 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



No. 2177-01

Table of Contents

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	9
3.2.2	TEST MODE APPLICABILITY:	10
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.4	DESCRIPTION OF SUPPORT UNITS	13
4.	TEST TYPES AND RESULTS (5150 ~ 5350MHz BAND)	14
4.1	CONDUCTED EMISSION MEASUREMENT	14
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
4.1.2	TEST INSTRUMENTS	14
4.1.3	TEST PROCEDURES	15
4.1.4	DEVIATION FROM TEST STANDARD	15
4.1.5	TEST SETUP	16
4.1.6	EUT OPERATING CONDITIONS	16
4.1.7	TEST RESULTS	17
4.2	RADIATED EMISSION MEASUREMENT	19
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	19
4.2.2	LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS	20
4.2.3	TEST INSTRUMENTS	21
4.2.4	TEST PROCEDURES	22
4.2.5	DEVIATION FROM TEST STANDARD	22
4.2.6	TEST SETUP	23
4.2.7	EUT OPERATING CONDITION	23
4.2.8	TEST RESULTS	24
4.3	PEAK TRANSMIT POWER MEASUREMENT	34
4.3.1	LIMITS OF PEAK TRANSMIT POWER MEASUREMENT	34
4.3.2	TEST INSTRUMENTS	34
4.3.3	TEST PROCEDURE	35
4.3.4	DEVIATION FROM TEST STANDARD	35
4.3.5	TEST SETUP	35
4.3.6	EUT OPERATING CONDITIONS	35
4.3.7	TEST RESULTS	36
4.4	PEAK POWER EXCURSION MEASUREMENT	46
4.4.1	LIMITS OF PEAK POWER EXCURSION MEASUREMENT	46



4.4.2	TEST INSTRUMENTS.....	46
4.4.3	TEST PROCEDURE.....	47
4.4.4	DEVIATION FROM TEST STANDARD	47
4.4.5	TEST SETUP	47
4.4.6	EUT OPERATING CONDITIONS	47
4.4.7	TEST RESULTS	48
4.5	PEAK POWER SPECTRAL DENSITY MEASUREMENT	54
4.5.1	LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT.....	54
4.5.2	TEST INSTRUMENTS.....	54
4.5.3	TEST PROCEDURES	55
4.5.4	DEVIATION FROM TEST STANDARD	55
4.5.5	TEST SETUP	55
4.5.6	EUT OPERATING CONDITIONS	55
4.5.7	TEST RESULTS	56
4.6	FREQUENCY STABILITY	62
4.6.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	62
4.6.2	TEST INSTRUMENTS.....	62
4.6.3	TEST PROCEDURE.....	62
4.6.4	DEVIATION FROM TEST STANDARD	62
4.6.5	TEST SETUP	63
4.6.6	EUT OPERATING CONDITION	63
4.6.7	TEST RESULTS	64
4.7	BAND EDGES MEASUREMENT	65
4.7.1	TEST INSTRUMENTS.....	65
4.7.2	TEST PROCEDURE.....	65
4.7.3	EUT OPERATING CONDITION	65
4.7.4	TEST RESULTS	65
4.8	ANTENNA REQUIREMENT	76
4.8.1	STANDARD APPLICABLE	76
4.8.2	ANTENNA CONNECTED CONSTRUCTION.....	76
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	77
6.	INFORMATION ON THE TESTING LABORATORIES	79



1. CERTIFICATION

PRODUCT: 802.11 a+g Wireless USB Dongle
BRAND NAME: GLOBAL SUN
MODEL NO.: WL UD 2554 17A
APPLICANT: GLOBAL SUN TECHNOLOGY INC.
TEST SAMPLE: Engineering Sample
TESTED: Oct. 21 ~ Dec. 20, 2004
STANDARDS: FCC Part 15, Subpart E (Section 15.407)
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Windy Chou, **DATE:** Dec. 21, 2004
(Windy Chou)

TECHNICAL
ACCEPTANCE : Gary Chang, **DATE:** Dec. 21, 2004
Responsible for (Gary Chang)
RF

APPROVED BY : Cody Chang, **DATE:** Dec. 21, 2004
(Cody Chang, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart E (Section 15.407)			
Standard Section	Test Type	Result	Remark
15.407(b)(5)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -18.88dB at 0.224MHz
15.407(b/1/2/3) (b)(5)	Electric Field Strength Spurious Emissions, 30MHz ~ 40000MHz	PASS	Meet the requirement of limit. Minimum passing margin is -1.42dB at 15720.00MHz
15.407(a/1/2/3)	Peak Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit.
15.407(a/1/2/3)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	802.11 a+g Wireless USB Dongle
MODEL NO.	WL UD 2554 17A
POWER SUPPLY	5.0Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 108Mbps *see Note 2) 802.11a: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 108Mbps *see Note 2)
FREQUENCY RANGE	802.11b & 802.11g: 2.412 ~ 2.462GHz 802.11a: 5.150 ~ 5.350GHz and 5.725 ~ 5.850GHz
NUMBER OF CHANNEL	802.11b & 802.11g: 11 for Normal mode / 1 for Turbo mode 802.11a: 13 for Normal mode / 5 for Turbo mode
CHANNEL SPACING	802.11b & 802.11g: 5MHz 802.11a: 20MHz for Normal mode / 40MHz for Turbo mode
OUTPUT POWER	52.481mW for 802.11b 44.875mW for 802.11g 41.210mW for 5.150 ~ 5.350GHz 41.305mW for 5.725 ~ 5.850GHz
ANTENNA TYPE	802.11b & 802.11g: Chip antenna with 2.0dBi gain 802.11a:Chip antenna with 4.0dBi gain
DATA CABLE	NA
I/O PORTS	USB
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT operates in both the 5GHz and 2.4GHz Bands and compatibility with 802.11a and 802.11b, 802.11g technology.
2. This EUT is capable of providing data rates of up to 108 Mbps in Turbo mode depending upon reception quality.
3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 5150 ~ 5250MHz, 5250MHz ~ 5350MHz bands:


Eight channels are provided to this EUT for normal mode.

Channel	Frequency
1	5180 MHz
2	5200 MHz
3	5220 MHz
4	5240 MHz
5	5260 MHz
6	5280 MHz
7	5300 MHz
8	5320 MHz

Three channels are provided to this EUT for turbo mode.

Channel	Frequency
1	5210 MHz
2	5250 MHz
3	5290 MHz

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





3.2.2 TEST MODE APPLICABILITY:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
1	X	X	X	X	

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	1 to 8	5	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	1 to 8	5	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	1 to 8	1, 4, 5, 8	OFDM	BPSK	6
802.11a Turbo	1 to 3	1, 2, 3	OFDM	BPSK	12



Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	1 to 8	1, 8	OFDM	BPSK	6
802.11a Turbo	1 to 3	1, 3	OFDM	BPSK	12

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11a	1 to 8	1, 4, 5, 8	OFDM	BPSK	6
802.11a Turbo	1 to 3	1, 2, 3	OFDM	BPSK	12



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a 802.11 a+g Wireless USB Dongle. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Compaq	N800C	470048-515	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY054147	FCC DoC Approved
3	600Ω Load	NA	NA	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m shielded cable without core
3	NA

NOTE: All power cords of the above support units are non shielded (1.8m).



4. TEST TYPES AND RESULTS (5150 ~ 5350MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 16, 2005
RF signal cable Woken	5D-FB	Cable-HYC01-01	Mar. 02, 2005
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Mar. 03, 2005
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Mar. 02, 2005
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:** 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- Connected the EUT to a Notebook system placed on a testing table.
- The Notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- The Notebook system sent "H" messages to its screen.
- The Notebook system sent "H" messages to printer, and the printer printed them on paper.
- Steps c ~ d were repeated.


4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 5	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.11	43.78	-	43.89	-	64.79	54.79	-20.90	-
2	0.224	0.12	43.66	-	43.78	-	62.66	52.66	-18.88	-
3	0.380	0.13	35.59	-	35.72	-	58.27	48.27	-22.55	-
4	0.601	0.13	35.99	-	36.12	-	56.00	46.00	-19.88	-
5	4.117	0.21	29.88	-	30.09	-	56.00	46.00	-25.91	-
6	14.879	0.77	34.14	-	34.91	-	60.00	50.00	-25.09	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 5	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	23deg. C, 67%RH, 991hPa	TESTED BY	Steven Lu

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.224	0.11	42.71	-	42.82	-	62.66	52.66	-19.84	-
2	0.384	0.12	36.05	-	36.17	-	58.18	48.18	-22.02	-
3	0.603	0.12	35.18	-	35.30	-	56.00	46.00	-20.70	-
4	1.813	0.16	33.50	-	33.66	-	56.00	46.00	-22.34	-
5	13.789	0.55	34.66	-	35.21	-	60.00	50.00	-24.79	-
6	22.676	0.69	26.66	-	27.35	-	60.00	50.00	-32.65	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

Frequencies (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBμV/m) *note 3
5150~5250	-27	68.3
5250~5350	-27	68.3
5725~5825	-27 *note 1	68.3
	-17 *note 2	78.3

NOTE:

1. For frequencies 10MHz or greater above or below the band edge.
2. All emissions within the frequency range from the band edge to 10MHz above or below the band edge.
3. The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$



4.2.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Jan. 13, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 21, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Feb. 03, 2005
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170241	Feb. 23, 2005
Preamplifier Agilent	8449B	3008A01961	Nov. 09, 2005
Preamplifier Agilent	8447D	2944A10629	Nov. 09, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218182/4	Mar. 04, 2005
RF signal cable HUBER+SUHNER	SUCOFLEX 104	218194/4	Mar. 04, 2005
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 1.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC4924-2.

4.2.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation

4.2.6 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.7 EUT OPERATING CONDITION

Same as 4.1.6

4.2.8 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 5	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	115.53	37.75 QP	43.50	-5.75	1.50 H	46	25.17	12.57
2	168.02	32.41 QP	43.50	-11.09	1.50 H	241	18.29	14.12
3	199.12	35.30 QP	43.50	-8.20	1.50 H	268	23.84	11.46
4	249.66	28.14 QP	46.00	-17.86	1.00 H	268	14.93	13.22
5	356.57	32.81 QP	46.00	-13.19	1.00 H	277	17.02	15.79
6	455.71	30.38 QP	46.00	-15.62	2.00 H	79	12.23	18.15
7	500.42	33.13 QP	46.00	-12.87	1.50 H	337	14.39	18.74
8	533.47	27.38 QP	46.00	-18.62	1.50 H	16	8.01	19.37
9	599.56	33.18 QP	46.00	-12.82	1.50 H	82	12.18	21.00
10	667.60	31.89 QP	46.00	-14.11	1.50 H	220	9.99	21.90
11	731.74	33.95 QP	46.00	-12.05	1.00 H	310	10.86	23.08
12	760.90	33.57 QP	46.00	-12.43	2.00 H	49	9.98	23.59
13	799.78	32.89 QP	46.00	-13.11	1.00 H	43	9.07	23.82
14	863.93	34.51 QP	46.00	-11.49	2.50 H	64	10.06	24.45
15	961.12	34.07 QP	54.00	-19.93	1.50 H	247	8.39	25.68

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 5	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	70.82	31.40 QP	40.00	-8.60	1.00 V	301	19.04	12.37
2	117.47	29.15 QP	43.50	-14.35	1.50 V	217	16.38	12.77
3	156.35	28.38 QP	43.50	-15.12	1.00 V	97	13.58	14.80
4	171.90	29.10 QP	43.50	-14.40	1.00 V	181	15.36	13.74
5	249.66	25.47 QP	46.00	-20.53	1.50 V	337	12.25	13.22
6	346.85	27.34 QP	46.00	-18.66	2.00 V	328	11.76	15.58
7	399.34	34.06 QP	46.00	-11.94	1.00 V	13	17.32	16.74
8	455.71	34.84 QP	46.00	-11.16	1.00 V	13	16.69	18.15
9	533.47	31.26 QP	46.00	-14.74	1.00 V	1	11.89	19.37
10	605.39	35.23 QP	46.00	-10.77	1.50 V	331	14.15	21.08
11	665.65	31.15 QP	46.00	-14.85	1.00 V	301	9.28	21.87
12	731.74	31.43 QP	46.00	-14.57	2.00 V	10	8.35	23.08
13	797.84	31.60 QP	46.00	-14.40	2.00 V	4	7.79	23.81
14	863.93	32.89 QP	46.00	-13.11	2.00 V	349	8.45	24.45
15	933.91	33.80 QP	46.00	-12.20	1.00 V	25	8.33	25.47

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

802.11a OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 62%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1053.00	48.50 PK	74.00	-25.50	1.37 H	120	21.97	26.53
1	#1053.00	46.11 AV	54.00	-7.89	1.37 H	120	19.58	26.53
2	#5150.00	52.98 PK	74.00	-15.32	1.19 H	115	13.88	39.10
2	#5150.00	42.21 AV	54.00	-11.79	1.19 H	115	3.11	39.10
3	*5180.00	103.04 PK			1.19 H	115	63.87	39.17
3	*5180.00	92.27 AV			1.19 H	115	53.10	39.17
4	6906.00	56.81 PK	68.30	-11.49	1.37 H	106	15.30	41.51
5	10360.00	59.53 PK	68.30	-8.77	1.36 H	133	14.24	45.29
6	#15540.00	64.97 PK	74.00	-9.03	1.23 H	130	16.43	48.54
6	#15540.00	50.90 AV	54.00	-3.10	1.23 H	130	2.36	48.54

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#”The radiated frequency falling in the restricted band.

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 62%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1052.00	47.03 PK	74.00	-26.97	1.28 V	41	20.50	26.53
1	#1052.00	44.54 AV	54.00	-9.46	1.28 V	41	18.01	26.53
2	3453.00	48.35 PK	68.30	-19.95	1.00 V	207	12.77	35.58
3	#5150.00	51.35 PK	74.00	-22.65	1.22 V	198	12.25	39.10
3	#5150.00	41.69 AV	54.00	-12.31	1.22 V	198	2.59	39.10
4	*5180.00	101.41 PK			1.22 V	198	62.24	39.17
4	*5180.00	91.75 AV			1.22 V	198	52.58	39.17
5	6906.00	55.15 PK	68.30	-13.15	1.19 V	168	13.64	41.51
6	10360.00	60.04 PK	68.30	-8.26	1.47 V	199	14.75	45.29
7	15540.00	67.44 PK	74.00	-6.56	1.52 V	133	18.90	48.54
7	15540.00	52.45 AV	54.00	-1.55	1.52 V	133	3.91	48.54

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. "*" : Fundamental frequency
 6. "#"The radiated frequency falling in the restricted band.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 62%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1053.00	48.83 PK	74.00	-25.17	1.35 H	102	22.30	26.53
1	#1053.00	46.72 AV	54.00	-7.28	1.35 H	102	20.19	26.53
2	*5240.00	103.69 PK			1.04 H	140	64.51	39.18
2	*5240.00	93.96 AV			1.04 H	140	54.78	39.18
3	6986.00	56.00 PK	68.30	-12.30	1.14 H	207	14.30	41.70
4	#15720.00	61.42 PK	74.00	-12.58	1.00 H	315	13.66	47.76
4	#15720.00	48.24 AV	54.00	-5.76	1.00 H	315	0.48	47.76

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1053.00	46.33 PK	74.00	-27.67	1.13 V	28	19.80	26.53
1	#1053.00	43.35 AV	54.00	-10.65	1.13 V	28	16.82	26.53
2	*5240.00	102.74 PK			1.01 V	139	63.56	39.18
2	*5240.00	93.10 AV			1.01 V	139	53.92	39.18
3	6986.00	55.17 PK	68.30	-13.13	1.38 V	356	13.47	41.70
4	#15720.00	67.38 PK	74.00	-6.62	1.20 V	136	19.62	47.76
4	#15720.00	52.58 AV	54.00	-1.42	1.20 V	136	4.82	47.76

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. "*" : Fundamental frequency
 6. "#"The radiated frequency falling in the restricted band.



EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 5	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 62%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1053.00	48.16 PK	74.00	-25.84	1.31 H	60	21.63	26.53
1	#1053.00	46.20 AV	54.00	-7.80	1.31 H	60	19.67	26.53
2	*5260.00	105.25 PK			1.44 H	104	66.09	39.16
2	*5260.00	94.96 AV			1.44 H	104	55.80	39.16
3	7013.00	56.30 PK	68.30	-12.00	1.64 H	210	14.45	41.85
4	#15780.00	61.31 PK	74.00	-12.69	1.48 H	216	14.05	47.25
4	#15780.00	47.49 AV	54.00	-6.51	1.48 H	216	0.23	47.25

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1053.00	46.85 PK	74.00	-27.15	1.02 V	61	20.32	26.53
1	#1053.00	44.06 AV	54.00	-9.94	1.02 V	61	17.53	26.53
2	*5260.00	101.43 PK			1.33 V	22	62.27	39.16
2	*5260.00	91.24 AV			1.33 V	22	52.08	39.16
3	7013.00	54.01 PK	68.30	-14.29	1.18 V	357	12.16	41.85
4	#15780.00	65.22 PK	74.00	-8.78	1.20 V	160	17.96	47.25
4	#15780.00	50.20 AV	54.00	-3.80	1.20 V	160	2.94	47.25

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#” The radiated frequency falling in the restricted band.

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 8	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	24deg. C, 62%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)
1	#1053.00	48.14 PK	74.00	-25.86	1.34 H	118	21.61	26.53
1	#1053.00	45.73 AV	54.00	-8.27	1.34 H	118	19.20	26.53
2	*5320.00	107.29 PK			1.40 H	105	68.14	39.15
2	*5320.00	97.21 AV			1.40 H	105	58.06	39.15
3	#5350.00	56.03 PK	74.00	-17.94	1.40 H	105	16.83	39.20
3	#5350.00	45.95 AV	54.00	-8.05	1.40 H	105	6.75	39.20
4	7093.00	56.14 PK	68.30	-12.16	1.65 H	253	13.62	42.52
5	#15960.00	60.31 PK	74.00	-13.69	1.45 H	174	15.35	44.96
5	#15960.00	46.88 AV	54.00	-7.12	1.45 H	174	1.92	44.96

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)
1	#1053.00	46.08 PK	74.00	-27.92	1.13 V	1	19.55	26.53
1	#1053.00	42.80 AV	54.00	-11.20	1.13 V	1	16.27	26.53
2	*5320.00	102.93 PK			1.32 V	24	63.78	39.15
2	*5320.00	92.96 AV			1.32 V	24	53.81	39.15
3	7093.00	55.97 PK	68.30	-12.33	1.02 V	172	13.45	42.52
4	#10640.00	57.05 PK	74.00	-16.95	1.10 V	152	10.82	46.23
4	#10640.00	44.96 AV	54.00	-9.04	1.10 V	152	-1.27	46.23
5	#15960.00	66.05 PK	74.00	-7.95	1.15 V	162	21.09	44.96
5	#15960.00	50.86 AV	54.00	-3.14	1.15 V	162	5.90	44.96

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#” The radiated frequency falling in the restricted band.

**802.11a Turbo OFDM modulation**

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3473.00	46.53 PK	68.30	-21.77	1.10 H	104	10.89	35.64
2	#5150.00	47.26 PK	74.00	-26.74	1.20 H	199	8.16	39.10
2	#5150.00	37.39 AV	54.00	-16.61	1.20 H	199	-1.71	39.10
3	*5210.00	101.89 PK			1.20 H	199	62.68	39.21
3	*5210.00	92.02 AV			1.20 H	199	52.81	39.21
4	6946.00	56.31 PK	68.30	-11.99	1.10 H	104	14.70	41.61
5	10420.00	54.62 PK	68.30	-13.68	1.04 H	92	8.85	45.77

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5150.00	44.43 PK	74.00	-29.57	1.03 V	38	5.33	39.10
1	#5150.00	35.80 AV	54.00	-18.20	1.03 V	38	-3.30	39.10
2	*5210.00	99.06 PK			1.03 V	38	59.85	39.21
2	*5210.00	90.43 AV			1.03 V	38	51.22	39.21
3	6946.00	51.88 PK	68.30	-16.42	1.02 V	42	10.27	41.61
4	10420.00	53.98 PK	68.30	-14.32	1.03 V	110	8.21	45.77

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#” The radiated frequency falling in the restricted band.

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 2	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5250.00	100.37 PK			1.20 H	37	61.20	39.17
1	*5250.00	91.30 AV			1.20 H	37	52.13	39.17
2	7000.00	54.90 PK	68.30	-13.40	1.02 H	188	13.16	41.74
3	10500.00	56.45 PK	68.30	-11.85	1.12 H	300	10.26	46.19

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5250.00	99.69 PK			1.05 V	326	60.52	39.17
1	*5250.00	90.13 AV			1.05 V	326	50.96	39.17
2	7000.00	51.45 PK	68.30	-16.85	1.00 V	144	9.71	41.74
3	10500.00	57.12 PK	68.30	-11.18	1.01 V	250	10.93	46.19

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. "*" : Fundamental frequency
 6. "#"The radiated frequency falling in the restricted band.

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 40 GHz
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5290.00	101.21 PK			1.02 H	300	62.08	39.13
1	*5290.00	99.01 AV			1.02 H	300	59.88	39.13
2	#5350.00	44.97 PK	68.30	-23.33	1.02 H	300	5.77	39.20
2	#5350.00	35.71 AV	54.00	-18.29	1.02 H	300	-3.49	39.20
3	7053.00	56.42 PK	68.30	-11.88	1.21 H	258	14.24	42.18
4	10580.00	57.46 PK	68.30	-10.84	1.17 H	247	11.39	46.07

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5290.00	99.43 PK			1.11 V	300	60.30	39.13
1	*5290.00	90.24 AV			1.11 V	300	51.11	39.13
2	#5350.00	43.13 PK	68.30	-25.17	1.11 V	300	3.93	39.20
2	#5350.00	33.94 AV	54.00	-20.06	1.11 V	300	-5.26	39.20
3	7053.00	53.40 PK	68.30	-14.90	1.00 V	240	11.22	42.18
4	10580.00	58.11 PK	68.30	-10.19	1.01 V	321	12.04	46.07

- NOTE:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value
 5. “*” : Fundamental frequency
 6. “#” The radiated frequency falling in the restricted band.



4.3 PEAK TRANSMIT POWER MEASUREMENT

4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT

Frequency Band	Limit
5.15 – 5.25GHz	The lesser of 50mW (17dBm) or 4dBm + 10logB
5.25 – 5.35GHz	The lesser of 250mW (24dBm) or 11dBm + 10logB
5.725 – 5.825GHz	The lesser of 1W (30dBm) or 17dBm + 10logB

NOTE: Where B is the 26dB emission bandwidth in MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set span to encompass the entire emission bandwidth of the signal.
3. Set RBW to 1MHz, VBW to 300kHz.
4. Using the spectrum analyzer's channel power measurement function to measure the output power.

NOTE:


The test is performed in accordance with FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices – Part 15, Subpart E, August 2002.

The transmitter output operates continuously therefore Method # 3 is used.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.3.7 TEST RESULTS


802.11a OFDM modulation

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	26dBc Occupied Bandwidth (MHz)	PASS/FAIL
1	5180	35.727	15.53	17.00	29.26	PASS
4	5240	32.063	15.06	17.00	26.32	PASS
5	5260	25.293	14.03	24.00	27.86	PASS
8	5320	31.623	15.00	24.00	26.67	PASS

NOTE: The 26dBc Occupied Bandwidth plot, please refer to the following pages.


Peak Power Output: CH 1




CH 4



CH 5



CH 8



*RBW 300 kHz Delta 1 [T1]
 *VBW 1 MHz -0.38 dB
 *Att 30 dB
 SWT 20 ms 29.26000000 MHz

Ref 20.5 dBm Offset 0.5 dB

Marker 1 [T1]
 -23.21 dBm
 5.164530000 GHz

D1 2.82 dBm
 D2 -23.18 dBm

Center 5.18 GHz Span 35 MHz

*RBW 300 kHz Delta 1 [T1]
 *VBW 1 MHz -1.09 dB
 SWT 20 ms 26.320000000 MHz

Ref 20.5 dBm *Att 30 dB

20 Offset 0.5 dB Marker 1 [T1]
 -22.09 dBm
 5.226350000 GHz


1 PK VIEW

D1 2.79 dBm
 -23.21 dBm


F1 F2

Center 5.24 GHz 3.5 MHz/ Span 35 MHz

CH 5



CH 8




**802.11a Turbo OFDM modulation**

EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		


CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	26dBc Occupied Bandwidth (MHz)	PASS/FAIL
1	5210	40.738	16.10	17.00	47.25	PASS
2	5250	40.644	16.09	17.00	49.18	PASS
3	5290	41.210	16.15	24.00	46.29	PASS

NOTE: The 26dBc Occupied Bandwidth plot, please refer to the following pages.

Peak Power Output: CH 1




CH 2







CH 3



26dB Occupied Bandwidth: CH 1




CH 2





CH 3





4.4 PEAK POWER EXCURSION MEASUREMENT

4.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Frequency Band	Limit
5.15 – 5.25 GHz	13dB
5.25 – 5.35 GHz	13dB
5.725 – 5.825 GHz	13dB

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set the spectrum bandwidth span to view the entire spectrum.
3. Using peak detector and Max-hold function for Trace 1 (RB=1MHz, VB=3MHz) and 2 (RB=1MHz, VB=300KHz).
4. The largest difference between Trace 1 and Trace 2 in any 1MHz band on any frequency was recorded.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.


4.4.7 TEST RESULTS

802.11a OFDM modulation


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5180	6.51	13	PASS
4	5240	7.55	13	PASS
5	5260	6.98	13	PASS
8	5320	7.59	13	PASS


CH 1




CH 4



CH 5



CH 8




**802.11a Turbo OFDM modulation**


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
1	5210	7.33	13	PASS
2	5250	7.78	13	PASS
3	5290	7.62	13	PASS


CH 1



CH 2



CH 3



4.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

Frequency Band	Limit
5.15 ~ 5.25GHz	4dBm
5.25 ~ 5.35GHz	11dBm
5.725 ~ 5.825GHz	17dBm

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURES

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW=1MHz, VBW=3MHz. The PPSD is the highest level found across the emission in any 1MHz band.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.


4.5.7 TEST RESULTS

802.11a OFDM modulation


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5180	1.39	4	PASS
4	5240	1.34	4	PASS
5	5260	2.88	11	PASS
8	5320	2.81	11	PASS


CH 1




CH 4



CH 5



CH 8




**802.11a Turbo OFDM modulation**


EUT	802.11 a+g Wireless USB Dongle	MODEL	WL UD 2554 17A
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	24deg.C, 64%RH, 991hPa
TESTED BY	Leo Hung		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 1 MHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	5210	-4.58	4	PASS
2	5250	-4.63	11	PASS
3	5290	-4.73	11	PASS


CH 1



CH 2



CH 3





4.6 FREQUENCY STABILITY

4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.02\%$ of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ANRITSU SPECTRUM ANALYZER	MS2667C	M10281	Aug. 12, 2005
WIT STANDARD TEMPERATURE AND HUMIDITY CHAMBER	TH-4S-C	W901030	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.6.3 TEST PROCEDURE

1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
2. Turn the EUT on and couple its output to a spectrum analyzer.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
6. The test chamber was allowed to stabilize at $+20$ degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.6.7 TEST RESULTS

Operating frequency: 5320MHz				Limit : $\pm 0.015\%$			
Temp. (°C)	Power supply (Vac)	2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	138.0	5319.9874	-0.0002368	5319.9864	-0.0002556	5319.9860	-0.0002632
	120.0	5319.9872	-0.0002406	5319.9864	-0.0002556	5319.9860	-0.0002632
	102.0	5319.9876	-0.0002331	5319.9862	-0.0002594	5319.9860	-0.0002632
40	138.0	5319.9842	-0.0002970	5319.9830	-0.0003195	5319.9826	-0.0003271
	120.0	5319.9854	-0.0002744	5319.9838	-0.0003045	5319.9830	-0.0003195
	102.0	5319.9854	-0.0002744	5319.9828	-0.0003233	5319.9832	-0.0003158
30	138.0	5319.9818	-0.0003421	5319.9818	-0.0003421	5319.9814	-0.0003496
	120.0	5319.9820	-0.0003383	5319.9818	-0.0003421	5319.9816	-0.0003459
	102.0	5319.9818	-0.0003421	5319.9818	-0.0003421	5319.9814	-0.0003496
20	138.0	5319.9804	-0.0003684	5319.9806	-0.0003647	5319.9808	-0.0003609
	120.0	5319.9800	-0.0003759	5319.9806	-0.0003647	5319.9808	-0.0003609
	102.0	5319.9802	-0.0003722	5319.9806	-0.0003647	5319.9806	-0.0003647
10	138.0	5319.9817	-0.0003440	5319.9822	-0.0003346	5319.9828	-0.0003233
	120.0	5319.9816	-0.0003459	5319.9820	-0.0003383	5319.9826	-0.0003271
	102.0	5319.9820	-0.0003383	5319.9824	-0.0003308	5319.9830	-0.0003195
0	138.0	5319.9848	-0.0002857	5319.9852	-0.0002782	5319.9864	-0.0002556
	120.0	5319.9846	-0.0002895	5319.9854	-0.0002744	5319.9864	-0.0002556
	102.0	5319.9850	-0.0002820	5319.9854	-0.0002744	5319.9864	-0.0002556
-10	138.0	5319.9884	-0.0002180	5319.9888	-0.0002105	5319.9898	-0.0001917
	120.0	5319.9882	-0.0002218	5319.9888	-0.0002105	5319.9896	-0.0001955
	102.0	5319.9882	-0.0002218	5319.9888	-0.0002105	5319.9896	-0.0001955
-20	138.0	5319.9926	-0.0001391	5319.9930	-0.0001316	5319.9930	-0.0001316
	120.0	5319.9928	-0.0001353	5319.9932	-0.0001278	5319.9928	-0.0001353
	102.0	5319.9928	-0.0001353	5319.9932	-0.0001278	5319.9932	-0.0001278
-30	138.0	5319.9948	-0.0000977	5319.9956	-0.0000827	5319.9968	-0.0000602
	120.0	5319.9944	-0.0001053	5319.9952	-0.0000902	5319.9964	-0.0000677
	102.0	5319.9946	-0.0001015	5319.9948	-0.0000977	5319.9966	-0.0000639

4.7 BAND EDGES MEASUREMENT

4.7.1 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.7.2 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 1MHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges were measured and recorded.

4.7.3 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

4.7.4 TEST RESULTS

For signals in the restricted bands above and below the 5.15 to 5.35GHz allocated band a measurement was made of the amplitude of the spurious emissions with respect to the intentional signals. The relative amplitude, in dBc, was applied to the average and peak field strength of the intentional signal made on the OATS to calculate the field strength of the unintentional signals.

The spectrum plots (Peak RBW=VBW=1MHz; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

**802.11a OFDM modulation****Channel 1 (5180MHz)**

The band edge emission plot on page 68 shows 44.49dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 103.04dBuV/m (Peak), so the maximum field strength in restrict band is $103.04 - 44.49 = 58.55$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 68 shows 54.39dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 92.27dBuV/m (Average), so the maximum field strength in restrict band is $92.27 - 54.39 = 37.88$ dBuV/m which is under 54dBuV/m limit.

Channel 8 (5320MHz)

The band edge emission plot on page 70 shows 45.35dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 8 is 107.29dBuV/m (Peak), so the maximum field strength in restrict band is $107.29 - 45.35 = 61.94$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 70 shows 54.81dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 8 is 97.21dBuV/m (Average), so the maximum field strength in restrict band is $97.21 - 54.81 = 42.40$ dBuV/m which is under 54dBuV/m limit.

**802.11a Turbo OFDM modulation****Channel 1 (5210MHz)**

The band edge emission plot on page 72 shows 51.90dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 101.89dBuV/m (Peak), so the maximum field strength in restrict band is $101.89 - 51.90 = 49.99$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 72 shows 57.44dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 is 92.02dBuV/m (Average), so the maximum field strength in restrict band is $92.02 - 57.44 = 34.58$ dBuV/m which is under 54dBuV/m limit.


Channel 3 (5290MHz)



The band edge emission plot on the pages 74 shows 55.03dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 3 is 101.21dBuV/m (Peak), so the maximum field strength in restrict band is $101.21 - 55.03 = 46.18$ dBuV/m which is under 74dBuV/m limit.


The band edge emission plot on the pages 74 shows 57.78dBc between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 3 is 99.01dBuV/m (Average), so the maximum field strength in restrict band is $99.01 - 57.78 = 41.23$ dBuV/m which is under 54dBuV/m limit.



802.11a OFDM modulation













802.11a Turbo OFDM modulation



Turbo Mode (CH 3)







4.8 ANTENNA REQUIREMENT

4.8.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407(a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.8.2 ANTENNA CONNECTED CONSTRUCTION



The antenna used in this product is Chip antenna without connector. The maximum Gain of the antenna is 4.0dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also