



www.ecmg-global.net

## FCC MPE REPORT

On Model Name: SMART PLAYER

Model Numbers: HS\*\* ("\*" can be 0-9)

Brand Name: N/A

FCC ID Number: O7T786-HEHS06

Prepared for HESIO INTERNATIONAL CO., LTD

Test Report #: SHE-1204-10805-FCC MPE

Tested by: Daomen Galanz  
Engineer Company Name

Reviewed by: Jameym ECMG  
Senior Engineer Company Name

QC Manager: Swall Zhang ECMG  
QC Manager Company Name

Test Report Released by: Swall Zhang August 8<sup>th</sup>, 2012  
Swall Zhang Date

## **Test Location**

*Tests performed in a Certified ANSI Semi-Anechoic Chamber and Shielded Room.*

*Test Site Location : Galanz*

*25 South Ronggui Rd., Shunde, Foshan,  
Guangdong, China*

*Tel : (86)-757-23612785*

*Fax : (86)-757-23612537*

## **Test Facility**

*The test facility was recognized, certified, or accredited by the following organizations:*

- *CNAL - LAB Code: L2244*

*Galanz EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.*

- *FCC - Registration No.: 580210*

*Galanz EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC was maintained in our files.*

## List of Test and Measurement Instruments

<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibrated Until</b>
<i>Spectrum Analyzer</i>	R&S	FSP30	100755	2012-11-30
<i>EMI Receiver</i>	SCHAFFNER	SMR4503	11725	2012-11-30
<i>LISN</i>	ETS	4825/2	1161	2012-11-30
<i>Coaxial Cable</i>	ATC	N/A	N/A	2012-11-30
<i>Double-ridged Wave guide horn</i>	ETS	3115	6587	2012-11-30
<i>Amplifier</i>	Agilent	83017A	MY39500438	2012-11-30
<i>Band filter</i>	ASI	82346	S06389	2012-11-30
<i>Biconilog Antenna</i>	ETS	3142C	00042672	2012-11-30
<i>Semi-anechoic Chamber</i>	ETS	N/A	N/A	2012-11-30

# ***Table of Contents***

---

<b><i>DISCLAIMER NOTICE</i></b>	<b><i>1</i></b>
<b><i>REPRODUCTION CLAUSE</i></b>	<b><i>1</i></b>
<b><i>OPINIONS AND INTERPRETATIONS</i></b>	<b><i>1</i></b>
<b><i>STATEMENT OF MEASUREMENT UNCERTAINTY</i></b>	<b><i>1</i></b>
<b><i>ADMINISTRATIVE DATA</i></b>	<b><i>2</i></b>
<b><i>EUT DESCRIPTION</i></b>	<b><i>3</i></b>
<b><i>ATTACHMENT 1 - RF EXPOSURE COMPLIANCE REQUIREMENT</i></b>	<b><i>5</i></b>

## **Disclaimer Notice**

*When government drawing, specification, or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawing, specifications, or other data, is not to be regarded by implication or otherwise in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell patented invention that may in any way be related thereto. This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.*

## **Reproduction Clause**

*Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from ECMG Electronic Technical Testing Corp (Shenzhen).*

## **Opinions and Interpretations**

*This test report relates to the abovementioned equipment under test (EUT). Without the permission of ECMG Electronic Technical Testing Corp (Shenzhen). Test Lab this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products. The manufacturer has sole responsibility of continued compliance of the device.*

## **Statement of Measurement Uncertainty**

*The data and results referenced in the document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error. Furthermore, component and process variability of devices similar to that tested may result in additional deviation.*

## **Administrative Data**

*Test Sample* : SMART PLAYER

*Model Name* : HS\*\*("\*" can be 0-9)

*Model Tested* : HS06

*Receipt Date* : April 29<sup>th</sup>, 2012

*Date Tested* : May 3<sup>rd</sup>, 2012 to June 27<sup>th</sup>, 2012

*Applicant* : HESIO INTERNATIONAL CO., LTD

*Address* : UNIT 1 3/F, GOOD HARVEST CENTRE, 33 ON CHUEN STREET FANLING, NT, HONGKONG

*Telephone* : (00852)2682 6421

*Fax* : (00852)2793 1668

*Manufacturer* : HESIO INTERNATIONAL CO., LTD

*Address* : UNIT 1 3/F, GOOD HARVEST CENTRE, 33 ON CHUEN STREET FANLING, NT, HONGKONG

*Telephone* : (00852)2682 6421

*Fax* : (00852)2793 1668

*Factory* : HESIO INTERNATIONAL CO., LTD

*Address* : UNIT 1 3/F, GOOD HARVEST CENTRE, 33 ON CHUEN STREET FANLING, NT, HONGKONG

*Telephone* : (00852)2682 6421

*Fax* : (00852)2793 1668

## EUT Description

*HESIO INTERNATIONAL CO., LTD., model tested HS06(referred to as the EUT in this report) is a SMART PLAYER.*

*The EUT is a SMART PLAYER which integrates an IEEE 802.11 b/g/n Wi-Fi module. main technical specifications of the EUT are as belows:*

Parameter		Range	
Basic parameters	Rated voltage	DC 5V	
	Rated Current	2A	
802.11b/g/n Adapter Parameters	Operating band	2400-2483.5MHz	
	WIFI Module Voltage	DC 3.0V	
	Working Frequency of Each Channel	Channel No.	Frequency (MHz)
		001	2412
		002	2417
		003	2422
		004	2427
		005	2432
		006	2437
	Frequency of Number	IEEE 802.11b/g: 11 channels; 802.11n HT 20MHz: 11 channels; 802.11n HT 40MHz: 7 channels.	
	Modulation Type	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM IEEE 802.11n H420: OFDM	
	Transmit Power	802.11g/n: 15dBm ±15% 802.11b: 18dBm ±15%.	
	Antenna Spec.	1. Antenna Gain(peak): 2dBi 2. Impedance: 50 Ohm nominal 3. Antenna Type: I-PEX External Receptacle Antenna(1T1R)	

Continue on the next page...

I/O Ports	LAN interface x 1	<i>Ethernet 10/100M Network</i>
	DC Power Jack	<i>5V DC Power connector</i>
	USB Port x 2	<i>USB devices may be connected via the USB port</i>
	SD/MMC Slot	<i>supports SD/MMC Pro</i>
	HDMI output	<i>High-Definition Multimedia Interface</i>
	AV composite port (Optional)	<i>YPbPr&amp; CVBS output</i>
	Standard accessories	<i>IR remote control</i>
Power Adapter	<i>Input</i>	<i>100-240V, 50/60Hz, max 0.5A</i>
	<i>Output</i>	<i>DC5V 2A</i>
	<i>Model</i>	<i>GSCC2000S005V015</i>
	<i>Brand name</i>	<i>GSP</i>

*NOTE: For more detailed informations or features please refer to user's manual of EUT.*

## ATTACHMENT 1 – RF EXPOSURE COMPLIANCE REQUIREMENT

### **Applicable Standard:**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### **Limits for General Population/Uncontrolled Exposure**

#### **a) Limits for Occupational/Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times / E / 2 , / H / 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

#### **(b) Limits for General Population/Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times / E / 2 , / H / 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } S \text{ (mW/m}^2\text{)} = E^2 / 377$$

$E$  = Electric Field (V/m)

$P$  = Peak RF output Power (W)

$G$  = EUT Antenna numeric gain (numeric)

$d$  = Separation distance between radiator and human body (m)

The formula can be changed to

$$S = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance  $d=0.2m$ , as well as the gain of the used antenna, the RF power density can be obtained.

Note :

The maximal conducted peak output power is 18.47dBm(0.070 Watt) in the high channel(2.462GHz).

The best case gain of the antenna is 2.0dBi.

2.0dB logarithmic terms convert to numeric result is nearly 1.58.

## Test Result:

Channel (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (W)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2462	1.58	18.47	0.0703	0.2210	1.0	Compliant

The unit does meet the requirement.