



FCC ID: 07VMA191522

IC: 5928A-MA191522

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : MONITOR AUDIO LTD.
Unit 2, 24 Brook Road Rayleigh, Essex. England SS6 7XJ
United Kingdom

Manufacturer : DONGGUAN BOSUN ELECTRONIC INC.
Zheng Long Industrial District, Sicun, Tangxia Town,
Dongguan City, Guangdong Province, China.

Equipment : Powered Speaker System

Type/Model : ASB-2

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm²

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test reports 130401050SHA-001:

The maximum output power = 24.02dBm = 252.348mW

The gain of antenna G = 3.00dBi = 1.995

R is chosen to be 20cm,

$S = PG / (4\pi R^2) = 252.348 * 1.995 / (4 * 3.14 * 20 * 20) = 0.10\text{mW/cm}^2$

This level is below the 1 mW/cm² MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.

Date of issue: May 29, 2013

Prepared by:

Wakeyou Wang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



FCC ID: O7VMA191522
IC: 5928A-MA191522

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.
To ensure compliance, operations at closer than this distance is not recommended.