

FCC 47 CFR MPE REPORT

MONITOR AUDIO LTD

Audio Amplifier

Model Number: airstream A100

FCC ID: O7VMA191811

Prepared for : MONITOR AUDIO LTD

**Unit 2, 24 Brook Road, Rayleigh, Essex England SS6 7XJ
United Kingdom**

Prepared By : EST Technology Co., Ltd.

**Santun(guantai Road), Houjie Town,
DongGuan City,GuangDong, China.
Tel: 86-769-83081888-808**

Report Number: ESTE-R1302003

Date of Test : Feb.1~25,2013

Date of Report : Feb.27,2013



Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G) \cdot 0.5/d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Channel	Frequency (MHz)	Peak output power (dBm)		Peak output power (mW)	
			Ant 1	Ant 2	Ant 1	Ant 2
IEEE 802.11b	Low :CH1	2412	12.35	10.47	17.18	11.14
	Middle: CH6	2437	12.31	10.25	17.02	10.59
	High: CH11	2462	12.75	10.07	18.84	10.16
IEEE 802.11g	Low :CH1	2412	10.17	7.88	10.40	6.14
	Middle: CH6	2437	10.18	8.21	10.42	6.62
	High: CH11	2462	10.37	8.34	10.89	6.82

Mode	Antenna gain		Power Density (S) (mW/cm ²)		Limited of Power Density (S) (mW/cm ²)	Test Result
	(dBi)	(Linear)	Ant 1	Ant 2		
IEEE 802.11b	2.2	1.66	0.0057	0.0037	1	Compiles
	2.2	1.66	0.0056	0.0035	1	Compiles
	2.2	1.66	0.0062	0.0034	1	Compiles
IEEE 802.11g	2.2	1.66	0.0034	0.0020	1	Compiles
	2.2	1.66	0.0034	0.0022	1	Compiles
	2.2	1.66	0.0036	0.0023	1	Compiles