

FCC 47 CFR MPE REPORT

MONITOR AUDIO LTD

Wireless Speaker

Model Number: AirStream WS100

FCC ID: O7VMA191823

Prepared for : MONITOR AUDIO LTD

Unit 2, 24 Brook Road, Rayleigh, Essex England SS6 7XJ
United Kingdom

Prepared By :EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town,
DongGuan City,GuangDong, China.
Tel: 86-769-83081888-808

Report Number: ESTE-R1205002

Date of Test : May.3~18, 2012

Date of Report : May.19, 2012

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 * P * G) / (0.5 * d)$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 * P * G) / (377 * d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



3、Calculated Result and Limit

3.1. Power From Adapter 1

Channel	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Antenna gain		Power Density (S) (mW/cm2)	Limited of Power Density (S) (mW/cm2)	Test Result
				(dBi)	(Linear)			
1	2403.585	16.36	43.25	2.2	1.66	0.0142	1	Compiles
24	2438.913	16.57	45.39	2.2	1.66	0.0150	1	Compiles
49	2477.313	16.21	41.78	2.2	1.66	0.0137	1	Compiles

3.2. Power From Adapter 2

Channel	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Antenna gain		Power Density (S) (mW/cm2)	Limited of Power Density (S) (mW/cm2)	Test Result
				(dBi)	(Linear)			
1	2403.585	16.33	42.95	2.2	1.66	0.0141	1	Compiles
24	2438.913	16.48	44.46	2.2	1.66	0.0147	1	Compiles
49	2477.313	16.20	41.68	2.2	1.66	0.0137	1	Compiles

