



FCC RADIO TEST REPORT-BT

FCC ID:O86T1500

Product : 10.1 Inch Full Ruggedized Tablet

Trade Name : N/A

Model Name : xTablet T1500

Serial Model : N/A

Report No. : NTEK-2015NT1211614F2

Prepared for

MobileDemand, LC.

1501 Boyson Square Drive Suite 101 Hiawatha, Iowa52233, United States.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,Xixiang Street
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599

Website:www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : MobileDemand, LC.

Address : 1501 Boyson Square Drive Suite 101 Hiawatha, Iowa52233,
United States.

Manufacture's Name : Emdoor Information Co.,Ltd.

Address : 3A 1/F Jinfulai Tower,No.49-1,Dabao Road,Baoan 28
District,Shenzhen, China.

Product description

Product name : 10.1 Inch Full Ruggedized Tablet

Model and/or type reference : xTablet T1500

Serial Model : N/A

Standards : FCC Part15.247: 01 Oct. 2015

Test procedure ANSI C63.10-2013

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : 11 Dec. 2015 ~15 Jan. 2016

Date of Issue : 15 Jan. 2016

Test Result : **Pass**

Testing Engineer : _____

Susan

(Susan Su)

Technical Manager : _____

Brown Lu

(Brown Lu)

Authorized Signatory : _____

Sam. Chen

(Sam Chen)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	24
3.2.1 RADIATED EMISSION LIMITS	24
3.2.2 TEST PROCEDURE	25
3.2.3 DEVIATION FROM TEST STANDARD	25
3.2.4 TEST SETUP	26
3.2.5 EUT OPERATING CONDITIONS	27
3.2.6 TEST RESULTS (BELOW 30 MHZ)	28
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	29
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	31
4 . NUMBER OF HOPPING CHANNEL	33
4.1 APPLIED PROCEDURES / LIMIT	33
4.1.1 TEST PROCEDURE	33
4.1.2 DEVIATION FROM STANDARD	33
4.1.3 TEST SETUP	33
4.1.4 EUT OPERATION CONDITIONS	33
4.1.5 TEST RESULTS	34
5 . AVERAGE TIME OF OCCUPANCY	35
5.1 APPLIED PROCEDURES / LIMIT	35

Table of Contents

	Page
5.1.1 TEST PROCEDURE	35
5.1.2 DEVIATION FROM STANDARD	35
5.1.3 TEST SETUP	36
5.1.4 EUT OPERATION CONDITIONS	36
5.1.5 TEST RESULTS	37
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	43
6.1 APPLIED PROCEDURES / LIMIT	43
6.1.1 TEST PROCEDURE	43
6.1.2 DEVIATION FROM STANDARD	43
6.1.3 TEST SETUP	43
6.1.4 EUT OPERATION CONDITIONS	43
6.1.5 TEST RESULTS	44
7 . BANDWIDTH TEST	50
7.1 APPLIED PROCEDURES / LIMIT	50
7.1.1 TEST PROCEDURE	50
7.1.2 DEVIATION FROM STANDARD	50
7.1.3 TEST SETUP	50
7.1.4 EUT OPERATION CONDITIONS	50
7.1.5 TEST RESULTS	51
8 . PEAK OUTPUT POWER TEST	57
8.1 APPLIED PROCEDURES / LIMIT	57
8.1.1 TEST PROCEDURE	57
8.1.2 DEVIATION FROM STANDARD	57
8.1.3 TEST SETUP	57
8.1.4 EUT OPERATION CONDITIONS	57
8.1.5 TEST RESULTS	58
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	64
9.1 DEVIATION FROM STANDARD	64
9.2 TEST SETUP	64
9.3 EUT OPERATION CONDITIONS	64
9.4 TEST RESULTS	65
10 . ANTENNA REQUIREMENT	72
10.1 STANDARD REQUIREMENT	72
10.2 EUT ANTENNA	72
11 . EUT TEST PHOTO	73
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	10.1 Inch Full Ruggedized Tablet	
Trade Name	N/A	
Model Name	xTablet T1500	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a 10.1 Inch Full Ruggedized Tablet	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
	Number Of Channel	79 CH
	Antenna Designation:	Please see Note 3.
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Adapter	Model:AW018WR-0500300UH Input: AC100-240V~, 50/60Hz,0.5A Output: 5V $\overline{\text{---}}$, 3A	
Battery	DC 3.7V,10000mAh	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	FPCB Antenna	N/A	1.0	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	normal link

For Conducted Emission	
Final Test Mode	Description
Mode 4	normal link

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.


2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS


Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test 1



Conducted Emission Test 2



Radiated Spurious Emission Test

E-1 EUT

2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	10.1 Inch Full Ruggedized Tablet	N/A	xTablet T1500	N/A	EUT
E-2	ADAPTER	N/A	AW018WR-0500300UH	N/A	
E-3	Earphone	N/A	2688	N/A	
E-4	Monitor	SONY	KDL-24EX520	N/A	
E-5	Printer	Canon	L11121E	LBP2900	
E-6	Personal computer	DELL	FT4Y23X	34413561645	
E-7	Monitor	DELL	IN2020MB	cn-0y6mhx-74261-11f-67es	
E-8	Keyboard	DELL	SK-8185	OY526KUS	
E-9	Mouse	DELL	MS111-P	cn-011d3v-71581-11e-1th7	

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	Power line	NO	YES	1.2m	
C-2	HDMI	NO	NO	1.0m	
C-3	Earphone	NO	NO	1.0m	
C-4	USB Cable	NO	NO	1.0m	
C-5	HDMI	NO	NO	1.0m	
C-6	USB Cable	NO	NO	1.0m	
C-7	USB Cable	NO	NO	1.0m	
C-8	USB Cable	NO	NO	1.0m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.12.22	2016.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
2	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
7	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
8	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
9	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1900	39.84	9.46	49.30	64.03	-14.73	QP
0.1900	16.13	9.46	25.59	54.03	-28.44	AVG
0.4818	39.22	9.48	48.70	56.31	-7.61	QP
0.4818	24.06	9.48	33.54	46.31	-12.77	AVG
0.7500	37.13	9.57	46.70	56.00	-9.30	QP
0.7500	21.00	9.57	30.57	46.00	-15.43	AVG
1.0740	37.14	9.56	46.70	56.00	-9.30	QP
1.0740	24.37	9.56	33.93	46.00	-12.07	AVG
1.5820	38.64	9.56	48.20	56.00	-7.80	QP
1.5820	22.12	9.56	31.68	46.00	-14.32	AVG
3.3820	37.13	9.64	46.77	56.00	-9.23	QP
3.3820	23.83	9.64	33.47	46.00	-12.53	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2061	41.64	9.46	51.10	63.36	-12.26	QP
0.2061	13.45	9.46	22.91	53.36	-30.45	AVG
0.3578	38.96	9.44	48.40	58.78	-10.38	QP
0.3578	21.06	9.44	30.50	48.78	-18.28	AVG
0.5260	38.24	9.46	47.70	56.00	-8.30	QP
0.5260	19.21	9.46	28.67	46.00	-17.33	AVG
0.7177	39.67	9.43	49.10	56.00	-6.90	QP
0.7177	25.00	9.43	34.43	46.00	-11.57	AVG
1.6935	38.25	9.45	47.70	56.00	-8.30	QP
1.6935	24.20	9.45	33.65	46.00	-12.35	AVG
3.1499	36.23	9.47	45.70	56.00	-10.30	QP
3.1699	19.31	9.47	28.78	46.00	-17.22	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from adapter AC 240V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.4858	39.61	9.49	49.10	56.24	-7.14	QP
0.4858	18.95	9.49	28.44	46.24	-17.80	AVG
0.9616	37.44	9.56	47.00	56.00	-9.00	QP
0.9616	15.95	9.56	25.51	46.00	-20.49	AVG
1.2016	38.34	9.56	47.90	56.00	-8.10	QP
1.2016	14.46	9.56	24.02	46.00	-21.98	AVG
2.4940	36.51	9.59	46.10	56.00	-9.90	QP
2.4940	11.99	9.59	21.58	46.00	-24.42	AVG
4.4298	35.03	9.67	44.70	56.00	-11.30	QP
4.4298	14.12	9.67	23.79	46.00	-22.21	AVG
6.1219	33.31	9.69	43.00	60.00	-17.00	QP
6.1219	10.93	9.69	20.62	50.00	-29.38	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from adapter AC 240V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.4778	37.64	9.46	47.10	56.38	-9.28	QP
0.4778	15.55	9.46	25.01	46.38	-21.37	AVG
0.5735	39.35	9.45	48.80	56.00	-7.20	QP
0.5735	13.09	9.45	22.54	46.00	-23.46	AVG
1.1370	36.76	9.44	46.20	56.00	-9.80	QP
1.1370	12.85	9.44	22.29	46.00	-23.71	AVG
2.4420	37.84	9.46	47.30	56.00	-8.70	QP
2.4420	13.77	9.46	23.23	46.00	-22.77	AVG
3.4140	33.93	9.47	43.40	56.00	-12.60	QP
3.4140	8.95	9.47	18.42	46.00	-27.58	AVG
6.3539	32.30	9.50	41.80	60.00	-18.20	QP
6.3539	11.40	9.50	20.90	50.00	-29.10	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from PC AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1621	42.64	9.46	52.10	65.35	-13.25	QP
0.1621	17.51	9.46	26.97	55.35	-28.38	AVG
0.3427	33.96	9.44	43.40	59.14	-15.74	QP
0.3427	7.27	9.44	16.71	49.14	-32.43	AVG
0.6500	31.66	9.44	41.10	56.00	-14.90	QP
0.6500	11.95	9.44	21.39	46.00	-24.61	AVG
0.9140	24.56	9.44	34.00	56.00	-22.00	QP
0.9140	11.47	9.44	20.91	46.00	-25.09	AVG
1.9536	23.54	9.46	33.00	56.00	-23.00	QP
1.9536	8.88	9.46	18.34	46.00	-27.66	AVG
4.4138	23.32	9.48	32.80	56.00	-23.20	QP
4.4138	11.50	9.48	20.98	46.00	-25.02	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from PC AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1912	38.74	9.46	48.20	63.98	-15.78	QP
0.1912	9.62	9.46	19.08	53.98	-34.90	AVG
0.3099	34.66	9.44	44.10	59.97	-15.87	QP
0.3099	8.99	9.44	18.43	49.97	-31.54	AVG
0.5620	33.15	9.45	42.60	56.00	-13.40	QP
0.5620	11.54	9.45	20.99	46.00	-25.01	AVG
0.7500	26.27	9.43	35.70	56.00	-20.30	QP
0.7500	10.00	9.43	19.43	46.00	-26.57	AVG
1.3340	22.50	9.45	31.95	56.00	-24.05	QP
1.3340	2.06	9.45	11.51	46.00	-34.49	AVG
4.7538	20.22	9.48	29.70	56.00	-26.30	QP
4.7538	4.53	9.48	14.01	46.00	-31.99	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from PC AC 240V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1995	39.04	9.46	48.50	63.63	-15.13	QP
0.1995	16.49	9.46	25.95	53.63	-27.68	AVG
0.5897	32.05	9.45	41.50	56.00	-14.50	QP
0.5897	15.12	9.45	24.57	46.00	-21.43	AVG
0.9616	25.86	9.44	35.30	56.00	-20.70	QP
0.9616	3.30	9.44	12.74	46.00	-33.26	AVG
2.8140	20.24	9.46	29.70	56.00	-26.30	QP
2.8140	4.68	9.46	14.14	46.00	-31.86	AVG
6.0377	23.00	9.50	32.50	60.00	-27.50	QP
6.0377	5.32	9.50	14.82	50.00	-35.18	AVG
8.8178	24.39	9.61	34.00	60.00	-26.00	QP
8.8178	5.78	9.61	15.39	50.00	-34.61	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from PC AC 240V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.5349	30.45	9.45	39.90	56.00	-16.10	QP
0.5349	4.77	9.45	14.22	46.00	-31.78	AVG
0.7860	25.77	9.43	35.20	56.00	-20.80	QP
0.7860	6.72	9.43	16.15	46.00	-29.85	AVG
1.8891	20.84	9.46	30.30	56.00	-25.70	QP
1.8891	1.02	9.46	10.48	46.00	-35.52	AVG
4.1619	18.83	9.47	28.30	56.00	-27.70	QP
4.1619	2.43	9.47	11.90	46.00	-34.10	AVG
7.5579	21.65	9.55	31.20	60.00	-28.80	QP
7.5579	10.61	9.55	20.16	50.00	-29.84	AVG
12.9336	20.59	9.74	30.33	60.00	-29.67	QP
12.9336	4.97	9.74	14.71	50.00	-35.29	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:


Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Peak	1 MHz	10 Hz

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	---

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Voltage :	DC 3.7V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.2924	8.54	18.66	27.20	40.00	-12.80	QP
V	90.8554	18.21	9.78	27.99	43.50	-15.51	QP
V	170.1947	16.13	12.54	28.67	43.50	-14.83	QP
V	312.1792	15.01	13.05	28.06	46.00	-17.94	QP
V	463.9696	14.40	16.21	30.61	46.00	-15.39	QP
V	520.8881	12.96	17.24	30.20	46.00	-15.80	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




Note: Mode 1Mbps(Mid CH) is the worst mode.

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	31.5091	5.92	19.03	24.95	40.00	-15.05	peak
H	71.0802	18.79	9.31	28.10	40.00	-11.90	peak
H	102.7192	12.93	10.27	23.20	43.50	-20.30	peak
H	189.0740	16.42	11.38	27.80	43.50	-15.70	peak
H	243.3771	17.35	10.65	28.00	46.00	-18.00	peak
H	343.1800	18.21	13.99	32.20	46.00	-13.80	peak

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Note: Mode 1Mbps(Mid CH) is the worst mode.

3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Mode :	DC 3.7V		

The Testing have been conformed to 10*2480MHz=24800MHz, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.103	59.65	-3.64	56.01	74.00	-17.99	Pk	Vertical
4804.103	41.88	-3.64	38.24	54.00	-15.76	AV	Vertical
7206.263	52.79	-0.95	51.84	74.00	-22.16	Pk	Vertical
7206.263	37.83	-0.95	36.88	54.00	-17.12	AV	Vertical
4804.561	59.92	-3.64	56.28	74.00	-17.72	Pk	Horizontal
4804.561	41.85	-3.64	38.21	54.00	-15.79	AV	Horizontal
7206.195	54.46	-0.95	53.51	74.00	-20.49	Pk	Horizontal
7206.195	38.24	-0.95	37.29	54.00	-16.71	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.376	58.42	-3.68	54.74	74.00	-19.26	Pk	Vertical
4882.376	41.76	-3.68	38.08	54.00	-15.92	AV	Vertical
7323.273	56.88	-0.82	56.06	74.00	-17.94	Pk	Vertical
7323.273	40.17	-0.82	39.35	54.00	-14.65	AV	Vertical
4882.364	59.54	-3.68	55.86	74.00	-18.14	Pk	Horizontal
4882.364	40.62	-3.68	36.94	54.00	-17.06	AV	Horizontal
7323.216	56.75	-0.82	55.93	74.00	-18.07	Pk	Horizontal
7323.216	41.62	-0.82	40.80	54.00	-13.20	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.327	59.84	-3.59	56.25	74.00	-17.75	Pk	Vertical
4960.327	42.92	-3.59	39.33	54.00	-14.67	AV	Vertical
7440.053	54.21	-0.68	53.53	74.00	-20.47	Pk	Vertical
7440.053	38.45	-0.68	37.77	54.00	-16.23	AV	Vertical
4960.316	58.57	-3.59	54.98	74.00	-19.02	Pk	Horizontal
4960.316	40.82	-3.59	37.23	54.00	-16.77	AV	Horizontal
7440.162	54.47	-0.68	53.79	74.00	-20.21	Pk	Horizontal
7440.162	38.34	-0.68	37.66	54.00	-16.34	AV	Horizontal

Note: Mode 1Mbps is the worst mode.

Radiated band edge:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	58.96	-13.06	45.90	74.00	-28.10	peak	Vertical
2390	56.48	-13.06	43.42	74.00	-30.58	peak	Horizontal
2483.5	60.21	-12.78	47.43	74.00	-26.57	peak	Vertical
2483.5	59.32	-12.78	46.54	74.00	-27.46	peak	Horizontal
1Mbps hopping							
2390	61.21	-13.06	48.15	74.00	-25.85	peak	Vertical
2390	60.56	-13.06	47.50	74.00	-26.50	peak	Horizontal
2483.5	59.79	-12.78	47.01	74.00	-26.99	peak	Vertical
2483.5	59.63	-12.78	46.85	74.00	-27.15	peak	Horizontal
2Mbps Non-hopping							
2390	59.67	-13.06	46.61	74.00	-27.39	peak	Vertical
2390	59.85	-13.06	46.79	74.00	-27.21	peak	Horizontal
2483.5	60.11	-12.78	47.33	74.00	-26.67	peak	Vertical
2483.5	58.74	-12.78	45.96	74.00	-28.04	peak	Horizontal
2Mbps hopping							
2390	59.67	-13.06	46.61	74.00	-27.39	peak	Vertical
2390	59.04	-13.06	45.98	74.00	-28.02	peak	Horizontal
2483.5	58.82	-12.78	46.04	74.00	-27.96	peak	Vertical
2483.5	57.63	-12.78	44.85	74.00	-29.15	peak	Horizontal
3Mbps Non-hopping							
2390	59.02	-13.06	45.96	74.00	-28.04	peak	Vertical
2390	60.32	-13.06	47.26	74.00	-26.74	peak	Horizontal
2483.5	59.14	-12.78	46.36	74.00	-27.64	peak	Vertical
2483.5	58.97	-12.78	46.19	74.00	-27.81	peak	Horizontal
3Mbps hopping							
2390	60.21	-13.06	47.15	74.00	-26.85	peak	Vertical
2390	57.66	-13.06	44.60	74.00	-29.40	peak	Horizontal
2483.5	59.01	-12.78	46.23	74.00	-27.77	peak	Vertical
2483.5	58.89	-12.78	46.11	74.00	-27.89	peak	Horizontal

4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥ 15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW=100kHz
VB	VBW $\geq$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW=100kHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode-GFSK		

Number of Hopping Channel	79
---------------------------	----



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- A Period Time = (channel number)*0.4
 DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
 DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
 DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH5 ,2DH5,3DH5		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH5	2441 MHz	0.88	0.09	0.4
2DH5	2441 MHz	1.23	0.13	0.4
3DH5	2441 MHz	0.88	0.09	0.4







EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH3,2DH3,3DH3		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH3	2441 MHz	1.66	0.27	0.4
2DH3	2441 MHz	1.24	0.20	0.4
3DH3	2441 MHz	0.88	0.14	0.4







EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH1	2441 MHz	0.43	0.14	0.4
2DH1	2441 MHz	0.41	0.13	0.4
3DH1	2441 MHz	0.42	0.13	0.4





6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (Channel Separation)
VB	100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.



6.1.5 TEST RESULTS

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: > 20dB bandwidth








EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth








EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.000	Complies
2441 MHz	1.000	Complies
2480 MHz	1.000	Complies

Ch. Separation Limits: >2/3 of 20dB bandwidth





7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	967.847	PASS
2441 MHz	967.474	PASS
2480 MHz	967.199	PASS







EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(2Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.353	PASS
2441 MHz	1.354	PASS
2480 MHz	1.352	PASS







EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.316	PASS
2441 MHz	1.318	PASS
2480 MHz	1.318	PASS





8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS


8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 VBW $\geq$ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS



EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	2.29	30
CH39	2441	2.87	30
CH78	2480	3.09	30
2Mbps			
CH00	2402	0.87	20.96
CH39	2441	0.76	20.96
CH78	2480	0.76	20.96
3Mbps			
CH00	2402	1.32	20.96
CH39	2441	1.31	20.96
CH78	2480	1.43	20.96















9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP



9.3 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.4 TEST RESULTS



EUT :	10.1 Inch Full Ruggedized Tablet	Model Name :	xTablet T1500
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH78 (1M/2M/3Mbps Mode)		



Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
1Mbps Non-hopping			
2400	62.61	20	Pass
2483.5	66.92	20	Pass
2Mbps Non-hopping			
2400	59.53	20	Pass
2483.5	60.45	20	Pass
3Mbps Non-hopping			
2400	58.11	20	Pass
2483.5	60.64	20	Pass
1Mbps hopping			
2400	64.16	20	Pass
2483.5	65.27	20	Pass
2Mbps hopping			
2400	61.26	20	Pass
2483.5	61.58	20	Pass
3Mbps hopping			
2400	59.79	20	Pass
2483.5	60.80	20	Pass



BDR mode (GFSK): Band Edge-Left Side





BDR mode (GFSK): Band Edge-Right Side





EDR mode ($\pi/4$ -DQPSK): Band Edge-Left Side

EDR mode ($\pi/4$ -DQPSK): Band Edge- Right Side


EDR mode(8DPSK): Band Edge-Left Side



EDR mode(8DPSK): Band Edge-Right Side



NOTE: Hopping enabled and disabled have evaluated, and the worst data was reported

10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

11. EUT TEST PHOTO

Radiated Measurement Photos



CONDUCTED EMISSION Photos

