

# SEA AIR AND LAND COMMUNICATIONS LTD

120 ST ASAPH STREET, PO BOX 22-621, CHRISTCHURCH, NEW ZEALAND  
Phone: +64 3 379-2298 Fax: +64 3 365-1580 Email: sales@salcom.co.nz

20 August 2001

## 11-78 and 11-75 4 Watt NRZ UHF POCSAG Transmitters

### Details of 11-78 & 11-75 Circuitry Similarities/Differences

#### Same circuitry;

RF lineup, synthesizer, modulator amp, modulator -low speed & high speed, VTXCO and RF oscillator, power control circuit, voltage regulators, micro-controller - substantial parts of circuitry, VCO lock.

#### Differences;

Input circuitry; -to pcb mounted terminal blocks (11-75), -to pcb mounted D15 socket (11-78)  
Power Connection; - to pcb mounted terminal blocks (11-75), -to pcb mounted power plug (11-78).  
Power adjustment/turndown circuit; 11-78 = 100mW to 4 Watt, 11-75 = 4 Watts only.  
Slew limiter, data generator.

#### Comments;

Differences between 11-78 and 11-75 relate to the input circuitry, data train generator circuitry and power adjustment circuitry.

The 11-75 generates its own data train whereas the 11-78 accepts a data train on its input. On both, the data train passes to the modulator via the micro-controller, so integrity of the data shape is maintained or controlled.

The 11-78 uses an rf power feedback circuitry to accurately adjust and control power at 100mW (EC requirement).

John Croft  
Engineering Manager  
Sea Air & Land Communications (Salcom) Ltd  
Christchurch  
New Zealand