



July 23, 2014

UL Japan, Inc.  
1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

FCC ID: O8CJM1L2S

To whom it may concern,

We, UL Japan, Inc., hereby declare that JM1, model : JM1L2S (FCC ID: O8CJM1L2S) of Aplix IP Holdings Corporation is exempt from RF exposure SAR evaluation as its output power meets the exclusion limits stated in FCC Part 2 §2.1093.

KDB 447498D01(v05r02) has the following exclusion for portable devices:  
The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{measured maximum equivalent isotropic radiated power(mW)}) / (\text{Minimum separation distance(mm)})] \cdot [\sqrt{f \text{ (GHz)}}]$   
 $\leq 3.0$  for 1g SAR and  $\leq 7.5$  for 10g extremity SAR where  
•  $f(\text{GHz})$  is the RF channel transmit frequency in GHz  
• Power and distance are rounded to the nearest mW and mm before calculation  
• The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

This device  $f = 2.48 \text{ GHz}$ , distance = 5mm (minimum separation distance: 5 mm was used in the calculation) and the measured maximum equivalent isotropic radiated power was 3 mW

So for this device:

$3 \text{ mW} [\text{measured maximum equivalent isotropic radiated power}] / 5 \text{ mm} [\text{minimum separation distance}] * (\sqrt{2.48}) = 0.9$   
\* calculation: measured maximum equivalent isotropic radiated power =  $10^{\text{((maximum peak output power [dBm] + antenna gain [dBi]) / 10)}}$   
 $= 10^{\text{((1.43 [dBm] + 3 [dBi]) / 10)}}$

\*This is less than 3.0, so no SAR is required.

Thank you for your attention to this matter.

Toyokazu Imamura  
Leader  
Consumer Technology Division  
UL Japan, Inc.

---

## UL Japan, Inc.

### Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400  
Facsimile: +81 463 50 6401