



CERTIFICATION TEST REPORT

FOR THE

POWERSCAN RF, BASE STATION

FCC PART 15 SUBPART C SECTIONS 15.209, 15.207 & 15.249

COMPLIANCE

DATE OF ISSUE: OCTOBER 9, 2000

PREPARED FOR: PREPARED BY:

PSC Scanning, Inc.

959 Terry Street

Eugene, OR 97402

Tracy Phillips

CKC Laboratories, Inc.

5473A Clouds Rest

Mariposa, CA 95338

P.O. No: 50140 W.O. No: 75197 Date of test: September 14, 2000

Report No: FC00-098

DOCUMENTATION CONTROL: APPROVED BY:

Tracy Phillips Dennis Ward

Documentation Control Supervisor

CKC Laboratories, Inc.

Director of Laboratories

CKC Laboratories, Inc.

This report contains a total of 36 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of CKC Laboratories, Inc.

Page 1 of 36 Report No: FC00-098

Dennis Ward

TABLE OF CONTENTS

Administrative Information	.3
Summary Of Results	
Equipment Under Test (EUT) Description	.4
Measurement Uncertainty	
EUT Operating Frequency	.4
Peripheral Devices	.4
Report Of Measurements	.5
Table 1: Fundamental Emission Levels	.5
Table 2: Six Highest Spurious Emission Levels - Transmit Mode (1 MHz - 10 GHz)	.6
Table 3: Six Highest Radiated Emission Levels - Receive Mode (30 MHz - 5 GHz)	.7
Table 4: Six Highest Conducted Emission Levels	.8
Table A: List Of Test Equipment	.9
EUT Setup	.10
Test Instrumentation And Analyzer Settings	
Table B: Analyzer Bandwidth Settings Per Frequency Range	.11
Spectrum Analyzer Detector Functions	
Peak	.12
Quasi-Peak	.12
Average	.12
Test Methods	.13
Radiated Emissions Testing	.13
Conducted Emissions Testing	. 14
Transmitter Characteristics	.14
Band Edge Measurements	.14
Power Output FCC Part 15.249 (a)	. 14
Sample Calculations	.15
Appendix A: Information About The Equipment Under Test	.16
Required EUT Changes To Comply	.17
Cable Information	
Photograph Showing Radiated Emissions	.19
Photograph Showing Radiated Emissions	.20
Photograph Showing Conducted Emissions	.21
Photograph Showing Conducted Emissions	
Appendix B: Measurement Data Sheets	.23
Band Edge Plot	.24
Band Edge Plot	.25

Page 2 of 36 Report No: FC00-098 CKC Laboratories, Inc. has Certificates of Accreditation from the following agencies:

DATech (Germany); A2LA (USA); FCC (USA); VCCI (Japan); BSMI (Taiwan); HOKLAS (Hong Kong).

CKC Laboratories, Inc. has Letters of Acceptance through an MRA for the following agencies:

ACA/NATA (Australia); SABS (South Africa); SWEDAC (Sweden); TUV Rheinland-Germany; TUV Rheinland-

Korea; TUV Rheinland-Russia; Radio Communications Agency (RA); NEMKO (Norway).

ADMINISTRATIVE INFORMATION

DATE OF TEST: September 14, 2000

PURPOSE OF TEST:To demonstrate the compliance of the

PowerScan RF, Base Station 900 MHz, with the requirements for FCC Part 15 Subpart C Sections 15.109, 15.207 & 15.249 devices.

MANUFACTURER: PSC Scanning, Inc.

959 Terry Street Eugene, OR 97402

REPRESENTATIVE: Jerry Kalina

TEST LOCATION: CKC Laboratories, Inc.

22105 Wilson River Hwy Tillamook, OR 97141

TEST PERSONNEL: Mike Wilkinson

TEST METHOD: ANSI C63.4 1992

FREQUENCY RANGE TESTED: 450 kHz - 10 GHz

EQUIPMENT UNDER TEST: PowerScan RF

Manuf: PSC Scanning, Inc.
Model: Base Station 900 MHz

Serial: 1305

FCC ID: 09NPWRSCAN-BS (pending)

Page 3 of 36 Report No: FC00-098

SUMMARY OF RESULTS

The PSC Scanning, Inc. PowerScan RF, Base Station, was tested in accordance with ANSI C63.4 1992 for compliance with FCC Part 15 Subpart C Sections 15.109, 15.207 & 15.249.

As received, the above equipment was found to be fully compliant with the limits of FCC Part 15 Subpart C Sections 15.109, 15.207 & 15.249. The results in this report apply only to the items tested, as identified herein.

EQUIPMENT UNDER TEST (EUT) DESCRIPTION

Handheld barcode scanner with base station.

MEASUREMENT UNCERTAINTY

Associated with data in this report is a $\pm 4dB$ measurement uncertainty.

EUT OPERATING FREQUENCY

The EUT was operating at 904.29640, 916.133094 & 924.86 MHz.

TEMPERATURE AND HUMIDITY DURING TESTING

The temperature during testing was within $+15^{\circ}$ C and $+35^{\circ}$ C. The relative humidity was between 20% and 75%.

PERIPHERAL DEVICES

The EUT was tested with the following peripheral device(s):

Termination Box

Manuf: PSC Scanning, Inc.

Model: Keyboard Wedge/RS232

Serial: 854-105-001

Page 4 of 36 Report No: FC00-098

REPORT OF MEASUREMENTS

The following tables report the highest worst case levels recorded during the tests performed on the PowerScan RF, Base Station 900 MHz. All readings taken are peak readings unless otherwise noted by a "Q" or "A". The data sheets from which these tables were compiled are contained in Appendix B.

	Table 1: Fundamental Emission Levels										
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$								NOTES			
904.330	89.3	22.1	-27.6	7.1		90.9	94.0	-3.1	V		
916.099	90.1	22.2	-27.6	7.2		91.9	94.0	-2.1	V		
924.783	91.0	22.3	-27.6	7.3		93.0	94.0	-1.0	V		

Test Method: ANSI C63.4 1992 NOTES: H = Horizontal Polarization Spec Limit: FCC Part 15.249 V = Vertical Polarization Test Distance: 3 Meters Q = Quasi Peak Reading Tested By: Mike Wilkinson Q = Quasi Peak Reading

COMMENTS: EUT is continuously transmitting with modulation on the following channels as indicated for each reading: Ch 0 = 904.29640, MHz Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%.

Page 5 of 36 Report No: FC00-098

1	Table 2: Six Highest Spurious Emission Levels - Transmit Mode (1 MHz - 10 GHz)											
FREQUENCY MHz	METER READING dBµV	COR Ant dB	RECTION Amp dB	ON FACT Cable dB	ORS Dist dB	CORRECTED READING dBµV/m	SPEC LIMIT dBµV/m	MARGIN DB	NOTES			
11.048	30.8	11.0	0.0	1.0		42.8	50.0	-7.2	N			
44.170	38.1	12.1	-27.6	1.5		24.1	40.0	-15.9	V			
55.090	41.4	7.6	-27.6	1.6		23.0	40.0	-17.0	V			
185.100	41.5	9.6	-27.0	3.0		27.1	43.5	-16.4	V			
1849.658	42.7	27.1	-36.6	5.7		38.9	54.0	-15.1	V			
2712.800	40.5	29.2	-34.9	7.5		42.3	54.0	-11.7	V			

Test Method: ANSI C63.4 1992 NOTES: H = Horizontal Polarization Spec Limit: FCC Part 15.249/209 V = Vertical Polarization Test Distance: 3 Meters V = Vertical Polarization New Polarization V =

COMMENTS: EUT is continuously transmitting with modulation on the following channels as indicated for each reading: Ch 0 = 904.29640, MHz Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 1.0 MHz to 10.0 GHz. Lowest clock = 3.68 MHz.

Page 6 of 36 Report No: FC00-098

	Table 3: Six Highest Radiated Emission Levels - Receive Mode (30 MHz - 5 GHz)											
FREQUENCY MHz	METER READING dBµV	COR Ant dB	RECTION Amp dB	ON FACT Cable dB	ORS Dist dB	CORRECTED READING dBµV/m	SPEC LIMIT dBµV/m	MARGIN DB	NOTES			
44.170	38.1	12.1	-27.6	1.5		24.1	40.0	-15.9	V			
55.090	41.4	7.6	-27.6	1.6		23.0	40.0	-17.0	V			
185.100	41.5	9.6	-27.0	3.0		27.1	43.5	-16.4	V			
915.016	37.9	22.2	-27.6	7.2		39.7	46.0	-6.3	V			
926.841	37.6	22.3	-27.6	7.3		39.6	46.0	-6.4	V			
935.575	37.7	22.4	-27.6	7.2		39.7	46.0	-6.3	Н			

Test Method: ANSI C63.4 1992 NOTES: H = Horizontal Polarization Spec Limit: FCC Part 15.109 V = Vertical Polarization Test Distance: 3 Meters V = Vertical Polarization Nested By: Mike Wilkinson V = Vertical Polarization V = Vertical Polarizatio

COMMENTS: EUT is Receive only mode on the following channels as indicated for each reading: Ch 0 = 904.29640, MHz Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 30.0 MHz to 5.0 GHz. Lowest clock = 3.68 MHz. Highest tuned frequency = 924.86 MHz.

Page 7 of 36 Report No: FC00-098

	Table 4: Six Highest Conducted Emission Levels											
FREQUENCY MHz	METER READING dBµV	COR Lisn dB	dB	ON FACT Cable dB	ORS dB	CORRECTED READING dBµV	SPEC LIMIT dBµV	MARGIN dB	NOTES			
0.458358	44.1	0.1		0.1		44.3	48.0	-3.7	В			
0.546117	42.2	0.1		0.1		42.4	48.0	-5.6	В			
0.606713	41.0	0.1		0.1		41.2	48.0	-6.8	В			
0.915959	41.2	0.2		0.2		41.6	48.0	-6.4	В			
1.035060	40.4	0.0		0.5		40.9	48.0	-7.1	В			
1.229383	39.3	0.0		0.2		39.5	48.0	-8.5	В			

Test Method: ANSI C63.4 1992 NOTES: Q = Quasi Peak Reading Spec Limit: FCC Section 15.207 A = Average Reading Tested By: Mike Wilkinson B = Black Lead W = White Lead

COMMENTS: EUT is continuously transmitting with modulation on Ch 0 = 904.29640 MHz. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 450 kHz to 30 MHz. AC input is 120 V, 60 Hz.

Page 8 of 36 Report No: FC00-098

TABLE A

LIST OF TEST EQUIPMENT

Industry Canada File No. IC 3082-A

Function	S/N	Calibration Date	Cal Due Date
HP 8593EM EMC Analyzer	3624A00159	10/05/1999	10/05/2000
Fischer LISN	none	12/28/1999	12/28/2000
Fischer LISN	none	12/28/1999	12/28/2000
HP 8447D Amplifier	2727A05392	02/14/2000	02/14/2001
Chase CBL6111C Bilog Antenna	2455	06/17/2000	06/17/2001
HP 8593EM EMC Analyzer	3624A00159	10/05/1999	10/05/2000
HP 83017A Amplifier	3123A00321	10/21/1999	10/21/2000
EMCO 3115 1-18 GHz Horn Antenna	9006-4854	02/17/2000	02/17/2001
EMCO 6502 Mag Loop Antenna	2156	01/26/2000	01/26/2001

Page 9 of 36 Report No: FC00-098

EUT SETUP

The equipment under test (EUT) and the peripheral listed were set up in a manner that represented their normal use. Any special conditions required for the EUT to operate normally are identified in the comments that accompany Table 1 for fundamental emission levels, Table 2 for spurious emission levels, Table 3 for receive mode levels and Table 4 for conducted emssions. Additionally, a complete description of the EUT is included on the information sheets contained in Appendix A.

During radiated emissions testing, the EUT was mounted on a nonconductive, rotating table 80 cm above the conductive grid. The nonconductive table dimensions were 1 meter by 1.5 meters. This configuration is typical for radiated emissions testing of table top devices.

During conducted emissions testing, the EUT was located 80 centimeters above the conducting ground plane on the same nonconducting table as was used for radiated testing. The metal plane was grounded to the earth through the green wire safety ground. Power to the EUT was provided via 3 meters of shielded power cable from a filter grounded to the metal plane to a LISN. The LISN was also grounded to the plane and attached to the LISN was a 4 ganged grounded outlet whose source was also shielded and 60 cm in length. All other objects were kept a minimum of 1 meter away from the EUT during the conducted test.

Page 10 of 36 Report No: FC00-098

TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed in Table A were used to collect both the radiated and conducted emissions data for the Base Station, PowerScan RF. For frequencies below 30 MHz, the magnetic loop antenna was used. For radiated measurements between 30 to 1000 MHz, the biconilog antenna was used. Above 1000 MHz, the horn antenna was used. All antennas were located at a distance of 3 meters from the edge of the EUT. Conducted emissions tests required the use of the FCC type LISN's.

The HP spectrum analyzer was used for all measurements. Table B shows the analyzer bandwidth settings that were used in designated frequency bands. For conducted emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used. A 10 dB external attenuator was also used during conducted tests, with internal offset correction in the analyzer. During radiated testing, the measurements were made with 0 dB of attenuation, a reference level of 97 dB μ V, and a vertical scale of 10 dB per division.

TABLE B: ANALYZER BANDWIDTH SETTINGS PER FREQUENCY RANGE

TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
CONDUCTED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	1 MHz	30 MHz	9 kHz
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz
RADIATED EMISSIONS	1000 MHz	10 GHz	1 MHz

Page 11 of 36 Report No: FC00-098

SPECTRUM ANALYZER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in Tables 1, 2, 3 & 4 indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "Peak" mode. Whenever a "Quasi-Peak" or "Average" reading is listed as one of the highest readings, this is indicated as a "Q" or an "A" in the appropriate table. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data for the PowerScan RF, Base Station 900 MHz.

Peak

In this mode, the Spectrum Analyzer or test engineer recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature of the analyzer called "peak hold," the analyzer had the ability to measure transients or low duty cycle transient emission peak levels. In this mode the analyzer made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

Quasi-Peak

When the true peak values exceeded or were within 2 dB of the specification limit, quasi-peak measurements were taken using the HP Quasi-Peak Adapter for the HP Spectrum Analyzer. The detailed procedure for making quasi peak measurements contained in the HP Quasi-Peak Adapter manual were followed.

Average

For certain frequencies, average measurements may be made using the spectrum analyzer. To make these measurements, the test engineer reduces the video bandwidth on the analyzer until the modulation of the signal is filtered out. At this point the analyzer is set into the linear mode and the scan time is reduced.

Page 12 of 36 Report No: FC00-098

TEST METHODS

The radiated and conducted emissions data of the Base Station, PowerScan RF, was taken with the HP Spectrum Analyzer. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the "Sample Calculations". The corrected data was then compared to the FCC Part 15, Subpart C, Sections 15.249, 15.207 & 15.109 emissions limits to determine compliance.

Preliminary and final measurements were taken in order to better ensure that all emissions from the EUT were found and maximized.

Radiated Emissions Testing

During the preliminary radiated scan, the EUT was powered up and operating in its defined test mode. The magnetic loop antenna was used to scan for frequencies below 30 MHz. The frequency range of 30 MHz - 1000 MHz was scanned with the biconilog antenna located about 1.5 meter above the ground plane in the vertical polarity. During this scan, the turntable was rotated and all peaks, which were at or near the limit, were recorded. Lastly, a scan of the FM band from 88 - 110 MHz was made, using a reduced resolution bandwidth and a reduced frequency span. The biconilog antenna was changed to the horizontal polarity and the above steps were repeated. The horn antenna was used to scan for frequencies above 1000 MHz. Care was taken to ensure that no frequencies were missed within the FM and TV bands. An analysis was performed to determine if the signals that were at or near the limit were caused by an ambient transmission. If unable to determine by analysis, the equipment was powered down to make the final determination if the EUT was the source of the emission.

For the final radiated scan, a thorough scan of all frequencies was made manually using a small frequency span, rotating the turntable as needed. Comparison with the previously recorded measurements was then made.

Using the peak readings from both scans as a guide, the test engineer then maximized the readings with respect to the table rotation, and antenna height. Photographs showing the final worst case configuration of the EUT are contained in Appendix A.

Page 13 of 36 Report No: FC00-098

Conducted Emissions Testing

For conducted emissions testing, a 30 to 50 second sweep time was used for automated measurements in the frequency bands of 450 kHz to 1.705 MHz, 1.705 MHz to 3 MHz, and 3 MHz to 30 MHz. All readings within 20 dB of the limit were recorded. At frequencies where the recorded emissions were close to the limit, further investigation was performed manually at a slower sweep rate.

TRANSMITTER CHARACTERISTICS

Band Edge Measurements

The fundamental frequency was kept within the permitted band 902 - 928 MHz. Refer to Appendix B for the band edge plots.

Power Output FCC Part 15.249 (a)

The maximum ERP of this transmitter was measured at a test distance of three meters, utilitzing all three channels. This measurement was made with the EUT's integral antenna, for there is no provision for connecting an external antenna.

Page 14 of 36 Report No: FC00-098

SAMPLE CALCULATIONS

The basic spectrum analyzer reading was converted using correction factors as shown in the six highest emissions readings in Tables 1 through 4. For radiated emissions in $dB\mu V/m$, the spectrum analyzer reading in $dB\mu V$ was corrected by using the following formula:

Meter reading (dBµV)

- + Antenna Factor (dB)
- + Cable Loss (dB)
- Distance Correction (dB)
- Pre-amplifier Gain (dB)
- = Corrected Reading($dB\mu V/m$)

This reading was then compared to the applicable specification limit to determine compliance.

A typical data sheet will display the following in column format:

Amp-A	Cable 1	Bilog	Cable					T1 co	L13w	L14b
# Freq Rdng Cbl-2	Horn N	Mag L	26.5	Dist	Corr	Spec Margin	Polar			

means reading number

Freq is the frequency in MHz of the obtained reading.

Rdng is the reading obtained on the spectrum analyzer in $dB\mu V$.

Amp-A is short for the preamplifier factor or gain in dB.

Bilog is the biconilog antenna factor in dB.

Horn is the horn antenna factor in dB.

Mag L is the magnetic loop antenna factor in dB.

26.5 is the high frequency preamplifier factor or gain in dB.

Cable is the cable loss in dB of the coaxial cable on the OATS.

Cbl-2 is the cable loss in dB of the high frequency coaxial cable on the OATS.

Dist is the distance factor (in dB). It is used when testing at a different test distance than the one stated in the spec.

Corr is the corrected reading which is now in $dB\mu V/m$ (field strength).

Spec is the specification limit (dB) stated in the agency's regulations.

Margin is the closeness to the specified limit in dB; + is over and - is under the limit.

Polar is the Polarity of the antenna with respect to earth.

T1 co is the cable loss in dB of the coaxial cable used for conducted emissions testing.

L13w is the LISN factor for the white lead.

L14b is the LISN factor for the black lead.

Page 15 of 36 Report No: FC00-098

APPENDIX A INFORMATION ABOUT THE EQUIPMENT UNDER TEST

Page 16 of 36 Report No: FC00-098

INFORMATION ABOUT THE EQ	INFORMATION ABOUT THE EQUIPMENT UNDER TEST							
Test Software/Firmware:	N/A							
CRT was displaying:	N/A							
Power Supply Manufacturer:	Ault							
Power Supply Part Number:	4004-0705							
AC Line Filter Manufacturer:	N/A							
AC Line Filter Part Number:	N/A							
The AC power cord is removable and is NOT shielded								
Line voltage used during testing:	120 VAC							

I/O PO	ORTS
Type	#
N/A	1

CRYSTAL OSCILLATORS						
Type	Freq. In MHz					
Y2	14.7456					

PRINTED CIRCUIT BOARDS									
Function	Model & Rev	Clocks, MHz	Layers	Location					
Handheld and Base Station Boards		14.7456		Y2					

REQUIRED EUT CHANGES TO COMPLY:	
None	

Page 17 of 36 Report No: FC00-098

CABLE INFORMATION

Cable #:	1	Cable(s) of this type:	1
Cable Type:	AC/DC Power Supply to Base Station	Shield Type:	
Construction:		Length In Meters:	1.6
Connected To End (1):		Connected To End (2):	Tied directly to power supply
Connector At End (1):		Connector At End (2):	Metal to Base Station
Shield Grounded At (1):		Shield Grounded At (2):	
Part Number:	4004-0705 (115	Number of Conductors:	3
	VAC)		
Notes:	·		

Page 18 of 36 Report No: FC00-098

PHOTOGRAPH SHOWING RADIATED EMISSIONS



Radiated Emissions - Front View

Page 19 of 36 Report No: FC00-098

PHOTOGRAPH SHOWING RADIATED EMISSIONS



Radiated Emissions - Back View

Page 20 of 36 Report No: FC00-098

PHOTOGRAPH SHOWING CONDUCTED EMISSIONS



Conducted Emissions - Front View

Page 21 of 36 Report No: FC00-098

PHOTOGRAPH SHOWING CONDUCTED EMISSIONS




Conducted Emissions - Side View

Page 22 of 36 Report No: FC00-098

APPENDIX B MEASUREMENT DATA SHEETS


Page 23 of 36 Report No: FC00-098

Band Edge Plot



Lowest Channel

Band Edge Plot



Highest Channel

Page 25 of 36 Report No: FC00-098 Test Location: CKC Laboratories, Inc. • 22105 Wilson River Hwy • Tillamook, OR 97141 • 800 500-4EMC

Customer: **PSC Scanning, Inc.**

Specification: FCC15.249

 Work Order #:
 75197
 Date:
 09/14/2000

 Test Type:
 Fundamental Power
 Time:
 15:17:32

Equipment: Base Station 900 MHz Sequence#: 5

Manufacturer: PSC Scanning, Inc. Tested By: Mike Wilkinson

Model: PowerScan RF Base Station

S/N: 1305

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Base Station 900 MHz*	PSC Scanning, Inc.	PowerScan RF Base Station	1305

Support Devices:

Function	Manufacturer	Model #	S/N
Termination Box	PSC Scanning, Inc.	Keyboard Wedge/RS232	854-105-001

Test Conditions / Notes:

EUT is continuously transmitting with modulation on the following channels as indicated for each reading: Ch 0 = 904.29640 MHz, Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%.

Measu	Reading listed by margin.						Test Distance: 3 Meters				
			Amp-A	Cable	Bilog						
#	Freq	Rdng					Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\muV/m$	$dB\mu V/m \\$	dB	Ant
1	924.783M	91.0	-27.6	+7.3	+22.3		+0.0	93.0	94.0	-1.0	Vert
									Ch 9		
2	916.099M	90.1	-27.6	+7.2	+22.2		+0.0	91.9	94.0	-2.1	Vert
									Ch 5		
3	904.330M	89.3	-27.6	+7.1	+22.1		+0.0	90.9	94.0	-3.1	Vert
									Ch 0		
4	916.099M	84.8	-27.6	+7.2	+22.2		+0.0	86.6	94.0	-7.4	Horiz
									Ch 5		
5	924.829M	84.6	-27.6	+7.3	+22.3		+0.0	86.6	94.0	-7.4	Horiz
									Ch 9		
6	904.338M	83.6	-27.6	+7.1	+22.1		+0.0	85.2	94.0	-8.8	Horiz
									Ch 0		

Page 26 of 36 Report No: FC00-098 Test Location: CKC Laboratories, Inc. • 22105 Wilson River Hwy • Tillamook, OR 97141 • 800 500-4EMC

Customer: **PSC Scanning, Inc.**

Specification: FCC15.249

 Work Order #:
 75197
 Date:
 09/14/2000

 Test Type:
 Harmonics & Spurious
 Time:
 15:52:34

Equipment: Base Station 900 MHz Sequence#: 6

Manufacturer: PSC Scanning, Inc. Tested By: Mike Wilkinson

Model: PowerScan RF Base Station

S/N: 1305

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Base Station 900 MHz*	PSC Scanning, Inc.	PowerScan RF Base Station	1305

Support Devices:

Function	Manufacturer	Model #	S/N
Termination Box	PSC Scanning, Inc.	Keyboard Wedge/RS232	854-105-001

Test Conditions / Notes:

EUT is continuously transmitting with modulation on the following channels as indicated for each reading: Ch 0 = 904.29640 MHz, Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 1.0 MHz to 10.0 GHz. Lowest clock = 3.68 MHz.

Measu	rement Data:	R	Reading lis	sted by m	argin.	Test Distance: 3 Meters					
			Amp-A	Cable	Bilog	26.5					
#	Freq	Rdng	Cable	Cbl-2	Mag L	Horn	Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	924.900M	91.0	-27.6	+7.3	+22.3	+0.0	+0.0	93.0	94.0	-1.0	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 9 Funda	amental	
2	916.099M	90.1	-27.6	+7.2	+22.2	+0.0	+0.0	91.9	94.0	-2.1	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5 Funda	amental	
3	904.338M	89.3	-27.6	+7.1	+22.1	+0.0	+0.0	90.9	94.0	-3.1	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 0 Funda		
4	11.048M	30.8	+0.0	+1.0	+0.0	+0.0	+0.0	42.8	50.0	-7.2	None
			+0.0	+0.0	+11.0	+0.0			Ch 0		
5	11.045M	30.4	+0.0	+1.0	+0.0	+0.0	+0.0	42.4	50.0	-7.6	Vert
			+0.0	+0.0	+11.0	+0.0			Ch 9		
6	11.050M	29.3	+0.0	+1.0	+0.0	+0.0	+0.0	41.3	50.0	-8.7	None
			+0.0	+0.0	+11.0	+0.0			Ch 5		
7	2712.800M	40.5	+0.0	+0.0	+0.0	-34.9	+0.0	42.3	54.0	-11.7	Vert
			+1.0	+6.5	+0.0	+29.2			Ch 0		
8	2774.710M	40.3	+0.0	+0.0	+0.0	-35.0	+0.0	41.9	54.0	-12.1	Vert
			+0.8	+6.7	+0.0	+29.1			Ch 9		
9	1849.658M	42.7	+0.0	+0.0	+0.0	-36.6	+0.0	38.9	54.0	-15.1	Vert
			+0.5	+5.2	+0.0	+27.1			Ch 9		
10	2748.532M	36.8	+0.0	+0.0	+0.0	-35.0	+0.0	38.5	54.0	-15.5	Vert
			+0.9	+6.6	+0.0	+29.2			Ch 5		
11	1808.555M	41.9	+0.0	+0.0	+0.0	-36.8	+0.0	38.1	54.0	-15.9	Vert
			+0.7	+5.0	+0.0	+27.3			Ch 0		
12	44.170M	38.1	-27.6	+1.5	+12.1	+0.0	+0.0	24.1	40.0	-15.9	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 0		

Page 27 of 36 Report No: FC00-098

13	1832.227M	41.5	+0.0	+0.0	+0.0	-36.7	+0.0	37.7	54.0	-16.3	Vert
			+0.6	+5.1	+0.0	+27.2			Ch 5		
14	185.100M	41.5	-27.0	+3.0	+9.6	+0.0	+0.0	27.1	43.5	-16.4	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5		
15	55.090M	41.4	-27.6	+1.6	+7.6	+0.0	+0.0	23.0	40.0	-17.0	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5		
16	49.290M	39.2	-27.5	+1.5	+9.5	+0.0	+0.0	22.7	40.0	-17.3	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5		
17	42.180M	35.4	-27.6	+1.4	+13.2	+0.0	+0.0	22.4	40.0	-17.6	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 9		
18	126.600M	38.1	-27.4	+2.4	+11.9	+0.0	+0.0	25.0	43.5	-18.5	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5		
19	125.700M	35.1	-27.4	+2.4	+11.9	+0.0	+0.0	22.0	43.5	-21.5	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 0		
20	185.500M	35.6	-27.0	+3.0	+9.6	+0.0	+0.0	21.2	43.5	-22.3	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 0		
21	185.500M	35.2	-27.0	+3.0	+9.6	+0.0	+0.0	20.8	43.5	-22.7	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 9		
22	376.500M	30.0	-27.2	+4.0	+15.7	+0.0	+0.0	22.5	46.0	-23.5	Vert
			+0.0	+0.0	+0.0	+0.0			Ch 5		
23	185.100M	33.7	-27.0	+3.0	+9.6	+0.0	+0.0	19.3	43.5	-24.2	Horiz
			+0.0	+0.0	+0.0	+0.0			Ch 5		

Page 28 of 36 Report No: FC00-098 Test Location: CKC Laboratories, Inc. • 22105 Wilson River Hwy • Tillamook, OR 97141 • 800 500-4EMC

Customer: **PSC Scanning, Inc.**

Specification: FCC 15.109

 Work Order #:
 75197
 Date:
 09/14/2000

 Test Type:
 Maximized Emissions
 Time:
 15:49:59

Equipment: Base Station 900 MHz Sequence#: 7

Manufacturer: PSC Scanning, Inc. Tested By: Mike Wilkinson

Model: PowerScan RF Base Station

S/N: 1305

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Base Station 900 MHz*	PSC Scanning, Inc.	PowerScan RF Base Station	1305

Support Devices:

Function	Manufacturer	Model #	S/N
Termination Box	PSC Scanning, Inc.	Keyboard Wedge/RS232	854-105-001

Test Conditions / Notes:

EUT is Receive only mode on the following channels as indicated for each reading: Ch 0 = 904.29640 MHz, Ch 5 = 916.133094, Ch 9 = 924.86. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 30.0 MHz to 5.0 GHz. Lowest clock = 3.68 MHz. Highest tuned frequency = 924.86 MHz.

Measur	rement Data:	R	eading li	sted by m	argin.	Test Distance: 3 Meters					
			Amp-A	Cable	Bilog						
#	Freq	Rdng					Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	935.575M	37.7	-27.6	+7.2	+22.4		+0.0	39.7	46.0	-6.3	Horiz
									Ch 9		
2	915.016M	37.9	-27.6	+7.2	+22.2		+0.0	39.7	46.0	-6.3	Vert
									Ch 0		
3	926.841M	37.6	-27.6	+7.3	+22.3		+0.0	39.6	46.0	-6.4	Vert
									Ch 5		
4	926.841M	37.4	-27.6	+7.3	+22.3		+0.0	39.4	46.0	-6.6	Horiz
									Ch 5		
5	935.575M	37.1	-27.6	+7.2	+22.4		+0.0	39.1	46.0	-6.9	Vert
									Ch 9		
6	915.001M	37.3	-27.6	+7.2	+22.2		+0.0	39.1	46.0	-6.9	Horiz
									Ch 0		
7	44.170M	38.1	-27.6	+1.5	+12.1		+0.0	24.1	40.0	-15.9	Vert
									Ch 5		
8	185.100M	41.5	-27.0	+3.0	+9.6		+0.0	27.1	43.5	-16.4	Vert
									Ch 5		
9	55.090M	41.4	-27.6	+1.6	+7.6		+0.0	23.0	40.0	-17.0	Vert
									Ch 5		
10	49.290M	39.2	-27.5	+1.5	+9.5		+0.0	22.7	40.0	-17.3	Vert
									Ch 5		
11	42.180M	35.4	-27.6	+1.4	+13.2		+0.0	22.4	40.0	-17.6	Vert
									Ch 9		
12	126.600M	38.1	-27.4	+2.4	+11.9		+0.0	25.0	43.5	-18.5	Vert
									Ch 5		

Page 29 of 36 Report No: FC00-098

13	125.700M	35.1	-27.4	+2.4	+11.9	+0.0	22.0	43.5	-21.5	Vert
								Ch 5		
14	185.500M	35.6	-27.0	+3.0	+9.6	+0.0	21.2	43.5	-22.3	Vert
								Ch 5		
15	185.500M	35.2	-27.0	+3.0	+9.6	+0.0	20.8	43.5	-22.7	Vert
								Ch 9		
16	376.500M	30.0	-27.2	+4.0	+15.7	+0.0	22.5	46.0	-23.5	Vert
								Ch 5		
17	185.100M	33.7	-27.0	+3.0	+9.6	+0.0	19.3	43.5	-24.2	Horiz
								Ch 5		

Page 30 of 36 Report No: FC00-098

CKC Laboratories, Inc. • 22105 Wilson River Hwy • Tillamook, OR 97141 • 800 500-4EMC Test Location:

Customer: PSC Scanning, Inc. Specification: **FCC 15.207 COND**

75197 Work Order #: Date: 09/14/2000 Test Type: Time: 16:21:02 **Conducted Emissions**

Equipment: Sequence#: 8 **Base Station 900 MHz** Tested By: Mike Wilkinson

Manufacturer: PSC Scanning, Inc. PowerScan RF Base Station Model:

S/N: 1305

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Base Station 900 MHz*	PSC Scanning, Inc.	PowerScan RF Base Station	1305

Support Devices:

T I			
Function	Manufacturer	Model #	S/N
Termination Box	PSC Scanning, Inc.	Keyboard Wedge/RS232	854-105-001

Test Conditions / Notes:


EUT is continuously transmitting with modulation on Ch 0 = 904.29640 MHz. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3°C and the humidity was 55%. Frequency range investigated was 450 kHz to 30 MHz. AC input is 120 V, 60 Hz.

Measur	ement Data:	Reading listed by margin.					Test Lead: Black				
			T1 co		L14b						
#	Freq	Rdng					Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	458.358k	44.1	+0.1		+0.1		+0.0	44.3	48.0	-3.7	Black
2	481.343k	43.7	+0.3		+0.1		+0.0	44.1	48.0	-3.9	Black
3	450.000k	44.0	+0.0		+0.1		+0.0	44.1	48.0	-3.9	Black
4	516.864k	43.0	+0.3		+0.1		+0.0	43.4	48.0	-4.6	Black
5	546.117k	42.2	+0.1		+0.1		+0.0	42.4	48.0	-5.6	Black
6	554.475k	42.0	+0.1		+0.1		+0.0	42.2	48.0	-5.8	Black
7	571.191k	41.5	+0.1		+0.1		+0.0	41.7	48.0	-6.3	Black
8	915.959k	41.2	+0.2		+0.2		+0.0	41.6	48.0	-6.4	Black
9	585.818k	41.2	+0.1		+0.1		+0.0	41.4	48.0	-6.6	Black
10	606.713k	41.0	+0.1		+0.1		+0.0	41.2	48.0	-6.8	Black
11	1.035M	40.4	+0.5		+0.0		+0.0	40.9	48.0	-7.1	Black
12	1.008M	40.1	+0.6		+0.0		+0.0	40.7	48.0	-7.3	Black

Page 31 of 36 Report No: FC00-098

13	594.176k	40.5	+0.1	+0.1	+0.0	40.7	48.0	-7.3	Black
14	1.058M	40.1	+0.4	+0.0	+0.0	40.5	48.0	-7.5	Black
15	995.360k	40.0	+0.5	+0.0	+0.0	40.5	48.0	-7.5	Black
16	987.002k	40.1	+0.4	+0.0	+0.0	40.5	48.0	-7.5	Black
17	1.041M	40.0	+0.4	+0.0	+0.0	40.4	48.0	-7.6	Black
18	964.017k	39.9	+0.2	+0.1	+0.0	40.2	48.0	-7.8	Black
19	886.706k	39.7	+0.3	+0.2	+0.0	40.2	48.0	-7.8	Black
20	938.943k	39.7	+0.1	+0.1	+0.0	39.9	48.0	-8.1	Black
21	1.123M	39.4	+0.2	+0.0	+0.0	39.6	48.0	-8.4	Black
22	1.112M	39.4	+0.2	+0.0	+0.0	39.6	48.0	-8.4	Black
23	853.274k	39.2	+0.2	+0.2	+0.0	39.6	48.0	-8.4	Black
24	1.229M	39.3	+0.2	+0.0	+0.0	39.5	48.0	-8.5	Black
25	880.437k	39.0	+0.3	+0.2	+0.0	39.5	48.0	-8.5	Black
26	1.140M	39.2	+0.2	+0.0	+0.0	39.4	48.0	-8.6	Black
27	824.021k	38.9	+0.2	+0.2	+0.0	39.3	48.0	-8.7	Black
28	840.737k	38.8	+0.2	+0.2	+0.0	39.2	48.0	-8.8	Black
29	640.145k	38.8	+0.1	+0.2	+0.0	39.1	48.0	-8.9	Black
30	1.196M	38.8	+0.2	+0.0	+0.0	39.0	48.0	-9.0	Black

Page 32 of 36 Report No: FC00-098



Test Location: CKC Laboratories, Inc. • 22105 Wilson River Hwy • Tillamook, OR 97141 • 800 500-4EMC

Customer: **PSC Scanning, Inc.** Specification: **FCC 15.207 COND**

 Work Order #:
 75197
 Date:
 09/14/2000

 Test Type:
 Conducted Emissions
 Time:
 16:31:09

Equipment: Base Station 900 MHz Sequence#: 9

Manufacturer: PSC Scanning, Inc. Tested By: Mike Wilkinson

Model: PowerScan RF Base Station

S/N: 1305

Equipment Under Test (* = EUT):

Function	Manufacturer	Model #	S/N
Base Station 900 MHz*	PSC Scanning, Inc.	PowerScan RF Base Station	1305

Support Devices:

T I			
Function	Manufacturer	Model #	S/N
Termination Box	PSC Scanning, Inc.	Keyboard Wedge/RS232	854-105-001

Test Conditions / Notes:

EUT is continuously transmitting with modulation on Ch 0 = 904.29640 MHz. EUT tested in the wall mount position. This is the worst case as found during preliminary testing. The temperature was 21.3° C and the humidity was 55%. Frequency range investigated was 450 kHz to 30 MHz. AC input is 120 V, 60 Hz.

Measur	Measurement Data: Reading listed by margin.					Test Lead: White					
			T1 co	L13w							
#	Freq	Rdng					Dist	Corr	Spec	Margin	Polar
	MHz	dΒμV	dB	dB	dB	dB	Table	$dB\mu V/m$	$dB\mu V/m$	dB	Ant
1	479.253k	42.4	+0.2	+0.0			+0.0	42.6	48.0	-5.4	White
2	452.090k	42.6	+0.0	+0.0			+0.0	42.6	48.0	-5.4	White
3	498.059k	41.9	+0.4	+0.0			+0.0	42.3	48.0	-5.7	White
4	487.611k	42.0	+0.3	+0.0			+0.0	42.3	48.0	-5.7	White
5	506.417k	41.6	+0.4	+0.0			+0.0	42.0	48.0	-6.0	White
6	550.296k	40.4	+0.1	+0.0			+0.0	40.5	48.0	-7.5	White
7	564.923k	39.7	+0.1	+0.0			+0.0	39.8	48.0	-8.2	White
8	571.191k	39.3	+0.1	+0.0			+0.0	39.4	48.0	-8.6	White
9	915.959k	38.5	+0.2	+0.0			+0.0	38.7	48.0	-9.3	White
10	610.892k	38.4	+0.1	+0.0			+0.0	38.5	48.0	-9.5	White
11	598.355k	38.1	+0.1	+0.0			+0.0	38.2	48.0	-9.8	White
12	999.539k	37.5	+0.6	+0.0			+0.0	38.1	48.0	-9.9	White

Page 34 of 36 Report No: FC00-098

13	903.422k	37.8	+0.3	+0.0	+0.0	38.1	48.0	-9.9	White
14	1.023M	37.5	+0.5	+0.0	+0.0	38.0	48.0	-10.0	White
15	976.554k	37.7	+0.3	+0.0	+0.0	38.0	48.0	-10.0	White
16	1.008M	37.3	+0.6	+0.0	+0.0	37.9	48.0	-10.1	White
17	1.048M	37.3	+0.4	+0.0	+0.0	37.7	48.0	-10.3	White
18	1.073M	37.2	+0.3	+0.0	+0.0	37.5	48.0	-10.5	White
19	936.854k	37.4	+0.1	+0.0	+0.0	37.5	48.0	-10.5	White
20	955.659k	37.1	+0.1	+0.0	+0.0	37.2	48.0	-10.8	White
21	1.137M	36.8	+0.2	+0.0	+0.0	37.0	48.0	-11.0	White
22	838.647k	36.8	+0.2	+0.0	+0.0	37.0	48.0	-11.0	White
23	1.223M	36.7	+0.2	+0.0	+0.0	36.9	48.0	-11.1	White
24	1.121M	36.7	+0.2	+0.0	+0.0	36.9	48.0	-11.1	White
25	884.616k	36.5	+0.3	+0.0	+0.0	36.8	48.0	-11.2	White
26	863.721k	36.6	+0.2	+0.0	+0.0	36.8	48.0	-11.2	White
27	631.787k	36.7	+0.1	+0.0	+0.0	36.8	48.0	-11.2	White
28	1.129M	36.5	+0.2	+0.0	+0.0	36.7	48.0	-11.3	White
29	876.258k	36.4	+0.3	+0.0	+0.0	36.7	48.0	-11.3	White
30	1.158M	36.1	+0.2	+0.0	+0.0	36.3	48.0	-11.7	White

