



H.B. Compliance Solutions

Intentional Radiator Test Report

For the

Microchip Technology Inc.

915 MHz Ultra Low-Power Sub-GHz Transceiver Module

Tested under

The FCC Rules contained in Title 47 of the CFR, Part 15.247 for

Digitally Transmitting Sequence

Prepared for:

Microchip Technology Inc.

2355 W. Chandler Blvd.

Chandler, Arizona 85224

Prepared By:

H.B. Compliance Solutions

3292 E. Mead Drive

Gilbert, Arizona 85298

Reviewed By:

A handwritten signature in black ink, appearing to read 'Hoosamuddin Bandukwala'.

Hoosamuddin Bandukwala



Cert # ATL-0062-E

Engineering Statement: The measurements shown in this report were made in accordance with the procedure indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurement made, the equipment tested is capable of operation in accordance with the requirements of Part 15 of the FCC Rules under normal use and maintenance.

Report Status Sheet

Revision #	Report Date	Reason for Revision
Ø	March 22, 2011	Initial Issue

Table of Contents

EXECUTIVE SUMMARY	4
1. Testing Summary	4
EQUIPMENT CONFIGURATION	5
1. Overview	5
2. Test Facility	6
3. Description of Test Sample	6
4. Equipment Configuration	6
5. Support Equipment	6
6. Ports and Cabling Information	7
7. Method of Monitoring EUT Operation	7
8. Mode of Operation	7
9. Modifications	7
10. Disposition of EUT	7
Criteria for Un-Intentional Radiators	8
1. Radiated Emissions	8
Emissions Tests Calculations	9
Criteria for Intentional Radiators	12
2. Conducted Emissions	12
3. Occupied Bandwidth	15
4. RF Power Output	19
5. Conducted Spurious Emissions	22
6. Radiated Spurious Emissions and Restricted Band	27
7. Emissions at Band Edges	29
8. Power Spectral Density	32
I. Test Equipment	36

EXECUTIVE SUMMARY

1. Testing Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15.247. All tests were conducted using measurement procedure from ANSI C63.4-2003 and FCC Public Notice 558074 DTS Guide March 23, 2005 as appropriate.

Test Name	Test Method/Standard	Result	Comments
Unintentional Radiated Emissions	15.109	Pass	
A/C Power Line Conducted Emissions	15.207	Pass	
Occupied Bandwidth	15.247(a)(2)	Pass	
Peak Output Power	15.247(b)	Pass	
Conducted Spurious Emissions	15.247(d)	Pass	
Radiated Spurious Emissions	15.247(d), 15.209(a), 15.205	Pass	
Emissions At Band Edges & Restricted Band	15.247(d), 15.209(a), 15.205	Pass	
Power Spectral Density	15.247(e)	Pass	

EQUIPMENT CONFIGURATION

1. Overview

H.B Compliance Solutions was contracted by Microchip Technology Inc. to perform testing on the 915 MHz Ultra Low-Power Sub-GHz Transceiver Module under the purchase order number 159432.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Microchip, Transceiver module.

The tests were based on FCC Part 15 Rules. The tests described in this document were formal tests as described with the objective of the testing was to evaluate compliance of the Equipment Under Test (EUT) to the requirements of the aforementioned specifications. Microchip should retain a copy of this document and it should be kept on file for at least five years after the manufacturing of the EUT has been permanently discontinued. The results obtained relate only to the item(s) tested.

Product Name:	915 MHz Ultra Low-Power Sub-GHz Transceiver Module
Model(s) Tested:	MRF89XAM9A
FCC ID:	OA3MRF89XAM9A
Supply Voltage Input:	Primary Power : 3.3 Vdc
Frequency Range:	903-927 MHz
No. of Channels:	Single Chanel
Type(s) of Modulation:	FSK
Range of Operation Power:	0.0117 Watts (conducted)
Emission Designator:	N/A
Channel Spacing(s)	None
Test Item:	Pre-Production
Type of Equipment :	Fixed
Antenna Requirement (§15.203) :	Type of Antenna: PCB Meander Gain of Antenna: -1dBi
Environmental Test Conditions:	Temperature: 15-35°C Humidity: 30-60% Barometric Pressure: 860-1060 mbar
Modification to the EUT:	None
Evaluated By:	Staff at Emerson Network
Test Date(s):	03/07/11 till 03/22/11

2. Test Facility

All testing was performed at Emerson Network Power. This facility is located at 2900 S. Diablo Way, Suite 190, Tempe, AZ 85282. All equipment used in making physical determination is accurate and bears recent traceability to the National Institute of Standards and Technology.

Test facility at Emerson Network power is an A2LA accredited test site. The A2LA certificate number is 2716.01. The scope of accreditation covers the FCC Method - 47 CFR Part 15, ICES-003, CISPR 22, AS/NZS 3548 and VCCI

Radiated Emissions measurements were performed in a semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at Emerson Network Power.

3. Description of Test Sample

The Microchip, The MRF89XAM9A is an Ultra Low-Power Sub-GHz surface mount transceiver module with integrated crystal, internal voltage regulator, matching circuitry and PCB antenna. The MRF89XAM9A module operates in the 902–928 MHz ISM frequency band. The module interfaces to many Microchip PIC microcontrollers through a 4-wire SPO interface. The operating voltage is 3.3VDC typical.

4. Equipment Configuration

Ref. ID	Name / Description	Model Number	Serial Number
# 1	915 MHz Ultra Low-Power Sub-GHz Transceiver Module	MRF89XAM9A	N/A

Table 1. Equipment Configuration

5. Support Equipment

All support equipment supplied is listed in the following Support Equipment List.

Ref ID	Name / Description	Manufacturer	Model #	Serial #
#2	DC Power Supply	Hewlett Packard	E3610A	KR83021468
#3	Laptop Computer	IBM	Thinkpad T 41	99-K3967
#4	Microcontroller Board	Microchip	PICDEM Z	BUR062000003

Table 2. Support Equipment

6. Ports and Cabling Information

Ref ID	Port name on the EUT	Cable Description	Qty.	Length (m)	Shielded? (Y/N)	Termination Box ID & Port ID
#5	Power	2 wire	1	1	N	DC Power Supply
#6	Serial	DB-9	1	2	N	Laptop

Table 3. Ports and Cabling Information

7. Method of Monitoring EUT Operation

A test receiver will be used to monitor the data transmission from the EUT.

8. Mode of Operation

The EUT will be configured to transmit at maximum power level. Test mode was provided to select the lower, middle and upper band of the transmitter by test software which was operated through a laptop computer. This software allowed the transmitter to switch between each channel and its mode from modulated to CW mode. These settings were created for testing purpose only.

9. Modifications

9.1 Modifications to EUT

No modifications were made to the EUT

9.2 Modifications to Test Standard

No Modifications were made to the test standard.

10. Disposition of EUT

The test sample including all support equipment submitted to H.B Compliance Solutions for testing will be returned to Microchip Technology Inc. upon completion of testing & certification

Criteria for Un-Intentional Radiators

1. Radiated Emissions

Test Requirement(s):	§15.109	Test Engineer(s):	Frank Farrone
Test Results:	Pass	Test Date(s):	03/15/11

Test Procedures:

The final radiated emissions test was performed using the parameters described above as worst case. That final test was conducted at a facility that meets the ANSI C63.4 NSA requirements. The frequency range noted in the data sheets was scanned/tested at that facility. Emissions were maximized as specified, by varying table azimuth, antenna height, and manipulating cables.

Using the mode of operation and configuration noted within this report, a final radiated emissions test was performed. The frequency range investigated (scanned), is also noted in this report. Radiated emissions measurements were made at the EUT azimuth and antenna height such that the maximum radiated emissions level will be detected. This requires the use of a turntable and an antenna positioner. The preferred method of a continuous azimuth search is utilized for frequency scans of the EUT field strength with both polarities of the measuring antenna. A calibrated, linearly polarized antenna was positioned at the specified distance from the periphery of the EUT.

Note: The specified distance is the horizontal separation between the closest periphery of the EUT and the center of the axis of the elements of the receiving antenna. However, if the receiving antenna is a log-periodic array, the specified distance shall be the distance between the closest periphery of the EUT and the front-to-back center of the array of elements.

Tests were made with the antenna positioned in both the horizontal and vertical polarization planes. The measurement was varied in height above the conducting ground plane to obtain the maximum signal strength. Though specified in the report, the measurement distance shall be 3 meters. At any measurement distance, the antenna height was varied from 1 meter to 4 meters. These height scans apply for both horizontal and vertical polarization, except that for vertical polarization the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the antenna clears the ground surface by at least 25 cm.

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
30 MHz to 1 GHz	120 kHz	120 kHz	N/A
1 GHz to 11 GHz	1MHz	N/A	1MHz
Measurements were made using the bandwidths and detectors specified. The video filter was at least as wide as the IF bandwidth of the measuring receiver.			

Table 4. Radiated Emissions – Measurement Bandwidth

Emissions Tests Calculations

In the case of indoor measurements, radiated emissions measurements are made by the manipulation of correction factors using Rohde and Schwarz ES-K1 software. This is done automatically by the software during the final measurement process.

In both cases, the level of the Field Strength of the interfering signal is calculated by adding the Antenna Factor, Cable Factor and by subtracting the Amplifier Gain from the measured reading. The basic equation is as follows:

$$FS = RA + AF + (CF - AG)$$

Where: FS = Field Strength

RA = Receiver (indicated) Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

This laboratory uses an approach of combining the CF and AG using an end-to-end measurement of the entire cabling system, including the test cable, any in-line amplifiers, attenuators, or transient protection networks, all measured in-situ.


For a sample calculation, assume a receiver reading of 52.5 dBuV is obtained. With an antenna factor of 7.4 and a combined cable factor (CF + AG) of -27.9:

$$FS = 52.5 + 7.4 + (-27.9) = 32 \text{ dBuV/m}$$


$$FS = 32 \text{ dBuV/m}$$

If desired, this can be converted into its corresponding level in uV/m:

$$FS = 10^{((32 \text{ dBuV/m})/20)} = 39.8 \text{ uV/m}$$



Plot 1 – Radiated Emissions – 30MHz to 1GHz



Plot 2 – Radiated Emissions – 1GHz to 3GHz

Frequency (MHz)	Measured Level	Height(cm)	Azimuth (deg)	Polarization
814.22	36.83	100	0	Vertical

Table 5. Final Measurement Results for Radiated Emissions

Criteria for Intentional Radiators

2. Conducted Emissions

Test Requirement(s):	§15.207	Test Engineer(s):	Frank Farrone
Test Results:	DC powered device	Test Date(s):	04/04/2011

Test Procedures: The EUT was placed on a non-metallic table, 80cm above the ground plane inside a shielded enclosure. The EUT was powered through a $50\Omega/50\mu\text{H}$ LISN. The conducted emissions tests were performed using the mode of operation and configuration noted within this report. The frequency range investigated (scanned), is also noted in this report. Conducted power line measurements are made, unless otherwise specified, over the frequency range from 150 kHz to 30 MHz to determine the line-to-ground radio-noise voltage that is conducted from the EUT power-input terminals that are directly (or indirectly via separate transformer or power supplies) connected to a public power network. Equipment is tested with power cords that are the same as those cords normally used or that have electrical or shielding characteristics that are the same as those cords normally used. Typically those measurements are made using a LISN (Line Impedance Stabilization Network). All 50 Ohm measuring ports of the LISN are terminated by 50 Ohms, either by the 50 Ohm EMI receiver or a 50 Ohm resistive load.

Refer to the Emissions Tests Calculations section in the Radiated Emissions section for sample calculations. For the purposes of the conducted emissions test, the Antenna Factor (AF) is replaced by the LISN correction factor.

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.150 - 30	9.0	9.0	9.0


Measurements were made using the bandwidths and detectors specified. No video filter was used.

Table 6. Conducted Emissions – Measurement Bandwidth

Frequency Range (MHz)	15.107(b), Class A Limits (dBuV)		15.107(a), Class B Limits (dBuV)	
	Quasi-Peak	Average	Quasi Peak	Average
0.15 – 0.5	79	66	66 - 56	56 - 46
0.5 – 5.0	73	60	56	46
5.0 – 30	73	60	60	50

Note 1 – The lower limit shall apply at the transition frequencies.

Table 7. Conducted Emissions Limits – FCC Limits from Section 15.107(a)(b)




Plot 3 – Conducted Emission Plot – Positive Side

Frequency (MHz)	Measured Level (dB _u V)	Transducer (dB)	Limit(dB _u V)	Margin(dB)
0.181	54.0	10.1	64	10.4
0.249	50.20	10.1	62	11.5
0.265	49.00	10.0	61	11.4
0.285	48.30	10.0	61	12.3
0.315	48.20	10.0	60	11.7

Table 8. Measurement Results for QP

Frequency (MHz)	Measured Level (dB _u V)	Transducer (dB)	Limit(dB _u V)	Margin(dB)
0.181	29.70	10.1	54	24.7
0.249	24.40	10.1	52	27.4
0.265	23.90	10.1	51	27.3
0.278	23.40	10.0	51	27.4
0.285	22.60	10.0	51	28.0
0.315	22.90	10.0	50	27.0

Table 9. Measurement Results for Average



Plot 4 – Conducted Emissions – Ground Side

Frequency (MHz)	Measured Level (dB μ V)	Transducer (dB)	Limit(dB μ V)	Margin(dB)
0.216	47.70	10.1	63	15.3
0.254	48.0	10.1	62	13.6
0.274	48.10	10.0	61	12.9
0.279	48.10	10.0	61	12.8
0.310	47.50	10.0	60	12.5
0.315	47.20	10.0	60	12.7

Table 10. Measurement Results for Quasi Peak

Frequency (MHz)	Measured Level (dB μ V)	Transducer (dB)	Limit	Margin
0.216	20.80	10.1	53	32.2
0.254	20.20	10.1	52	31.4
0.274	20.10	10.0	51	30.9
0.279	20.10	10.0	51	30.7
0.310	19.60	10.0	50	30.4
0.315	19.50	10.0	50	30.3

Table 11. Measurement Results for Average

3. Occupied Bandwidth

Test Requirement(s):	15.247(a)(2)	Test Engineer(s):	Hoosam B.
Test Results:	Pass	Test Date(s):	03/07/11

Test Procedure: As required by 47 CFR 15.247(a): System using digital modulation techniques may operate in the 902-928MHz, 2400 – 2483.5MHz, and 5725 – 5850MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer. The measured highest peak power was set relative to zero dB reference. The RBW of the Spectrum Analyzer was set to 100kHz and VBW>RBW. Measurements were carried out at the low, mid and high channels of the TX band at the output terminals of the EUT.


Frequency (MHz)	Recorded Measurement	Specification Limit
902.8	563.288 kHz	≥ 500 kHz
915.0	566.114 kHz	≥ 500 kHz
926.5	568.397 kHz	≥ 500 kHz

Table 12. Occupied Bandwidth Summary 50kbps Data Rate, Test Results


Frequency (MHz)	Recorded Measurement	Specification Limit
902.8	560.920 kHz	≥ 500 kHz
915.0	563.647 kHz	≥ 500 kHz
926.5	563.518 kHz	≥ 500 kHz

Table 13. Occupied Bandwidth Summary 2kbps Data Rate, Test Results


The following pages show measurements of Occupied Bandwidth plots:




Plot 5 – Lowest Channel – 6dB BW FSK Modulation 50kbps Data Rate




Plot 6 – Middle Channel – 6dB BW FSK Modulation 50kbps Data Rate




Plot 7 – Highest Channel – 6dB BW FSK Modulation 50kbps Data Rate



Plot 8 – Lowest Channel – 6dB BW FSK Modulation 2kbps Data Rate



Plot 9 – Middle Channel – 6dB BW FSK Modulation 2kbps Data Rate



Plot 10 – Highest Channel – 6dB BW FSK Modulation 2kbps Data Rate

4. RF Power Output


Test Requirement(s):	§15.247(b)(3)	Test Engineer(s):	Hoosam B.
Test Results:	Pass	Test Date(s):	03/07/11

Test Procedures: As required by 47 CFR 15.247(b)(3), RF Power output measurements were made at the RF output terminals of the EUT.


Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer capable of making power measurements. Measurements were made at the low, mid, and high channels of the entire frequency band.

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Specification Limit
903.2	9.81	0.00957	1W
915.4	10.69	0.01172	1W
926.8	10.42	0.01101	1W


Table 14. RF Power Output, Conducted Test Results



Plot 11 – Lowest Channel - Output Power



Plot 12 – Middle Channel -Output Power



5. Conducted Spurious Emissions

Test Requirement(s):	§15.247(c)	Test Engineer(s):	Frank Farrone
Test Results:	Pass	Test Date(s):	03/17/11

Test Procedures:	As required by 47 CFR 15.247(c): In any 100kHz bandwidth the frequency band in which the spread spectrum or digitally modulation intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either and RF conducted or a radiated measurement. Conducted spurious emissions at antenna terminal measurements were made at the RF output antenna terminal of the EUT.
	Customer provided a test mode internal to the EUT to control the RF modulation, and frequency channel. The EUT was connected through an attenuator to a Spectrum Analyzer with RBW set to 100KHz and VBW \geq RBW. The Spectrum Analyzer was set to sweep from 30MHz up to 10 th harmonic of the fundamental or 40GHz whichever is the lesser. Measurements were made at the low, mid and high frequency of the transmit band.

Frequency (MHz)	Measured Level (dBm)	Limit (dBm)
1810.00	-64.5	-10.0
7230.00	-51.30	-10.0
8130.00	-60.8	-10.0


Table 16. Lowest Channel – Conducted Spurious Emissions, Test Results

Frequency (MHz)	Measured Level (dBm)	Limit (dBm)
1830.00	-64.50	-10.0
2750.00	-67.00	-10.0
7330.00	-54.30	-10.0


Table 17. Middle Channel – Conducted Spurious Emissions, Test Results

Frequency (MHz)	Measured Level (dBm)	Limit (dBm)
1850.00	-62.00	-10.0
5570.00	-67.00	-10.0
7420.00	-55.30	-10.0


Table 18. Highest Channel – Conducted Spurious Emissions, Test Results




Plot 14 – Lowest Channel (30MHz to 3GHz)




Plot 15 – Lowest Channel (1GHz to 10GHz)




Plot 16 – Middle Channel (30MHz to 1GHz)



Plot 17 – Middle Channel (1GHz to 10GHz)



Plot 18 – Highest Channel (30MHz to 1GHz)



Plot 19 – Highest Channel (1GHz to 10GHz)

6. Radiated Spurious Emissions and Restricted Band

Test Requirement(s):	§15.247(d), 15.209(a), 15.205	Test Engineer(s):	Tom Karas
Test Results:	Pass	Test Date(s):	03/17/11

Test Procedures: As required by 47 CFR 15.247, Radiated spurious measurements were made in accordance with the procedures of the ANSI C63.4-2003.

The EUT was placed on a wooden table inside a 3 meter semi-anechoic chamber. The EUT was set on continuous transmit.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The frequency range up to the 10th harmonic was investigated.

Detector Setting	Resolution Bandwidth	Video Bandwidth	Span
Peak	1MHz	1MHz	As necessary
Average	1MHz	10Hz	0 Hz

Table 19 - Analyzer Settings

Frequency (MHz)	Peak Amplitude (dBuV/m)	Peak Limit (dBuV/m)	Average Amplitude (dBuV/m)	Average Limit (dBuV/m)
1811.11	51.53	74.0	N/A	54.0
3611.11*	47.95	74.0	N/A	54.0
5422.22*	49.85	74.0	N/A	54.0
8933.33	51.81	74.0	N/A	54.0

Table 20 - Spurious Radiated Emission Data – Low Band

Note: Frequency marked with “*” falls under the restricted band

Frequency (MHz)	Peak Amplitude (dbuV/m)	Peak Limit (dBuV/m)	Average Amplitude (dBuV/m)	Average Limit (dBuV/m)
1833.33	50.84	74.0	N/A	54.0
3666.66*	48.06	74.0	N/A	54.0
7366.66*	49.94	74.0	N/A	54.0

Table 11– Spurious Radiated Emission Data – Mid Band

Frequency (MHz)	Peak Amplitude (dbuV/m)	Peak Limit (dBuV/m)	Average Amplitude (dBuV/m)	Average Limit (dBuV/m)
1855.55	42.05	74.0	N/A	54.0
2777.77*	43.67	74.0	N/A	54.0
3711.11*	51.63	74.0	N/A	54.0
5600.00	49.43	74.0	N/A	54.0

Table 22– Spurious Radiated Emission Data – High Band

7. Emissions at Band Edges

Test Requirement(s):	§15.247(d), 15.209(a), 15.205	Test Engineer(s):	Hoosam B.
Test Results:	Pass	Test Date(s):	03/07/11


Test Procedures: As required by 47 CFR 15.247, Band edge radiated emissions measurements were made at the RF antenna output terminals of the EUT.

The EUT was placed on a wooden table inside a 3 meter semi-anechoic chamber. The EUT was set on continuous transmit.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The EUT was set up at maximum power, first on the lowest operating channel, then on the highest operating channel of the transmit band.

Frequency (MHz)	Measured Level (dB)	Detector	Limit
902.0	-34.00	Peak	-20dBc
928.0	-33.00	Peak	-20dBc


Table 23 – Band Edge Emissions Summary




Plot 20 – Lowest Channel (Band Edge) 50kbps Data Rate



Plot 21 – Highest Channel (Band Edge) 50kbps Data Rate



Plot 22 – Lowest Channel (Band Edge) 2kbps Data Rate



Plot 23 – Highest Channel (Band Edge) 2kbps Data Rate

8. Power Spectral Density

Test Requirement(s):	§15.247(d)	Test Engineer(s):	Hoosam B.
Test Results:	Pass	Test Date(s):	03/07/11

Test Procedures: As required by 47 CFR 15.247(d), For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3kHz band during any time interval of continuous transmission. Power spectral density measurements were made at the RF antenna output terminals of the EUT.

The EUT output was connected directly to the spectrum analyzer through an attenuator. The measurements were made at the RF antenna output terminals of the EUT.

Detector Setting	Resolution Bandwidth	Sweep Time	Span
Peak	3KHz	100 seconds	300 kHz


Table 24 – Analyzer settings

Frequency (MHz)	Measured Level	Limit
903	5.811	8 dBm
914.8	6.973	8 dBm
926.3	6.583	8 dBm


Table 25. PSD Summary Test Result – 50kpbs Data Rate

Frequency (MHz)	Measured Level	Limit
903	3.832	8 dBm
914.8	5.447	8 dBm
926.3	5.327	8 dBm


Table 25. PSD Summary Test Result – 2kbps Data Rate




Plot 24 – Lowest Channel (PSD) 50kbps Data Rate




Plot 25 – Middle Channel (PSD) 50kbps Data Rate




Plot 26 – Highest Channel (PSD) 50kbps Data Rate



Plot 27 – Lowest Channel (PSD) 2kbps Data Rate



Plot 28 – Middle Channel (PSD) 2kbps Data Rate



Plot 29 – Highest Channel (PSD) 2kbps Data Rate

I. Test Equipment

Equipment	Manufacturer	Model	Serial #	Last Cal Date	Cal Due Date
Power Supply	H.P	E3610A	KR83021468	NCR	None
Spectrum Analyzer	Agilent	E4402B	USA1192757	Sep/24/10	Sep/24/11
DMM	H.P	34401A	US36054008	Nov/11/10	Nov/11/11
Spectrum Analyzer	H.P.	8595E	3543A01606	Apr/08/10	Apr/08/11
Combiner/Splitter	Mini-Circuits	ZFSC-2-2	None	NCR	None
High Pass Filter	Mini-Circuits	VHF-3100+	15542	NCR	None
Temperature Meter	Fluke	52	6767008	10/30/10	10/30/11
Attenuator 30dB	Bird	10-A-MFN-30	0031039	11/03/10	11/03/11
Directional Coupler	Werlatone	C1795-13	18722	Oct/01/10	Oct/01/11
Variable Attenuator	H.P.	None	None	NCR	None
EMI Receiver	R&S	ESCS-30	828985/007	Sep/03/10	Sep/03/11
Signal Generator	R&S	SMY02	1062.5502.12	NCR	None
Attenuator 20dB	Mini Circuits	CAT-20	10012	NCR	None
Horn Antenna	EMCO	3115	9505-4428	Nov/04/09	Nov/04/11
Bilog Antena	Chase	CBL6140	1040	Nov/09/09	Nov/09/11

Table 26 – Test Equipment List

END OF TEST REPORT