



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S,12th , Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China

Phone:86-755-26748099

Fax:86-755-26748089

<http://www.szhtw.com.cn>



RF Exposure REPORT

FCC Per 47 CFR 2.1093(b)

Report Reference No......: TRE1205010802 R/C:89247

FCC ID......: OAASPR7928AEW

Compiled by

(position+printed name+signature) ..: File administrators Eric Zhang

Eric Zhang

Supervised by

(position+printed name+signature) ..: Test Engineer Tim Zhang

Tim Zhang

Approved by

(position+printed name+signature) ..: Manager Wenliang Li

Wenliang Li

Date of issue.....: Jun 12, 2012

Testing Laboratory Name: **Shenzhen Huatongwei International Inspection Co., Ltd**

Address.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name: **SHENZHEN SCOPE SCIENTIFIC DEVELOPMENT CO.,LTD**

Address.....: Building NO.1&4 The West haosi Industry.Shajing Town.Baoan District,Shenzhen

Test specification:

Standard: **FCC Per 47 CFR 2.1093(b)**

TRF Originator: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **Tablet Computer(TABLET PC)**

Trade Mark: /

Model/Type reference.....: SP-R79XXX-XW

Listed Models: /

Operation Frequency.....: From 2400MHz to 2483.5MHz

Result : **Positive**

RF Exposure R E P O R T

Test Report No. :	TRE1205010802	Jun 12, 2012
		Date of issue

Equipment under Test : Tablet Computer(TABLET PC)

Model /Type : SP-R79XXX-XW

Listed Models : /

Applicant : SHENZHEN SCOPE SCIENTIFIC DEVELOPMENT CO.,LTD

Address : Building NO.1&4 The West haosi Industry.Shajing Town.Baoan District,Shenzhen

Manufacturer : SHENZHEN SCOPE SCIENTIFIC DEVELOPMENT CO.,LTD

Address : Building NO.1&4 The West haosi Industry.Shajing Town.Baoan District,Shenzhen

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>SUMMARY</u>	4
1.1.	EUT configuration	4
1.2.	Power supply system utilised	4
1.3.	Description of the test mode	4
1.4.	NOTE	4
<u>2.</u>	<u>TEST ENVIRONMENT</u>	6
2.1.	Address of the test laboratory	6
2.2.	Environmental conditions	6
2.3.	Statement of the measurement uncertainty	6
<u>3.</u>	<u>METHOD OF MEASUREMENT</u>	6
3.1.	Applicable Standard	6
3.2.	Limit	7
3.3.	RF Exposure	7
<u>4.</u>	<u>CONCLUSION</u>	7

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

1.2. Power supply system utilised

Power supply voltage	:	<input checked="" type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input type="radio"/> Other (specified in blank below)	

1.3. Description of the test mode

IEEE 802.11b/g/n: Eleven channels are provided to the EUT.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

1.4. NOTE

1. The EUT is an 802.11b/g/n Tablet Computer(TABLET PC) ,The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN 802.11b/g/n	FCC Part 15 Subpart C (Section15.247)	TRE1205010801
RF Exposure Report	FCC Per 47 CFR 2.1093(b)	TRE1205010802

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
802.11b	√	—	—	—
802.11g	√	—	—	—
802.11n(20MHz)	√	—	—	—
802.11n(40MHz)	√	—	—	—

3. The EUT incorporates a SISO function, Physically, the EUT provides one completed transmitter and one completed receiver.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

3.2. Limit

Exposure category	<u>low threshold</u>	<u>high threshold</u>
general population	$(60/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(120/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(900/f_{\text{GHz}})$ mW, $d < 20$ cm
occupational	$(375/f_{\text{GHz}})$ mW, $d < 2.5$ cm $(900/f_{\text{GHz}})$ mW, $d \geq 2.5$ cm	$(2250/f_{\text{GHz}})$ mW, $d < 20$ cm

F=frequency in GHz

3.3. RF Exposure

TEST RESULTS

The max peak ouput power is 10.99dBm . The antenna gain is 1.8dBi. EIRP=12.79dBm=19mW<60/2.48=24mW, so the SAR is not required.

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the general population RF Exposure.

.....End of Report.....