



No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM170100062201  
Page: 1 of 22

## FCC REPORT

**Application No.:** SZEM1701000622CR  
**Applicant:** Alpheus Digital Co., Limited  
**Manufacturer:** Alpheus Digital Co., Limited  
**Factory:** Alpheus Digital Co., Limited  
**Product Name:** Door Windows Sensor  
**Model No.(EUT):** DW3-101  
**Trade Mark:** BDS  
**FCC ID:** OC7DW3-101  
**Standards:** 47 CFR Part 15, Subpart C (2016)  
**Date of Receipt:** 2017-02-22  
**Date of Test:** 2017-02-23 to 2017-03-08  
**Date of Issue:** 2017-03-14

<b>Test Result:</b>	<b>PASS *</b>
---------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention, only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

## 2 Version

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2017-03-14		Original

Authorized for issue by:			
Tested By		 Bill Chen /Project Engineer	2017-03-14
Checked By		 Eric Fu /Reviewer	Date
			2017-03-14
			Date

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10(2013)	PASS
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.231 (b)	ANSI C63.10(2013)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.231 (b)/15.209	ANSI C63.10(2013)	PASS
20dB Bandwidth	47 CFR Part 15, Subpart C Section 15.231 (c)	ANSI C63.10(2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.231 (a)	ANSI C63.10(2013)	PASS

## 4 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 TEST SUMMARY .....</b>	<b>3</b>
<b>4 CONTENTS .....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 TEST ENVIRONMENT AND MODE.....	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 TEST LOCATION .....	6
5.6 TEST FACILITY .....	7
5.7 DEVIATION FROM STANDARDS.....	7
5.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	7
5.10 EQUIPMENT LIST .....	8
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>10</b>
6.1 ANTENNA REQUIREMENT .....	10
6.2 SPURIOUS EMISSIONS.....	11
6.2.1 <i>Spurious Emissions</i> .....	11
6.3 20dB BANDWIDTH.....	17
6.4 DWELL TIME .....	19
<b>7 PHOTOGRAPHS - TEST SETUP .....</b>	<b>21</b>
7.1 RADIATED EMISSION .....	21
<b>8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....</b>	<b>22</b>

## 5 General Information

### 5.1 Client Information

Applicant:	Alpheus Digital Co., Limited
Address of Applicant:	Unit B, 23/F., Phase I, Kingsford Industrial Bldg., 26-32 Kwai Hei Street, Kwai Chung, Hong Kong.
Manufacturer:	Alpheus Digital Co., Limited
Address of Manufacturer:	Unit B, 23/F., Phase I, Kingsford Industrial Bldg., 26-32 Kwai Hei Street, Kwai Chung, Hong Kong.
Factory:	Alpheus Digital Co., Limited
Address of Factory:	Unit B, 23/F., Phase I, Kingsford Industrial Bldg., 26-32 Kwai Hei Street, Kwai Chung, Hong Kong.

### 5.2 General Description of EUT

Name:	Door Windows Sensor
Mode No.:	DW3-101
Trade Mark:	BDS
Sample Type:	Portable production
Operation Frequency:	345MHz
Channel Numbers:	1
Modulation Type:	FSK
Antenna Type:	Integral
Antenna Gain:	-2dBi
Power Supply:	6.0V DC(3.0V x 2 "CR2025" Size Batteries)

### **5.3 Test Environment and Mode**

<b>Operating Environment:</b>	
Temperature:	25.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1008 mbar
<b>Test mode:</b>	
Transmitting mode:	Keep the EUT in transmitting mode with modulation.

### **5.4 Description of Support Units**

The EUT has been tested independent unit.

### **5.5 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

## 5.7 Deviation from Standards

None.

## 5.8 Abnormalities from Standard Conditions

None.

## 5.9 Other Information Requested by the Customer

None.

## 5.10 Equipment List

<b>Field Strength of the Fundamental Signal</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13
EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2016-10-09	2017-10-09
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24

<b>Dwell Time</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

<b>20dB Bandwidth</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170100062201  
Page: 9 of 22

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
7	Horn Antenna(26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12
8	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

## 6 Test results and Measurement Data

### 6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement:  An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>EUT Antenna:</b>	
	
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -2dBi.	

## 6.2 Spurious Emissions

### 6.2.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.231(b) and 15.209				
Test Method:	ANSI C63.10: 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	345MHz	77.25		Average Value	
		97.25		Peak Value	
Limit: (Harmonic)	Frequency	Limit (dBuV/m @3m)		Remark	
	Harmonics which not fall into the restriction band	57.25		Average Value	
		77.25		Peak Value	

Test Procedure:	<ol style="list-style-type: none"> <li>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation</li> <li>c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</li> </ol>
Test Setup:	




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Mode:	Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

### Measurement Data


#### 6.2.1.1 Field Strength Of The Fundamental Signal

Peak value:								
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
345	2.05	14.08	26.75	86.52	75.90	97.25	-21.35	Horizontal
345	2.05	14.08	26.75	82.21	71.59	97.25	-25.66	Vertical


**6.2.1.2 Spurious Emissions****Below 1GHz**

QP value:

Horizontal



Vertical



Condition: 3m VERTICAL

Job No. : 00622CR

Test mode: TX

Freq	Cable	Ant	Preamp	Read	Limit	Over	Over	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	30.00	0.60	18.70	27.36	25.14	17.08	40.00	-22.92
2	90.22	1.10	8.71	27.21	29.59	12.19	43.50	-31.31
3	253.84	1.69	12.38	26.53	29.95	17.49	46.00	-28.51
4	519.06	2.62	18.33	27.67	25.62	18.90	46.00	-27.10
5	690.00	2.88	21.52	27.43	54.17	51.14	77.25	-26.11
6	1000.00	3.70	24.30	26.30	23.53	25.23	54.00	-28.77



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100062201  
Page: 16 of 22

## Above 1GHz

Peak value:

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1724.082	26.77	4.73	38.08	66.29	59.71	74	-14.29	Vertical
2069.805	28.05	5.07	38.11	64.03	59.04	74	-14.96	Vertical
2414.629	29.15	5.36	38.15	67.05	63.41	74	-10.59	Vertical
2761.924	30.44	5.70	38.18	65.57	63.53	74	-10.47	Vertical
3103.070	31.50	6.01	38.26	56.41	55.66	74	-18.34	Vertical
3449.074	32.11	6.26	38.44	55.04	54.97	74	-19.03	Vertical
2069.805	28.05	5.07	38.11	74.73	69.74	74	-4.26	Horizontal
2414.629	29.15	5.36	38.15	70.44	66.80	74	-7.20	Horizontal
2761.924	30.44	5.70	38.18	69.88	67.84	74	-6.16	Horizontal
3103.070	31.50	6.01	38.26	67.17	66.42	74	-7.58	Horizontal
3449.074	32.11	6.26	38.44	61.93	61.86	74	-12.14	Horizontal
3792.666	33.04	6.54	38.61	56.37	57.34	74	-16.66	Horizontal


Average value:

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1724.082	26.77	4.73	38.08	48.91	42.33	54	-11.67	Vertical
2069.805	28.05	5.07	38.11	46.64	41.65	54	-12.35	Vertical
2414.629	29.15	5.36	38.15	49.69	46.05	54	-7.95	Vertical
2761.924	30.44	5.70	38.18	47.75	45.71	54	-8.29	Vertical
3103.070	31.50	6.01	38.26	38.83	38.08	54	-15.92	Vertical
3449.074	32.11	6.26	38.44	38.78	38.71	54	-15.29	Vertical
2069.805	28.05	5.07	38.11	55.51	50.52	54	-3.48	Horizontal
2414.629	29.15	5.36	38.15	50.69	47.05	54	-6.95	Horizontal
2761.924	30.44	5.70	38.18	50.52	48.48	54	-5.52	Horizontal
3103.070	31.50	6.01	38.26	47.97	47.22	54	-6.78	Horizontal
3449.074	32.11	6.26	38.44	44.62	44.55	54	-9.45	Horizontal
3792.666	33.04	6.54	38.61	40.76	41.73	54	-12.27	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.


### 6.3 20dB Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.231 (c)
Test Method:	ANSI C63.10:2013
Test Setup:	
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Mode:	Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


**Measurement Data**

20dB bandwidth (MHz)	Limit (MHz)	Results
0.057	0.10875	Pass

**Test plot as follows:**




## 6.4 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.231 (a) (1)
Test Method:	ANSI C63.10:2013
Test Setup:	
Limit:	Not more than 5 seconds
Test Mode:	Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


### Measurement Data

Test item	Limit	Results
Transmitting time	≤5S	Pass

**Test plot as follows:**

## 7 Photographs - Test setup

### 7.1 Radiated Emission





## **8 Photographs - EUT Constructional Details**

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1701000622CR.