

RF Exposure / SAR Statement
No. : 10402743S-E-R1

Applicant	:	Anritsu Corporation
Type of Equipment	:	Network Master Flex
Model No.	:	MT1100A
FCC ID	:	OCS-MT1100A

Anritsu Corporation declares that Model : MT1100A
complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "MT1100A" as calculated
from FCC Part 1, §1.1310, TABLE 1 (B) Limits for General Population / Uncontrolled Exposure.
This calculation is based on the highest EIRP possible from the system,
considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P =	10.00	mW (Maximum average output power with tolerance) *1)
G =	2.00	Numerical Antenna gain; equal to 3.00 dBi
r =	20.0	cm

For: MT1100A **S = 0.00397 mW/cm²**

*1) The value is based on the specification provided by the customer.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401