



## FCC PART 15.249


### TEST REPORT

For

### Yitinfu Electronics technology (Shenzhen) Co., Ltd.

7/F, Bldg E, jingchangda Technological Park, Guanlan Town, Shenzhen, China

**FCC ID: OCUYTF18220120608**

<b>Report Type:</b> Original Report	<b>Product Type:</b> 2.4 GHz fixed-wing aircraft
<b>Test Engineer:</b>	Brown Lu 
<b>Report Number:</b>	RSZ120606801-00
<b>Report Date:</b>	2012-06-18
<b>Reviewed By:</b>	Sula Huang  EMC Engineer
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen). This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk “★” (Rev.2)

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	3
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
JUSTIFICATION .....	5
EQUIPMENT MODIFICATIONS .....	5
CONFIGURATION OF TEST SETUP .....	5
BLOCK DIAGRAM OF TEST SETUP .....	5
<b>SUMMARY OF TEST RESULTS .....</b>	<b>6</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT.....</b>	<b>7</b>
APPLICABLE STANDARD .....	7
ANTENNA CONNECTOR CONSTRUCTION .....	7
<b>FCC§15.205, §15.209&amp;§15.249- RADIATED EMISSIONS .....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
MEASUREMENT UNCERTAINTY .....	8
TEST EQUIPMENT SETUP .....	8
EUT SETUP .....	9
TEST PROCEDURE .....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	9
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST RESULTS SUMMARY .....	10
TEST DATA .....	10
<b>FCC§15.249(D) - OUT OF BAND EMISSION (50DB ATTENUATION) .....</b>	<b>13</b>
APPLICABLE STANDARD .....	13
TEST PROCEDURE .....	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST DATA .....	13
<b>PRODUCT SIMILARITY DECLARATION LETTER .....</b>	<b>15</b>

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Yitinfu Electronics technology (Shenzhen) Co., Ltd.* 's product, model number: *YTF-182 (FCC ID: OCUYTF18220120608)* or the "EUT" in this report is a *2.4 GHz fixed-wing aircraft*, which was measured approximately: 18.0 cm (L) × 18.0 cm (W) × 7.0 cm (H), rated input voltage: 4 ×AAA 1.5V alkaline battery

*Note: The product, model YTF-182, YTF-yak54, YTF-p51, they are electrically identical, only different in model No.. Model YTF-182 was selected for full testing, which was explained for details in the attached declaration letter.*

*All measurement and test data in this report was gathered from production sample serial number: 1206002 (Assigned by BACL, Shenzhen). The EUT was received on 2012-06-06.*

### Objective

This type approval report is prepared on behalf of *Yitinfu Electronics technology (Shenzhen) Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

### Related Submittal(s)/Grant(s)

No related submittal(s)

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured in a testing mode which provided by manufacturer.


### Equipment Modifications

No modifications were made to the unit tested.

### Configuration of Test Setup



### Block Diagram of Test Setup



## SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	N/A*
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.249(d)	Outside of Band Emission (50dB attenuation)	Compliance

Note: EUT is powered by battery only.

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

### **Antenna Connector Construction**

The EUT use an integrated monopole antenna arrangement, which was permanently attached and the maximum gain was 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

**Result:** Compliant.

## FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS

### Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 4.0 dB. (k=2, 95% level of confidence).

### Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000MHz:


RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto

Above 1000MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto

Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

## EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2011-11-24	2012-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2011-11-17	2012-11-16
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2012-03-17	2013-03-16
Mini-Circuits	Amplifier	ZVA-213+	2011-11-24	2012-03-08	2013-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2012-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23
Electro-Mechanics	Horn antenna	3116	9510-2270	2011-10-14	2012-10-13

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249, with the worst margin reading of:

**1.22 dB at 4935.2 MHz** in the **Horizontal** polarization

## Test Data

### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.2 kPa

*The testing was performed by Brown Lu on 2012-06-14.*

*Test Mode: Transmitting*

## 1) 30 MHz to 25 GHz:

Freq. (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/QP/Ave.)	Direction (Degree)	Height (m)	Polar (H/V)	Ant. Loss (dB)	Cable loss (dB)	Amp. Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC 15.209/ FCC 15.249/ FCC 15.205		
										Limit (dB $\mu$ V/m)	Margin (dB)	Comment
<b>Low Channel</b>												
4836	40.06	Ave.	134	1.4	H	34.6	4.30	26.50	52.46	54	1.54*	Harmonic
4836	38.73	Ave.	223	1.0	V	34.6	4.30	26.50	51.13	54	2.87*	Harmonic
2418	82.37	Ave.	335	1.1	V	29.6	3.03	26.50	88.5	94	5.50	Fund.
4836	51.28	PK	134	1.4	H	34.6	4.30	26.50	63.68	74	10.32	Harmonic
2389.4	56.99	PK	227	1.6	H	29.6	3.03	26.50	63.12	74	10.88	Spurious
2418	76.50	Ave.	45	1.5	H	29.6	3.03	26.50	82.63	94	11.37	Fund.
7254	25.58	Ave.	86	1.6	H	37.9	5.22	26.50	42.2	54	11.80	Harmonic
7254	24.36	Ave.	178	1.2	V	37.9	5.22	26.50	40.98	54	13.02	Harmonic
2490.7	52.45	PK	36	1.4	H	30.6	3.11	26.50	59.66	74	14.34	Spurious
132.32	41.72	QP	180	3.1	H	12.20	0.56	25.38	29.1	43.5	14.40	Spurious
2490.7	30.59	Ave.	36	1.4	H	30.6	3.11	26.50	37.8	54	16.20	Spurious
2389.4	31.35	Ave.	227	1.6	H	29.6	3.03	26.50	37.48	54	16.52	Spurious
2418	89.77	PK	335	1.1	V	29.6	3.03	26.50	95.9	114	18.10	Fund.
4836	42.32	PK	223	1.0	V	34.6	4.30	26.50	54.72	74	19.28	Harmonic
7254	37.77	PK	178	1.2	V	37.9	5.22	26.50	54.39	74	19.61	Harmonic
2418	86.05	PK	45	1.5	H	29.6	3.03	26.50	92.18	114	21.82	Fund.
7254	35.19	PK	86	1.6	H	37.9	5.22	26.50	51.81	74	22.19	Harmonic
<b>Middle Channel</b>												
4885.6	40.02	Ave.	68	1.2	H	34.6	4.36	26.50	52.48	54	1.52*	Harmonic
4885.6	38.21	Ave.	257	1.1	V	34.6	4.36	26.50	50.67	54	3.33*	Harmonic
2442.8	82.46	Ave.	38	1.5	H	30.6	3.11	26.50	89.67	94	4.33	Fund.
2442.8	82.65	Ave.	118	1.3	V	30.2	3.11	26.50	89.46	94	4.54	Fund.
4885.6	51.15	PK	68	1.2	H	34.6	4.36	26.50	63.61	74	10.39	Harmonic
7328.4	24.07	Ave.	304	1.6	H	37.9	5.09	26.50	40.56	54	13.44	Harmonic
4885.6	47.69	PK	257	1.1	V	34.6	4.36	26.50	60.15	74	13.85	Harmonic
132.32	41.54	QP	180	3.1	H	12.20	0.56	25.38	28.92	43.5	14.58	Spurious
7328.4	21.13	Ave.	198	1.3	V	37.9	5.09	26.50	37.62	54	16.38	Harmonic
2442.8	89.79	PK	118	1.3	V	30.2	3.11	26.50	96.60	114	17.40	Fund.
2442.8	89.25	PK	38	1.5	H	30.6	3.11	26.50	96.46	114	17.54	Fund.
7328.4	36.12	PK	304	1.6	H	37.9	5.09	26.50	52.61	74	21.39	Harmonic
7328.4	32.33	PK	198	1.3	V	37.9	5.09	26.50	48.82	74	25.18	Harmonic

Freq. (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/QP/Ave.)	Direction (Degree)	Height (m)	Polar (H/V)	Ant. Loss (dB)	Cable loss (dB)	Amp. Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	FCC 15.209/ FCC 15.249/ FCC 15.205		
										Limit (dB $\mu$ V/m)	Margin (dB)	Comment
<b>High Channel</b>												
4935.2	40.28	Ave.	133	1.3	H	34.6	4.4	26.50	52.78	54	1.22*	Harmonic
4935.2	38.81	Ave.	254	1.5	V	34.6	4.4	26.50	51.31	54	2.69*	Harmonic
2467.6	83.67	Ave.	46	1.6	V	30.2	3.11	26.50	90.48	94	3.52*	Fund.
2467.6	83.15	Ave.	35	1.4	H	30.6	3.11	26.50	90.36	94	3.64*	Fund.
4935.2	51.17	PK	133	1.3	H	34.6	4.4	26.50	63.67	74	10.33	Harmonic
2484.1	55.44	PK	327	1.2	V	30.2	3.11	26.50	62.25	74	11.75	Spurious
2342.6	56.13	PK	241	1.4	V	29.0	2.98	26.50	61.61	74	12.39	Spurious
7402.8	24.32	Ave.	331	1.6	H	37.2	5.20	26.50	40.22	54	13.78	Harmonic
132.32	41.86	QP	180	3.1	H	12.20	0.56	25.38	29.24	43.5	14.26	Spurious
7402.8	23.32	Ave.	124	1	V	37.2	5.20	26.50	39.22	54	14.78	Harmonic
2484.1	32.18	Ave.	327	1.2	V	30.2	3.11	26.50	38.99	54	15.01	Spurious
4935.2	45.24	PK	254	1.5	V	34.6	4.4	26.50	57.74	74	16.26	Harmonic
2467.6	90.39	PK	46	1.6	V	30.2	3.11	26.50	97.20	114	16.80	Fund.
2467.6	89.87	PK	35	1.4	H	30.6	3.11	26.50	97.08	114	16.92	Fund.
2342.6	31.15	Ave.	241	1.4	V	29.0	2.98	26.50	36.63	54	17.37	Spurious
7402.8	37.13	PK	124	1	V	37.2	5.20	26.50	53.03	74	20.97	Harmonic
7402.8	36.42	PK	331	1.6	H	37.2	5.20	26.50	52.32	74	21.68	Harmonic

\*Within measurement uncertainty.

## FCC§15.249(d) - OUT OF BAND EMISSION (50dB ATTENUATION)

### Applicable Standard

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2011-11-24	2012-11-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Data

#### Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\* The testing was performed by Brown Lu on 2012-06-14.


Test Result: Compliance. Please refer to the following table and plots:

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Delta Limit (dBc)
2398.192	51.80	≥50
2484.308	52.60	≥50

## Band Edge: Left Side



## Band Edge: Right Side



## PRODUCT SIMILARITY DECLARATION LETTER



### **Yitinfu Electronics technology (Shenzhen) Co., Ltd**

Add: 7/F, Bldg E, jingchangda Technological Park, Guanlan Town, Shenzhen, China  
Tel: 0755-27998089

Fax: 0755-27998073

### **Product Similarity Declaration**

To Whom It May Concern,

We Yitinfu Electronics technology (Shenzhen) Co., Ltd, Hereby declare that our 2.4 GHz fixed-wing aircraft Model Number YTF-yak54, YTF-p51 electrically identical with the Model Number YTF-182 that was certified by BACL. The differences between Number YTF-yak54, YTF-p51and YTF-182 are their Model Number due to marketing purposes.

Please contact me if you have any question.

Signature:

A handwritten signature in black ink, appearing to read 'Qing Quan Chen'.

Qing Quan Chen

Manager

2012-06-14

\*\*\*\*\* END OF REPORT \*\*\*\*\*