



	www.ISONAS.com		
Model:	RC-03-PRX		
SN:	2312-11		
Addr:	192.168.1.161		
MAC:	00-18-C8-00-2E-CA		
Red-Pwr	Blk-Gnd	Grn-REX	Ora-AUX
Blu-Door	Prk-COM	Tan-NO	Gry-NC
Yel(+)	Whi(-)	Pur-Ttl1	Brn-Ttl2

Note: Model Number can be the following:

RC-03-PRX (product without keypad)

RC-03-PRX-K (product with keypad)

Z-Ultimate 3000T White

A pearl white topcoated polyester thermal transfer facestock with permanent acrylic adhesive. Ideal for thermal transfer applications that require outstanding print quality and unparalleled smear and scratch resistance. UL recognized for indoor and outdoor use when used with compatible Zebra Resin Ribbons. Recommended for use in a wide variety of applications, including shelf or scan-pallet labels, water-immersed labels, or labels in contact with moving parts.

Features

- Chemical Resistant
- High Durability
- High Heat
- Water Resistant

Media Characteristics

Label: Thermal Transfer

Facestock Material: Polyester

Resistance: Abrasion, Ammonia, Bleach, Blood, Body Fluid, Grease, IPA, Oil, Water, Window Cleaner, Alcohol, Salt Water

Physical Characteristics

Finish: Gloss, Coated

Adhesive: Permanent Acrylic

Liner Description: 50# SBK

Adhesive Caliper: 1 mils

Facestock Caliper: 2 mils

Liner Caliper: 3 mils

Total Caliper: 6 mils

Surface To Label Use: Glass, Metals, Pebbled Surfaces, Plastics

Operating Characteristics

Acceptance: CSA Acceptance, UL Recognized

Min Application Temperature: 50° F (10° C)

Min Service Temperature: -40° F (-40° C)

Max Service Temperature: 302° F (150° C)