



 www.ISONAS.com

Model: RC-03-ALLE-K
SN: 1116-32
Addr: 192.168.1.119
MAC: 00-18-C8-2E-3A-8D

Red-Pwr	Blk-Gnd	Grn-REX	Ora-AUX
Blu-Door	Pnk-COM	Tan-NO	Gry-NC
Yel(+)	Vnli(-)	Pur-Ttl1	Brn-Ttl2



 www.ISONAS.com

Model: RC-03-ALLE
SN: 1116-32
Addr: 192.168.1.119
MAC: 00-18-C8-2E-3A-8D

Red-Pwr	Blk-Gnd	Grn-REX	Ora-AUX
Blu-Door	Pnk-COM	Tan-NO	Gry-NC
Yel(+)	Whi(-)	Pur-Ttl1	Brn-Ttl2

Z-Ultimate 3000T White

A pearl white top coated polyester thermal transfer face stock with permanent acrylic adhesive. Ideal for thermal transfer applications that require outstanding print quality and unparalleled smear and scratch resistance. UL recognized for indoor and outdoor use when used with compatible Zebra Resin Ribbons. Recommended for use in a wide variety of applications, including shelf or scan-pallet labels, water-immersed labels, or labels in contact with moving parts.

Features

- Chemical Resistant
- High Durability
- High Heat
- Water Resistant

Media Characteristics

Label: Thermal Transfer

Face stock Material: Polyester

Resistance: Abrasion, Ammonia, Bleach, Blood, Body Fluid, Grease, IPA, Oil, Water, Window Cleaner, Alcohol, Salt Water

Physical Characteristics

Finish: Gloss, Coated

Adhesive: Permanent Acrylic

Liner Description: 50# SBK

Adhesive Caliper: 1 mils

Face stock Caliper: 2 mils

Liner Caliper: 3 mils

Total Caliper: 6 mils

Surface to Label Use: Glass, Metals, Pebbled Surfaces, Plastics

Operating Characteristics

Acceptance: CSA Acceptance, UL Recognized

Min Application Temperature: 50° F (10° C)

Min Service Temperature: -40° F (-40° C)

Max Service Temperature: 302° F (150° C)