

FCC EMC Test Report

FCC ID: ODD-VM690

For
Electromagnetic Interference
Of

Product : VINCI MV 7-in Family Tablet

Trade Name : N/A

Model Number : VM-6910

Prepared for

Rullingnet Corporation Limited

Unit 1210, Level 12, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name : Rullingnet Corporation Limited
Address : Unit 1210, Level 12, Core F, Cyberport 3, 100 Cyberport
Road, Hong Kong

Manufacturer's Name : Rullingnet Corporation Limited
Address : Unit 1210, Level 12, Core F, Cyberport 3, 100 Cyberport
Road, Hong Kong

Product description

Product name : VINCI MV 7-in Family Tablet
Model and/or type reference : VM-6910
FCC Part15B:2012

Standards : ANSI C63.4:2009

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with Part 15 of FCC Rules. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : 18 Sep. 2013 ~18 Nov. 2013
Date of Issue : 18 Nov. 2013
Test Result : **Pass**

Testing Engineer : 
(Jason Chen)

Technical Manager : 
(Brown Lu)


Authorized Signatory : 
(Bovey Yang)

Table of Contents	Page
1 . TEST SUMMARY	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 DESCRIPTION OF TEST SETUP	8
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	10
2.5 MEASUREMENT INSTRUMENTS LIST	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION	12
3.1.2 TEST PROCEDURE	13
3.1.3 TEST SETUP	13
3.1.4 EUT OPERATING CONDITIONS	13
3.1.5 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	16
3.2.2 TEST PROCEDURE	16
3.2.3 TEST SETUP	17
3.2.4 EUT OPERATING CONDITIONS	17
3.2.5 TEST RESULTS	18
3.2.6 TEST RESULTS(Above 1GHz)	24
4 . EUT TEST PHOTO	26

1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
FCC Part15B:2012 ANSI C63.4: 2009	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report
- (2) For client's request and manual description, the test will not be executed.

1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd.

Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration Number:238937; IC Registration Number:9270A-1

CNAS Registration Number:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKC01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
NTEKA01	ANSI	30MHz ~ 1000MHz	4.7	
		1GHz ~6GHz	5.0	

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	VINCI MV 7-in Family Tablet					
Model Name	VM-6910					
Serial No	N/A					
Model Difference	N/A					
Product Description	<p>The EUT is a VINCI MV 7-in Family Tablet.</p> <table border="1"><tr><td>Operating frequency:</td><td>24MHz</td></tr><tr><td>Connecting I/O port:</td><td>USB</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>		Operating frequency:	24MHz	Connecting I/O port:	USB
Operating frequency:	24MHz					
Connecting I/O port:	USB					
Adapter	<p>Model: JY-05200 Input:100-240VAC 50/60Hz 0.3A Output: DC 5.0V/2.0A</p>					
Battery	<p>Model No.: 357095P Rated Voltage: 3.7V Charge Limit: 4.2V Capacity : 2500mAh</p>					

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description
Mode 1	Charge + TF Card Playing video Mode
Mode 2	Charge + OTG Playing video Mode
Mode 3	Charge+ Downloading

For Conducted Test	
Final Test Mode	Description
Mode 1	Charge + TF Card Playing video Mode


For Radiated Test	
Final Test Mode	Description
Mode 1	Charge + TF Card Playing video Mode
Mode 2	Charge + OTG Playing video Mode
Mode 3	Charge+ Downloading

2.3 DESCRIPTION OF TEST SETUP


Mode 1:



Mode 2:



Mode 3:



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	VINCI MV 7-in Family Tablet	iView	VM-6910	N/A	EUT
E-2	Adapter	N/A	N/A	JK050150-802USD	accessory equipment
E-3	Earphone	N/A	S879	N/A	
E-4	USB Disk	N/A	4G	N/A	
E-5	PC	IBM	T43	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.0m	Power cable
C-2	NO	NO	1.0m	Earphone cable
C-3	Yes	NO	2.0cm	OTG cable
C-4	Yes	Yes	1 m	USB cable

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" means "shielded" "with core"; "NO" means "unshielded" "without core".

2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101313	Jul. 06, 2014
2	LISN	EMCO	3816/2	00042990	Jul. 06, 2014
3	50Ω Switch	ANRITSU CORP	MP59B	6200983704	Jul. 06, 2014
4	Test Cable	N/A	C01	N/A	Jul. 06, 2014
5	Test Cable	N/A	C02	N/A	Jul. 06, 2014
6	Test Cable	N/A	C03	N/A	Jul. 06, 2014
7	EMI Test Receiver	R&S	ESCI	101160	Jul. 06, 2014
8	Passive Voltage Probe	ESH2-Z3	R&S	100196	Jul. 06, 2014
9	Triple-Loop Antenna	EVERFINE	LIA-2	11020003	Jul. 06, 2014
10	Absorbing Clamp	R&S	MDS-21	100423	Jul. 08, 2014

2.5.2 RADIATED TEST SITE

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Bilog Antenna	TESEQ	CBL6111D	31216	Jul. 06, 2014
2	Test Cable	N/A	R-01	N/A	Jul. 06, 2014
3	Test Cable	N/A	R-02	N/A	Jul. 06, 2014
4	EMI Test Receiver	R&S	ESCI-7	101318	Jul. 06, 2014
5	Antenna Mast	EM	SC100_1	N/A	N/A
6	Turn Table	EM	SC100	060531	N/A
7	50Ω Switch	Anritsu Corp	MP59B	6200983705	Jul. 06, 2014
8	Spectrum Analyzer	Aglient	E4407B	MY45108040	Jul. 06. 2014
9	Horn Antenna	EM	EM-AH-10180	2011071402	Jul. 06. 2014
10	Amplifier	EM	EM-30180	060538	Jul. 06. 2014

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (A and B) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.1.5 TEST RESULTS

EUT :	VINCI MV 7-in Family Tablet	Model Name. :	VM-6910
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2013-10-29
Test Mode :	Mode 1	Phase :	L
Test Voltage :	DC 5V from adapter AC 120V/60Hz		

Freq.	Reading	Factor	Measurement	Limit	Over	Detector
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	
0.214	24.8	10.71	35.51	63.04	-27.53	peak
0.37	28.95	10.78	39.73	58.5	-18.77	peak
1.69	29.89	10.52	40.41	56	-15.59	peak
4.8979	31.53	10.64	42.17	56	-13.83	peak
0.37	22.87	10.78	33.65	48.5	-14.85	AVG
1.15	19.15	10.52	29.67	46	-16.33	AVG
4.8979	25.23	10.64	35.87	46	-10.13	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name. :	VM-6910
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Date :	2013-10-29
Test Mode :	Mode 1	Phase :	N
Test Voltage :	DC 5V from adapter AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
						peak
0.15	29.61	11.59	41.20	65.78	-24.58	peak
1.67	26.13	10.52	36.65	56.00	-19.35	peak
4.89	27.63	10.63	38.26	56.00	-17.74	peak
0.16	19.68	11.54	31.22	55.56	-24.34	AVG
1.70	14.59	10.52	25.11	46.00	-20.89	AVG
4.89	19.98	10.63	30.61	46.00	-15.39	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

Notes:


- (1) The limit for radiated test was performed according to as following:
FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

3.2.2 TEST PROCEDURE


- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP(AV) Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.2.3 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


3.2.5 TEST RESULTS

EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from adapter AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
						peak
216.024	17.97	9.98	27.95	46.00	-18.05	peak
263.819	20.9	14.62	35.52	46.00	-10.48	peak
312.1793	22.27	15.13	37.4	46.00	-8.6	peak
408.946	18.21	18.68	36.89	46.00	-9.11	peak
360.4476	19.88	16.46	36.34	46.00	-9.66	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-08-30
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from adapter AC 120V/60Hz		

	Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
	98.8324	20.14	10.51	30.65	43.50	-12.85	peak
	148.441	24.88	11.83	36.71	43.50	-6.79	peak
	312.1792	18.6	15.13	33.73	46.00	-12.27	peak
	668.1422	12.13	23.81	35.94	46.00	-10.06	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 2	Polarization :	Horizontal
Test Power :	DC 5V from adapter AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
						peak
98.83	31.22	10.51	41.73	43.50	-1.77	peak
148.44	27.04	11.83	38.87	43.50	-4.63	peak
197.89	28.92	8.99	37.91	43.50	-5.59	peak
297.22	26.90	14.70	41.60	46.00	-4.40	peak
312.18	26.20	15.13	41.33	46.00	-4.67	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 2	Polarization :	Vertical
Test Power :	DC 5V from adapter AC 120V/60Hz		

	Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
197.89	26.41	8.99	35.40	43.50	-8.10	peak	
297.22	25.90	14.70	40.60	46.00	-5.40	peak	
408.95	20.29	18.68	38.97	46.00	-7.03	peak	
744.87	13.29	26.43	39.72	46.00	-6.28	peak	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 3	Polarization :	Horizontal
Test Power :	DC 5V from adapter AC 120V/60Hz		

	Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
	165.49	27.42	10.78	38.20	43.50	-5.30	peak
	270.37	28.87	14.09	42.96	46.00	-3.04	peak
	668.14	18.75	23.81	42.56	46.00	-3.44	peak
	897.00	15.85	27.75	43.60	46.00	-2.40	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 3	Polarization :	Vertical
Test Power :	DC 5V from adapter AC 120V/60Hz		

	Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
	43.51	16.00	11.43	27.43	40.00	-12.57	peak
	166.07	25.94	10.73	36.67	43.50	-6.83	peak
	502.94	21.21	20.73	41.94	46.00	-4.06	peak
	668.14	20.17	23.81	43.98	46.00	-2.02	peak
	890.73	13.89	27.46	41.35	46.00	-4.65	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit




3.2.6 TEST RESULTS(Above 1GHz)

EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 1	Polarization :	Horizontal
Test Power :	DC 5V from adapter AC 120V/60Hz		

	Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
1825.00	62.20	-14.79	47.41	74.00	-26.59		peak
1187.50	61.39	-18.27	43.12	74.00	-30.88		peak
2000.00	63.39	-13.30	50.09	74.00	-23.91		peak
5037.50	52.18	-3.83	48.35	74.00	-25.65		peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit






EUT :	VINCI MV 7-in Family Tablet	Model Name :	VM-6910
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Test Date :	2013-10-30
Test Mode :	Mode 1	Polarization :	Vertical
Test Power :	DC 5V from adapter AC 120V/60Hz		

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
						peak
1175.00	62.77	-18.47	44.30	74.00	-29.70	peak
1825.00	62.20	-14.79	47.41	74.00	-26.59	peak
1987.50	64.63	-13.53	51.10	74.00	-22.90	peak
5037.50	52.93	-3.83	49.10	74.00	-24.90	peak

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Antenna Factor + Cable Loss.
3. N/A means All Data have pass Limit



4. EUT TEST PHOTO**Radiated Measurement Photos (30-1000MHz)****Radiated Measurement Photos (1000-6000MHz)**

Conducted Measurement Photos