



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR FCC CERTIFICATION

Test report file number : E029R-023

Applicant : HANTEL CO., LTD.

Address : #518-8, You Jin B/D, Dogok-Dong, Kangnam-Ku, Seoul, 135-270, Korea

Manufacturer : HANTEL CO., LTD.

Address : #518-8, You Jin B/D, Dogok-Dong, Kangnam-Ku, Seoul, 135-270, Korea

Type of Equipment : PAGER (All other receiver subject to Part 15)

FCC ID : ODG900FAN

Model Name : TITAN III-FLEX

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 10 pages (including this page)

Date of Incoming : September 06, 2002

Date of Issuing : September 11, 2002

SUMMARY

The equipment complies with the requirements of **FCC CFR 47 PART 15 SUBPART B, SECTION 15.101.**

This test report contains only the results of a single test of the sample supplied for the examination. It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by: G. W. Lee
G. W. Lee/ Assistant Chief Engineer

Reviewed by: Y. K. Kwon
Y. K. Kwon/ Chief Engineer

This report shall not be reproduced except in full without our written approval.

FCC-003 (Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: +82-31-746-8500, FAX: +82-31-746-8700)

EMC Testing Dept : 426-1 Daeangyong-Ri Chwol-Myun Kwangju-City, Kyunggi-Do 464-860 Korea (TEL: +82-31-765-8288, FAX: +82-31-766-2904)



ONETECH

Testing & Evaluation Lab.

Unknown document property name.

Page 2 of 10

FCC ID. : Error!

File No. : Error!

Unknown document property name.

EMC Div.
ONETECH Corp.

EMC Div.
ONETECH Corp.



CONTENTS

	Page
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 RELATED SUBMITTAL(S) / GRANT(S)	5
2.3 TEST SYSTEM DETAILS	5
2.4 TEST METHODOLOGY	5
2.5 TEST FACILITY	5
3. SYSTEM TEST CONFIGURATION.....	6
3.1 JUSTIFICATION	6
3.2 EUT EXERCISE SOFTWARE.....	6
3.3 CABLE DESCRIPTION	6
3.4 NOISE SUPPRESSION PARTS ON CABLE	6
3.5 EQUIPMENT MODIFICATIONS	6
3.6 CONFIGURATION OF TEST SYSTEM	6
4. PRELIMINARY TEST.....	7
4.1 AC POWER LINE CONDUCTED EMISSION TEST	7
4.2 RADIATED EMISSION TEST.....	7
5. FINAL RESULT OF MEASUREMENT	8
5.1 RADIATED EMISSION TEST.....	8
6. FIELD STRENGTH CALCULATION.....	10
7. LIST OF TEST EQUIPMENT	11

Unknown document property name.

1. VERIFICATION OF COMPLIANCE

-. APPLICANT : HANTEL CO., LTD.
 -. ADDRESS : #518-8, You Jin B/D, Dogok-Dong, Kangnam-Ku, Seoul, 135-270, Korea
 -. CONTACT PERSON : Mr. Beom-Seok, Park/ Engineer
 -. TELEPHONE NO : +82-2-571-4653
 -. FCC ID : ODG900FAN
 -. MODEL NO/NAME : TITAN III-FLEX
 -. SERIAL NUMBER : N/A
 -. DATE : September 11, 2002

DEVICE TYPE	All other receiver subject to Part 15 - Unintentional Radiator
E.U.T. DESCRIPTION	PAGER
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	ANSI C63.4/1992
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15, SECTION 15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

Unknown document property name.

2. GENERAL INFORMATION

2.1 Product Description

The HANTEL CO., LTD., Model TITAN III-FLEX (referred to as the EUT in this report) is a FLEX Alpha-Numeric Display Pager which using a microcomputer to control radio frequency (RF) circuits and other customized decoding hardware to receive, decode, store. Product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
LIST OF EACH OSC. OR CRY. FREQ.(FREQ.>=1MHz)	12.8MHz, 20.945MHz on the main board
POWER REQUIREMENT	DC1.5V Battery
NUMBER OF LAYERS	4 Layers: Main and LCD Board
TUNING FREQUENCY	929MHz ~ 932MHz
DETECT METHOD	Super-heterodyne Detector
LOCAL OSCILLATOR	1st Local Osc. Frequency = Tuning Frequency – 21.4MHz (1st IF)

Model Differences:

The difference(s) compared to the EUT is as follows: none

2.2 Related Submittal(s) / Grant(s)

Original submittal only

2.3 Test System Details

The model numbers for all the equipments that were used in the tested system is:

Model	Manufacturer	FCC ID	Description	Connected to
TITAN III-FLEX	HANTEL CO., LTD.	ODG900FAN	PAGER (EUT)	N/A
TC-1101A	TESCOM	N/A	FLEX PAGER TESTER	N/A

2.4 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4/1992. Radiated testing was performed at a distance of 3 meters from EUT to the antenna.

2.5 Test Facility

The open area test site and conducted measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-080 Korea. Description details of test facilities were submitted to the Commission on January 18, 2002. (Registration Number: 92819)

Unknown document property name.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN BOARD	HANTEL CO., LTD.	BFT3ESAI_RF	N/A
LCD BOARD	HANTEL CO., LTD.	TITAN 3F LG	N/A

3.2 EUT exercise Software

During Radiated Emission Tests, TESCOM signal generator model no: TC-1101A was used to radiate an unmodulated CW signal to EUT at 1 near top and 1 near bottom frequency in order to stabilize the local oscillator of the EUT.

3.3 Cable Description

-. Not applicable

3.4 Noise Suppression Parts on Cable

-. Not applicable

3.5 Equipment Modifications

To achieve compliance to CLASS B levels, the following change(s) was made by ONETECH Corp. during compliance testing:

“There were no Modified items during EMI test”

3.6 Configuration of Test System

Line Conducted Test : It does not need to test this requirement, because of the power of the EUT is supplied from a DC battery

Radiated Emission Test : Preliminary radiated emission test was conducted using the procedure in ANSI C63.4/1992 8.3.1.1 to determine the worse operating conditions. Final radiated emission test was conducted at 3 meters open area test site.



Unknown document property name.

4. PRELIMINARY TEST

4.1 AC Power line Conducted Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
N/A	N/A
It does not need to test this requirement, because of the power of the EUT is supplied from a DC battery.	

4.2 Radiated Emission Test

During Preliminary Test, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Standby	
Receiving	X

Unknown document property name.

5. FINAL RESULT OF MEASUREMENT

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level

5.1 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

Humidity Level : 51 % Temperature : 23 °C
 Limits apply to : FCC CFR 47, PART 15, SUBPART B, SECTION 15.109
 Type of Test : All other receiver subject to Part 15
 Result : PASSED BY -12.30 dB at 929.03 MHz at near bottom frequency
PASSED BY -12.80 dB at 953.36 MHz at near top frequency

EUT : PAGER Date: September 10, 2002
 Operating Condition : Receiving mode
 Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)
 Distance : 3 Meter
 Operating Frequency : Near Bottom Frequency: 929.025 MHz

Radiated Emissions		Ant	Correction Factors		Total	FCC CLASS B	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
141.04	13.94	V	12.65	1.31	27.90	43.50	-15.60
237.59	12.02	H	11.51	1.77	25.30	46.00	-20.70
647.55	4.82	V	19.91	3.07	27.80	46.00	-18.20
713.98	6.31	V	20.80	3.39	30.50	46.00	-15.50
929.03	6.85	V	22.81	4.04	33.70	46.00	-12.30
930~5000	*	-	-	-	-	-	-

Radiated Emission Tabulated Data

Remark: The “*” means equal or less than 5dB


Unknown document property name.

Operating Frequency : Near Top Frequency: 931.975 MHz

Radiated Emissions		Ant	Correction Factors		Total	FCC CLASS B	
Freq. (MHz)	Amp. (dBuV)	Pol.	Ant. (dBuV/m)	Cable (dB)	Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
143.97	14.35	V	12.92	1.33	28.60	43.50	-14.90
238.77	11.17	H	11.56	1.77	24.50	46.00	-21.50
953.36	5.82	V	23.27	4.11	33.20	46.00	-12.80
960~5000	*	-	-	-	-	-	-

Radiated Emission Tabulated Data

Remark: The "*" means equal or less than 5dB



Tested by: Young-Min, Choi / Project Engineer

Unknown document property name.

6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

+ Meter reading (dBuV)

+ Cable Loss (dB)

+ Antenna Factor (Loss) (dB/meter)

= Corrected Reading (dBuV/meter)

- Specification Limit (dBuV/meter)

= dB Relative to Spec (+/- dB)



Unknown document property name.

7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVS 10	827864/005	OCT/01	12MONTH	■
2.	Test receiver	R/S	ESHS 10	834467/007	APR/02	12MONTH	
3.	Spectrum analyzer	HP	8566B	3407A08547	AUG/02	12MONTH	■
4.	Spectrum analyzer	HP	8568B	3109A05456	APR/02	12MONTH	■
5.	RF preselector	HP	85685A	3107A01264	APR/02	12MONTH	■
6.	Quasi-Peak Adapter	HP	85650A	3107A01542	APR/02	12MONTH	■
7.	Biconical antenna	EMCO	3104C	9109-4441 9109-4443 9109-4444	APR/02	12MONTH	■
8.	Log Periodic antenna	EMCO	3146	9109-3213 9109-3214 9109-3217	APR/02	12MONTH	■
9.	Horn antenna	SCHWARZBECK	BBHA 9120D	BBHA9120D294	JUNE/02	12MONTH	■
10.	LISN	EMCO	3825/2	9109-1867 9109-1869	AUG/02	12MONTH	
11.	Computer System	HP	98581C	98543A	N/A	N/A	■
	Hard disk drive		9153C	CMC762Z9153	N/A	N/A	■
12.	Position Controller	EMCO	1090	9107-1038	N/A	N/A	■
13.	Turn Table	EMCO	1080-1.21	9109-1576	N/A	N/A	■
14.	Antenna Master	EMCO	1070-1	9109-1624	N/A	N/A	■