

## Nemko Korea Co., Ltd.

165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Republic of Korea  
TEL:+82 31 330-1700 FAX:+82 31 322 2332

### FCC & IC EVALUATION REPORT FOR CERTIFICATION

**Project No. :** NK-24-R-205

**Dates of receipt :** May 7, 2024

**Applicant :** i-SENS, Inc.

**Dates of Issue :** September 12, 2024

43, Banpo-daero 28-gil, Seocho-gu, Seoul  
06646, Korea, Republic of

**Test Site :**

Nemko Korea Co., Ltd.

**FCC ID :**

**OELBM002**

**IC :**

**21003-BM002**

**Applicant :**

**i-SENS, Inc.**

**Brand Name :**

**i-Sens, Inc.**

**Model:**

**BM002**

**Additional Model(s):**

-

**EUT Type:**

**BLE Module**

**Classification:** **FCC Part 15 Digital Transmission System (DTS)**

**Date of Test:** **August 9, 2024 ~ August 15, 2024**

**Applied Standard:** **FCC 47 CFR Part 15.247**

**RSS-Gen Issue 5, RSS-247 Issue 3**

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Tested By : Hyeonseung Lee  
Test Engineer

Reviewed By : Hoonpyo Lee  
Technical Manager

**Revision History**

Rev.	Issue Date	Revisions	Revised By
00	August 23, 2024	Initial issue	Hyeonseung Lee

## **TABLE OF CONTENTS**

<b>1. INTRODUCTION</b> .....	<b>4</b>
1.1 Test facility .....	4
1.2 Accreditation and listing .....	4
<b>2. EUT INFORMATION &amp; TEST CONDITIONS</b> .....	<b>5</b>
2.1 EUT Information .....	5
2.2 Operation During Test.....	6
2.3 Support Equipment .....	8
2.4 Setup Drawing.....	8
<b>3. ANTENNA REQUIREMENTS</b> .....	<b>9</b>
<b>4. SUMMARY OF TEST RESULTS</b> .....	<b>10</b>
<b>5. TEST METHODOLOGY</b> .....	<b>11</b>
<b>6. DESCRIPTION OF TESTS</b> .....	<b>12</b>
6.1 6 dB Bandwidth / Occupied Bandwidth.....	12
6.2 Peak Output Power .....	13
6.3 Power Spectral Density .....	14
6.4 Band Edge / Conducted Spurious Emissions .....	15
6.5 Radiated Emissions .....	16
6.7 AC Line Conducted Emissions.....	17
<b>7. TEST DATA</b> .....	<b>18</b>
7.1 6 dB Bandwidth / Occupied Bandwidth.....	18
7.2 Peak Output Power .....	21
7.3 Power Spectral Density .....	23
7.4 Band Edge / Conducted Spurious Emissions .....	25
7.5 Radiated Spurious Emissions .....	28
7.6 Radiated Band Edge .....	36
7.7 Radiated Emissions_Below 1GHz .....	39
7.8 AC Line Conducted .....	41
<b>8. TEST EQUIPMENT</b> .....	<b>41</b>
<b>9. ACCURACY OF MEASUREMENT &amp; DECISION RULE</b> .....	<b>43</b>
9.1 Uncertainty Calculation .....	43
9.2 Decision rule.....	43

## **1. INTRODUCTION**

### **1.1 Test facility**

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014), the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) was used in determining radiated and conducted emissions emanating.

These measurement tests were conducted at **Nemko Korea Co., Ltd.**

The site address 165-51, Yurim-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, 17042, Rep. of Korea.

### **1.2 Accreditation and listing**

Accreditation type	Accreditation number
	CAB Accreditation for DOC Designation No. KR0026
	KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme) Registration No. KT155
 Industry Canada	Canada IC Registered site Site No. 29506
	VCCI registration site(RE/CE/Telecom CE) Member No. 2118
	EMC CBTL TL124
	KCC(RRL)Designated Lab. Registration No. KR0026

## **2. EUT INFORMATION & TEST CONDITIONS**

### **2.1 EUT Information**

#### **2.1.1 Specifications**

EUT Type	BLE Module
Model Name	BM002
Frequency of Operation	2 402 MHz ~ 2 480 MHz
Peak Output Power (Conducted)	-2.93 dBm
Number of Channels	40 CH
Modulations	GFSK
Antenna Gain (peak)	-0.35 dBi
Antenna Setup	1TX / 1RX
EUT Rated Voltage	3.0 Vdc
EUT Test Voltage	3.0 Vdc
Remarks	-

## 2.2 Operation During Test

The EUT is the transceiver which is Bluetooth v5.2 supporting Bluetooth LE mode(Only 1 Mbps). The Laptop PC was used to control the EUT to transmit the wanted TX channel continuously (duty cycle < 98%) by the testing program (RF Tools) and testing command supported by manufacturer. The operating voltage of EUT was 3 Vdc supplied from jig board connected to USB port on Laptop PC.

The EUT was tested at the lowest, middle and the highest channels with the maximum output power in accordance with the manufacturer's specifications. The worst data were recorded in the report.

### 2.2.1 Table of Test power setting

Frequency	Mode	Modulation	Power setting Level
2 402 MHz ~ 2 480 MHz	BLE 1Mbps	GFSK	0

### 2.2.2 Table of Test frequency

Frequency band	Modulation	Test Channel (CH)	Frequency (MHz)
2.4 GHz	GFSK	0	2 402
		19	2 440
		39	2 480

### 2.2.3 Average Output Power

Mode	Frequency	Average Output Power (dBm)	Antenna Gain (dBi)	e.i.r.p (dBm)
Bluetooth LE 1Mbps	2 402	-3.96	-0.35	-4.31
	2 440	-3.31		-3.66
	2 480	-3.42		-3.77

### 2.2.4 Antenna Information

Frequency band	Modulation	Antenna TX mode	Support CDD	Support MIMO
2.4 GHz	GFSK	<input checked="" type="checkbox"/> 1TX, <input type="checkbox"/> 2TX	<input type="checkbox"/> Yes, <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes, <input checked="" type="checkbox"/> No

## 2.2.5 Additional Information Related to Testing

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for all conducted testing.

## 2.2.6 Worst-case Configuration and Mode

Radiated emission below 1GHz was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The emissions (Band-edge & spurious emissions) were investigated in three orthogonal orientations X, Y and Z.

Accordingly, the orientation was determined and tested as shown in the table below:

Test Items	X	Y	Z
Band-edge	O	-	-
Spurious emissions	O	-	-


## 2.2.7 Additional model covered by this report

The purpose of the marketing and the color of the product are different.

## 2.3 Support Equipment

EUT	i-SENS, Inc. Model : BM002	S/N: N/A
Laptop Computer	LG Model : 15Z90N-VP50ML	FCC DOC S/N : 003NZET038884
AC/DC Adapter	LG Model : WA-48B19FS	FCC DOC S/N : AKDS7648893016463

## 2.4 Setup Drawing



### **3. ANTENNA REQUIREMENTS**

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15 and RSS-Gen.

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

RSS-Gen Section 6.8

: The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below)

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

The transmitter has permanently attached Dielectric Chip antenna (Internal antenna) on board.

Used Antenna	
Model name	2 402 MHz ~ 2 480 MHz
	Max. peak gain (dBi)
IB24FE-Receiver (Embedded Antenna)	3.36

## **4. SUMMARY OF TEST RESULTS**

The EUT has been tested according to the following specification:

Name of Test	FCC Paragraph No.	IC Paragraph No.	Test Limit	Test Condition	Result	Remark
6dB Bandwidth	15.247(a)(2)	RSS-247 (5.2)(a)	> 500 kHz	Conducted	Complies	-
Occupied Bandwidth	-	RSS-Gen (6.7)				
Peak Output Power	15.247(b)(3)	RSS-247 (5.4)(d)	< 1 Watt < 4 Watt(e.i.r.p.)		Complies	-
Power Spectral Density	15.247(e)	RSS-247 (5.2)(b)	< 8 dBm/3 kHz		Complies	-
Band Edge / Conducted Spurious Emission	15.247(d)	RSS-247 (5.5)	≥ 20 dBc		Complies	-
Radiated Spurious Emission	15.205, 15.209	RSS-Gen (8.9),(8.10)	< 74 dB $\mu$ V/m (PK) < 54 dB $\mu$ V/m (AV) Radiated limits detailed in 15.209	Radiated	Complies	-
AC Line Conducted Emission	15.207	RSS-Gen (8.8)	FCC 15.207 Limits	Line Conducted	Complies	-


## **5. TEST METHODOLOGY**

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. RSS-Gen Issue 5
5. RSS-247 Issue 3
6. ANSI C63.10-2013.

## **6. DESCRIPTION OF TESTS**

### ***6.1 6 dB Bandwidth / Occupied Bandwidth***

#### **Test Setup**



#### **Test Measurement Method**

ANSI C63.10-2013, Section 11.8.2 Option 2

KDB 558074 D01 v05r02, Section 8.2

RSS-Gen section 6.7

#### **Test Procedure**

##### **- 6 dB Bandwidth (DTS Chanel Bandwidth)**

EUTs 6 dB bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

RBW = 100 kHz

VBW > 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow trace to fully stabilize.

The bandwidth measurement function on the spectrum analyzer is used to measure the 6 dB bandwidth.

##### **- Occupied Bandwidth**

EUTs occupied bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

Span = Set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

Detector = Set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.

RBW = 1% to 5% of the actual occupied / x dB bandwidth

VBW > 3 x RBW, Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

## 6.2 Peak Output Power

### Test Setup



### Test Measurement Method

ANSI C63.10-2013, Section 11.9.1.1  
KDB 558074 D01 v05r02, Section 8.3.1.1

### Test Procedure

EUTs Maximum Peak Conducted Output Power is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

RBW  $\geq$  DTS bandwidth

VBW  $\geq$  3 x RBW

Span  $\geq$  3 x RBW

Sweep time = auto couple

Detector = peak

Trace mode = max hold

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

## 6.3 Power Spectral Density

### Test Setup



### Test Measurement Method

ANSI C63.10-2013, Section 11.10.2 Method PKPSD  
KDB 558074 D01 v05r02, Section 8.4

### Test Procedure

EUTs Power Spectral Density is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

Center frequency = DTS channel center frequency

Span = 1.5 times the DTS channel bandwidth

RBW  $\geq$  3 kHz

VBW  $\geq$  3 x RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow the trace to stabilize.

The peak search function on the spectrum analyzer is used to determine the maximum amplitude level within the RBW.

## 6.4 Band Edge / Conducted Spurious Emissions

### Test Setup



### Test Measurement Method

ANSI C63.10-2013, Section 11.11.3  
KDB 558074 D01 v05r02, Section 8.5, Section 8.7.2

### Test Procedure

EUTs Conducted spurious emissions are measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

#### 1) Reference Level

Center frequency = DTS channel center frequency

Span  $\geq 1.5 \times$  DTS bandwidth

RBW = 100 kHz

VBW  $\geq 3 \times$  RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

#### 2) Unwanted Emissions

Set the center frequency and span to encompass frequency range to be measured.

RBW = 100 kHz

VBW  $\geq 3 \times$  RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

## 6.5 Radiated Emissions

### Test Measurement Method

ANSI C63.10-2013, Section 6.6.4.3, Section 11.11, Section 11.12  
KDB 558074 D01 v05r02, Section 8.6, Section 8.7

### Test Procedure

The measurement was performed at the test site that is specified in accordance with ANSI C63.10-2013. The spurious emission was scanned from 9 kHz to 30 MHz using Loop Antenna and 30 to 1000 MHz using Trilog broadband test antenna. Above 1 GHz, Horn antenna was used. For emissions testing at below 1GHz, The test equipment was placed on turntable with 0.8 m above ground. For emission measurements above 1 GHz, The test equipment was placed on turntable with 1.5 m above ground. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The EUT, cable, wire arrangement and mode of operation that has the highest amplitude relative to the limit was selected. Then, the turn table was rotated from 0° to 360° and an antenna mast was moved from 1 m to 4 m height to maximize the suspected highest amplitude signal. The final maximized level was recorded.

At frequencies below 1000 MHz, measurements performed using the CISPR quasi-peak detection. At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in ANSI 63.10-2013 section 11.12. Peak emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Trace mode = max hold. Average emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 10 kHz, Detector = Peak, Trace mode = max hold. Allow max hold to run for at least 50 times (1/duty cycle) traces.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88–216	150	3
216–960	200	3
Above 960	500	3

Radiated Emissions Limits per 47 CFR 15.209(a) & RSS-Gen (8.9)

## 6.7 AC Line Conducted Emissions

### Test Measurement Method

ANSI C63.10-2013, Section 6.2

### Test Procedure

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure. It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6. A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room. Rohde & Schwarz (ENV216) of the 50 ohm/50  $\mu$ H Line Impedance Stabilization Network (LISN) are bonded to the shielded room. The EUT is powered from the Rohde & Schwarz LISN. Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ". If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs. All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1 meter length. Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 200 msec sweep time. The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCI). The detector functions were set to CISPR quasi-peak mode & average mode. The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

## 7. TEST DATA

### **7.1 6 dB Bandwidth / Occupied Bandwidth**

FCC §15.247(a)(2)  
RSS-247 (5.2)(a), RSS-Gen (6.7)

**Test Mode : Set to Lowest channel, Middle channel and Highest channel**

#### Result

##### **- 6 dB Bandwidth**

Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Bandwidth Limit (kHz)
LE 1Mbps	0	2 402	677.3	500
	19	2 440	689.2	500
	39	2 480	669.6	500

##### **- Occupied Bandwidth**

Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Occupied Bandwidth (MHz)	Limit (MHz)
LE 1Mbps	0	2 402	1.097	-
	19	2 440	1.098	-
	39	2 480	1.091	-

## PLOTS OF EMISSIONS


### LE 1Mbps, 6 dB Bandwidth, Lowest Channel (2 402 MHz)





### LE 1Mbps, 6 dB Bandwidth, Middle Channel (2 440 MHz)



### LE 1Mbps, 6 dB Bandwidth, Highest Channel (2 480 MHz)



**LE 1Mbps, Occupied Bandwidth, Lowest Channel (2 402 MHz)**

**LE 1Mbps, Occupied Bandwidth, Middle Channel (2 440 MHz)**

**LE 1Mbps, Occupied Bandwidth, Highest Channel (2 480 MHz)**


## 7.2 Peak Output Power

FCC §15.247(b)(3)  
RSS-247(5.4)(d)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

### Result

Bluetooth Mode & Data Rate	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Antenna Gain (dBi)	e.i.r.p. (dBm)	Limit (dBm)
LE 1Mbps	2 402	-3.49	30.00	-0.35	-3.84	36.00
	2 440	-2.97	30.00		-3.32	36.00
	2 480	-2.93	30.00		-3.28	36.00


### Notes:

1. The following equation was used for spectrum offset:  
Spectrum offset (dB) = Attenuator (dB) + Cable Loss (dB) + SMA Type Connector Loss (dB)


2. The following equation was used for e.i.r.p. calculation:  
$$\text{e.i.r.p. (dBm)} = \text{Peak output power (dBm)} + \text{Antenna gain (dBi)}$$

## PLOTS OF EMISSIONS


### LE 1Mbps, Peak Output Power, Lowest Channel (2 402 MHz)



### LE 1Mbps, Peak Output Power, Middle Channel (2 440 MHz)



### LE 1Mbps, Peak Output Power, Highest Channel (2 480 MHz)



## 7.3 Power Spectral Density

FCC §15.247(e)  
RSS-247(5.2)(b)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

### Result

Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Measured PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Margin (dB)
LE 1Mbps	0	2 402	-18.25	8.00	-26.25
	19	2 440	-16.22	8.00	-24.22
	39	2 480	-16.94	8.00	-24.94


#### Notes:

1. The following equation was used for spectrum offset:


$$\text{Spectrum offset (dB)} = \text{Attenuator (dB)} + \text{Cable Loss (dB)} + \text{SMA Type Connector Loss (dB)}$$

## PLOTS OF EMISSIONS

### LE 1Mbps, Power Spectral Density, Lowest Channel (2 402 MHz)



### LE 1Mbps, Power Spectral Density, Middle Channel (2 440 MHz)



### LE 1Mbps, Power Spectral Density, Highest Channel (2 480 MHz)



## 7.4 Band Edge / Conducted Spurious Emissions

FCC §15.247(d)  
RSS-247(5.5)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

### Result


Bluetooth Mode & Data Rate	Channel No.	Frequency (MHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
LE 1Mbps	0	2 402	More than 20 dBc	20
	19	2 440	More than 20 dBc	20
	39	2 480	More than 20 dBc	20

### Notes:

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for the spurious emissions test.

## PLOTS OF EMISSIONS (Band Edge)

### LE 1Mbps, Band Edge, Lowest Channel (2 402 MHz)



### LE 1Mbps, Reference Level, Middle Channel (2 440 MHz)




### LE 1Mbps, Band Edge, Highest Channel (2 480 MHz)



## PLOTS OF EMISSIONS (Conducted Spurious Emissions)

### LE 1Mbps, Conducted Spurious Emissions, Lowest Channel (2 402 MHz)



### LE 1Mbps, Conducted Spurious Emissions, Middle Channel (2 440 MHz)



### LE 1Mbps, Conducted Spurious Emissions, Highest Channel (2 480 MHz)



## 7.5 Radiated Spurious Emissions

FCC §15.205, §15.209, §15.247(d)  
RSS-Gen (8.9),(8.10)

Test Mode : Set to Lowest channel, Middle channel and Highest channel

### Result

#### **LE 1Mbps\_Lowest channel (2 402 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4 804.00	44.63	V	PK	6.1	50.76	74.00	23.24
4 804.00	39.95	V	AV	6.1	46.08	54.00	7.92
12 507.70	41.84	V	PK	15.6	57.44	74.00	16.56
12 555.62	30.59	V	AV	15.7	46.29	54.00	7.71
17 870.40	38.68	V	PK	18.1	56.74	74.00	17.26
17 929.60	27.28	V	AV	18.2	45.48	54.00	8.52
23 668.20	45.80	V	PK	1.5	47.28	74.00	26.72

#### **LE 1Mbps\_Middle channel (2 440 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4 880.00	44.74	V	PK	5.9	50.66	74.00	23.34
4 879.78	38.99	H	AV	5.9	44.91	54.00	9.09
12 487.40	42.34	H	PK	15.6	57.92	74.00	16.08
12 672.54	30.35	H	AV	16.1	46.45	54.00	7.55
17 817.70	38.61	H	PK	17.9	56.53	74.00	17.47
17 877.80	27.58	H	AV	18.1	45.66	54.00	8.34
23 625.20	46.74	V	PK	1.2	47.98	74.00	26.02

**LE 1Mbps\_Highest channel (2 480 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 065.13	57.80	V	PK	-11.5	46.26	74.00	27.74
4 960.11	44.14	H	PK	6.1	50.28	74.00	23.72
4 960.22	39.23	H	AV	6.1	45.37	54.00	8.63
12 652.20	41.99	V	PK	15.9	57.93	74.00	16.07
12 680.04	30.10	V	AV	16.2	46.26	54.00	7.74
17 760.20	38.92	V	PK	17.8	56.73	74.00	17.27
17 934.20	27.35	V	AV	18.2	45.55	54.00	8.45
23 754.50	46.54	H	PK	1.3	47.86	74.00	26.14

**Zoom scan (LE 1Mbps\_4 804 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4 804.30	47.02	V	PK	6.1	53.16	74.00	20.84
4 803.80	41.69	V	AV	6.1	47.82	54.00	6.18

**Zoom scan (LE 1Mbps\_4 880 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4 879.44	47.15	V	PK	5.9	53.07	74.00	20.93
4 879.80	41.86	V	AV	5.9	47.78	54.00	6.22

**Zoom scan (LE 1Mbps\_4 960 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4 959.52	47.32	V	PK	6.1	53.46	74.00	20.54
4 959.92	41.66	V	AV	6.1	47.80	54.00	6.20


**Notes:**

1. \*Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
2. \*\*AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Average measurement was not performed when peak-detected emission complies with the average limit.
4. Other spurious was under 20 dB below Fundamental.
5. Bluetooth 1Mbps, Low channel (2 402 MHz) was the worst condition.
6. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
7. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
8. Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.
9. The spectrum was measured from 1 GHz to 10th harmonic and the worst-case emissions were reported.


## PLOTS OF EMISSIONS


### Worst Case



#### ***BLE 1Mbps, Lowest Channel (2 402 MHz) : 1 GHz to 7 GHz\_Peak***






#### ***BLE 1Mbps Lowest Channel (2 402 MHz) : 7 GHz to 12.75 GHz\_Peak***



**BLE 1Mbps Lowest Channel (2 402 MHz) : 12.75 GHz to 18 GHz\_Peak****BLE 1Mbps, Lowest Channel (2 402 MHz) : 18 GHz to 26.5 GHz\_Peak**

**Zoom scan (BLE 1Mbps 4 804 MHz)\_Peak**

**BLE 1Mbps, Lowest Channel (2 402 MHz) : 1 GHz to 7 GHz\_Average**


**BLE 1Mbps Lowest Channel (2 402 MHz) : 7 GHz to 12.75 GHz\_Average**

**BLE 1Mbps, Lowest Channel (2 402 MHz) : 12.75 GHz to 18 GHz\_Average**


**Zoom scan (BLE 1Mbps 4 804 MHz)\_Average**

## 7.6 Radiated Band Edge

FCC §15.205, §15.209  
RSS-Gen (8.9),(8.10)

Test Mode : Set to Lowest channel and Highest channel

### Result

#### **BLE 1Mbps, Lowest Channel (2 402 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 354.10	51.86	H	PK	-5.3	46.57	74.00	27.43
2 389.99	45.73	V	PK	-5.2	40.54	74.00	33.46

#### **BLE 1Mbps, Highest Channel (2 480 MHz)**


Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 483.50	53.66	H	PK	-4.7	48.92	74.00	25.08
2 483.50	40.98	H	AV	-4.7	36.24	54.00	17.76
2 483.64	64.81	H	PK	-4.7	60.07	74.00	13.93
2 483.63	41.44	H	AV	-4.7	36.70	54.00	17.30



### Notes:

1. \*Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, AV = Average
2. \*\*AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Average measurement was not performed when peak-detected emission complies with the average limit.
4. Other spurious was under 20 dB below Fundamental.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
6. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.

## PLOTS OF EMISSIONS

### ***BLE 1Mbps, Lowest Channel (2 402 MHz)\_Peak***



**BLE 1Mbps, Highest Channel (2.480 MHz)\_Peak****BLE 1Mbps, Highest Channel (2.480 MHz)\_Average**

## 7.7 Radiated Emissions\_Below 1GHz

FCC §15.209  
RSS-Gen (8.9),(8.10)

### Result

#### **BLE 1Mbps, Highest Channel (2 480 MHz)**

Frequency (MHz)	Reading (dB $\mu$ V)	Pol* (H/V)	Mode*	AF+CL+Amp (dB)**	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
49.98	34.50	V	QP	-5.5	29.05	40.00	10.95
74.52	37.34	H	QP	-11.4	25.94	40.00	14.06
181.71	39.39	H	QP	-8.4	31.02	43.50	12.48
289.38	41.60	H	QP	-3.9	37.69	46.00	8.31
310.56	41.40	H	QP	-3.6	37.77	46.00	8.23
411.18	37.27	H	QP	-1.5	35.81	46.00	10.19

#### **Radiated Measurements at 3meters**


##### **Notes:**

1. The worst-case emission was reported.
2. \*Pol. : H = Horizontal, V = Vertical, Mode : PK = Peak, QP = Quasi-Peak
3. \*\*AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
4. Measurements using CISPR quasi-peak mode below 1 GHz.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
6. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).  
Per FCC part 15.31(o), test results were not reported.  
Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.  
Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.
7. The limit is on the FCC §15.209.

## PLOTS OF EMISSIONS

### Worst Case

**Radiated emission below 1GHz, LE 1Mbps, Lowest Channel (2 402 MHz)**



## 7.8 AC Line Conducted

FCC §15.207  
RSS-Gen(8.8)

Result : N/P

**Note : The AC power line test was not performed because the EUT is only supplied with DC power.**

## **8. TEST EQUIPMENT**

No.	Instrument	Manufacture	Model	Serial No.	Calibration Date	Next Calibration Date
1	DIGITAL MULTIMETER	EZ DIGITAL	DM-334	2111395	2023-10-11	2024-10-11
2	Humidity Temperature	Lutron	MHB-382SD	AK.26553	2023-10-18	2024-10-18
3	Signal Generator	R&S	SMB100A	175861	2024-03-29	2025-03-29
4	Signal & Spectrum Analyzer	KEYSIGHT	N9030B	MY57144327	2024-03-27	2025-03-27
5	System DC Power Supply	H.P	6653A	3502A-01527	2024-07-02	2025-07-02
6	10 dB Attenuator	API technologies corp	40A2W-10	1912	2024-03-29	2025-03-29
7	EMI TEST RECEIVER	R&S	ESW44	103318	2024-01-08	2025-01-08
8	Trilog-Broadband antenna	Schwarzbeck	VULB9163	01431	2022-11-16	2024-11-16
9	DOUBLE RIDGED HORN ANTENNA	R&S	HF907	103175	2024-01-11	2025-01-11
10	Horn Antenna	Q-par Angus	QMS-00208	17519	2024-03-29	2025-03-29
11	Horn Antenna	Q-par Angus	QMS-00225	32226	2024-01-11	2025-01-11
12	AMPLIFIER	HP	8447F	2805A03406	2024-01-09	2025-01-09
13	Signal Conditioning Unit	R&S	SCU-18F	101056	2024-01-09	2025-01-09
14	Signal Conditioning Unit	R&S	SCU26F	100750	2024-01-11	2025-01-11
15	Open Switch and Control Unit	R&S	OSP220	102977	N/A	N/A
16	WiFi Filter Bank	R&S	U082	N/A	N/A	N/A
17	HYGROMETER	O-230	DRETEC	N/A	2024-01-12	2025-01-12
18	EMI TEST RECEIVER	R&S	ESR3	102930	2024-07-02	2025-07-02
19	TWO-LINE-V-NETWORK	R&S	ENV216	102829	2024-07-03	2025-07-03

## **9. ACCURACY OF MEASUREMENT & DECISION RULE**

### **9.1 Uncertainty Calculation**

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

PARAMETER	UNCERTAINTY
Radiated Disturbance, 30 MHz to 1 GHz	4.40 dB
Radiated Disturbance, Above 1 GHz	4.58 dB

### **9.2 Decision rule**

The choice of whether or not to include the measurement uncertainty of the measuring system used in the test in the conformance determination.:

- Application of internal procedures used in type testing where traceability of measurement uncertainty is established.
- Applying the decision that the standard used for type testing does not require it.

**END REPORT**