



FCC RADIO TEST REPORT

FCC ID : OEOM7218D1MRM0
Equipment : ML7218D1-MERCURY-M0-PE11
Brand Name : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
Model Name : ML7218D1-MERCURY-M0-PE11
Applicant : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
10-11/F, Building 1, 61 Shengxia Road,
PuDongDistrict,Shanghai, China 201203
Manufacturer : Dongguan Shengmengtai Surface Mount Technology Co.,Ltd
Room 301, Building 7, No. 45 Kangyi Road, QingxiTown,
Dongguan City
Standard : FCC Part 15 Subpart C §15.247

The product was received on Apr. 27, 2025 and testing was performed from May 13, 2025 to May 28, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment	22
5 Measurement Uncertainty	23
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR542704A	01	Initial issue of report	Jun. 17, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Danny Lee

Report Producer: Hannah Yang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth - LE (125 kbps, 500 kbps, 1Mbps, 2Mbps), and Zigbee 2.4GHz Antenna Type Zigbee: PCB Antenna		
Antenna information		
2405 MHz ~ 2480 MHz	Peak Gain (dBi)	1.9

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH23-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	11	2405	19	2445
	12	2410	20	2450
	13	2415	21	2455
	14	2420	22	2460
	15	2425	23	2465
	16	2430	24	2470
	17	2435	25	2475
	18	2440	26	2480


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	250kbps / O-QPSK
	Mode 1: Zigbee Tx CH11_2405 MHz
	Mode 2: Zigbee Tx CH18_2440 MHz
	Mode 3: Zigbee Tx CH25_2475 MHz
	Mode 4: Zigbee Tx CH26_2480 MHz
AC Conducted Emission	Mode 1: Zigbee TX + USB Cable(Charging from Notebook)
Remark: - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. - The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	TP00117D	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	Lenovo	IdeaPad Gaming 3 15IHU6	PD9AX201NG	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A
5.	Fixture 1	TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.	Telink Burning EVK V3	N/A	N/A	N/A
6.	Fixture 2	TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.	Telink AIOT-DK1-V2	N/A	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “BDT v.5.8.3” was installed in Laptop which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	May 19, 2025 ~ May 28, 2025	Aug. 28, 2025	Radiation (03CH23-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	62028 & 003	30MHz~1GHz	Nov. 27, 2024	May 19, 2025 ~ May 28, 2025	Nov. 26, 2025	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421580	9kHz~1GHz	Jul. 14, 2024	May 19, 2025 ~ May 28, 2025	Jul. 13, 2025	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	N/A	Sep. 27, 2024	May 19, 2025 ~ May 28, 2025	Sep. 26, 2025	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18E N	1GHz~18GHz	Jun. 20, 2024	May 19, 2025 ~ May 28, 2025	Jun. 19, 2025	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZB ECK	BBHA 9170	1224	18GHz~40GHz	Jun. 24, 2024	May 19, 2025 ~ May 28, 2025	Jun. 23, 2025	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Sep. 02, 2024	May 19, 2025 ~ May 28, 2025	Sep. 01, 2025	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	N/A	Aug. 21, 2024	May 19, 2025 ~ May 28, 2025	Aug. 20, 2025	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303B	TP211542	N/A	Oct. 21, 2024	May 19, 2025 ~ May 28, 2025	Oct. 20, 2025	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 19, 2025 ~ May 28, 2025	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 19, 2025 ~ May 28, 2025	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 19, 2025 ~ May 28, 2025	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019122	RK-002348	N/A	N/A	May 19, 2025 ~ May 28, 2025	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	N/A	Nov. 26, 2024	May 19, 2025 ~ May 28, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/231119/231122	N/A	Nov. 26, 2024	May 19, 2025 ~ May 28, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	May 19, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 19, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZB ECK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 23, 2024	May 19, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	May 19, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	May 19, 2025	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	May 19, 2025	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	May 19, 2025	Sep. 22, 2025	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	May 13, 2025 ~ May 28, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	May 13, 2025 ~ May 28, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	May 13, 2025 ~ May 28, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	E-Instrument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	May 13, 2025 ~ May 28, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	May 13, 2025 ~ May 28, 2025	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2025/5/13~2025/5/28	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Zigbee	250kbps	1	11	2405	2.325	1.438	0.50	Pass
Zigbee	250kbps	1	18	2440	2.314	1.501	0.50	Pass
Zigbee	250kbps	1	25	2475	2.306	1.507	0.50	Pass
Zigbee	250kbps	1	26	2480	2.061	1.380	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Zigbee	250kbps	1	11	2405	6.96	30.00	1.90	8.86	36.00	Pass
Zigbee	250kbps	1	18	2440	6.57	30.00	1.90	8.47	36.00	Pass
Zigbee	250kbps	1	25	2475	6.52	30.00	1.90	8.42	36.00	Pass
Zigbee	250kbps	1	26	2480	6.49	30.00	1.90	8.39	36.00	Pass





TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
Zigbee	250kbps	1	11	2405	6.10	-6.12	1.90	8.00	Pass
Zigbee	250kbps	1	18	2440	6.00	-6.03	1.90	8.00	Pass
Zigbee	250kbps	1	25	2475	5.55	-7.31	1.90	8.00	Pass
Zigbee	250kbps	1	26	2480	5.71	-4.47	1.90	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.





**6dB Bandwidth**

<250kbps>

6 dB Bandwidth Plot on Channel 11**6 dB Bandwidth Plot on Channel 18****6 dB Bandwidth Plot on Channel 25****6 dB Bandwidth Plot on Channel 26**





**99% Occupied Bandwidth**

<250kbps>

99% Occupied Bandwidth Plot on Channel 11**99% Occupied Bandwidth Plot on Channel 18****99% Occupied Bandwidth Plot on Channel 25****99% Occupied Bandwidth Plot on Channel 26**





**Power Spectral Density (dBm/3kHz)**

<250kbps>

Power Density (dBm/3kHz) Plot Channel 11**Power Density (dBm/3kHz) Plot Channel 18****Power Density (dBm/3kHz) Plot Channel 25****Power Density (dBm/3kHz) Plot Channel 26**

**Band Edge and Conducted Spurious Emission**


<250kbps>

Channel 11**100kHz PSD reference Level Plot****Plot on Channel 11****Spurious Emission 30MHz~1GHz Plot****Spurious Emission 1GHz~26.5GHz Plot**




Channel 18

100kHz PSD reference Level Plot




-

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 25


100kHz PSD reference Level Plot




Plot on Channel 25



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 26


100kHz PSD reference Level Plot




Plot on Channel 26



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	23.6 ~ 24.9°C
		Relative Humidity :	46.3 ~ 52.7%

EUT Information

Report NO : 542704
Test Mode : Mode 1
Test Voltage : Power from system
Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.158010	---	33.90	55.57	21.67	L1	FLO	20.0
0.158010	49.92	---	65.57	15.65	L1	FLO	20.0
0.178890	---	33.20	54.54	21.34	L1	FLO	20.0
0.178890	47.06	---	64.54	17.48	L1	FLO	20.0
0.205260	---	28.63	53.40	24.77	L1	FLO	20.0
0.205260	43.63	---	63.40	19.77	L1	FLO	20.0
0.468510	---	28.79	46.54	17.75	L1	FLO	20.0
0.468510	34.48	---	56.54	22.06	L1	FLO	20.0
0.546270	---	36.88	46.00	9.12	L1	FLO	20.0
0.546270	42.82	---	56.00	13.18	L1	FLO	20.0
0.606750	---	25.50	46.00	20.50	L1	FLO	20.0
0.606750	35.61	---	56.00	20.39	L1	FLO	20.0
3.043500	---	22.63	46.00	23.37	L1	FLO	20.1
3.043500	33.03	---	56.00	22.97	L1	FLO	20.1
3.300540	---	24.60	46.00	21.40	L1	FLO	20.1
3.300540	37.14	---	56.00	18.86	L1	FLO	20.1
3.568920	---	26.83	46.00	19.17	L1	FLO	20.1
3.568920	39.90	---	56.00	16.10	L1	FLO	20.1
3.707430	---	26.86	46.00	19.14	L1	FLO	20.1

3.707430	39.48	---	56.00	16.52	L1	FLO	20.1
3.968250	---	26.28	46.00	19.72	L1	FLO	20.1
3.968250	38.60	---	56.00	17.40	L1	FLO	20.1
4.345980	---	24.15	46.00	21.85	L1	FLO	20.1
4.345980	32.46	---	56.00	23.54	L1	FLO	20.1

EUT Information

Report NO : 542704
 Test Mode : Mode 1
 Test Voltage : Power from system
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.165750	---	35.98	55.17	19.19	N	FLO	20.0
0.165750	49.85	---	65.17	15.32	N	FLO	20.0
0.191310	---	33.89	53.98	20.09	N	FLO	20.0
0.191310	45.50	---	63.98	18.48	N	FLO	20.0
0.211740	---	28.76	53.14	24.38	N	FLO	20.0
0.211740	42.24	---	63.14	20.90	N	FLO	20.0
0.314250	---	27.85	49.86	22.01	N	FLO	20.0
0.314250	37.62	---	59.86	22.24	N	FLO	20.0
0.458250	---	25.30	46.72	21.42	N	FLO	20.0
0.458250	36.32	---	56.72	20.40	N	FLO	20.0
0.496050	---	31.60	46.07	14.47	N	FLO	20.0
0.496050	40.19	---	56.07	15.88	N	FLO	20.0
0.526920	---	35.55	46.00	10.45	N	FLO	20.0
0.526920	41.84	---	56.00	14.16	N	FLO	20.0
0.583530	---	32.98	46.00	13.02	N	FLO	20.0
0.583530	40.85	---	56.00	15.15	N	FLO	20.0
2.917590	---	23.18	46.00	22.82	N	FLO	20.1
2.917590	32.80	---	56.00	23.20	N	FLO	20.1
3.162750	---	23.28	46.00	22.72	N	FLO	20.1

3.162750	34.41	---	56.00	21.59	N	FLO	20.1
3.409260	---	25.48	46.00	20.52	N	FLO	20.1
3.409260	37.58	---	56.00	18.42	N	FLO	20.1
3.762870	---	27.14	46.00	18.86	N	FLO	20.1
3.762870	39.20	---	56.00	16.80	N	FLO	20.1
4.106130	---	25.55	46.00	20.45	N	FLO	20.1
4.106130	35.45	---	56.00	20.55	N	FLO	20.1
4.720740	---	23.13	46.00	22.87	N	FLO	20.2
4.720740	30.25	---	56.00	25.75	N	FLO	20.2



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Leo Li, Karl Hou and Lucifer Jiang	Relative Humidity(%):	55 ~ 58.7
		Temperature(°C):	20.9 ~ 22.4

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes





Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Zigbee O-QPSK	11	2405	250kbps	-	-
Mode 2	2400-2483.5	1	Zigbee O-QPSK	18	2440	250kbps	-	-
Mode 3	2400-2483.5	1	Zigbee O-QPSK	25	2475	250kbps	-	-
Mode 4	2400-2483.5	1	Zigbee O-QPSK	26	2480	250kbps	-	-
Mode 5	2400-2483.5	1	Zigbee O-QPSK	26	2480	250kbps	-	LF







C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Zigbee O-QPSK	11	2389.99	39.75	54.00	-14.25	H	Avg.	Pass	-	Band Edge
	Zigbee O-QPSK	11	4810.00	44.75	74.00	-29.25	H	Peak	Pass	-	Harmonic
2	Zigbee O-QPSK	18	2361.48	39.46	54.00	-14.54	V	Avg.	Pass	-	Band Edge
	Zigbee O-QPSK	18	7320.00	44.52	54.00	-9.48	H	Avg.	Pass	-	Harmonic
3	Zigbee O-QPSK	25	2483.53	42.27	54.00	-11.73	H	Avg.	Pass	-	Band Edge
	Zigbee O-QPSK	25	7425.00	43.23	54.00	-10.77	V	Avg.	Pass	-	Harmonic
4	Zigbee O-QPSK	26	2483.52	41.14	54.00	-12.86	H	Avg.	Pass	-	Band Edge
	Zigbee O-QPSK	26	7440.00	45.07	54.00	-8.93	V	Avg.	Pass	-	Harmonic
5	Zigbee O-QPSK	26	144.46	38.18	43.50	-5.32	H	QP	Pass	-	LF



Mode	1																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Zigbee_CH11_2405MHz																																																																																									
ANT	1																																																																																									
Pol.	Horizontal						Fundamental																																																																																			
Peak	 Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2322.26</td><td>50.71</td><td>74.00</td><td>-23.29</td><td>37.86</td><td>27.30</td><td>7.11</td><td>31.92</td><td>10.36</td><td>102</td><td>106</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2322.26	50.71	74.00	-23.29	37.86	27.30	7.11	31.92	10.36	102	106	Peak	 Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>101.73</td><td>-----</td><td>-----</td><td>89.03</td><td>27.06</td><td>7.24</td><td>31.98</td><td>10.38</td><td>102</td><td>106</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2405.00	101.73	-----	-----	89.03	27.06	7.24	31.98	10.38	102	106	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2322.26	50.71	74.00	-23.29	37.86	27.30	7.11	31.92	10.36	102	106	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2405.00	101.73	-----	-----	89.03	27.06	7.24	31.98	10.38	102	106	Peak																																																																														
Avg	 Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2389.99</td><td>39.75</td><td>54.00</td><td>-14.25</td><td>27.23</td><td>26.90</td><td>7.21</td><td>31.97</td><td>10.38</td><td>102</td><td>106</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2389.99	39.75	54.00	-14.25	27.23	26.90	7.21	31.97	10.38	102	106	Average	 Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2405.00</td><td>100.42</td><td>-----</td><td>-----</td><td>87.73</td><td>27.04</td><td>7.24</td><td>31.97</td><td>10.38</td><td>102</td><td>106</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2405.00	100.42	-----	-----	87.73	27.04	7.24	31.97	10.38	102	106	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2389.99	39.75	54.00	-14.25	27.23	26.90	7.21	31.97	10.38	102	106	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2405.00	100.42	-----	-----	87.73	27.04	7.24	31.97	10.38	102	106	Average																																																																														



Mode	1																																																																																													
	Band Edge																																																																																													
	2400-2483.5_Zigbee_CH11_2405MHz																																																																																													
ANT	1																																																																																													
Pol.	Vertical					Fundamental																																																																																								
Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2327.10</td><td>51.42</td><td>74.00</td><td>-22.58</td><td>38.56</td><td>27.30</td><td>7.11</td><td>31.92</td><td>10.37</td><td>397 71 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	cm	deg	1 2327.10	51.42	74.00	-22.58	38.56	27.30	7.11	31.92	10.37	397 71 Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2405.00</td><td>97.70</td><td>-----</td><td>-----</td><td>85.00</td><td>27.06</td><td>7.24</td><td>31.98</td><td>10.38</td><td>397</td><td>71 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2405.00	97.70	-----	-----	85.00	27.06	7.24	31.98	10.38	397	71 Peak		
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	cm	deg																																																																																					
1 2327.10	51.42	74.00	-22.58	38.56	27.30	7.11	31.92	10.37	397 71 Peak																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																				
1 2405.00	97.70	-----	-----	85.00	27.06	7.24	31.98	10.38	397	71 Peak																																																																																				
Avg	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2369.66</td><td>39.46</td><td>54.00</td><td>-14.54</td><td>26.66</td><td>27.20</td><td>7.18</td><td>31.95</td><td>10.37</td><td>397</td><td>71 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2369.66	39.46	54.00	-14.54	26.66	27.20	7.18	31.95	10.37	397	71 Average	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2405.00</td><td>96.15</td><td>-----</td><td>-----</td><td>83.45</td><td>27.06</td><td>7.24</td><td>31.98</td><td>10.38</td><td>397</td><td>71 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg	1 2405.00	96.15	-----	-----	83.45	27.06	7.24	31.98	10.38	397	71 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																				
1 2369.66	39.46	54.00	-14.54	26.66	27.20	7.18	31.95	10.37	397	71 Average																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																						
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm	deg																																																																																				
1 2405.00	96.15	-----	-----	83.45	27.06	7.24	31.98	10.38	397	71 Average																																																																																				





Mode	1																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5_Zigbee_CH11_2405MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4810.00</td><td>44.75</td><td>74.00</td><td>-29.25</td><td>33.91</td><td>32.52</td><td>10.14</td><td>33.16</td><td>1.34</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7215.00</td><td>51.76</td><td>-----</td><td>-----</td><td>36.12</td><td>37.06</td><td>12.45</td><td>35.91</td><td>2.04</td><td>100</td><td>119 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4810.00	44.75	74.00	-29.25	33.91	32.52	10.14	33.16	1.34	--	Peak	2	7215.00	51.76	-----	-----	36.12	37.06	12.45	35.91	2.04	100	119 Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4810.00</td><td>44.69</td><td>74.00</td><td>-29.31</td><td>33.85</td><td>32.52</td><td>10.14</td><td>33.16</td><td>1.34</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7215.00</td><td>50.30</td><td>-----</td><td>-----</td><td>34.61</td><td>37.12</td><td>12.45</td><td>35.92</td><td>2.04</td><td>100</td><td>352 Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4810.00	44.69	74.00	-29.31	33.85	32.52	10.14	33.16	1.34	--	Peak	2	7215.00	50.30	-----	-----	34.61	37.12	12.45	35.92	2.04	100	352 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4810.00	44.75	74.00	-29.25	33.91	32.52	10.14	33.16	1.34	--	Peak																																																																																																														
2	7215.00	51.76	-----	-----	36.12	37.06	12.45	35.91	2.04	100	119 Peak																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4810.00	44.69	74.00	-29.31	33.85	32.52	10.14	33.16	1.34	--	Peak																																																																																																														
2	7215.00	50.30	-----	-----	34.61	37.12	12.45	35.92	2.04	100	352 Peak																																																																																																														

Remark: The unwanted signal 7215.00 MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).







Mode	2																																																																																																			
	Band Edge - L																																																																																																			
	2400-2483.5_Zigbee_CH18_2440MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2334.10</td><td>50.55</td><td>74.00</td><td>-23.45</td><td>37.77</td><td>27.22</td><td>7.12</td><td>31.93</td><td>10.37</td><td>304</td><td>101</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2334.10	50.55	74.00	-23.45	37.77	27.22	7.12	31.93	10.37	304	101	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>100.31</td><td>-----</td><td>-----</td><td>87.75</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>304</td><td>101</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	100.31	-----	-----	87.75	26.90	7.28	32.00	10.38	304	101	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2334.10	50.55	74.00	-23.45	37.77	27.22	7.12	31.93	10.37	304	101	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	100.31	-----	-----	87.75	26.90	7.28	32.00	10.38	304	101	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2363.58</td><td>39.45</td><td>54.00</td><td>-14.55</td><td>26.66</td><td>27.20</td><td>7.17</td><td>31.95</td><td>10.37</td><td>304</td><td>101</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2363.58	39.45	54.00	-14.55	26.66	27.20	7.17	31.95	10.37	304	101	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>98.82</td><td>-----</td><td>-----</td><td>86.26</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>304</td><td>101</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	98.82	-----	-----	86.26	26.90	7.28	32.00	10.38	304	101	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2363.58	39.45	54.00	-14.55	26.66	27.20	7.17	31.95	10.37	304	101	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2440.00	98.82	-----	-----	86.26	26.90	7.28	32.00	10.38	304	101	Average																																																																																								



Mode	2																																														
	Band Edge - R																																														
	2400-2483.5_Zigbee_CH18_2440MHz																																														
ANT	1																																														
Pol.	Horizontal						Fundamental																																								
Peak	Date: 2025-05-28  Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2497.00</td><td>50.56</td><td>74.00</td><td>-23.44</td><td>37.96</td><td>26.90</td><td>7.36</td><td>32.04</td><td>10.38</td><td>304</td><td>101</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2497.00	50.56	74.00	-23.44	37.96	26.90	7.36	32.04	10.38	304	101	Peak	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1 2497.00	50.56	74.00	-23.44	37.96	26.90	7.36	32.04	10.38	304	101	Peak																																				
Avg	Date: 2025-05-28  Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2491.40</td><td>39.35</td><td>54.00</td><td>-14.65</td><td>26.75</td><td>26.90</td><td>7.35</td><td>32.03</td><td>10.38</td><td>304</td><td>101</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2491.40	39.35	54.00	-14.65	26.75	26.90	7.35	32.03	10.38	304	101	Average	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1 2491.40	39.35	54.00	-14.65	26.75	26.90	7.35	32.03	10.38	304	101	Average																																				



Mode	2																																																																																									
	Band Edge - L																																																																																									
	2400-2483.5_Zigbee_CH18_2440MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2341.31</td><td>50.37</td><td>74.00</td><td>-23.63</td><td>37.69</td><td>27.10</td><td>7.14</td><td>31.93</td><td>10.37</td><td>400</td><td>70</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2341.31	50.37	74.00	-23.63	37.69	27.10	7.14	31.93	10.37	400	70	Peak	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>93.95</td><td>-----</td><td>-----</td><td>81.39</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>400</td><td>70</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	93.95	-----	-----	81.39	26.90	7.28	32.00	10.38	400	70	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2341.31	50.37	74.00	-23.63	37.69	27.10	7.14	31.93	10.37	400	70	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2440.00	93.95	-----	-----	81.39	26.90	7.28	32.00	10.38	400	70	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2361.48</td><td>39.46</td><td>54.00</td><td>-14.54</td><td>26.67</td><td>27.20</td><td>7.17</td><td>31.95</td><td>10.37</td><td>400</td><td>70</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2361.48	39.46	54.00	-14.54	26.67	27.20	7.17	31.95	10.37	400	70	Average	Level (dBuV/m) Date: 2025-05-28  Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>92.50</td><td>-----</td><td>-----</td><td>79.94</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>400</td><td>70</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2440.00	92.50	-----	-----	79.94	26.90	7.28	32.00	10.38	400	70	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2361.48	39.46	54.00	-14.54	26.67	27.20	7.17	31.95	10.37	400	70	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2440.00	92.50	-----	-----	79.94	26.90	7.28	32.00	10.38	400	70	Average																																																																														



Mode	2										
	Band Edge - R										
	2400-2483.5_Zigbee_CH18_2440MHz										
ANT	1										
Pol.	Vertical						Fundamental				
Peak	</										



Mode	2																																																																																																																									
	Harmonic																																																																																																																									
	2400-2483.5_Zigbee_CH18_2440MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>4880.00</td><td>45.08</td><td>74.00</td><td>-28.92</td><td>33.87</td><td>32.66</td><td>10.25</td><td>33.17</td><td>1.47 -- -- Peak</td></tr><tr><td>2</td><td>7320.00</td><td>53.64</td><td>74.00</td><td>-20.36</td><td>37.76</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01 100 115 Peak</td></tr><tr><td>3</td><td>7320.00</td><td>44.52</td><td>54.00</td><td>-9.48</td><td>28.64</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01 100 115 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	4880.00	45.08	74.00	-28.92	33.87	32.66	10.25	33.17	1.47 -- -- Peak	2	7320.00	53.64	74.00	-20.36	37.76	37.36	12.49	35.98	2.01 100 115 Peak	3	7320.00	44.52	54.00	-9.48	28.64	37.36	12.49	35.98	2.01 100 115 Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>4880.00</td><td>46.08</td><td>74.00</td><td>-27.92</td><td>34.87</td><td>32.66</td><td>10.25</td><td>33.17</td><td>1.47 -- -- Peak</td></tr><tr><td>2</td><td>7320.00</td><td>53.00</td><td>74.00</td><td>-21.00</td><td>37.12</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01 100 250 Peak</td></tr><tr><td>3</td><td>7320.00</td><td>43.88</td><td>54.00</td><td>-10.12</td><td>28.00</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01 100 250 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	4880.00	46.08	74.00	-27.92	34.87	32.66	10.25	33.17	1.47 -- -- Peak	2	7320.00	53.00	74.00	-21.00	37.12	37.36	12.49	35.98	2.01 100 250 Peak	3	7320.00	43.88	54.00	-10.12	28.00	37.36	12.49	35.98	2.01 100 250 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1	4880.00	45.08	74.00	-28.92	33.87	32.66	10.25	33.17	1.47 -- -- Peak																																																																																																																	
2	7320.00	53.64	74.00	-20.36	37.76	37.36	12.49	35.98	2.01 100 115 Peak																																																																																																																	
3	7320.00	44.52	54.00	-9.48	28.64	37.36	12.49	35.98	2.01 100 115 Average																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1	4880.00	46.08	74.00	-27.92	34.87	32.66	10.25	33.17	1.47 -- -- Peak																																																																																																																	
2	7320.00	53.00	74.00	-21.00	37.12	37.36	12.49	35.98	2.01 100 250 Peak																																																																																																																	
3	7320.00	43.88	54.00	-10.12	28.00	37.36	12.49	35.98	2.01 100 250 Average																																																																																																																	



Mode	3																																																																																		
	Band Edge																																																																																		
	2400-2483.5_Zigbee_CH25_2475MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2485.23</td><td>51.74</td><td>74.00</td><td>-22.26</td><td>39.20</td><td>26.85</td><td>7.34</td><td>32.03</td><td>10.38</td><td>100</td><td>105</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2485.23	51.74	74.00	-22.26	39.20	26.85	7.34	32.03	10.38	100	105	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2475.00</td><td>98.85</td><td>-----</td><td>-----</td><td>86.36</td><td>26.80</td><td>7.33</td><td>32.02</td><td>10.38</td><td>100</td><td>105</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2475.00	98.85	-----	-----	86.36	26.80	7.33	32.02	10.38	100	105	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2485.23	51.74	74.00	-22.26	39.20	26.85	7.34	32.03	10.38	100	105	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2475.00	98.85	-----	-----	86.36	26.80	7.33	32.02	10.38	100	105	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.53</td><td>42.27</td><td>54.00</td><td>-11.73</td><td>29.74</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>100</td><td>105</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.53	42.27	54.00	-11.73	29.74	26.84	7.34	32.03	10.38	100	105	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2475.00</td><td>97.45</td><td>-----</td><td>-----</td><td>84.96</td><td>26.80</td><td>7.33</td><td>32.02</td><td>10.38</td><td>100</td><td>105</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2475.00	97.45	-----	-----	84.96	26.80	7.33	32.02	10.38	100	105	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2483.53	42.27	54.00	-11.73	29.74	26.84	7.34	32.03	10.38	100	105	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2475.00	97.45	-----	-----	84.96	26.80	7.33	32.02	10.38	100	105	Average																																																																								



Mode	3																																																																																		
	Band Edge																																																																																		
	2400-2483.5_Zigbee_CH25_2475MHz																																																																																		
ANT	1																																																																																		
Pol.	Vertical						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2489.00</td><td>50.83</td><td>74.00</td><td>-23.17</td><td>38.24</td><td>26.09</td><td>7.35</td><td>32.03</td><td>10.38</td><td>374</td><td>70</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2489.00	50.83	74.00	-23.17	38.24	26.09	7.35	32.03	10.38	374	70	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2475.00</td><td>95.11</td><td>-----</td><td>-----</td><td>82.62</td><td>26.80</td><td>7.33</td><td>32.02</td><td>10.38</td><td>374</td><td>70</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2475.00	95.11	-----	-----	82.62	26.80	7.33	32.02	10.38	374	70	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2489.00	50.83	74.00	-23.17	38.24	26.09	7.35	32.03	10.38	374	70	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2475.00	95.11	-----	-----	82.62	26.80	7.33	32.02	10.38	374	70	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.53</td><td>40.67</td><td>54.00</td><td>-13.33</td><td>28.14</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>374</td><td>70</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.53	40.67	54.00	-13.33	28.14	26.84	7.34	32.03	10.38	374	70	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2475.00</td><td>93.81</td><td>-----</td><td>-----</td><td>81.32</td><td>26.80</td><td>7.33</td><td>32.02</td><td>10.38</td><td>374</td><td>70</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2475.00	93.81	-----	-----	81.32	26.80	7.33	32.02	10.38	374	70	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2483.53	40.67	54.00	-13.33	28.14	26.84	7.34	32.03	10.38	374	70	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2475.00	93.81	-----	-----	81.32	26.80	7.33	32.02	10.38	374	70	Average																																																																								



Mode	3																																																																																																																																																							
	Harmonic																																																																																																																																																							
	2400-2483.5_Zigbee_CH25_2475MHz																																																																																																																																																							
ANT	1																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4950.00</td><td>45.95</td><td>74.00</td><td>-28.05</td><td>34.35</td><td>32.80</td><td>10.37</td><td>33.18</td><td>1.61</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7425.00</td><td>50.11</td><td>74.00</td><td>-23.89</td><td>34.42</td><td>37.20</td><td>12.57</td><td>36.06</td><td>1.98</td><td>100</td><td>214</td><td>Peak</td></tr><tr><td>3</td><td>7425.00</td><td>40.99</td><td>54.00</td><td>-13.01</td><td>25.30</td><td>37.20</td><td>12.57</td><td>36.06</td><td>1.98</td><td>100</td><td>214</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4950.00	45.95	74.00	-28.05	34.35	32.80	10.37	33.18	1.61	--	--	Peak	2	7425.00	50.11	74.00	-23.89	34.42	37.20	12.57	36.06	1.98	100	214	Peak	3	7425.00	40.99	54.00	-13.01	25.30	37.20	12.57	36.06	1.98	100	214	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4950.00</td><td>45.24</td><td>74.00</td><td>-28.76</td><td>33.64</td><td>32.80</td><td>10.37</td><td>33.18</td><td>1.61</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7425.00</td><td>52.35</td><td>74.00</td><td>-21.65</td><td>36.66</td><td>37.20</td><td>12.57</td><td>36.06</td><td>1.98</td><td>100</td><td>234</td><td>Peak</td></tr><tr><td>3</td><td>7425.00</td><td>43.23</td><td>54.00</td><td>-10.77</td><td>27.54</td><td>37.20</td><td>12.57</td><td>36.06</td><td>1.98</td><td>100</td><td>234</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4950.00	45.24	74.00	-28.76	33.64	32.80	10.37	33.18	1.61	--	--	Peak	2	7425.00	52.35	74.00	-21.65	36.66	37.20	12.57	36.06	1.98	100	234	Peak	3	7425.00	43.23	54.00	-10.77	27.54	37.20	12.57	36.06	1.98	100	234	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																														
1	4950.00	45.95	74.00	-28.05	34.35	32.80	10.37	33.18	1.61	--	--	Peak																																																																																																																																												
2	7425.00	50.11	74.00	-23.89	34.42	37.20	12.57	36.06	1.98	100	214	Peak																																																																																																																																												
3	7425.00	40.99	54.00	-13.01	25.30	37.20	12.57	36.06	1.98	100	214	Average																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																														
1	4950.00	45.24	74.00	-28.76	33.64	32.80	10.37	33.18	1.61	--	--	Peak																																																																																																																																												
2	7425.00	52.35	74.00	-21.65	36.66	37.20	12.57	36.06	1.98	100	234	Peak																																																																																																																																												
3	7425.00	43.23	54.00	-10.77	27.54	37.20	12.57	36.06	1.98	100	234	Average																																																																																																																																												





Mode	4																																																																																			
	Band Edge																																																																																			
	2400-2483.5_Zigbee_CH26_2480MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.60</td><td>51.81</td><td>74.00</td><td>-22.19</td><td>39.28</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>122</td><td>105</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.60	51.81	74.00	-22.19	39.28	26.84	7.34	32.03	10.38	122	105	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>99.10</td><td>-----</td><td>-----</td><td>86.62</td><td>26.80</td><td>7.33</td><td>32.03</td><td>10.38</td><td>122</td><td>105</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	99.10	-----	-----	86.62	26.80	7.33	32.03	10.38	122	105	Peak
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.60	51.81	74.00	-22.19	39.28	26.84	7.34	32.03	10.38	122	105	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2480.00	99.10	-----	-----	86.62	26.80	7.33	32.03	10.38	122	105	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.52</td><td>41.14</td><td>54.00</td><td>-12.86</td><td>28.61</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>122</td><td>105</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.52	41.14	54.00	-12.86	28.61	26.84	7.34	32.03	10.38	122	105	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>98.00</td><td>-----</td><td>-----</td><td>85.52</td><td>26.80</td><td>7.33</td><td>32.03</td><td>10.38</td><td>122</td><td>105</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	98.00	-----	-----	85.52	26.80	7.33	32.03	10.38	122	105	Average
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.52	41.14	54.00	-12.86	28.61	26.84	7.34	32.03	10.38	122	105	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2480.00	98.00	-----	-----	85.52	26.80	7.33	32.03	10.38	122	105	Average																																																																									



Mode	4																																																																																			
	Band Edge																																																																																			
	2400-2483.5_Zigbee_CH26_2480MHz																																																																																			
ANT	1																																																																																			
Pol.	Vertical						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.52</td><td>50.89</td><td>74.00</td><td>-23.11</td><td>38.29</td><td>26.90</td><td>7.36</td><td>32.04</td><td>10.38</td><td>367</td><td>68</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.52	50.89	74.00	-23.11	38.29	26.90	7.36	32.04	10.38	367	68	Peak	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>96.74</td><td>-----</td><td>-----</td><td>84.26</td><td>26.80</td><td>7.33</td><td>32.03</td><td>10.38</td><td>367</td><td>68</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	96.74	-----	-----	84.26	26.80	7.33	32.03	10.38	367	68	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.52	50.89	74.00	-23.11	38.29	26.90	7.36	32.04	10.38	367	68	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2480.00	96.74	-----	-----	84.26	26.80	7.33	32.03	10.38	367	68	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.52</td><td>40.42</td><td>54.00</td><td>-13.58</td><td>27.89</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>367</td><td>68</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.52	40.42	54.00	-13.58	27.89	26.84	7.34	32.03	10.38	367	68	Average	Level (dBuV/m) Date: 2025-05-28 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2480.00</td><td>95.49</td><td>-----</td><td>-----</td><td>83.01</td><td>26.80</td><td>7.33</td><td>32.03</td><td>10.38</td><td>367</td><td>68</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2480.00	95.49	-----	-----	83.01	26.80	7.33	32.03	10.38	367	68	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.52	40.42	54.00	-13.58	27.89	26.84	7.34	32.03	10.38	367	68	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2480.00	95.49	-----	-----	83.01	26.80	7.33	32.03	10.38	367	68	Average																																																																									



Mode	4																																																																																																																																																																							
	Harmonic																																																																																																																																																																							
	2400-2483.5_Zigbee_CH26_2480MHz																																																																																																																																																																							
ANT	1																																																																																																																																																																							
Pol.	Horizontal							Vertical																																																																																																																																																																
Peak Avg	 Level (dBuV/m) vs Frequency (MHz). Date: 2025-05-28. Limits: PEAK_74, AVG_54. Peaks at 4960 and 7440 MHz.							 Level (dBuV/m) vs Frequency (MHz). Date: 2025-05-28. Limits: PEAK_74, AVG_54. Peaks at 4960 and 7440 MHz.																																																																																																																																																																
	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>48.62</td><td>74.00</td><td>-25.38</td><td></td><td>37.00</td><td>32.80</td><td>10.38</td><td>33.18</td><td>1.62</td><td>100</td><td>123</td><td>Peak</td></tr><tr><td>2</td><td>4960.00</td><td>38.66</td><td>54.00</td><td>-15.34</td><td></td><td>27.04</td><td>32.80</td><td>10.38</td><td>33.18</td><td>1.62</td><td>100</td><td>123</td><td>Average</td></tr><tr><td>3</td><td>7440.00</td><td>50.38</td><td>74.00</td><td>-23.62</td><td></td><td>34.68</td><td>37.20</td><td>12.59</td><td>36.07</td><td>1.98</td><td>100</td><td>290</td><td>Peak</td></tr><tr><td>4</td><td>7440.00</td><td>39.20</td><td>54.00</td><td>-14.80</td><td></td><td>23.50</td><td>37.20</td><td>12.59</td><td>36.07</td><td>1.98</td><td>100</td><td>290</td><td>Average</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	48.62	74.00	-25.38		37.00	32.80	10.38	33.18	1.62	100	123	Peak	2	4960.00	38.66	54.00	-15.34		27.04	32.80	10.38	33.18	1.62	100	123	Average	3	7440.00	50.38	74.00	-23.62		34.68	37.20	12.59	36.07	1.98	100	290	Peak	4	7440.00	39.20	54.00	-14.80		23.50	37.20	12.59	36.07	1.98	100	290	Average	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4960.00</td><td>45.05</td><td>74.00</td><td>-28.95</td><td></td><td>33.43</td><td>32.80</td><td>10.38</td><td>33.18</td><td>1.62</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7440.00</td><td>53.84</td><td>74.00</td><td>-20.16</td><td></td><td>38.14</td><td>37.20</td><td>12.59</td><td>36.07</td><td>1.98</td><td>100</td><td>242</td><td>Peak</td></tr><tr><td>3</td><td>7440.00</td><td>45.07</td><td>54.00</td><td>-8.93</td><td></td><td>29.37</td><td>37.20</td><td>12.59</td><td>36.07</td><td>1.98</td><td>100</td><td>242</td><td>Average</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4960.00	45.05	74.00	-28.95		33.43	32.80	10.38	33.18	1.62	--	--	Peak	2	7440.00	53.84	74.00	-20.16		38.14	37.20	12.59	36.07	1.98	100	242	Peak	3	7440.00	45.07	54.00	-8.93		29.37	37.20	12.59	36.07	1.98	100	242	Average
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																												
1	4960.00	48.62	74.00	-25.38		37.00	32.80	10.38	33.18	1.62	100	123	Peak																																																																																																																																																											
2	4960.00	38.66	54.00	-15.34		27.04	32.80	10.38	33.18	1.62	100	123	Average																																																																																																																																																											
3	7440.00	50.38	74.00	-23.62		34.68	37.20	12.59	36.07	1.98	100	290	Peak																																																																																																																																																											
4	7440.00	39.20	54.00	-14.80		23.50	37.20	12.59	36.07	1.98	100	290	Average																																																																																																																																																											
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																												
1	4960.00	45.05	74.00	-28.95		33.43	32.80	10.38	33.18	1.62	--	--	Peak																																																																																																																																																											
2	7440.00	53.84	74.00	-20.16		38.14	37.20	12.59	36.07	1.98	100	242	Peak																																																																																																																																																											
3	7440.00	45.07	54.00	-8.93		29.37	37.20	12.59	36.07	1.98	100	242	Average																																																																																																																																																											



Mode	5																																																																																																																																																																																																														
	LF																																																																																																																																																																																																														
	2400-2483.5_Zigbee_CH26_2480MHz																																																																																																																																																																																																														
ANT	1																																																																																																																																																																																																														
Pol.	Horizontal						Vertical																																																																																																																																																																																																								
QPI Peak	Level (dBuV/m) Date: 2025-05-21 Site : 03CH23-HY Condition: QP 3m CBL6111D_62020 & 003_241127 HORIZONTAL <table><tr><th rowspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBm</th><th>dBm</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>56.19</td><td>33.76</td><td>40.00</td><td>-6.24</td><td>53.38</td><td>12.21</td><td>0.91</td><td>32.77</td><td>0.03</td><td>298 126 QP</td></tr><tr><td>2</td><td>144.46</td><td>38.18</td><td>43.50</td><td>-5.32</td><td>51.91</td><td>17.39</td><td>1.55</td><td>32.73</td><td>0.06</td><td>197 354 QP</td></tr><tr><td>3</td><td>156.10</td><td>36.97</td><td>43.50</td><td>-6.53</td><td>51.15</td><td>16.88</td><td>1.62</td><td>32.74</td><td>0.06</td><td>201 357 QP</td></tr><tr><td>4</td><td>204.60</td><td>32.22</td><td>43.50</td><td>-11.28</td><td>47.93</td><td>15.17</td><td>1.83</td><td>32.77</td><td>0.06</td><td>196 354 QP</td></tr><tr><td>5</td><td>238.55</td><td>37.47</td><td>46.00</td><td>-8.53</td><td>48.17</td><td>20.03</td><td>1.99</td><td>32.80</td><td>0.08</td><td>100 25 QP</td></tr><tr><td>6</td><td>396.66</td><td>39.50</td><td>46.00</td><td>-6.50</td><td>47.95</td><td>21.63</td><td>2.61</td><td>32.80</td><td>0.11</td><td>-- -- Peak</td></tr></table>							Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Level	Factor	Loss	Factor	Factor					MHz	dBm	dBm	dB	dBuV	dB/m	dB	dB	cm	deg	1	56.19	33.76	40.00	-6.24	53.38	12.21	0.91	32.77	0.03	298 126 QP	2	144.46	38.18	43.50	-5.32	51.91	17.39	1.55	32.73	0.06	197 354 QP	3	156.10	36.97	43.50	-6.53	51.15	16.88	1.62	32.74	0.06	201 357 QP	4	204.60	32.22	43.50	-11.28	47.93	15.17	1.83	32.77	0.06	196 354 QP	5	238.55	37.47	46.00	-8.53	48.17	20.03	1.99	32.80	0.08	100 25 QP	6	396.66	39.50	46.00	-6.50	47.95	21.63	2.61	32.80	0.11	-- -- Peak	Level (dBuV/m) Date: 2025-05-21 Site : 03CH23-HY Condition: QP 3m CBL6111D_62020 & 003_241127 VERTICAL <table><tr><th rowspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBm</th><th>dBm</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>56.19</td><td>30.14</td><td>40.00</td><td>-9.86</td><td>49.76</td><td>12.21</td><td>0.91</td><td>32.77</td><td>0.03</td><td>100 46 QP</td></tr><tr><td>2</td><td>132.82</td><td>30.54</td><td>43.50</td><td>-12.96</td><td>44.11</td><td>17.62</td><td>1.47</td><td>32.72</td><td>0.06</td><td>197 101 QP</td></tr><tr><td>3</td><td>252.13</td><td>36.82</td><td>46.00</td><td>-9.18</td><td>47.42</td><td>20.09</td><td>2.05</td><td>32.82</td><td>0.08</td><td>-- -- Peak</td></tr><tr><td>4</td><td>420.91</td><td>33.69</td><td>46.00</td><td>-12.31</td><td>41.19</td><td>22.55</td><td>2.70</td><td>32.85</td><td>0.10</td><td>-- -- Peak</td></tr><tr><td>5</td><td>744.89</td><td>34.26</td><td>46.00</td><td>-11.74</td><td>35.12</td><td>28.14</td><td>3.69</td><td>32.81</td><td>0.12</td><td>-- -- Peak</td></tr><tr><td>6</td><td>849.65</td><td>39.50</td><td>46.00</td><td>-6.50</td><td>38.86</td><td>29.10</td><td>3.78</td><td>32.39</td><td>0.15</td><td>-- -- Peak</td></tr></table>						Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Level	Factor	Loss	Factor	Factor					MHz	dBm	dBm	dB	dBuV	dB/m	dB	dB	cm	deg	1	56.19	30.14	40.00	-9.86	49.76	12.21	0.91	32.77	0.03	100 46 QP	2	132.82	30.54	43.50	-12.96	44.11	17.62	1.47	32.72	0.06	197 101 QP	3	252.13	36.82	46.00	-9.18	47.42	20.09	2.05	32.82	0.08	-- -- Peak	4	420.91	33.69	46.00	-12.31	41.19	22.55	2.70	32.85	0.10	-- -- Peak	5	744.89	34.26	46.00	-11.74	35.12	28.14	3.69	32.81	0.12	-- -- Peak	6	849.65	39.50	46.00	-6.50	38.86	29.10	3.78	32.39	0.15	-- -- Peak
		Limit		Read	Ant	Cable		Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																			
		Freq	Level	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																							
	MHz	dBm	dBm	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																					
1	56.19	33.76	40.00	-6.24	53.38	12.21	0.91	32.77	0.03	298 126 QP																																																																																																																																																																																																					
2	144.46	38.18	43.50	-5.32	51.91	17.39	1.55	32.73	0.06	197 354 QP																																																																																																																																																																																																					
3	156.10	36.97	43.50	-6.53	51.15	16.88	1.62	32.74	0.06	201 357 QP																																																																																																																																																																																																					
4	204.60	32.22	43.50	-11.28	47.93	15.17	1.83	32.77	0.06	196 354 QP																																																																																																																																																																																																					
5	238.55	37.47	46.00	-8.53	48.17	20.03	1.99	32.80	0.08	100 25 QP																																																																																																																																																																																																					
6	396.66	39.50	46.00	-6.50	47.95	21.63	2.61	32.80	0.11	-- -- Peak																																																																																																																																																																																																					
	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																					
	Freq	Level	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																								
	MHz	dBm	dBm	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																					
1	56.19	30.14	40.00	-9.86	49.76	12.21	0.91	32.77	0.03	100 46 QP																																																																																																																																																																																																					
2	132.82	30.54	43.50	-12.96	44.11	17.62	1.47	32.72	0.06	197 101 QP																																																																																																																																																																																																					
3	252.13	36.82	46.00	-9.18	47.42	20.09	2.05	32.82	0.08	-- -- Peak																																																																																																																																																																																																					
4	420.91	33.69	46.00	-12.31	41.19	22.55	2.70	32.85	0.10	-- -- Peak																																																																																																																																																																																																					
5	744.89	34.26	46.00	-11.74	35.12	28.14	3.69	32.81	0.12	-- -- Peak																																																																																																																																																																																																					
6	849.65	39.50	46.00	-6.50	38.86	29.10	3.78	32.39	0.15	-- -- Peak																																																																																																																																																																																																					



Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Zigbee for 250kbps	100	-	-	10Hz

