



FCC RADIO TEST REPORT

FCC ID : OEOML9118AGM0
Equipment : ML9118A-GAIA-M0-PG12
Brand Name : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
Model Name : ML9118A-GAIA-M0-PG12
Applicant : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
10-11/F, Building 1, 61 Shengxia Road,
PuDongDistrict,Shanghai, China 201203
Manufacturer : Dongguan Shengmengtai Surface Mount Technology Co.,Ltd
Room 301, Building 7, No. 45 Kangyi Road, QingxiTown,
Dongguan City
Standard : FCC Part 15 Subpart C §15.247

The product was received on Apr. 27, 2025 and testing was performed from May 22, 2025 to Jun. 27, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment.....	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR542702C	01	Initial issue of report	Jul. 11, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Danny Lee

Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth-LE, Wi-Fi 2.4GHz 802.11b/g/n/ax, and Zigbee (2.4GHz)		
Antenna Type WLAN: PCB Antenna		
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.6

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010 TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		



2.2 Test Mode

This device support 26/52/106/242-tone RU.

The 242-tone RU is covered by 20MHz channel.


The final test modes include the worst data rates for each modulation shown in the table below.

Single Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ax HE20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :WLAN (2.4GHz) Tx + Fixture with USB Cable(Charging from Notebook)
Remark: 1. The detailed Radiated test modes are shown in Appendix C. 2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	TP00117D	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	Lenovo	IdeaPad Gaming 3 15IHU6	PD9AX201NG	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A
5.	Fixture	TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.	AIOT-DK2-V3	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BDT v.5.8.4” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	May 23, 2025~ Jun. 26, 2025	Aug. 28, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Dec. 17, 2024	May 23, 2025~ Jun. 26, 2025	Dec. 16, 2025	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 14, 2024	May 23, 2025~ Jun. 26, 2025	Jul. 13, 2025	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18E N	1GHz~18GHz	May 20, 2025	May 23, 2025~ Jun. 26, 2025	May 19, 2026	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1230	18GHz~40GHz	Oct. 25, 2024	May 23, 2025~ Jun. 26, 2025	Oct. 24, 2025	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 27, 2024	May 23, 2025~ Jun. 26, 2025	Sep. 26, 2025	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060872	18-40GHz	Nov. 29, 2024	May 23, 2025~ Jun. 26, 2025	Nov. 28, 2025	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 24, 2024	May 23, 2025~ Jun. 26, 2025	Sep. 23, 2025	Radiation (03CH22-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY53290053	3Hz~26.5GHz	Sep. 09, 2024	May 23, 2025~ Jun. 26, 2025	Sep. 08, 2025	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Dec. 24, 2024	May 23, 2025~ Jun. 26, 2025	Dec. 23, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 23, 2025~ Jun. 26, 2025	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 23, 2025~ Jun. 26, 2025	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 23, 2025~ Jun. 26, 2025	N/A	Radiation (03CH22-HY)
Software	Audix	E3	RK-002347	N/A	N/A	May 23, 2025~ Jun. 26, 2025	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	May 23, 2025~ Jun. 26, 2025	Mar. 04, 2026	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER/EM CI	SUCOFLEX 102/EMCI01Y- KM-KM-500/E MCI01Y-KM-K M-9000	804611/2,24 0914, 25043351,25 043350	30MHz~40GHz	May 19, 2025	May 23, 2025~ Jun. 26, 2025	May 18, 2026	Radiation (03CH22-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	May 22, 2025~ Jun. 27, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SN O31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	May 22, 2025~ Jun. 27, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	May 22, 2025~ Jun. 27, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	E-Instrument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	May 22, 2025~ Jun. 27, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final _version_2405 13	N/A	Conducted Other Test Item	N/A	May 22, 2025~ Jun. 27, 2025	N/A	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jun. 02, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 02, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Jun. 02, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Jun. 02, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Jun. 02, 2025	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	Jun. 02, 2025	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Jun. 02, 2025	Sep. 22, 2025	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.6 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2025/5/22~2025/6/27	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant1	Ant2	Ant1	Ant2		
11b	1Mbps	1	1	2412	12.19	-	10.07	-	0.50	Pass
11b	1Mbps	1	6	2437	12.19	-	10.07	-	0.50	Pass
11b	1Mbps	1	11	2462	12.22	-	10.07	-	0.50	Pass
11g	6Mbps	1	1	2412	17.83	-	16.34	-	0.50	Pass
11g	6Mbps	1	6	2437	17.84	-	16.34	-	0.50	Pass
11g	6Mbps	1	11	2462	17.81	-	16.35	-	0.50	Pass
HT20	MCS0	1	1	2412	18.60	-	17.58	-	0.50	Pass
HT20	MCS0	1	6	2437	18.61	-	17.57	-	0.50	Pass
HT20	MCS0	1	11	2462	18.62	-	17.57	-	0.50	Pass
HT40	MCS0	1	3	2422	37.73	-	36.31	-	0.50	Pass
HT40	MCS0	1	6	2437	37.70	-	36.31	-	0.50	Pass
HT40	MCS0	1	9	2452	37.71	-	36.31	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna															
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)		Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	13.24	-	30.00	-	2.60	-	15.84	-	36.00	-	Pass
11b	1Mbps	1	6	2437	13.27	-	30.00	-	2.60	-	15.87	-	36.00	-	Pass
11b	1Mbps	1	11	2462	13.48	-	30.00	-	2.60	-	16.08	-	36.00	-	Pass
11g	6Mbps	1	1	2412	5.63	-	30.00	-	2.60	-	8.23	-	36.00	-	Pass
11g	6Mbps	1	6	2437	5.53	-	30.00	-	2.60	-	8.13	-	36.00	-	Pass
11g	6Mbps	1	11	2462	5.78	-	30.00	-	2.60	-	8.38	-	36.00	-	Pass
HT20	MCS0	1	1	2412	5.48	-	30.00	-	2.60	-	8.08	-	36.00	-	Pass
HT20	MCS0	1	6	2437	5.40	-	30.00	-	2.60	-	8.00	-	36.00	-	Pass
HT20	MCS0	1	11	2462	5.49	-	30.00	-	2.60	-	8.09	-	36.00	-	Pass
HT40	MCS0	1	3	2422	5.28	-	30.00	-	2.60	-	7.88	-	36.00	-	Pass
HT40	MCS0	1	6	2437	5.42	-	30.00	-	2.60	-	8.02	-	36.00	-	Pass
HT40	MCS0	1	9	2452	5.29	-	30.00	-	2.60	-	7.89	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band Single Antenna											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)		DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	-14.37	-	2.60	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-14.01	-	2.60	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-13.90	-	2.60	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-22.75	-	2.60	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-23.38	-	2.60	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-22.42	-	2.60	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-22.96	-	2.60	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-22.90	-	2.60	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-22.65	-	2.60	-	8.00	-	Pass
HT40	MCS0	1	3	2422	-25.64	-	2.60	-	8.00	-	Pass
HT40	MCS0	1	6	2437	-25.28	-	2.60	-	8.00	-	Pass
HT40	MCS0	1	9	2452	-24.72	-	2.60	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna											
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
						Ant1	Ant2	Ant1	Ant2		
HE20	MCS0	1	1	2412	Full	19.13	-	19.01	-	0.50	Pass
HE20	MCS0	1	6	2437	Full	19.14	-	19.02	-	0.50	Pass
HE20	MCS0	1	11	2462	Full	19.13	-	19.03	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)		Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
HE20	MCS0	1	1	2412	Full	5.50	-	30.00	-	2.60	-	8.10	-	36.00	-	Pass
HE20	MCS0	1	1	2412	26/0	-3.97	-	30.00	-	2.60	-	-1.37	-	36.00	-	Pass
HE20	MCS0	1	1	2412	52/37	-1.69	-	30.00	-	2.60	-	0.91	-	36.00	-	Pass
HE20	MCS0	1	1	2412	106/53	-0.70	-	30.00	-	2.60	-	1.90	-	36.00	-	Pass
HE20	MCS0	1	6	2437	Full	5.43	-	30.00	-	2.60	-	8.03	-	36.00	-	Pass
HE20	MCS0	1	6	2437	26/4	-4.36	-	30.00	-	2.60	-	-1.76	-	36.00	-	Pass
HE20	MCS0	1	6	2437	52/38	-2.79	-	30.00	-	2.60	-	-0.19	-	36.00	-	Pass
HE20	MCS0	1	6	2437	106/53	0.33	-	30.00	-	2.60	-	2.93	-	36.00	-	Pass
HE20	MCS0	1	11	2462	Full	5.51	-	30.00	-	2.60	-	8.11	-	36.00	-	Pass
HE20	MCS0	1	11	2462	26/8	-2.68	-	30.00	-	2.60	-	-0.08	-	36.00	-	Pass
HE20	MCS0	1	11	2462	52/40	-1.36	-	30.00	-	2.60	-	1.24	-	36.00	-	Pass
HE20	MCS0	1	11	2462	106/54	0.62	-	30.00	-	2.60	-	3.22	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band Single Antenna												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Peak PSD (dBm/3kHz)		DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
						Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
HE20	MCS0	1	1	2412	Full	-22.74	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	1	2412	26/0	-22.88	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	1	2412	52/37	-23.25	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	1	2412	106/53	-23.15	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	6	2437	Full	-22.75	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	6	2437	26/4	-23.09	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	6	2437	52/38	-22.86	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	6	2437	106/53	-23.13	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	11	2462	Full	-22.64	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	11	2462	26/8	-22.78	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	11	2462	52/40	-22.87	-	2.60	-	8.00	-	Pass
HE20	MCS0	1	11	2462	106/54	-23.09	-	2.60	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

**6dB and 99% Occupied Bandwidth**


<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11aN20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11aN40>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11ax20>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




Power Spectral Density(dBm/3kHz)

<802.11b>






<802.11g>






<802.11aN20>






<802.11aN40>





<802.11ax20>







**Band Edges and Spurious Emission**

Number of TX = 1, Ant. 1 (Measured)

Test Mode : 802.11b

Test Channel : 01


100kHz PSD reference Level**Channel 01 Plot****Spurious Emission 30MHz~1GHz****Spurious Emission 1GHz~26.5GHz**




Test Mode : 802.11b

Test Channel : 06


100kHz PSD reference Level



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 06


100kHz PSD reference Level



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11aN20

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11a/N20

Test Channel : 06


100kHz PSD reference Level



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11aN20

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11aN40

Test Channel : 03


100kHz PSD reference Level




Channel 03 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11aN40

Test Channel : 06


100kHz PSD reference Level



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11aN40

Test Channel : 09


100kHz PSD reference Level




Channel 09 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ax20_FullIRU

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ax20_FullIRU

Test Channel : 06


100kHz PSD reference Level



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11ax20_FullIRU

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	21.1~23.3℃
		Relative Humidity :	43.7~53.9%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

542702
Mode 1
Power from system
Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.150000	---	36.77	56.00	19.23	L1	FLO	20.0
0.150000	53.55	---	66.00	12.45	L1	FLO	20.0
0.179700	---	31.33	54.50	23.17	L1	FLO	20.0
0.179700	46.61	---	64.50	17.89	L1	FLO	20.0
0.201750	---	29.38	53.54	24.16	L1	FLO	20.0
0.201750	44.21	---	63.54	19.33	L1	FLO	20.0
0.253500	---	23.18	51.64	28.46	L1	FLO	20.0
0.253500	35.36	---	61.64	26.28	L1	FLO	20.0
0.420000	---	33.41	47.45	14.04	L1	FLO	20.0
0.420000	40.17	---	57.45	17.28	L1	FLO	20.0
0.469500	---	26.94	46.52	19.58	L1	FLO	20.0
0.469500	32.98	---	56.52	23.54	L1	FLO	20.0
1.952070	---	22.21	46.00	23.79	L1	FLO	20.1
1.952070	28.85	---	56.00	27.15	L1	FLO	20.1
4.236990	---	17.14	46.00	28.86	L1	FLO	20.1
4.236990	23.68	---	56.00	32.32	L1	FLO	20.1
15.836640	---	28.43	50.00	21.57	L1	FLO	20.6
15.836640	33.20	---	60.00	26.80	L1	FLO	20.6

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

542702
Mode 1
Power from system
Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.152633	---	38.12	55.86	17.74	N	FLO	20.0
0.152633	54.12	---	65.86	11.74	N	FLO	20.0
0.170250	---	30.13	54.95	24.82	N	FLO	20.0
0.170250	47.38	---	64.95	17.57	N	FLO	20.0
0.190500	---	30.76	54.02	23.26	N	FLO	20.0
0.190500	45.17	---	64.02	18.85	N	FLO	20.0
0.226410	---	25.05	52.58	27.53	N	FLO	20.0
0.226410	38.99	---	62.58	23.59	N	FLO	20.0
0.419280	---	33.50	47.46	13.96	N	FLO	20.0
0.419280	40.49	---	57.46	16.97	N	FLO	20.0
0.471570	---	27.94	46.49	18.55	N	FLO	20.0
0.471570	35.44	---	56.49	21.05	N	FLO	20.0
1.981500	---	21.53	46.00	24.47	N	FLO	20.0
1.981500	27.97	---	56.00	28.03	N	FLO	20.0
3.903000	---	17.86	46.00	28.14	N	FLO	20.1
3.903000	25.37	---	56.00	30.63	N	FLO	20.1
16.459440	---	28.38	50.00	21.62	N	FLO	20.7
16.459440	33.43	---	60.00	26.57	N	FLO	20.7



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Ken Kuo and York Huang	Temperature :	19.8~23.5°C
		Relative Humidity :	57.7~63.5%

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	802.11b	01	2412	1Mbps	-	-
Mode 2	2400-2483.5	1	802.11b	06	2437	1Mbps	-	-
Mode 3	2400-2483.5	1	802.11b	11	2462	1Mbps	-	-
Mode 4	2400-2483.5	1	802.11g	01	2412	6Mbps	-	-
Mode 5	2400-2483.5	1	802.11g	06	2437	6Mbps	-	-
Mode 6	2400-2483.5	1	802.11g	11	2462	6Mbps	-	-
Mode 7	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Full RU	-
Mode 8	2400-2483.5	1	802.11ax HE20	06	2437	MCS0	Full RU	-
Mode 9	2400-2483.5	1	802.11ax HE20	11	2462	MCS0	Full RU	-
Mode 10	2400-2483.5	1	802.11ax HE20	1	2412	MCS0	106 RU	-
Mode 11	2400-2483.5	1	802.11n HT40	03	2422	MCS0	-	-

**FCC RADIO TEST REPORT**

Report No. : FR542702C

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 12	2400-2483.5	1	802.11n HT40	06	2437	MCS0	-	-
Mode 13	2400-2483.5	1	802.11n HT40	09	2452	MCS0	-	-
Mode 14	2400-2483.5	1	802.11n HT20	01	2412	MCS0	-	-
Mode 15	2400-2483.5	1	802.11ax HE20	01	2412	MCS0	Full RU	LF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	802.11b	01	2334.83	49.42	54.00	-4.58	H	Avg.	Pass	-	Band Edge
	802.11b	01	4824.00	50.77	54.00	-3.23	V	Avg.	Pass	-	Harmonic
2	802.11b	06	2359.78	49.60	54.00	-4.40	H	Avg.	Pass	-	Band Edge
	802.11b	06	4874.00	49.15	54.00	-4.85	V	Avg.	Pass	-	Harmonic
3	802.11b	11	2483.58	42.48	54.00	-11.52	H	Avg.	Pass	-	Band Edge
	802.11b	11	2382.00	48.37	54.00	-5.63	H	Avg.	Pass	-	Harmonic
4	802.11g	01	2389.95	49.35	54.00	-4.65	V	Avg.	Pass	-	Band Edge
	802.11g	01	2646.00	47.72	54.00	-6.28	V	Avg.	Pass	-	Harmonic
5	802.11g	06	2389.88	43.31	54.00	-10.69	H	Avg.	Pass	-	Band Edge
	802.11g	06	2670.00	47.36	54.00	-6.64	H	Avg.	Pass	-	Harmonic
6	802.11g	11	2483.58	39.48	54.00	-14.52	H	Avg.	Pass	-	Band Edge



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
6	802.11g	11	2696.00	46.35	54.00	-7.65	H	Avg.	Pass	-	Harmonic
7	802.11ax HE20	01	2389.82	50.94	54.00	-3.06	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	01	2651.00	47.96	54.00	-6.04	H	Avg.	Pass	Full RU	Harmonic
8	802.11ax HE20	06	2388.99	45.16	54.00	-8.84	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	06	2686.00	47.87	54.00	-6.13	H	Avg.	Pass	Full RU	Harmonic
9	802.11ax HE20	11	2484.31	42.26	54.00	-11.74	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	11	2704.00	47.50	54.00	-6.50	H	Avg.	Pass	Full RU	Harmonic
10	802.11ax HE20	1	2389.95	50.02	54.00	-3.98	V	Avg.	Pass	106 RU	Band Edge
	802.11ax HE20	1	2651.00	48.34	54.00	-5.66	H	Avg.	Pass	106 RU	Harmonic
11	802.11n HT40	03	2389.97	47.79	54.00	-6.21	H	Avg.	Pass	-	Band Edge
	802.11n HT40	03	2661.00	49.82	54.00	-4.18	H	Avg.	Pass	-	Harmonic

X1.Summary of each worse mode

**FCC RADIO TEST REPORT**





Report No. : FR542702C

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
12	802.11n HT40	06	2493.07	47.97	54.00	-6.03	H	Avg.	Pass	-	Band Edge
	802.11n HT40	06	2676.00	49.33	54.00	-4.67	H	Avg.	Pass	-	Harmonic
13	802.11n HT40	09	2484.30	42.67	54.00	-11.33	H	Avg.	Pass	-	Band Edge
	802.11n HT40	09	2230.00	49.71	54.00	-4.29	H	Avg.	Pass	-	Harmonic
14	802.11n HT20	01	2389.95	50.90	54.00	-3.10	H	Avg.	Pass	-	Band Edge
	802.11n HT20	01	2651.00	48.16	54.00	-5.84	H	Avg.	Pass	-	Harmonic
15	802.11ax HE20	01	800.18	35.92	46.00	-10.08	H	QP	Pass	-	LF



FCC RADIO TEST REPORT

Report No. : FR542702C

Mode	1																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-06-19  Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2334.44</td><td>54.91</td><td>74.00</td><td>-19.09</td><td>43.24</td><td>26.81</td><td>7.98</td><td>32.55</td><td>9.43</td><td>100</td><td>164</td><td>Peak</td></tr></tbody></table> Level (dBuV/m) Date: 2025-06-19  Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>106.21</td><td>-----</td><td>-----</td><td>94.48</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>100</td><td>164</td><td>Peak</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2334.44	54.91	74.00	-19.09	43.24	26.81	7.98	32.55	9.43	100	164	Peak		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	106.21	-----	-----	94.48	26.80	8.09	32.60	9.44	100	164	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2334.44	54.91	74.00	-19.09	43.24	26.81	7.98	32.55	9.43	100	164	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2412.00	106.21	-----	-----	94.48	26.80	8.09	32.60	9.44	100	164	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-06-19  Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2334.83</td><td>49.42</td><td>54.00</td><td>-4.58</td><td>37.76</td><td>26.80</td><td>7.98</td><td>32.55</td><td>9.43</td><td>100</td><td>164</td><td>Average</td></tr></tbody></table> Level (dBuV/m) Date: 2025-06-19  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>102.93</td><td>-----</td><td>-----</td><td>91.20</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>100</td><td>164</td><td>Average</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2334.83	49.42	54.00	-4.58	37.76	26.80	7.98	32.55	9.43	100	164	Average		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	102.93	-----	-----	91.20	26.80	8.09	32.60	9.44	100	164	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2334.83	49.42	54.00	-4.58	37.76	26.80	7.98	32.55	9.43	100	164	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2412.00	102.93	-----	-----	91.20	26.80	8.09	32.60	9.44	100	164	Average																																																																																								



Mode	1																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11b_CH01_2412MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-06-19 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 231023362362238824142440 Frequency (MHz) Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2334.70</td><td>54.37</td><td>74.00</td><td>-19.63</td><td>42.70</td><td>26.81</td><td>7.98</td><td>32.55</td><td>9.43</td><td>400</td><td>98</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2334.70	54.37	74.00	-19.63	42.70	26.81	7.98	32.55	9.43	400	98	Peak	Level (dBuV/m) Date: 2025-06-19 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 100014001800220026003000 Frequency (MHz) Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>101.56</td><td>-----</td><td>-----</td><td>89.83</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>400</td><td>98</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	101.56	-----	-----	89.83	26.80	8.09	32.60	9.44	400	98	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2334.70	54.37	74.00	-19.63	42.70	26.81	7.98	32.55	9.43	400	98	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	101.56	-----	-----	89.83	26.80	8.09	32.60	9.44	400	98	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-06-19 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 231023362362238824142440 Frequency (MHz) Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2329.37</td><td>48.27</td><td>54.00</td><td>-5.73</td><td>36.52</td><td>26.90</td><td>7.97</td><td>32.55</td><td>9.43</td><td>400</td><td>98</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2329.37	48.27	54.00	-5.73	36.52	26.90	7.97	32.55	9.43	400	98	Average	Level (dBuV/m) Date: 2025-06-19 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 100014001800220026003000 Frequency (MHz) Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2412.00</td><td>98.31</td><td>-----</td><td>-----</td><td>86.57</td><td>26.80</td><td>8.10</td><td>32.60</td><td>9.44</td><td>400</td><td>98</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2412.00	98.31	-----	-----	86.57	26.80	8.10	32.60	9.44	400	98	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2329.37	48.27	54.00	-5.73	36.52	26.90	7.97	32.55	9.43	400	98	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2412.00	98.31	-----	-----	86.57	26.80	8.10	32.60	9.44	400	98	Average																																																																														



Mode	1																																																																																																																																																																																																																																																																																									
	Harmonic																																																																																																																																																																																																																																																																																									
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																																																																																																																																																																																																									
ANT	1																																																																																																																																																																																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																																																																																																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2168.00</td><td>51.53</td><td>74.00</td><td>-22.47</td><td>40.44</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>147</td><td>168</td><td>Peak</td><td></td></tr><tr><td>2</td><td>2168.00</td><td>44.52</td><td>54.00</td><td>-9.48</td><td>33.43</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>147</td><td>168</td><td>Average</td><td></td></tr><tr><td>3</td><td>2330.00</td><td>54.98</td><td>74.00</td><td>-19.02</td><td>43.23</td><td>26.90</td><td>7.97</td><td>32.55</td><td>9.43</td><td>125</td><td>163</td><td>Peak</td><td></td></tr><tr><td>4</td><td>2330.00</td><td>49.06</td><td>54.00</td><td>-4.94</td><td>37.31</td><td>26.90</td><td>7.97</td><td>32.55</td><td>9.43</td><td>125</td><td>163</td><td>Average</td><td></td></tr><tr><td>5</td><td>2654.00</td><td>52.54</td><td>74.00</td><td>-21.46</td><td>39.92</td><td>27.46</td><td>8.35</td><td>32.68</td><td>9.49</td><td>115</td><td>171</td><td>Peak</td><td></td></tr><tr><td>6</td><td>2654.00</td><td>48.12</td><td>54.00</td><td>-5.88</td><td>35.50</td><td>27.46</td><td>8.35</td><td>32.68</td><td>9.49</td><td>115</td><td>171</td><td>Average</td><td></td></tr><tr><td>7</td><td>4824.00</td><td>50.46</td><td>74.00</td><td>-23.54</td><td>39.03</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>100</td><td>146</td><td>Peak</td><td></td></tr><tr><td>8</td><td>4824.00</td><td>46.77</td><td>54.00</td><td>-7.23</td><td>35.34</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>100</td><td>146</td><td>Average</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	2168.00	51.53	74.00	-22.47	40.44	26.40	7.71	32.44	9.42	147	168	Peak		2	2168.00	44.52	54.00	-9.48	33.43	26.40	7.71	32.44	9.42	147	168	Average		3	2330.00	54.98	74.00	-19.02	43.23	26.90	7.97	32.55	9.43	125	163	Peak		4	2330.00	49.06	54.00	-4.94	37.31	26.90	7.97	32.55	9.43	125	163	Average		5	2654.00	52.54	74.00	-21.46	39.92	27.46	8.35	32.68	9.49	115	171	Peak		6	2654.00	48.12	54.00	-5.88	35.50	27.46	8.35	32.68	9.49	115	171	Average		7	4824.00	50.46	74.00	-23.54	39.03	32.20	11.53	33.67	1.37	100	146	Peak		8	4824.00	46.77	54.00	-7.23	35.34	32.20	11.53	33.67	1.37	100	146	Average		Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2170.00</td><td>48.29</td><td>74.00</td><td>-25.71</td><td>37.19</td><td>26.40</td><td>7.72</td><td>32.44</td><td>9.42</td><td>145</td><td>156</td><td>Peak</td><td></td></tr><tr><td>2</td><td>2170.00</td><td>37.79</td><td>54.00</td><td>-16.21</td><td>26.69</td><td>26.40</td><td>7.72</td><td>32.44</td><td>9.42</td><td>145</td><td>156</td><td>Average</td><td></td></tr><tr><td>3</td><td>2336.00</td><td>53.52</td><td>74.00</td><td>-20.48</td><td>41.88</td><td>26.78</td><td>7.98</td><td>32.55</td><td>9.43</td><td>400</td><td>98</td><td>Peak</td><td></td></tr><tr><td>4</td><td>2336.00</td><td>46.93</td><td>54.00</td><td>-7.07</td><td>35.29</td><td>26.78</td><td>7.98</td><td>32.55</td><td>9.43</td><td>400</td><td>98</td><td>Average</td><td></td></tr><tr><td>5</td><td>2654.00</td><td>52.87</td><td>74.00</td><td>-21.13</td><td>40.25</td><td>27.46</td><td>8.35</td><td>32.68</td><td>9.49</td><td>307</td><td>107</td><td>Peak</td><td></td></tr><tr><td>6</td><td>2654.00</td><td>47.26</td><td>54.00</td><td>-6.74</td><td>34.64</td><td>27.46</td><td>8.35</td><td>32.68</td><td>9.49</td><td>307</td><td>107</td><td>Average</td><td></td></tr><tr><td>7</td><td>4824.00</td><td>53.15</td><td>74.00</td><td>-20.85</td><td>41.72</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>300</td><td>175</td><td>Peak</td><td></td></tr><tr><td>8</td><td>4824.00</td><td>50.77</td><td>54.00</td><td>-3.23</td><td>39.34</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>300</td><td>175</td><td>Average</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	2170.00	48.29	74.00	-25.71	37.19	26.40	7.72	32.44	9.42	145	156	Peak		2	2170.00	37.79	54.00	-16.21	26.69	26.40	7.72	32.44	9.42	145	156	Average		3	2336.00	53.52	74.00	-20.48	41.88	26.78	7.98	32.55	9.43	400	98	Peak		4	2336.00	46.93	54.00	-7.07	35.29	26.78	7.98	32.55	9.43	400	98	Average		5	2654.00	52.87	74.00	-21.13	40.25	27.46	8.35	32.68	9.49	307	107	Peak		6	2654.00	47.26	54.00	-6.74	34.64	27.46	8.35	32.68	9.49	307	107	Average		7	4824.00	53.15	74.00	-20.85	41.72	32.20	11.53	33.67	1.37	300	175	Peak		8	4824.00	50.77	54.00	-3.23	39.34	32.20	11.53	33.67	1.37	300	175	Average	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																														
1	2168.00	51.53	74.00	-22.47	40.44	26.40	7.71	32.44	9.42	147	168	Peak																																																																																																																																																																																																																																																																														
2	2168.00	44.52	54.00	-9.48	33.43	26.40	7.71	32.44	9.42	147	168	Average																																																																																																																																																																																																																																																																														
3	2330.00	54.98	74.00	-19.02	43.23	26.90	7.97	32.55	9.43	125	163	Peak																																																																																																																																																																																																																																																																														
4	2330.00	49.06	54.00	-4.94	37.31	26.90	7.97	32.55	9.43	125	163	Average																																																																																																																																																																																																																																																																														
5	2654.00	52.54	74.00	-21.46	39.92	27.46	8.35	32.68	9.49	115	171	Peak																																																																																																																																																																																																																																																																														
6	2654.00	48.12	54.00	-5.88	35.50	27.46	8.35	32.68	9.49	115	171	Average																																																																																																																																																																																																																																																																														
7	4824.00	50.46	74.00	-23.54	39.03	32.20	11.53	33.67	1.37	100	146	Peak																																																																																																																																																																																																																																																																														
8	4824.00	46.77	54.00	-7.23	35.34	32.20	11.53	33.67	1.37	100	146	Average																																																																																																																																																																																																																																																																														
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																														
1	2170.00	48.29	74.00	-25.71	37.19	26.40	7.72	32.44	9.42	145	156	Peak																																																																																																																																																																																																																																																																														
2	2170.00	37.79	54.00	-16.21	26.69	26.40	7.72	32.44	9.42	145	156	Average																																																																																																																																																																																																																																																																														
3	2336.00	53.52	74.00	-20.48	41.88	26.78	7.98	32.55	9.43	400	98	Peak																																																																																																																																																																																																																																																																														
4	2336.00	46.93	54.00	-7.07	35.29	26.78	7.98	32.55	9.43	400	98	Average																																																																																																																																																																																																																																																																														
5	2654.00	52.87	74.00	-21.13	40.25	27.46	8.35	32.68	9.49	307	107	Peak																																																																																																																																																																																																																																																																														
6	2654.00	47.26	54.00	-6.74	34.64	27.46	8.35	32.68	9.49	307	107	Average																																																																																																																																																																																																																																																																														
7	4824.00	53.15	74.00	-20.85	41.72	32.20	11.53	33.67	1.37	300	175	Peak																																																																																																																																																																																																																																																																														
8	4824.00	50.77	54.00	-3.23	39.34	32.20	11.53	33.67	1.37	300	175	Average																																																																																																																																																																																																																																																																														



Mode	2																																																																									
	Band Edge - L																																																																									
	2400-2483.5_802.11b_CH06_2437MHz																																																																									
ANT	1																																																																									
Pol.	Horizontal	Fundamental																																																																								
Peak	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2359.66 55.45 74.00 -18.55 43.67 26.90 8.02 32.57 9.43 116 162</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2359.66 55.45 74.00 -18.55 43.67 26.90 8.02 32.57 9.43 116 162	Peak								Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2437.00 106.19 ----- 94.58 26.66 8.12 32.62 9.45 116 162</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2437.00 106.19 ----- 94.58 26.66 8.12 32.62 9.45 116 162	Peak							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																										
1 2359.66 55.45 74.00 -18.55 43.67 26.90 8.02 32.57 9.43 116 162	Peak																																																																									
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																										
1 2437.00 106.19 ----- 94.58 26.66 8.12 32.62 9.45 116 162	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2359.78 49.60 54.00 -4.40 37.82 26.90 8.02 32.57 9.43 116 162</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2359.78 49.60 54.00 -4.40 37.82 26.90 8.02 32.57 9.43 116 162	Average								Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dB dBuV dB/m dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2437.00 103.11 ----- 91.45 26.70 8.13 32.62 9.45 116 162</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dB dBuV dB/m dB dB dB cm deg									1 2437.00 103.11 ----- 91.45 26.70 8.13 32.62 9.45 116 162	Average							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																										
1 2359.78 49.60 54.00 -4.40 37.82 26.90 8.02 32.57 9.43 116 162	Average																																																																									
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dB dBuV dB/m dB dB dB cm deg																																																																										
1 2437.00 103.11 ----- 91.45 26.70 8.13 32.62 9.45 116 162	Average																																																																									



Mode	2										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Horizontal						Fundamental				
Peak											



Mode	2																																																																																																	
	Band Edge - L																																																																																																	
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2359.02</td><td>53.36</td><td>74.00</td><td>-20.64</td><td>41.59</td><td>26.89</td><td>8.02</td><td>32.57</td><td>9.43</td><td>300</td><td>115 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2359.02	53.36	74.00	-20.64	41.59	26.89	8.02	32.57	9.43	300	115 Peak	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>101.03</td><td>-----</td><td>-----</td><td>89.44</td><td>26.64</td><td>8.12</td><td>32.62</td><td>9.45</td><td>300</td><td>115 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	101.03	-----	-----	89.44	26.64	8.12	32.62	9.45	300	115 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2359.02	53.36	74.00	-20.64	41.59	26.89	8.02	32.57	9.43	300	115 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2437.00	101.03	-----	-----	89.44	26.64	8.12	32.62	9.45	300	115 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2359.66</td><td>46.50</td><td>54.00</td><td>-7.50</td><td>34.72</td><td>26.90</td><td>8.02</td><td>32.57</td><td>9.43</td><td>300</td><td>115 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2359.66	46.50	54.00	-7.50	34.72	26.90	8.02	32.57	9.43	300	115 Average	Level (dBuV/m) Date: 2025-06-20 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>97.72</td><td>-----</td><td>-----</td><td>86.11</td><td>26.66</td><td>8.12</td><td>32.62</td><td>9.45</td><td>300</td><td>115 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	97.72	-----	-----	86.11	26.66	8.12	32.62	9.45	300	115 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2359.66	46.50	54.00	-7.50	34.72	26.90	8.02	32.57	9.43	300	115 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2437.00	97.72	-----	-----	86.11	26.66	8.12	32.62	9.45	300	115 Average																																																																																							



Mode	2										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Vertical						Fundamental				
Peak											



Mode	2																																																																																																																																																																																																																													
	Harmonic																																																																																																																																																																																																																													
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																																																																																																																													
ANT	1																																																																																																																																																																																																																													
Pol.	Horizontal	Vertical																																																																																																																																																																																																																												
Peak Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2202.00</td><td>52.36</td><td>74.00</td><td>-21.64</td><td>41.12</td><td>26.52</td><td>7.77</td><td>32.46</td><td>9.41</td><td>109 168 Peak</td></tr><tr><td>2 2202.00</td><td>45.81</td><td>54.00</td><td>-8.19</td><td>34.57</td><td>26.52</td><td>7.77</td><td>32.46</td><td>9.41</td><td>109 168 Average</td></tr><tr><td>3 2678.00</td><td>52.54</td><td>74.00</td><td>-21.46</td><td>39.87</td><td>27.48</td><td>8.38</td><td>32.68</td><td>9.49</td><td>114 170 Peak</td></tr><tr><td>4 2678.00</td><td>47.74</td><td>54.00</td><td>-6.26</td><td>35.07</td><td>27.48</td><td>8.38</td><td>32.68</td><td>9.49</td><td>114 170 Average</td></tr><tr><td>5 4874.00</td><td>49.71</td><td>74.00</td><td>-24.29</td><td>38.22</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>102 210 Peak</td></tr><tr><td>6 4874.00</td><td>45.82</td><td>54.00</td><td>-8.18</td><td>34.33</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>102 210 Average</td></tr><tr><td>7 7311.00</td><td>51.88</td><td>74.00</td><td>-22.12</td><td>35.99</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>100 123 Peak</td></tr><tr><td>8 7311.00</td><td>45.03</td><td>54.00</td><td>-8.97</td><td>29.14</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>100 123 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2202.00	52.36	74.00	-21.64	41.12	26.52	7.77	32.46	9.41	109 168 Peak	2 2202.00	45.81	54.00	-8.19	34.57	26.52	7.77	32.46	9.41	109 168 Average	3 2678.00	52.54	74.00	-21.46	39.87	27.48	8.38	32.68	9.49	114 170 Peak	4 2678.00	47.74	54.00	-6.26	35.07	27.48	8.38	32.68	9.49	114 170 Average	5 4874.00	49.71	74.00	-24.29	38.22	32.30	11.60	33.67	1.26	102 210 Peak	6 4874.00	45.82	54.00	-8.18	34.33	32.30	11.60	33.67	1.26	102 210 Average	7 7311.00	51.88	74.00	-22.12	35.99	37.20	14.28	36.59	1.00	100 123 Peak	8 7311.00	45.03	54.00	-8.97	29.14	37.20	14.28	36.59	1.00	100 123 Average	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2202.00</td><td>50.80</td><td>74.00</td><td>-23.20</td><td>39.56</td><td>26.52</td><td>7.77</td><td>32.46</td><td>9.41</td><td>128 156 Peak</td></tr><tr><td>2 2202.00</td><td>43.21</td><td>54.00</td><td>-10.79</td><td>31.97</td><td>26.52</td><td>7.77</td><td>32.46</td><td>9.41</td><td>128 156 Average</td></tr><tr><td>3 2674.00</td><td>52.40</td><td>74.00</td><td>-21.60</td><td>39.77</td><td>27.44</td><td>8.38</td><td>32.68</td><td>9.49</td><td>335 107 Peak</td></tr><tr><td>4 2674.00</td><td>46.69</td><td>54.00</td><td>-7.31</td><td>34.06</td><td>27.44</td><td>8.38</td><td>32.68</td><td>9.49</td><td>335 107 Average</td></tr><tr><td>5 4874.00</td><td>52.09</td><td>74.00</td><td>-21.91</td><td>40.60</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>281 192 Peak</td></tr><tr><td>6 4874.00</td><td>49.15</td><td>54.00</td><td>-4.85</td><td>37.66</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>281 192 Average</td></tr><tr><td>7 7311.00</td><td>51.41</td><td>74.00</td><td>-22.59</td><td>35.52</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>363 168 Peak</td></tr><tr><td>8 7311.00</td><td>44.01</td><td>54.00</td><td>-9.99</td><td>28.12</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>363 168 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2202.00	50.80	74.00	-23.20	39.56	26.52	7.77	32.46	9.41	128 156 Peak	2 2202.00	43.21	54.00	-10.79	31.97	26.52	7.77	32.46	9.41	128 156 Average	3 2674.00	52.40	74.00	-21.60	39.77	27.44	8.38	32.68	9.49	335 107 Peak	4 2674.00	46.69	54.00	-7.31	34.06	27.44	8.38	32.68	9.49	335 107 Average	5 4874.00	52.09	74.00	-21.91	40.60	32.30	11.60	33.67	1.26	281 192 Peak	6 4874.00	49.15	54.00	-4.85	37.66	32.30	11.60	33.67	1.26	281 192 Average	7 7311.00	51.41	74.00	-22.59	35.52	37.20	14.28	36.59	1.00	363 168 Peak	8 7311.00	44.01	54.00	-9.99	28.12	37.20	14.28	36.59	1.00	363 168 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																				
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																					
1 2202.00	52.36	74.00	-21.64	41.12	26.52	7.77	32.46	9.41	109 168 Peak																																																																																																																																																																																																																					
2 2202.00	45.81	54.00	-8.19	34.57	26.52	7.77	32.46	9.41	109 168 Average																																																																																																																																																																																																																					
3 2678.00	52.54	74.00	-21.46	39.87	27.48	8.38	32.68	9.49	114 170 Peak																																																																																																																																																																																																																					
4 2678.00	47.74	54.00	-6.26	35.07	27.48	8.38	32.68	9.49	114 170 Average																																																																																																																																																																																																																					
5 4874.00	49.71	74.00	-24.29	38.22	32.30	11.60	33.67	1.26	102 210 Peak																																																																																																																																																																																																																					
6 4874.00	45.82	54.00	-8.18	34.33	32.30	11.60	33.67	1.26	102 210 Average																																																																																																																																																																																																																					
7 7311.00	51.88	74.00	-22.12	35.99	37.20	14.28	36.59	1.00	100 123 Peak																																																																																																																																																																																																																					
8 7311.00	45.03	54.00	-8.97	29.14	37.20	14.28	36.59	1.00	100 123 Average																																																																																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																					
1 2202.00	50.80	74.00	-23.20	39.56	26.52	7.77	32.46	9.41	128 156 Peak																																																																																																																																																																																																																					
2 2202.00	43.21	54.00	-10.79	31.97	26.52	7.77	32.46	9.41	128 156 Average																																																																																																																																																																																																																					
3 2674.00	52.40	74.00	-21.60	39.77	27.44	8.38	32.68	9.49	335 107 Peak																																																																																																																																																																																																																					
4 2674.00	46.69	54.00	-7.31	34.06	27.44	8.38	32.68	9.49	335 107 Average																																																																																																																																																																																																																					
5 4874.00	52.09	74.00	-21.91	40.60	32.30	11.60	33.67	1.26	281 192 Peak																																																																																																																																																																																																																					
6 4874.00	49.15	54.00	-4.85	37.66	32.30	11.60	33.67	1.26	281 192 Average																																																																																																																																																																																																																					
7 7311.00	51.41	74.00	-22.59	35.52	37.20	14.28	36.59	1.00	363 168 Peak																																																																																																																																																																																																																					
8 7311.00	44.01	54.00	-9.99	28.12	37.20	14.28	36.59	1.00	363 168 Average																																																																																																																																																																																																																					



Mode	3																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH11_2462MHz																																																																																	
ANT	1																																																																																	
Pol.	Horizontal					Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2484.23 51.15 74.00 -22.85 39.42 26.74 8.18 32.65 9.46 100 163</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg									1 2484.23 51.15 74.00 -22.85 39.42 26.74 8.18 32.65 9.46 100 163	Peak								Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2462.00 102.34 ----- 90.67 26.70 8.15 32.63 9.45 100 163</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg									1 2462.00 102.34 ----- 90.67 26.70 8.15 32.63 9.45 100 163	Peak							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg																																																																																		
1 2484.23 51.15 74.00 -22.85 39.42 26.74 8.18 32.65 9.46 100 163	Peak																																																																																	
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg																																																																																		
1 2462.00 102.34 ----- 90.67 26.70 8.15 32.63 9.45 100 163	Peak																																																																																	
Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2483.58 42.48 54.00 -11.52 30.75 26.74 8.18 32.65 9.46 100 163</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg									1 2483.58 42.48 54.00 -11.52 30.75 26.74 8.18 32.65 9.46 100 163	Average								Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2462.00 99.07 ----- 87.40 26.70 8.15 32.63 9.45 100 163</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg									1 2462.00 99.07 ----- 87.40 26.70 8.15 32.63 9.45 100 163	Average							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg																																																																																		
1 2483.58 42.48 54.00 -11.52 30.75 26.74 8.18 32.65 9.46 100 163	Average																																																																																	
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq Level Line Margin Level Factor Loss Factor Factor																																																																																		
MHz dBuV/m dBuV/m dB dB/dB dB dB dB cm deg																																																																																		
1 2462.00 99.07 ----- 87.40 26.70 8.15 32.63 9.45 100 163	Average																																																																																	



Mode	3																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH11_2462MHz																																																																																	
ANT	1																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2499.39</td><td>51.42</td><td>74.00</td><td>-22.58</td><td>39.62</td><td>26.00</td><td>8.20</td><td>32.66</td><td>9.46</td><td>200 182 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg	1 2499.39	51.42	74.00	-22.58	39.62	26.00	8.20	32.66	9.46	200 182 Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2462.00</td><td>100.10</td><td>-----</td><td>-----</td><td>88.43</td><td>26.70</td><td>8.15</td><td>32.63</td><td>9.45</td><td>200 182 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg	1 2462.00	100.10	-----	-----	88.43	26.70	8.15	32.63	9.45	200 182 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg																																																																									
1 2499.39	51.42	74.00	-22.58	39.62	26.00	8.20	32.66	9.46	200 182 Peak																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg																																																																									
1 2462.00	100.10	-----	-----	88.43	26.70	8.15	32.63	9.45	200 182 Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2483.55</td><td>42.11</td><td>54.00</td><td>-11.89</td><td>30.38</td><td>26.74</td><td>8.18</td><td>32.65</td><td>9.46</td><td>200 182 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg	1 2483.55	42.11	54.00	-11.89	30.38	26.74	8.18	32.65	9.46	200 182 Average	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:2.400kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2462.00</td><td>96.87</td><td>-----</td><td>-----</td><td>85.23</td><td>26.66</td><td>8.16</td><td>32.64</td><td>9.46</td><td>200 182 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg	1 2462.00	96.87	-----	-----	85.23	26.66	8.16	32.64	9.46	200 182 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg																																																																									
1 2483.55	42.11	54.00	-11.89	30.38	26.74	8.18	32.65	9.46	200 182 Average																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	cm deg																																																																									
1 2462.00	96.87	-----	-----	85.23	26.66	8.16	32.64	9.46	200 182 Average																																																																									



Mode	3																																																																																																																																																																																																																																																																					
	Harmonic																																																																																																																																																																																																																																																																					
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																																																																																																																																																																																					
ANT	1																																																																																																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																																																																																																				
Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2218.00</td><td>53.82</td><td>74.00</td><td>-20.18</td><td>42.48</td><td>26.60</td><td>7.80</td><td>32.47</td><td>9.41</td><td>106 167 Peak</td></tr><tr><td>2 2218.00</td><td>47.39</td><td>54.00</td><td>-6.61</td><td>36.05</td><td>26.60</td><td>7.80</td><td>32.47</td><td>9.41</td><td>106 167 Average</td></tr><tr><td>3 2382.00</td><td>54.60</td><td>74.00</td><td>-19.40</td><td>43.01</td><td>26.60</td><td>8.05</td><td>32.58</td><td>9.44</td><td>167 162 Peak</td></tr><tr><td>4 2382.00</td><td>48.37</td><td>54.00</td><td>-5.63</td><td>36.78</td><td>26.60</td><td>8.05</td><td>32.58</td><td>9.44</td><td>167 162 Average</td></tr><tr><td>5 2704.00</td><td>53.13</td><td>74.00</td><td>-20.87</td><td>40.42</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>110 170 Peak</td></tr><tr><td>6 2704.00</td><td>48.07</td><td>54.00</td><td>-5.93</td><td>35.36</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>110 170 Average</td></tr><tr><td>7 4924.00</td><td>48.91</td><td>74.00</td><td>-25.09</td><td>37.26</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>120 145 Peak</td></tr><tr><td>8 4924.00</td><td>45.54</td><td>54.00</td><td>-8.46</td><td>33.89</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>120 145 Average</td></tr><tr><td>9 7386.00</td><td>49.04</td><td>74.00</td><td>-24.96</td><td>33.31</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>-- -- Peak</td></tr><tr><td>10 7386.00</td><td>40.01</td><td>54.00</td><td>-13.99</td><td>24.28</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2218.00	53.82	74.00	-20.18	42.48	26.60	7.80	32.47	9.41	106 167 Peak	2 2218.00	47.39	54.00	-6.61	36.05	26.60	7.80	32.47	9.41	106 167 Average	3 2382.00	54.60	74.00	-19.40	43.01	26.60	8.05	32.58	9.44	167 162 Peak	4 2382.00	48.37	54.00	-5.63	36.78	26.60	8.05	32.58	9.44	167 162 Average	5 2704.00	53.13	74.00	-20.87	40.42	27.50	8.42	32.69	9.48	110 170 Peak	6 2704.00	48.07	54.00	-5.93	35.36	27.50	8.42	32.69	9.48	110 170 Average	7 4924.00	48.91	74.00	-25.09	37.26	32.50	11.67	33.67	1.15	120 145 Peak	8 4924.00	45.54	54.00	-8.46	33.89	32.50	11.67	33.67	1.15	120 145 Average	9 7386.00	49.04	74.00	-24.96	33.31	37.13	14.28	36.71	1.03	-- -- Peak	10 7386.00	40.01	54.00	-13.99	24.28	37.13	14.28	36.71	1.03	-- -- Average	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2220.00</td><td>51.26</td><td>74.00</td><td>-22.74</td><td>39.93</td><td>26.60</td><td>7.80</td><td>32.48</td><td>9.41</td><td>122 192 Peak</td></tr><tr><td>2 2220.00</td><td>44.36</td><td>54.00</td><td>-9.64</td><td>33.03</td><td>26.60</td><td>7.80</td><td>32.48</td><td>9.41</td><td>122 192 Average</td></tr><tr><td>3 2386.00</td><td>52.63</td><td>74.00</td><td>-21.37</td><td>41.07</td><td>26.64</td><td>8.06</td><td>32.58</td><td>9.44</td><td>143 187 Peak</td></tr><tr><td>4 2386.00</td><td>45.81</td><td>54.00</td><td>-8.19</td><td>34.25</td><td>26.64</td><td>8.06</td><td>32.58</td><td>9.44</td><td>143 187 Average</td></tr><tr><td>5 2704.00</td><td>52.55</td><td>74.00</td><td>-21.45</td><td>39.84</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>292 106 Peak</td></tr><tr><td>6 2704.00</td><td>47.26</td><td>54.00</td><td>-6.74</td><td>34.55</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>292 106 Average</td></tr><tr><td>7 4924.00</td><td>51.31</td><td>74.00</td><td>-22.69</td><td>39.66</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>273 192 Peak</td></tr><tr><td>8 4924.00</td><td>48.16</td><td>54.00</td><td>-5.84</td><td>36.51</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>273 192 Average</td></tr><tr><td>9 7386.00</td><td>48.91</td><td>74.00</td><td>-25.09</td><td>33.18</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>-- -- Peak</td></tr><tr><td>10 7386.00</td><td>39.88</td><td>54.00</td><td>-14.12</td><td>24.15</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2220.00	51.26	74.00	-22.74	39.93	26.60	7.80	32.48	9.41	122 192 Peak	2 2220.00	44.36	54.00	-9.64	33.03	26.60	7.80	32.48	9.41	122 192 Average	3 2386.00	52.63	74.00	-21.37	41.07	26.64	8.06	32.58	9.44	143 187 Peak	4 2386.00	45.81	54.00	-8.19	34.25	26.64	8.06	32.58	9.44	143 187 Average	5 2704.00	52.55	74.00	-21.45	39.84	27.50	8.42	32.69	9.48	292 106 Peak	6 2704.00	47.26	54.00	-6.74	34.55	27.50	8.42	32.69	9.48	292 106 Average	7 4924.00	51.31	74.00	-22.69	39.66	32.50	11.67	33.67	1.15	273 192 Peak	8 4924.00	48.16	54.00	-5.84	36.51	32.50	11.67	33.67	1.15	273 192 Average	9 7386.00	48.91	74.00	-25.09	33.18	37.13	14.28	36.71	1.03	-- -- Peak	10 7386.00	39.88	54.00	-14.12	24.15	37.13	14.28	36.71	1.03	-- -- Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																																																													
1 2218.00	53.82	74.00	-20.18	42.48	26.60	7.80	32.47	9.41	106 167 Peak																																																																																																																																																																																																																																																													
2 2218.00	47.39	54.00	-6.61	36.05	26.60	7.80	32.47	9.41	106 167 Average																																																																																																																																																																																																																																																													
3 2382.00	54.60	74.00	-19.40	43.01	26.60	8.05	32.58	9.44	167 162 Peak																																																																																																																																																																																																																																																													
4 2382.00	48.37	54.00	-5.63	36.78	26.60	8.05	32.58	9.44	167 162 Average																																																																																																																																																																																																																																																													
5 2704.00	53.13	74.00	-20.87	40.42	27.50	8.42	32.69	9.48	110 170 Peak																																																																																																																																																																																																																																																													
6 2704.00	48.07	54.00	-5.93	35.36	27.50	8.42	32.69	9.48	110 170 Average																																																																																																																																																																																																																																																													
7 4924.00	48.91	74.00	-25.09	37.26	32.50	11.67	33.67	1.15	120 145 Peak																																																																																																																																																																																																																																																													
8 4924.00	45.54	54.00	-8.46	33.89	32.50	11.67	33.67	1.15	120 145 Average																																																																																																																																																																																																																																																													
9 7386.00	49.04	74.00	-24.96	33.31	37.13	14.28	36.71	1.03	-- -- Peak																																																																																																																																																																																																																																																													
10 7386.00	40.01	54.00	-13.99	24.28	37.13	14.28	36.71	1.03	-- -- Average																																																																																																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																																																													
1 2220.00	51.26	74.00	-22.74	39.93	26.60	7.80	32.48	9.41	122 192 Peak																																																																																																																																																																																																																																																													
2 2220.00	44.36	54.00	-9.64	33.03	26.60	7.80	32.48	9.41	122 192 Average																																																																																																																																																																																																																																																													
3 2386.00	52.63	74.00	-21.37	41.07	26.64	8.06	32.58	9.44	143 187 Peak																																																																																																																																																																																																																																																													
4 2386.00	45.81	54.00	-8.19	34.25	26.64	8.06	32.58	9.44	143 187 Average																																																																																																																																																																																																																																																													
5 2704.00	52.55	74.00	-21.45	39.84	27.50	8.42	32.69	9.48	292 106 Peak																																																																																																																																																																																																																																																													
6 2704.00	47.26	54.00	-6.74	34.55	27.50	8.42	32.69	9.48	292 106 Average																																																																																																																																																																																																																																																													
7 4924.00	51.31	74.00	-22.69	39.66	32.50	11.67	33.67	1.15	273 192 Peak																																																																																																																																																																																																																																																													
8 4924.00	48.16	54.00	-5.84	36.51	32.50	11.67	33.67	1.15	273 192 Average																																																																																																																																																																																																																																																													
9 7386.00	48.91	74.00	-25.09	33.18	37.13	14.28	36.71	1.03	-- -- Peak																																																																																																																																																																																																																																																													
10 7386.00	39.88	54.00	-14.12	24.15	37.13	14.28	36.71	1.03	-- -- Average																																																																																																																																																																																																																																																													
Avg																																																																																																																																																																																																																																																																						



Mode	4																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_802.11g_CH01_2412MHz																																																																																																			
ANT	1																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.78</td><td>58.86</td><td>74.00</td><td>-15.14</td><td>47.34</td><td>26.61</td><td>8.06</td><td>32.59</td><td>9.44</td><td>141</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.78	58.86	74.00	-15.14	47.34	26.61	8.06	32.59	9.44	141	360	Peak	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>105.88</td><td>-----</td><td>-----</td><td>94.15</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>141</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	105.88	-----	-----	94.15	26.80	8.09	32.60	9.44	141	360	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2388.78	58.86	74.00	-15.14	47.34	26.61	8.06	32.59	9.44	141	360	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2412.00	105.88	-----	-----	94.15	26.80	8.09	32.60	9.44	141	360	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>48.20</td><td>54.00</td><td>-5.80</td><td>36.69</td><td>26.60</td><td>8.06</td><td>32.59</td><td>9.44</td><td>141</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	48.20	54.00	-5.80	36.69	26.60	8.06	32.59	9.44	141	360	Average	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>98.04</td><td>-----</td><td>-----</td><td>86.31</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>141</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	98.04	-----	-----	86.31	26.80	8.09	32.60	9.44	141	360	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2389.95	48.20	54.00	-5.80	36.69	26.60	8.06	32.59	9.44	141	360	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2412.00	98.04	-----	-----	86.31	26.80	8.09	32.60	9.44	141	360	Average																																																																																								



Mode	4																																																																																									
	Band Edge																																																																																									
	2400-2483.5_802.11g_CH01_2412MHz																																																																																									
ANT	1																																																																																									
Pol.	Vertical					Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2389.17</td><td>60.49</td><td>74.00</td><td>-13.51</td><td>48.97</td><td>26.61</td><td>8.06</td><td>32.59</td><td>9.44</td><td>362 113 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2389.17	60.49	74.00	-13.51	48.97	26.61	8.06	32.59	9.44	362 113 Peak	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2412.00</td><td>107.87</td><td>-----</td><td>-----</td><td>96.14</td><td>26.80</td><td>8.09</td><td>32.60</td><td>9.44</td><td>362 113 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2412.00	107.87	-----	-----	96.14	26.80	8.09	32.60	9.44	362 113 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																	
1 2389.17	60.49	74.00	-13.51	48.97	26.61	8.06	32.59	9.44	362 113 Peak																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																	
1 2412.00	107.87	-----	-----	96.14	26.80	8.09	32.60	9.44	362 113 Peak																																																																																	
Avg	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2389.95</td><td>49.35</td><td>54.00</td><td>-4.65</td><td>37.84</td><td>26.60</td><td>8.06</td><td>32.59</td><td>9.44</td><td>362 113 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2389.95	49.35	54.00	-4.65	37.84	26.60	8.06	32.59	9.44	362 113 Average	Level (dBuV/m) Date: 2025-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 2412.00</td><td>100.08</td><td>-----</td><td>-----</td><td>88.39</td><td>26.76</td><td>8.09</td><td>32.60</td><td>9.44</td><td>362 113 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 2412.00	100.08	-----	-----	88.39	26.76	8.09	32.60	9.44	362 113 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																	
1 2389.95	49.35	54.00	-4.65	37.84	26.60	8.06	32.59	9.44	362 113 Average																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																	
1 2412.00	100.08	-----	-----	88.39	26.76	8.09	32.60	9.44	362 113 Average																																																																																	



Mode	4																																																																																																																																																																																																											
	Harmonic																																																																																																																																																																																																											
	2400-2483.5_802.11g_CH01_2412MHz																																																																																																																																																																																																											
ANT	1																																																																																																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																																																																																																					
Peak Avg	Level (dBuV/m) Date: 2025-06-11 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2166.00</td><td>49.35</td><td>74.00</td><td>-24.65</td><td>38.26</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>100</td><td>138</td><td>Peak</td></tr><tr><td>2</td><td>2166.00</td><td>38.66</td><td>54.00</td><td>-15.34</td><td>27.57</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>100</td><td>138</td><td>Average</td></tr><tr><td>3</td><td>2646.00</td><td>52.79</td><td>74.00</td><td>-21.21</td><td>40.14</td><td>27.50</td><td>8.34</td><td>32.68</td><td>9.49</td><td>114</td><td>5</td><td>Peak</td></tr><tr><td>4</td><td>2646.00</td><td>47.21</td><td>54.00</td><td>-6.79</td><td>34.56</td><td>27.50</td><td>8.34</td><td>32.68</td><td>9.49</td><td>114</td><td>5</td><td>Average</td></tr><tr><td>5</td><td>4824.00</td><td>46.67</td><td>74.00</td><td>-27.33</td><td>35.24</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2166.00	49.35	74.00	-24.65	38.26	26.40	7.71	32.44	9.42	100	138	Peak	2	2166.00	38.66	54.00	-15.34	27.57	26.40	7.71	32.44	9.42	100	138	Average	3	2646.00	52.79	74.00	-21.21	40.14	27.50	8.34	32.68	9.49	114	5	Peak	4	2646.00	47.21	54.00	-6.79	34.56	27.50	8.34	32.68	9.49	114	5	Average	5	4824.00	46.67	74.00	-27.33	35.24	32.20	11.53	33.67	1.37	--	--	Peak	Level (dBuV/m) Date: 2025-06-11 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2166.00</td><td>49.44</td><td>74.00</td><td>-24.56</td><td>38.35</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>400</td><td>115</td><td>Peak</td></tr><tr><td>2</td><td>2166.00</td><td>38.78</td><td>54.00</td><td>-15.22</td><td>27.69</td><td>26.40</td><td>7.71</td><td>32.44</td><td>9.42</td><td>400</td><td>115</td><td>Average</td></tr><tr><td>3</td><td>2646.00</td><td>55.34</td><td>74.00</td><td>-18.66</td><td>42.69</td><td>27.50</td><td>8.34</td><td>32.68</td><td>9.49</td><td>332</td><td>113</td><td>Peak</td></tr><tr><td>4</td><td>2646.00</td><td>47.72</td><td>54.00</td><td>-6.28</td><td>35.07</td><td>27.50</td><td>8.34</td><td>32.68</td><td>9.49</td><td>332</td><td>113</td><td>Average</td></tr><tr><td>5</td><td>4824.00</td><td>45.72</td><td>74.00</td><td>-28.28</td><td>34.29</td><td>32.20</td><td>11.53</td><td>33.67</td><td>1.37</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2166.00	49.44	74.00	-24.56	38.35	26.40	7.71	32.44	9.42	400	115	Peak	2	2166.00	38.78	54.00	-15.22	27.69	26.40	7.71	32.44	9.42	400	115	Average	3	2646.00	55.34	74.00	-18.66	42.69	27.50	8.34	32.68	9.49	332	113	Peak	4	2646.00	47.72	54.00	-6.28	35.07	27.50	8.34	32.68	9.49	332	113	Average	5	4824.00	45.72	74.00	-28.28	34.29	32.20	11.53	33.67	1.37	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																			
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																		
1	2166.00	49.35	74.00	-24.65	38.26	26.40	7.71	32.44	9.42	100	138	Peak																																																																																																																																																																																																
2	2166.00	38.66	54.00	-15.34	27.57	26.40	7.71	32.44	9.42	100	138	Average																																																																																																																																																																																																
3	2646.00	52.79	74.00	-21.21	40.14	27.50	8.34	32.68	9.49	114	5	Peak																																																																																																																																																																																																
4	2646.00	47.21	54.00	-6.79	34.56	27.50	8.34	32.68	9.49	114	5	Average																																																																																																																																																																																																
5	4824.00	46.67	74.00	-27.33	35.24	32.20	11.53	33.67	1.37	--	--	Peak																																																																																																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																		
1	2166.00	49.44	74.00	-24.56	38.35	26.40	7.71	32.44	9.42	400	115	Peak																																																																																																																																																																																																
2	2166.00	38.78	54.00	-15.22	27.69	26.40	7.71	32.44	9.42	400	115	Average																																																																																																																																																																																																
3	2646.00	55.34	74.00	-18.66	42.69	27.50	8.34	32.68	9.49	332	113	Peak																																																																																																																																																																																																
4	2646.00	47.72	54.00	-6.28	35.07	27.50	8.34	32.68	9.49	332	113	Average																																																																																																																																																																																																
5	4824.00	45.72	74.00	-28.28	34.29	32.20	11.53	33.67	1.37	--	--	Peak																																																																																																																																																																																																



Mode	5																																																																																		
	Band Edge - L																																																																																		
	2400-2483.5_802.11g_CH06_2437MHz																																																																																		
ANT	1																																																																																		
Pol.	Horizontal						Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2333.50</td><td>53.86</td><td>74.00</td><td>-20.14</td><td>42.17</td><td>26.83</td><td>7.98</td><td>32.55</td><td>9.43</td><td>100</td><td>163</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2333.50	53.86	74.00	-20.14	42.17	26.83	7.98	32.55	9.43	100	163	Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2437.00</td><td>102.97</td><td>74.00</td><td>28.97</td><td>91.33</td><td>26.68</td><td>8.13</td><td>32.62</td><td>9.45</td><td>100</td><td>163</td><td>Peak</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2437.00	102.97	74.00	28.97	91.33	26.68	8.13	32.62	9.45	100	163	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2333.50	53.86	74.00	-20.14	42.17	26.83	7.98	32.55	9.43	100	163	Peak																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2437.00	102.97	74.00	28.97	91.33	26.68	8.13	32.62	9.45	100	163	Peak																																																																								
Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2389.88</td><td>43.31</td><td>54.00</td><td>-10.69</td><td>31.00</td><td>26.60</td><td>8.06</td><td>32.59</td><td>9.44</td><td>100</td><td>163</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2389.88	43.31	54.00	-10.69	31.00	26.60	8.06	32.59	9.44	100	163	Average	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2437.00</td><td>95.18</td><td>54.00</td><td>41.18</td><td>83.52</td><td>26.70</td><td>8.13</td><td>32.62</td><td>9.45</td><td>100</td><td>163</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2437.00	95.18	54.00	41.18	83.52	26.70	8.13	32.62	9.45	100	163	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2389.88	43.31	54.00	-10.69	31.00	26.60	8.06	32.59	9.44	100	163	Average																																																																								
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 2437.00	95.18	54.00	41.18	83.52	26.70	8.13	32.62	9.45	100	163	Average																																																																								



Mode	5																																																																									
	Band Edge - L																																																																									
	2400-2483.5_802.11g_CH06_2437MHz																																																																									
ANT	1																																																																									
Pol.	Vertical	Fundamental																																																																								
Peak	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2386.20 51.29 74.00 -22.71 39.73 26.64 8.06 32.58 9.44 200 182</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg									1 2386.20 51.29 74.00 -22.71 39.73 26.64 8.06 32.58 9.44 200 182	Peak								Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2437.00 99.47 ----- 87.83 26.68 8.13 32.62 9.45 200 182</td><td>Peak</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg									1 2437.00 99.47 ----- 87.83 26.68 8.13 32.62 9.45 200 182	Peak							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg																																																																										
1 2386.20 51.29 74.00 -22.71 39.73 26.64 8.06 32.58 9.44 200 182	Peak																																																																									
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg																																																																										
1 2437.00 99.47 ----- 87.83 26.68 8.13 32.62 9.45 200 182	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2389.12 40.27 54.00 -13.73 28.75 26.61 8.06 32.59 9.44 200 182</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg									1 2389.12 40.27 54.00 -13.73 28.75 26.61 8.06 32.59 9.44 200 182	Average								Level (dBuV/m) Date: 2025-06-19 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level Line Margin Level Factor Loss Factor Factor</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th>MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>1 2437.00 91.71 ----- 80.05 26.70 8.13 32.62 9.45 200 182</td><td>Average</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level Line Margin Level Factor Loss Factor Factor									MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg									1 2437.00 91.71 ----- 80.05 26.70 8.13 32.62 9.45 200 182	Average							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																	
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg																																																																										
1 2389.12 40.27 54.00 -13.73 28.75 26.61 8.06 32.59 9.44 200 182	Average																																																																									
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																		
Freq Level Line Margin Level Factor Loss Factor Factor																																																																										
MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB dB cm deg																																																																										
1 2437.00 91.71 ----- 80.05 26.70 8.13 32.62 9.45 200 182	Average																																																																									



Mode	5	
	Band Edge - R	
	2400-2483.5_802.11g_CH06_2437MHz	
ANT	1	
Pol.	Vertical	Fundamental
Peak		







Mode	5																																																																																																																																			
	Harmonic																																																																																																																																			
	2400-2483.5_802.11g_CH06_2437MHz																																																																																																																																			
ANT	1																																																																																																																																			
Pol.	Horizontal																																																																																																																																			
Peak Avg	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL																																																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>2206.00</td><td>52.18</td><td>74.00</td><td>-21.82</td><td>40.90</td><td>26.56</td><td>7.78</td><td>32.47</td><td>9.41</td><td>166</td><td>167</td><td>Peak</td></tr><tr><td>2</td><td>2206.00</td><td>42.75</td><td>54.00</td><td>-11.25</td><td>31.47</td><td>26.56</td><td>7.78</td><td>32.47</td><td>9.41</td><td>166</td><td>167</td><td>Average</td></tr><tr><td>3</td><td>2670.00</td><td>52.56</td><td>74.00</td><td>-21.44</td><td>39.98</td><td>27.40</td><td>8.37</td><td>32.68</td><td>9.49</td><td>112</td><td>170</td><td>Peak</td></tr><tr><td>4</td><td>2670.00</td><td>47.36</td><td>54.00</td><td>-6.64</td><td>34.78</td><td>27.40</td><td>8.37</td><td>32.68</td><td>9.49</td><td>112</td><td>170</td><td>Average</td></tr><tr><td>5</td><td>4874.00</td><td>47.36</td><td>74.00</td><td>-26.64</td><td>35.87</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>7311.00</td><td>51.56</td><td>74.00</td><td>-22.44</td><td>35.67</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>100</td><td>119</td><td>Peak</td></tr><tr><td>7</td><td>7311.00</td><td>41.98</td><td>54.00</td><td>-12.02</td><td>26.09</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>100</td><td>119</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1	2206.00	52.18	74.00	-21.82	40.90	26.56	7.78	32.47	9.41	166	167	Peak	2	2206.00	42.75	54.00	-11.25	31.47	26.56	7.78	32.47	9.41	166	167	Average	3	2670.00	52.56	74.00	-21.44	39.98	27.40	8.37	32.68	9.49	112	170	Peak	4	2670.00	47.36	54.00	-6.64	34.78	27.40	8.37	32.68	9.49	112	170	Average	5	4874.00	47.36	74.00	-26.64	35.87	32.30	11.60	33.67	1.26	--	--	Peak	6	7311.00	51.56	74.00	-22.44	35.67	37.20	14.28	36.59	1.00	100	119	Peak	7	7311.00	41.98	54.00	-12.02	26.09	37.20	14.28	36.59	1.00	100	119	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																										
	1	2206.00	52.18	74.00	-21.82	40.90	26.56	7.78	32.47	9.41	166	167	Peak																																																																																																																							
	2	2206.00	42.75	54.00	-11.25	31.47	26.56	7.78	32.47	9.41	166	167	Average																																																																																																																							
	3	2670.00	52.56	74.00	-21.44	39.98	27.40	8.37	32.68	9.49	112	170	Peak																																																																																																																							
	4	2670.00	47.36	54.00	-6.64	34.78	27.40	8.37	32.68	9.49	112	170	Average																																																																																																																							
	5	4874.00	47.36	74.00	-26.64	35.87	32.30	11.60	33.67	1.26	--	--	Peak																																																																																																																							
6	7311.00	51.56	74.00	-22.44	35.67	37.20	14.28	36.59	1.00	100	119	Peak																																																																																																																								
7	7311.00	41.98	54.00	-12.02	26.09	37.20	14.28	36.59	1.00	100	119	Average																																																																																																																								
Vertical																																																																																																																																				
	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL																																																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>2204.00</td><td>49.85</td><td>74.00</td><td>-24.15</td><td>38.58</td><td>26.54</td><td>7.78</td><td>32.46</td><td>9.41</td><td>210</td><td>154</td><td>Peak</td></tr><tr><td>2</td><td>2204.00</td><td>39.80</td><td>54.00</td><td>-14.20</td><td>28.53</td><td>26.54</td><td>7.78</td><td>32.46</td><td>9.41</td><td>210</td><td>154</td><td>Average</td></tr><tr><td>3</td><td>2678.00</td><td>51.78</td><td>74.00</td><td>-22.22</td><td>39.11</td><td>27.48</td><td>8.38</td><td>32.68</td><td>9.49</td><td>307</td><td>107</td><td>Peak</td></tr><tr><td>4</td><td>2678.00</td><td>46.38</td><td>54.00</td><td>-7.62</td><td>33.71</td><td>27.48</td><td>8.38</td><td>32.68</td><td>9.49</td><td>307</td><td>107</td><td>Average</td></tr><tr><td>5</td><td>4874.00</td><td>47.99</td><td>74.00</td><td>-26.01</td><td>36.50</td><td>32.30</td><td>11.60</td><td>33.67</td><td>1.26</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>7311.00</td><td>50.77</td><td>74.00</td><td>-23.23</td><td>34.88</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>285</td><td>187</td><td>Peak</td></tr><tr><td>7</td><td>7311.00</td><td>41.09</td><td>54.00</td><td>-12.91</td><td>25.20</td><td>37.20</td><td>14.28</td><td>36.59</td><td>1.00</td><td>285</td><td>187</td><td>Average</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1	2204.00	49.85	74.00	-24.15	38.58	26.54	7.78	32.46	9.41	210	154	Peak	2	2204.00	39.80	54.00	-14.20	28.53	26.54	7.78	32.46	9.41	210	154	Average	3	2678.00	51.78	74.00	-22.22	39.11	27.48	8.38	32.68	9.49	307	107	Peak	4	2678.00	46.38	54.00	-7.62	33.71	27.48	8.38	32.68	9.49	307	107	Average	5	4874.00	47.99	74.00	-26.01	36.50	32.30	11.60	33.67	1.26	--	--	Peak	6	7311.00	50.77	74.00	-23.23	34.88	37.20	14.28	36.59	1.00	285	187	Peak	7	7311.00	41.09	54.00	-12.91	25.20	37.20	14.28	36.59	1.00	285	187	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																											
1	2204.00	49.85	74.00	-24.15	38.58	26.54	7.78	32.46	9.41	210	154	Peak																																																																																																																								
2	2204.00	39.80	54.00	-14.20	28.53	26.54	7.78	32.46	9.41	210	154	Average																																																																																																																								
3	2678.00	51.78	74.00	-22.22	39.11	27.48	8.38	32.68	9.49	307	107	Peak																																																																																																																								
4	2678.00	46.38	54.00	-7.62	33.71	27.48	8.38	32.68	9.49	307	107	Average																																																																																																																								
5	4874.00	47.99	74.00	-26.01	36.50	32.30	11.60	33.67	1.26	--	--	Peak																																																																																																																								
6	7311.00	50.77	74.00	-23.23	34.88	37.20	14.28	36.59	1.00	285	187	Peak																																																																																																																								
7	7311.00	41.09	54.00	-12.91	25.20	37.20	14.28	36.59	1.00	285	187	Average																																																																																																																								



Mode	6																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11g_CH11_2462MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2489.28</td><td>50.44</td><td>74.00</td><td>-23.56</td><td>38.65</td><td>26.79</td><td>8.19</td><td>32.65</td><td>9.46</td><td>117</td><td>166</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2489.28	50.44	74.00	-23.56	38.65	26.79	8.19	32.65	9.46	117	166	Peak	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>95.29</td><td>-----</td><td>-----</td><td>83.58</td><td>26.74</td><td>8.15</td><td>32.63</td><td>9.45</td><td>117</td><td>166</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	95.29	-----	-----	83.58	26.74	8.15	32.63	9.45	117	166	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2489.28	50.44	74.00	-23.56	38.65	26.79	8.19	32.65	9.46	117	166	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	95.29	-----	-----	83.58	26.74	8.15	32.63	9.45	117	166	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2483.58</td><td>39.48</td><td>54.00</td><td>-14.52</td><td>27.75</td><td>26.74</td><td>8.18</td><td>32.65</td><td>9.46</td><td>117</td><td>166</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2483.58	39.48	54.00	-14.52	27.75	26.74	8.18	32.65	9.46	117	166	Average	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2462.00</td><td>87.78</td><td>-----</td><td>-----</td><td>76.07</td><td>26.74</td><td>8.15</td><td>32.63</td><td>9.45</td><td>117</td><td>166</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	87.78	-----	-----	76.07	26.74	8.15	32.63	9.45	117	166	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2483.58	39.48	54.00	-14.52	27.75	26.74	8.18	32.65	9.46	117	166	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	87.78	-----	-----	76.07	26.74	8.15	32.63	9.45	117	166	Average																																																																									



Mode	6																																																																																								
	Band Edge																																																																																								
	2400-2483.5_802.11g_CH11_2462MHz																																																																																								
ANT	1																																																																																								
Pol.	Vertical					Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-06-18  PEAK_BE_74					Level (dBuV/m) Date: 2025-06-18  PEAK_74																																																																																			
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2497.04</td><td>49.88</td><td>74.00 -24.12</td><td>38.08</td><td>26.80</td><td>8.20</td><td>32.66</td><td>9.46</td><td>112</td><td>187 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2497.04	49.88	74.00 -24.12	38.08	26.80	8.20	32.66	9.46	112	187 Peak	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2462.00</td><td>92.95</td><td>-----</td><td>81.24</td><td>26.74</td><td>8.15</td><td>32.63</td><td>9.45</td><td>112</td><td>187 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2462.00	92.95	-----	81.24	26.74	8.15	32.63	9.45	112
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2497.04	49.88	74.00 -24.12	38.08	26.80	8.20	32.66	9.46	112	187 Peak																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2462.00	92.95	-----	81.24	26.74	8.15	32.63	9.45	112	187 Peak																																																																																
Avg	Level (dBuV/m) Date: 2025-06-18  AVG_BE_54					Level (dBuV/m) Date: 2025-06-18  AVG_54																																																																																			
	Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2483.77</td><td>39.09</td><td>54.00 -14.91</td><td>27.36</td><td>26.74</td><td>8.18</td><td>32.65</td><td>9.46</td><td>112</td><td>187 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2483.77	39.09	54.00 -14.91	27.36	26.74	8.18	32.65	9.46	112	187 Average	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2462.00</td><td>85.19</td><td>-----</td><td>73.48</td><td>26.74</td><td>8.15</td><td>32.63</td><td>9.45</td><td>112</td><td>187 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2462.00	85.19	-----	73.48	26.74	8.15	32.63	9.45	112
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2483.77	39.09	54.00 -14.91	27.36	26.74	8.18	32.65	9.46	112	187 Average																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2462.00	85.19	-----	73.48	26.74	8.15	32.63	9.45	112	187 Average																																																																																



Mode	6																																																																																																																																																																																																																																																																																																																					
	Harmonic																																																																																																																																																																																																																																																																																																																					
	2400-2483.5_802.11g_CH11_2462MHz																																																																																																																																																																																																																																																																																																																					
ANT	1																																																																																																																																																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																																																																																																																																																				
Peak	Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2230.00</td><td>51.95</td><td>74.00</td><td>-22.05</td><td>40.50</td><td>26.70</td><td>7.82</td><td>32.48</td><td>9.41</td><td>106</td><td>169</td><td>Peak</td><td></td></tr><tr><td>2</td><td>2230.00</td><td>44.06</td><td>54.00</td><td>-9.94</td><td>32.61</td><td>26.70</td><td>7.82</td><td>32.48</td><td>9.41</td><td>106</td><td>169</td><td>Average</td><td></td></tr><tr><td>3</td><td>2390.00</td><td>51.11</td><td>74.00</td><td>-22.89</td><td>39.60</td><td>26.60</td><td>8.06</td><td>32.59</td><td>9.44</td><td>166</td><td>161</td><td>Peak</td><td></td></tr><tr><td>4</td><td>2390.00</td><td>39.87</td><td>54.00</td><td>-14.13</td><td>28.36</td><td>26.60</td><td>8.06</td><td>32.59</td><td>9.44</td><td>166</td><td>161</td><td>Average</td><td></td></tr><tr><td>5</td><td>2696.00</td><td>52.12</td><td>74.00</td><td>-21.88</td><td>39.41</td><td>27.50</td><td>8.41</td><td>32.69</td><td>9.49</td><td>100</td><td>8</td><td>Peak</td><td></td></tr><tr><td>6</td><td>2696.00</td><td>46.35</td><td>54.00</td><td>-7.65</td><td>33.64</td><td>27.50</td><td>8.41</td><td>32.69</td><td>9.49</td><td>100</td><td>8</td><td>Average</td><td></td></tr><tr><td>7</td><td>4924.00</td><td>46.11</td><td>74.00</td><td>-27.89</td><td>34.46</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>--</td><td>--</td><td>Peak</td><td></td></tr><tr><td>8</td><td>7386.00</td><td>48.81</td><td>74.00</td><td>-25.19</td><td>33.08</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>--</td><td>--</td><td>Peak</td><td></td></tr><tr><td>9</td><td>7386.00</td><td>39.16</td><td>54.00</td><td>-14.84</td><td>23.43</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>--</td><td>--</td><td>Average</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	2230.00	51.95	74.00	-22.05	40.50	26.70	7.82	32.48	9.41	106	169	Peak		2	2230.00	44.06	54.00	-9.94	32.61	26.70	7.82	32.48	9.41	106	169	Average		3	2390.00	51.11	74.00	-22.89	39.60	26.60	8.06	32.59	9.44	166	161	Peak		4	2390.00	39.87	54.00	-14.13	28.36	26.60	8.06	32.59	9.44	166	161	Average		5	2696.00	52.12	74.00	-21.88	39.41	27.50	8.41	32.69	9.49	100	8	Peak		6	2696.00	46.35	54.00	-7.65	33.64	27.50	8.41	32.69	9.49	100	8	Average		7	4924.00	46.11	74.00	-27.89	34.46	32.50	11.67	33.67	1.15	--	--	Peak		8	7386.00	48.81	74.00	-25.19	33.08	37.13	14.28	36.71	1.03	--	--	Peak		9	7386.00	39.16	54.00	-14.84	23.43	37.13	14.28	36.71	1.03	--	--	Average		Level (dBuV/m) Date: 2025-06-18 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2230.00</td><td>49.95</td><td>74.00</td><td>-24.05</td><td>38.50</td><td>26.70</td><td>7.82</td><td>32.48</td><td>9.41</td><td>301</td><td>90</td><td>Peak</td><td></td></tr><tr><td>2</td><td>2230.00</td><td>42.50</td><td>54.00</td><td>-11.50</td><td>31.05</td><td>26.70</td><td>7.82</td><td>32.48</td><td>9.41</td><td>301</td><td>90</td><td>Average</td><td></td></tr><tr><td>3</td><td>2378.00</td><td>49.12</td><td>74.00</td><td>-24.88</td><td>37.47</td><td>26.74</td><td>8.05</td><td>32.58</td><td>9.44</td><td>300</td><td>119</td><td>Peak</td><td></td></tr><tr><td>4</td><td>2378.00</td><td>38.13</td><td>54.00</td><td>-15.87</td><td>26.48</td><td>26.74</td><td>8.05</td><td>32.58</td><td>9.44</td><td>300</td><td>119</td><td>Average</td><td></td></tr><tr><td>5</td><td>2704.00</td><td>51.77</td><td>74.00</td><td>-22.23</td><td>39.06</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>300</td><td>98</td><td>Peak</td><td></td></tr><tr><td>6</td><td>2704.00</td><td>44.19</td><td>54.00</td><td>-9.81</td><td>31.48</td><td>27.50</td><td>8.42</td><td>32.69</td><td>9.48</td><td>300</td><td>98</td><td>Average</td><td></td></tr><tr><td>7</td><td>4924.00</td><td>46.24</td><td>74.00</td><td>-27.76</td><td>34.59</td><td>32.50</td><td>11.67</td><td>33.67</td><td>1.15</td><td>--</td><td>--</td><td>Peak</td><td></td></tr><tr><td>8</td><td>7386.00</td><td>49.34</td><td>74.00</td><td>-24.66</td><td>33.61</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>--</td><td>--</td><td>Peak</td><td></td></tr><tr><td>9</td><td>7386.00</td><td>39.46</td><td>54.00</td><td>-14.54</td><td>23.73</td><td>37.13</td><td>14.28</td><td>36.71</td><td>1.03</td><td>--</td><td>--</td><td>Average</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	2230.00	49.95	74.00	-24.05	38.50	26.70	7.82	32.48	9.41	301	90	Peak		2	2230.00	42.50	54.00	-11.50	31.05	26.70	7.82	32.48	9.41	301	90	Average		3	2378.00	49.12	74.00	-24.88	37.47	26.74	8.05	32.58	9.44	300	119	Peak		4	2378.00	38.13	54.00	-15.87	26.48	26.74	8.05	32.58	9.44	300	119	Average		5	2704.00	51.77	74.00	-22.23	39.06	27.50	8.42	32.69	9.48	300	98	Peak		6	2704.00	44.19	54.00	-9.81	31.48	27.50	8.42	32.69	9.48	300	98	Average		7	4924.00	46.24	74.00	-27.76	34.59	32.50	11.67	33.67	1.15	--	--	Peak		8	7386.00	49.34	74.00	-24.66	33.61	37.13	14.28	36.71	1.03	--	--	Peak		9	7386.00	39.46	54.00	-14.54	23.73	37.13	14.28	36.71	1.03	--	--	Average	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																																										
1	2230.00	51.95	74.00	-22.05	40.50	26.70	7.82	32.48	9.41	106	169	Peak																																																																																																																																																																																																																																																																																																										
2	2230.00	44.06	54.00	-9.94	32.61	26.70	7.82	32.48	9.41	106	169	Average																																																																																																																																																																																																																																																																																																										
3	2390.00	51.11	74.00	-22.89	39.60	26.60	8.06	32.59	9.44	166	161	Peak																																																																																																																																																																																																																																																																																																										
4	2390.00	39.87	54.00	-14.13	28.36	26.60	8.06	32.59	9.44	166	161	Average																																																																																																																																																																																																																																																																																																										
5	2696.00	52.12	74.00	-21.88	39.41	27.50	8.41	32.69	9.49	100	8	Peak																																																																																																																																																																																																																																																																																																										
6	2696.00	46.35	54.00	-7.65	33.64	27.50	8.41	32.69	9.49	100	8	Average																																																																																																																																																																																																																																																																																																										
7	4924.00	46.11	74.00	-27.89	34.46	32.50	11.67	33.67	1.15	--	--	Peak																																																																																																																																																																																																																																																																																																										
8	7386.00	48.81	74.00	-25.19	33.08	37.13	14.28	36.71	1.03	--	--	Peak																																																																																																																																																																																																																																																																																																										
9	7386.00	39.16	54.00	-14.84	23.43	37.13	14.28	36.71	1.03	--	--	Average																																																																																																																																																																																																																																																																																																										
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																																										
1	2230.00	49.95	74.00	-24.05	38.50	26.70	7.82	32.48	9.41	301	90	Peak																																																																																																																																																																																																																																																																																																										
2	2230.00	42.50	54.00	-11.50	31.05	26.70	7.82	32.48	9.41	301	90	Average																																																																																																																																																																																																																																																																																																										
3	2378.00	49.12	74.00	-24.88	37.47	26.74	8.05	32.58	9.44	300	119	Peak																																																																																																																																																																																																																																																																																																										
4	2378.00	38.13	54.00	-15.87	26.48	26.74	8.05	32.58	9.44	300	119	Average																																																																																																																																																																																																																																																																																																										
5	2704.00	51.77	74.00	-22.23	39.06	27.50	8.42	32.69	9.48	300	98	Peak																																																																																																																																																																																																																																																																																																										
6	2704.00	44.19	54.00	-9.81	31.48	27.50	8.42	32.69	9.48	300	98	Average																																																																																																																																																																																																																																																																																																										
7	4924.00	46.24	74.00	-27.76	34.59	32.50	11.67	33.67	1.15	--	--	Peak																																																																																																																																																																																																																																																																																																										
8	7386.00	49.34	74.00	-24.66	33.61	37.13	14.28	36.71	1.03	--	--	Peak																																																																																																																																																																																																																																																																																																										
9	7386.00	39.46	54.00	-14.54	23.73	37.13	14.28	36.71	1.03	--	--	Average																																																																																																																																																																																																																																																																																																										