

RF Exposure Evaluation Report

APPLICANT : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
EQUIPMENT : ML9118A-GAIA-M0-PG12
BRAND NAME : TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
MODEL NAME : ML9118A-GAIA-M0-PG12
FCC ID : OEOML9118AGM0
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Jul. 03, 2025 and completed on Jul. 03, 2025. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA532411	Rev. 01	Initial issue of report.	Jul. 07, 2025



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
Address	10-11/F, Building 1, 61 Shengxia Road, PuDongDistrict, Shanghai, China 201203

Manufacturer	
Company Name	Dongguan Shengmengtai Surface Mount Technology Co.,Ltd
Address	Room 301, Building 7, No. 45 Kangyi Road, QingxiTown, Dongguan City

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	ML9118A-GAIA-M0-PG12
Brand Name	TELINK SEMICONDUCTOR (SHANG HAI) CO., LTD.
Model Name	ML9118A-GAIA-M0-PG12
FCC ID	OEOML9118AGM0
Wireless Technology and Frequency Range	WLAN2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz ZigBee: 2405 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20 Bluetooth LE ZigBee: O-QPSK
Antenna Type	WLAN/Bluetooth/ZigBee: PCB Antenna
Antenna Gain	WLAN2.4GHz: 2.60 dBi Bluetooth: 2.60 dBi ZigBee: 2.60 dBi
HW Version	V1.0
SW Version	V1.0
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. The device supports IEEE 802.15.4 include Zigbee/Thread, the characteristic is the same, the power level and the gain value is the same.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

**3. Maximum RF average output tune up power among production units****<WLAN 2.4GHz >**

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	15.00
	802.11g	7.00
	802.11n-HT20	7.00
	802.11n-HT40	7.00
	802.11ax-HT20	7.00

< Bluetooth >

Mode	Maximum Average Power (dBm)
Bluetooth LE	5.00

<ZigBee>

Mode		Maximum Average power(dBm)
2.4GHz	ZigBee/Thread	12.00

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
2.4GHz WLAN	2412.0	2.60	15.00	17.600	57.544	0.011	1.000
Bluetooth LE	2402.0	2.60	5.00	7.600	5.754	0.001	1.000
ZigBee/Thread	2405.0	2.60	12.00	14.600	28.840	0.006	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, ZigBee (or Thread) and Bluetooth (or WLAN 2.4GHz) cannot transmit simultaneously.
4. According to the EUT characteristic, WLAN 2.4GHz and Bluetooth cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----