

# RF Exposure Evaluation Report

## 1 RF EXPOSURE

Product Name	AOA/AOD
Model No.	TLSR8278IP48D
Test Mode	TX
FCC ID	OEOTLSR8278IP48D

### 1.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.2 EUT RF EXPOSURE EVALUATION

Operational Mode:BLE						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power (dBm)	Maximum tune-up Power (mW)	Calculated value	Exclusion threshold
2402MHz	3.81	$\pm 1$	4.81	3.03	0.94	3
2442MHz	3.00	$\pm 1$	4.00	2.51	0.78	3
2480MHz	1.60	$\pm 1$	2.60	1.82	0.57	3

Conclusion: the calculated value  $\leq 3.0$ , SAR is exempted.