

FCC PART 15.249
EMI MEASUREMENT AND TEST REPORT
For
PEGA LIMITED

Unit 10A, 12/F, Tower 2, China Hong Kong City, No.33 Canton Road, Tsim Sha Tsui, Hong Kong

FCC ID: OF5PG-IH119TX

July 6, 2012

This Report Concerns: Original Report	Equipment Type: 2.4G Wireless Home Theater Audio and Charger Dock (TX)
Test Engineer:	Eric Li <i>Eric Li</i>
Report No.:	BST12060250Y-1ER-3
Receive EUT Date/Test Date:	June 29, 2012/ July 2-5, 2012
Reviewed By:	Christina Deng <i>Christina Deng</i>
Prepared By:	 Shenzhen BST Technology Co.,Ltd. 3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District, Shenzhen, Guangdong, China Tel: 0755-26747751 ~ 3 Fax: 0755-26747751 ~ 3 ext.826

Note: The test report is specially limited to the above company and this particular sample only. It may not be duplicated without prior written consent of Shenzhen BST Technology Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the US Government.

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information.....	3
1.2.	Measurement Uncertainty	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration.....	4
2.3.	Support Equipment List	5
2.4.	Test Conditions	5
3.	FCC ID LABEL.....	6
4.	TEST RESULTS SUMMARY	7
	Modifications	7
5.	TEST EQUIPMENT USED	8
6.	ANTENNA REQUIREMENT	9
6.1.	Standard Applicable.....	9
6.2.	Antenna Connected Construction	9
6.3.	Result	9
7.	CONDUCTED POWER LINE TEST	10
7.1.	Test Equipment	10
7.2.	Test Procedure	10
7.3.	Test Setup.....	10
7.4.	Conducted Power line Emission Limits.....	10
7.5.	Conducted Power Line Test Result.....	11
8.	RADIATED EMISSION TEST	13
8.1.	Test Equipment	13
8.2.	Test Procedure	13
8.3.	Radiated Test Setup	13
8.4.	Radiated Emission Limit.....	15
8.5.	Radiated Emission Test Result	16
9.	BAND EDGE	18
9.1.	Test Equipment	18
9.2.	Test Procedure	18
9.3.	Band Edge FCC 15.249(d) Limit.....	18
9.4.	Band Edge Test Result.....	19

1. GENERAL INFORMATION

1.1. Report information

1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BST approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BST in any way guarantees the later performance of the product/equipment.

1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BST therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BST, unless the applicant has authorized BST in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of

Shenzhen Certification Technology Service Co., Ltd

(FCC Registered Test Site Number: 197647) on

2F, Building B, East Area of Nanchang Second Industrial Zone, Gushu 2nd Road,

Bao'an District, shenzhen 518126, China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description	: 2.4G Wireless Home Theater Audio and Charger Dock (TX)
Applicant	: PEGA LIMITED Unit 10A, 12/F, Tower 2, China Hong Kong City, No.33 Canton Road, Tsim Sha Tsui, Hong Kong
Manufacturer	: PEGA LIMITED Haibin Industrial Zone, Xinye Road, 65 TH Block Xixiang Town, Bao'an District, ShenZhen City, China
Model Number	: PG-IH119, proCube
Trade Name	: iPega, Promate
Frequency	: 2401-2479MHz
Power Supply	: DC 5V

2.2. Block Diagram of EUT Configuration




Figure 1 EUT Setup

2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used “ √ ”
PC system	AM1830	N/A	Acer	√
Printer	HP1020	N/A	HP	√
Router	TL-R402M	07115200391	TP-LINK	√

2.4. Test Conditions

Temperature: 20~25

Relative Humidity: 50~63 %

3. FCC ID LABEL

FCC ID: OF5PG-IH119TX

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: 1. This device may not cause harmful interference, and 2. This device must accept any interference received, including interference that may cause undesired operation.

Label Location on EUT

EUT View/ FCC ID Label Location



4. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant

Remark: "N/A" means "Not applicable".

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

Modifications

No modification was made.

5. TEST EQUIPMENT USED

Equipment/Facilities	Manufacturer	Model #	serial no.	Last Calibrated	Calibrated until
Cable	Resenberger	N/A	NO.1	Mar 10 , 2012	Mar 10 , 2013
Cable	SCHWARZBECK	N/A	NO.2	Mar 10 , 2012	Mar 10 , 2013
Cable	SCHWARZBECK	N/A	NO.3	Mar 10 , 2012	Mar 10 , 2013
LISN	Rohde & Schwarz	ESH3-Z5	100305	Mar 10 , 2012	Mar 10 , 2013
50 Ω Coaxial Switch	ANRITSU CORP	MP59B	6200283933	Mar 10 , 2012	Mar 10 , 2013
EMI Test Receiver	Rohde & Schwarz	ESP13	100180	Oct.11,2011	Oct.11,2012
Spectrum Analyzer	Rohde & Schwarz	FSP40	100273	Sep.10,2011	Sep.10,2012
3m Semi-Anechoic Chamber	Albatross Projects	9m×6m×6m	N/A	Feb.20,2012	Feb.20,2013
Signal Generator	FLUKE	PM5418 + Y/C	LO747012	Feb.20,2012	Feb.20,2013
Signal Generator	FLUKE	PM5418TX	LO738007	Feb.20,2012	Feb.20,2013
Loop Antenna	SCHWARZBECK	FMZB1516	113	Jan.30,2012	Jan.30,2013
Trilog-Super Broadband Antenna	SCHWARZBECK	VULB9161	9161-4079	Sep.22,2011	Sep.22,2012
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-564	Sep.22,2011	Sep.22,2012
Ultra Broadband Antenna	Rohde & Schwarz	HL-562	100110	June.15,2012	June.15,2013
AMN	Rohde & Schwarz	ESH3-Z5	100196	Oct.11,2011	Oct.11,2012
AMN	Rohde & Schwarz	ESH3-Z5	100197	Oct.11,2011	Oct.11,2012
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	N/A	N/A	N/A
Power Meter	Rohde & Schwarz	NRVD	100041	Feb.20,2012	Feb.20,2013
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	Feb.20,2012	Feb.20,2013
Coaxial Cable with N-connectors	SCHWARZBECK	AK9515H	95549	Sep.22,2011	Sep.22,2012
Radio Communication Test Set	Rohde & Schwarz	CMS 54	846621/024	Feb.20,2012	Feb.20,2013
Modulation Analyzer	Hewlett-Packard	8901B	2303A00362	Feb.20,2012	Feb.20,2013
Absorbing clamp	Rohde & Schwarz	MDS-21	N/A	Oct.11,2011	Oct.11,2012

6. ANTENNA REQUIREMENT

6.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is PCB antenna. The antenna is permanently attached. Refer to the product photo.

6.3. Result

Compliance

7. CONDUCTED POWER LINE TEST

7.1. Test Equipment


Please refer to section 5 this report.

7.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uh coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling impedance with 50ohm termination.

Both sides of A.C. Line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement. Conducted emissions were measured over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9KHz.

7.3. Test Setup



For the actual test configuration, Please refer to the related items-Photos of testing

7.4. Conducted Power line Emission Limits

FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50


Note: In the above table, the tighter limit applies at the band edges.

7.5. Conducted Power Line Test Result

Pass.

Date of Test:	July 3, 2012	Temperature:	25°C
EUT:	2.4G Wireless Home Theater Audio and Charger Dock (TX)	Humidity:	53%
Model No.:	PG-IH119, proCube	Power Supply:	DC 5V power by PC USB port PC power: AC120V/60Hz
Test Mode:	TX	Test Engineer:	Eric Li

L Line




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV)	Margin (dB)	Limit (dBuV)	Detector Type
1	*	0.162	0.141	41.440	41.581	-24.076	65.657	QUASIPeAK
2		0.216	0.159	38.710	38.869	-25.245	64.114	QUASIPeAK
3		0.339	0.190	30.450	30.640	-29.960	60.600	QUASIPeAK
4		2.864	0.410	25.850	26.260	-29.740	56.000	QUASIPeAK
5		9.060	0.590	30.690	31.280	-28.720	60.000	QUASIPeAK
6		19.298	0.900	23.670	24.570	-35.430	60.000	QUASIPeAK

Note:

1. All Reading Levels are Quasi-Peak, The average measurement was not performed when the Quasi-Peak measured data under the limit of average detection.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

N Line



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Measure Level (dBuV)	Margin (dB)	Limit (dBuV)	Detector Type
1		0.162	0.141	36.470	36.611	-29.046	65.657	QUASIPeAK
2	*	0.177	0.146	44.540	44.686	-20.543	65.229	QUASIPeAK
3		0.216	0.159	36.600	36.759	-27.355	64.114	QUASIPeAK
4		0.361	0.190	30.180	30.370	-29.601	59.971	QUASIPeAK
5		2.068	0.390	30.450	30.840	-25.160	56.000	QUASIPeAK
6		9.850	0.713	29.720	30.433	-29.567	60.000	QUASIPeAK

Note:

1. All Reading Levels are Quasi-Peak, The average measurement was not performed when the Quasi-Peak measured data under the limit of average detection.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

8. RADIATED EMISSION TEST

8.1. Test Equipment

Please refer to section 5 this report.

8.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit.

8.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



8.4. Radiated Emission Limit

All emission from a digital device,including any network of conductors and apparatus connected thereto,shall not exceed the level of field strength specified below :

A . Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency (MHZ)	Field as trength of Fundamental(3m)			Field as trength of Harmonics(3m)		
	mV/m	dBuV/m		uV/m	dBuV/m	
902~928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400~2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(3) The emission limit in this paragraph os based on measurement instrumentation employing an average detector.Measurement using instrumentation with a peak detector function,corresponding to 20dB above the maximum permitted average limit.

B. Spurious Radiated Emissions.

Frequency (MHz)	Limit			
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dBμV/m)	Measurement distance (m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
0.009 - 0.490	2400/F(kHz)	/	300	
0.490 - 1.705	24000/F(kHz)	/	30	
1.705-30	30	29.5	30	
30 - 88	100	40	3	
88 - 216	150	43.5	3	
216 - 960	200	46	3	
Above 960	500	54	3	

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table,the tighter limit applies at the band edges.

(3) Distagncce refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

8.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2401	85.21/97.45	VERT	94/114	8.79/16.55
2401	86.14/98.32	HORIZ	94/114	7.86/15.68

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2441	84.33/97.07	VERT	94/114	9.67/16.93
2441	85.18/98.13	HORIZ	94/114	8.82/15.87

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2479	84.75/97.67	VERT	94/114	9.25/16.33
2479	85.31/98.54	HORIZ	94/114	8.69/15.46

B. Harmonics Radiated Emissions Data

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4802.0	31.72/43.91	VERT	54.0/74.0	22.28/30.09
4802.0	34.08/46.74	HORIZ	54.0/74.0	19.20/27.26

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4882.0	31.39/43.87	VERT	54.0/74.0	22.61/30.13
4882.0	33.91/45.92	HORIZ	54.0/74.0	20.09/28.08

Emissions attenuated more than 20 dB below the permissible value are not reported.

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4958.0	32.03/44.51	VERT	54.0/74.0	21.97/29.49
4958.0	34.01/45.80	HORIZ	54.0/74.0	19.99/28.20

Emissions attenuated more than 20 dB below the permissible value are not reported.

C. General Radiated Emissions Data

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	HORIZ	-	-
-	-	VERT	-	-

Emissions attenuated more than 20 dB below the permissible value are not reported.

9. BAND EDGE

9.1. Test Equipment

Please refer to Section 5 this report.

9.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

9.3. Band Edge FCC 15.249(d) Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100kHz bandwidth within the band that contains the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.4. Band Edge Test Result

Pass

TX 2401MHz

Frequency (MHz)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	PEAK	AV	PEAK	AV	PEAK	AV	
2345.040	52.91	39.80	74	54	21.09	14.20	Vertical
2400.000	59.73	44.47	74	54	14.27	9.53	
2386.699	54.78	41.39	74	54	19.22	12.61	Horizontal
2400.000	60.22	45.64	74	54	13.78	8.36	

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.


TX 2479MHz

Frequency (MHz)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	PEAK	AV	PEAK	AV	PEAK	AV	
2484.054	56.35	39.81	74	54	17.65	14.19	Vertical
2484.367	55.28	41.41	74	54	18.72	12.59	Horizontal


Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.


Vertical (PK) TX 2401MHz




Vertical (AV) TX 2401MHz




Horizontal (PK) TX 2401MHz




Horizontal (AV) TX 2401MHz




Vertical (PK) TX 2479MHz



Vertical (AV) TX 2479MHz



Horizontal (PK) TX 2479MHz



Horizontal (AV) TX 2479MHz

