

March 1, 1999

Federal Communications Commission
Equipment Authorization Division
7435 Oakland Mills Road
Columbia, MD 21046

Subject: Maximum Permissible Exposure calculations for **FCC ID: OFY-ACM-0001**

To whom it may concern,

ACM is submitting a low power transmitter for the Audit-Data and Audit-Air devices. The unit has a low power Transmitter that operates at 916.5 with a radiated output power of .025 mW.

Assuming a worst case of no duty cycle.

For an Isotropic radiator the surface area of a sphere can be used to determine the area over which the transmitter energy is radiated.

$$\text{Surface area of a sphere} = 4\pi r^2$$

In this case where the antenna is an integral part of the unit and cannot be removed. The exposure level can be calculated as follows for the 1.0 dBi antenna gain:

$$\text{MPE distance} = (\text{output power} * \text{duty cycle} * 10 * (\text{antenna gain} / 10)) / (4\pi * \text{Exposure Limit (mW/cm}^2\text{)})^{1/2}$$

$$\begin{aligned} \text{OFY-ACM-0001 MPE distance} &= (.025 \text{ mW} * 1 * 4 * 3.14 * 1)^{1/2} \\ &= .045 \text{ cm} \\ &= .017 \text{ in} \end{aligned}$$

If you have any questions please do not hesitate to call me.

Sincerely,

Chris Byleckie
Technical Director
Electronic Compliance Laboratories